

MANTRAM LT AERIAL BUNCHED CABLES

Stranded & Compacted Aluminium Conductor for Phase and Street Lighting With X.L.P.E Insulation , Bare or Insulated All Aluminium Alloy Messenger Conductor Confirming to IS-14255:95 With latest Amendment

With Bare Messenger Conductor										
S No	Type & Size	No of Wires		Thickness of X.L.P.E Insulation		Breaking Load of Messenger	Approx Weight of Cable	Maximum D.C Resistance Ohms/km		A.C Current Rating Amps
				Phase	Messenger					
		Phase	Messenger	mm	mm	KN(min)	Kg/Km	Phase	Messenger	In air at 40°C
1	1CX16 mm ² +25 mm ²	7	7	1.2	N.A	7.0	120	1.91	1.38	75
2	3CX16 mm ² +25 mm ²	7	7	1.2	N.A	7.0	240	1.91	1.38	65
3	1CX25 mm ² +25 mm ²	7	7	1.2	N.A	7.0	150	1.20	1.38	100
4	3CX25 mm ² +25 mm ²	7	7	1.2	N.A	7.0	330	1.20	1.38	85
5	1CX35 mm ² +25 mm ²	7	7	1.2	N.A	7.0	185	0.868	1.38	120
6	3CX35 mm ² +25 mm ²	7	7	1.2	N.A	7.0	410	0.868	1.38	105
7	1CX35mm ² +35 mm ²	7	7	1.2	N.A	9.8	205	0.868	0.986	120
8	3CX35 mm ² +35 mm ²	7	7	1.2	N.A	9.8	440	0.868	0.986	105
9	1CX50 mm ² +35 mm ²	7	7	1.5	N.A	9.8	250	0.641	0.986	150
10	3CX50 mm ² +35 mm ²	7	7	1.5	N.A	9.8	570	0.641	0.986	130
11	3CX70 mm ² +50 mm ²	12/19	7	1.5	N.A	14.0	780	0.443	0.689	155
13	3CX95 mm ² +70 mm ²	15/19	7	1.5	N.A	19.7	1055	0.320	0.492	185
*14	3CX120 mm ² +95 mm ²	15/19	7	1.6	N.A	26.6	1330	0.253	0.357	220
*15	3CX150 mm ² +95 mm ²	15/19	7	1.8	N.A	26.6	1550	0.206	0.357	250

* Cables are not covered in IS-14255:95

With Insulated Messenger Conductor										
S No	Type & Size	No of Wires		Thickness of X.L.P.E Insulation		Breaking Load of Messenger	Approx Weight of Cable	Maximum D.C Resistance Ohms/km		A.C Current Rating Amps
				Phase	Messenger					
		Phase	Messenger	mm	mm	KN(min)	Kg/Km	Phase	Messenger	In air at 40°C
1	1CX16 mm ² +25 mm ²	7	7	1.2	1.2	7.0	150	1.91	1.38	75
2	3CX16 mm ² +25 mm ²	7	7	1.2	1.2	7.0	270	1.91	1.38	65
3	1CX25 mm ² +25 mm ²	7	7	1.2	1.2	7.0	175	1.20	1.38	100
4	3CX25 mm ² +25 mm ²	7	7	1.2	1.2	7.0	350	1.20	1.38	85
5	1CX35 mm ² +25 mm ²	7	7	1.2	1.2	7.0	205	0.868	1.38	120
6	3CX35 mm ² +25 mm ²	7	7	1.2	1.2	7.0	435	0.868	1.38	105
7	1CX35mm ² +35 mm ²	7	7	1.2	1.2	9.8	230	0.868	0.986	120
8	3CX35 mm ² +35 mm ²	7	7	1.2	1.2	9.8	465	0.868	0.986	105
9	1CX50 mm ² +35 mm ²	7	7	1.5	1.2	9.8	280	0.641	0.986	150
10	3CX50 mm ² +35 mm ²	7	7	1.5	1.2	9.8	600	0.641	0.986	130
11	3CX70 mm ² +50 mm ²	12/19	7	1.5	1.5	14.0	820	0.443	0.689	155
13	3CX95 mm ² +70 mm ²	15/19	7	1.5	1.5	19.7	1100	0.320	0.492	185
*14	3CX120 mm ² +95 mm ²	15/19	7	1.6	1.5	26.6	1380	0.253	0.357	220
*15	3CX150 mm ² +95 mm ²	15/19	7	1.8	1.5	26.6	1610	0.206	0.357	250

* Cables are not covered in IS-14255:95