ASTRAKOREAQG®

MANUAL START PORTABLE GENERATOR

WWW 68 dBA 1 1 Running Hours

AST3800

AST4500





Model	AST3800	AST4500
Rated frequency (Hz)	50	50
Max. output (kVA)	2.4	3.3
Phase NO.	1	1
Overall dimension (L×W×H) (mm)	650 x 440 x 460	650 x 440 x 460
Dry weight(kg)	42	44
Noise level (7m) dB(A)	68	68
Engine Model	ST160	ST200
Engine Type	Single cylinder, air-cooled, four- stroke, OHV	Single cylinder, air-cooled, four- stroke, OHV
Cylinder NObore×stroke (mm)	1-68×45	1-68×54
Displacement (ml)	163	196
Cooling system	Air cooled	Air cooled
Starting system	Recoil	Recoil
Lube oil brand	CD grade or SAE10W-30, 15W-40	CD grade or SAE10W-30, 15W-40
Lube capacity (L)	0.6	0.6
Fuel tank capacity (L)	15	15



















Robin Machineries and Equipment P.O. Box 5229, Dubai, UAE

Tel +971 4 221 7124 / 221 5841 | Fax +971 4 223 4493 Email: alawitra@emirates.net.ae | Website: www.robinme.ae