

## Solution — Even Matrices

### 1 Modeling

The modeling part of the exercise is straightforward. You are given a matrix of numbers

$$M = \begin{pmatrix} x_{1,1} & x_{1,2} & \cdots & x_{1,n} \\ x_{2,1} & x_{2,2} & \cdots & x_{2,n} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n,1} & x_{n,2} & \cdots & x_{n,n} \end{pmatrix}$$

and you are required to calculate the number of quadruples  $(i_1, i_2, j_1, j_2)$  where  $1 \leq i_1 \leq i_2 \leq n$  and  $1 \leq j_1 \leq j_2 \leq n$  and for which the sum

$$\sum_{i=i_1}^{i_2} \sum_{j=j_1}^{j_2} x_{i,j}$$

is even.

### 2 Algorithm Design

By looking at the constraints we see that  $n$  is at most 200. On the other hand, what is the maximum number of quadruples  $(i_1, i_2, j_1, j_2)$  with the required properties? In the extreme case when all the bits of  $M$  are zeros then any quadruple is fine, which means that the answer can be of order  $\Theta(n^4)$ . However, if  $n = 200$  then even just going through all the quadruples is infeasible ( $200^4$  is more than a billion). As the bounds on  $n$  in the first and the second test set are smaller, this might be a strategy that brings us partial points and thus let us explore this idea further.

**$O(n^6)$  solution (20 points).** For a given quadruple  $(i_1, i_2, j_1, j_2)$ , how much time do we need to check that  $\sum_{i'=i_1}^{i_2} \sum_{j'=j_1}^{j_2} x_{i',j'}$  is even? Assuming we have the matrix stored in a data structure with random access, we can do the check in roughly  $(i_2 - i_1)(j_2 - j_1)$  time. In the worst case this can take quadratic time, e.g. if  $i_2 = j_2 = \Theta(n)$  and  $i_1 = j_1 = 1$ . Therefore, to iterate over all possible quadruples and check if the elements of a submatrix induced by a quadruple sum to an even number takes  $O(n^6)$  time. Since the first test set guarantees that  $n$  is at most 10, this brute-force solution passes the first test set. The second test set puts a bound of  $n \leq 50$ , which implies that a faster than  $\Theta(n^6)$  solution is needed.

**$O(n^4)$  solution (70 points).** Let us try to improve the  $O(n^6)$  solution such that it passes the second test set as well. Since  $n \leq 50$  we can at least iterate through all  $\Theta(n^4)$  possible quadruples in time. Hence it suffices to improve the part of the algorithm that checks the parity of the sum of elements in a fixed submatrix. Drawing inspiration from the problem *Even Pairs*

we try achieve this by using the technique of *precomputation* (see lecture 1 slides). Let us define  $P_{i,j}$ , for any  $1 \leq i, j \leq n$  as follows:

$$P_{i,j} = \sum_{i'=1}^i \sum_{j'=1}^j x_{i',j'},$$

and we set  $P_{i,0}$  and  $P_{0,i}$  to be zero for any  $i \in \{0, \dots, n\}$ . It is not hard to see that

$$\sum_{i=i_1}^{i_2} \sum_{j=j_1}^{j_2} x_{i,j} = P_{i_2,j_2} - P_{i_2,j_1-1} - P_{i_1-1,j_2} + P_{i_1-1,j_1-1}. \quad (1)$$

Thus, computing the parity of the sum of elements of a fixed submatrix can be done in  $O(1)$  time, once we know all the values  $P_{i,j}$ . Similarly as in (1), we can compute a particular value  $P_{i,j}$  in constant time if we have the values  $P_{i',j'}$ , for  $i' \leq i$  and  $j' \leq j$ . Namely,

$$P_{i,j} = x_{i,j} + P_{i-1,j} + P_{i,j-1} - P_{i-1,j-1}. \quad (2)$$

This shows that we do the precomputation in quadratic time and thus the whole algorithm can be implemented in  $O(n^4)$ .

**$O(n^3)$  solution (100 points).** By generalizing the approach from the problem *Even Pairs* we were able to design an algorithm which works in quartic time and achieves seventy points. However, to come up with a solution faster than  $\Theta(n^4)$ , and thus achieve the full number of points, some creativity and new ideas are required. The key new ingredient is the idea of *dimensionality reduction*. We reduce our 2-dimensional problem to the 1-dimensional problem of calculating the number of pairs  $(i, j)$  in a given array  $y_1, \dots, y_n$  such that  $\sum_{k=i}^j y_k$  is even. Observe that the 1-dimensional problem is equivalent to *Even Pairs*, which we know how to solve in  $O(n)$  time.

Let us define a sequence of variables  $Y_{i_1,i_2}$ , for  $1 \leq i_1 \leq i_2 \leq n$  as follows:

$$Y_{i_1,i_2} = \# \text{ of pairs } (j_1, j_2) \text{ such that } 1 \leq j_1 \leq j_2 \leq n \text{ and } \sum_{i=i_1}^{i_2} \sum_{j=j_1}^{j_2} x_{i,j} \text{ is even.}$$

By definition the solution to the problem is equal to  $\sum_{i_1=1}^n \sum_{i_2=i_1}^n Y_{i_1,i_2}$ . Observe that for a fixed  $i_1$  and  $i_2$ , calculating  $Y_{i_1,i_2}$  is very similar to *Even Pairs*; the main difference being that instead of an array of numbers we have a matrix where each column plays a role of a single cell in the 1-dimensional version. This motivates the definition of an array  $S_{i_1,i_2} = (s_1, \dots, s_n)$  where

$$s_j = \sum_{i=i_1}^{i_2} x_{i,j}.$$

Finally, the main observation is that  $Y_{i_1,i_2}$  is equal to the number of pairs  $(j_1, j_2)$ , where  $1 \leq j_1 \leq j_2 \leq n$ , such that  $\sum_{j=j_1}^{j_2} s_j$  is even. This shows that the calculation of  $Y_{i_1,i_2}$  can be reduced to *Even Pairs* and since we can create the array  $S_{i_1,i_2}$  in linear time (by using precomputation as in the previous solution) we can calculate  $Y_{i_1,i_2}$  in linear time. Iterating this procedure over all pairs  $(i_1, i_2)$  ( $1 \leq i_1 \leq i_2 \leq n$ ) we obtain an  $O(n^3)$  solution.

### 3 Implementation

We use a global two-dimensional vector `vector<vector<int>> M[201][201]` to store the input values and similarly `vector<vector<int>> pM[201][201]` stores the values of the precomputed matrix P, where `pM[i][j]` contains the value  $P_{i,j}$ .

By using (2) we calculate the values of pM with the following piece of code which runs in  $O(n^2)$  time.

```
1 // First we initialize the values of pM[0][i] and pM[i][0] to zero.
2 for (int i = 0; i <= n; ++i) {
3     pM[i][0] = 0;
4     pM[0][i] = 0;
5 }
6
7 // Here we compute pM[i][j] by using the values pM[i'][j'] for i' <= i
8 // and j' <= j.
9 for (int i = 1; i <= n; ++i)
10     for (int j = 1; j <= n; ++j)
11         pM[i][j] = pM[i-1][j] + pM[i][j-1] - pM[i-1][j-1] + M[i][j];
```

Iteration through all possible submatrices can be easily done with four nested loops. The following snippet of code does that and calculates the sum of the elements of a submatrix in constant time by using precomputed matrix P.

```
1 // The variable counter will keep track of the number of quadruples
2 // whose corresponding submatrix has even sum.
3 int counter = 0;
4
5 for (int i1 = 1; i1 <= n; ++i1) {
6     for (int j1 = 1; j1 <= n; ++j1) {
7         for (int i2 = i1; i2 <= n; ++i2) {
8             for (int j2 = j1; j2 <= n; ++j2) {
9                 // qtuple is the element sum of the submatrix
10                 // given by (i1, j1, i2, j2).
11                 int qtuple;
12                 qtuple = pM[i2][j2] - pM[i2][j1-1] - pM[i1-1][j2] + pM[i1-1][j1-1];
13                 if (qtuple % 2 == 0)
14                     ++counter;
15             }
16         }
17     }
18 }
19
20 // Output the result.
21 std::cout << counter << std::endl;
```

### 4 Appendix

The following code is an implementation of the  $O(n^3)$  solution explained in Section 2.

```
1 #include <iostream>
2 #include <vector>
3
4 typedef std::vector<int> VI;
5 typedef std::vector<VI> VVI;
6
```

```

7 void testcase() {
8     int n; std::cin >> n;
9
10    // Input matrix
11    VVI M = VVI(n + 1, VI(n + 1));
12    // pm[i][j] = sum of elements in the submatrix (1, 1, i, j)
13    VVI pM = VVI(n + 1, VI(n + 1));
14
15
16    for (int i = 1; i <= n; ++i)
17        for (int j = 1; j <= n; ++j)
18            std::cin >> M[i][j];
19
20    for (int i = 0; i <= n; ++i) {
21        pM[0][i] = 0;
22        pM[i][0] = 0;
23    }
24
25    for (int i = 1; i <= n; ++i)
26        for (int j = 1; j <= n; ++j)
27            pM[i][j] = pM[i-1][j] + pM[i][j-1] - pM[i-1][j-1] + M[i][j];
28
29    int solution = 0;
30    for (int i1 = 1; i1 <= n; ++i1) {
31        for (int i2 = i1; i2 <= n; ++i2) {
32            // We reduce the problem to one dimension.
33            VI S(201); // We do Even Pairs on array S.
34            VI pS(201); // pS contains partial sums of S.
35            pS[0] = 0;
36            for (int k = 1; k <= n; ++k) {
37                S[k] = pM[i2][k] - pM[i2][k-1] - pM[i1-1][k] + pM[i1-1][k-1];
38                pS[k] = pS[k - 1] + S[k];
39            }
40
41            // Do Even Pairs O(n) algorithm on array S.
42            int even = 0, odd = 0;
43            for (int j = 1; j <= n; ++j) {
44                // even = number of partial sums of array
45                // (S[1], ..., S[j - 1]) that are even.
46                // odd = number of partial sums of array
47                // (S[1], ..., S[j - 1]) that are odd.
48                if (pS[j] % 2 == 0) ++even;
49                else ++odd;
50            }
51
52            solution += even * (even - 1) / 2;
53            solution += odd * (odd - 1) / 2;
54            solution += even;
55        }
56    }
57
58    std::cout << solution << std::endl;
59 }
60
61 int main() {
62     std::ios_base::sync_with_stdio(false);
63
64     int t; std::cin >> t;
65     for (int i = 0; i < t; ++i) {

```

```
66     testcase();  
67 }  
68 }
```