

Operating systems

What is an operating system

Acts as an intermediary between a user and hardware

Operating systems goals

Execute user programs, and solve user problems

Make the computer system convenient to use

Use the computer hardware in an efficient manner

Computer systems structure

Hardware

Basic computing resources

Cpu, memory, i/o device

Operating system

Controls and coordinates use of hardware among various applications and users

Application programs

Define ways in which the system resources are used to solve the computing problems of the users

Word processors, compilers, web browsers, database systems, video games

Users

People, machines, other computers

What operating systems do

Users want convenience, ease of use, and good performance

Dont care about resource utilization

Shared computers like mainframe or minicomputer must keep all users happy

Users dedicate systems such as workstations have dedicated resources but frequently use shared resources from servers

Handheld computers are resource poor, optimized for usability and battery life

Some computers have little or no user interface, such as embedded computers in devices and automobiles

Operating system definition

OS is a resource allocator

Manages all resources

Decides between conflicting requests for efficient and fair resource use

OS is a control program

Controls execution of programs to prevent errors and improper use of the computer

No universal accepted definition

One program running at all times on the computer is the kernel

Everything else is either

A system program (ships with the operating system)

An application program

Computer startup

Bootstrap program

Loaded at power-up or reboot

Typically stored in ROM or EPROM, generally known as firmware

Initializes all aspects of system

Loads operating system kernel and starts execution

Computer system organization

Computer system operation

- One or more CPUs, device controllers connect through common bus providing access to shared memory
- Concurrent execution of CPUs and devices competing for memory cycles

Memory - connected by bus

- CPU
- Disk controller
- USB controller
- Graphics adapter

Computer system operations

- i/o device and the CPU can execute concurrently
- Each device controller is in charge of a particular device type
- Each device controller has a local buffer
- CPU moves data from/to main memory to/from local buffers
- I/O is from the device to local buffer of controller
- Device controller informs CPU that it has finished its operation by causing an interrupt

Common functions of interrupts

- Interrupts transfer control to the interrupt service routine generally, through the interrupt vector
- Interrupt vector contains the addresses of all the service routines
- Interrupt architecture must save the address of the interrupted instruction
- A trap or exception is a software generated interrupt caused either by an error or a user request
- An operating system is interrupt driven

Interrupt handling

- The operating system preserves the state of the CPU by storing registers and the program counter
- Determines which type of interrupt has occurred
 - Polling
 - Goes by each device and queries if it started interrupt
 - Vectored interrupt system
 - You know which addresses to go to when interrupt happens
- Separate segments of code determine what action should be take for each type of interrupt

I/o structure

- After i/o starts control returns to user program only upon i/o completion
 - Wait instruction idles the CPU until the next interrupt
 - Wait loop (contention for memory access)
 - At most one i/o request is outstanding at a time, no simultaneous i/o processing

Storage structure

Main memory

- Only large storage media that the CPU can access directly

- Random access

- Typically volatile

Secondary storage

- Extension of main memory that provides large non volatile storage capacity

Hard disks

- Rigid metal or glass platters covered with magnetic recording material

- Disk surface is logically divided into tracks which are subdivided into sectors

- The disk controller determines the logical interaction between the device and the computer

Solid-state disks

- Faster than hard disks non volatile

Structure hierarchy

- Storage systems organized in hierarchy

- Speed

- Cost

- Volatility

Caching

- copying information into faster storage system; main memory can be viewed as a cache for secondary storage

Device driver

- For each device controller to manage i/o

- Provides uniform interface between controller and kernel

Storage device hierarchy

- Registers - fastest - most expensive

- Cache

- Main memory

- Solid-state disk

- Hard disk

- Optical disk

- Magnetic tapes - slowest - cheapest

Direct memory access structure

- Used for high speed i/o device able to transmit information at close to memory speeds

- Device controller transfers blocks of data from buffer storage directly to main memory without CPU intervention

- Only one interrupt is generated per block rather than the one interrupt per byte

Computer system architecture

- Most systems use a single general purpose processor

- Most systems have special purpose processors

- Multiprocessors systems growing in use and importance

- Also known as parallel systems, tightly coupled systems

- Advantage include

- Increased throughput

- Economy of scale

- Increased reliability

- Graceful degradation or fault tolerance

- Two types

- Asymmetric multiprocessing

- Each processor is assigns a special tasks

- Symmetric multiprocessor

- Each processor is a clone

Clustered systems

- Like multiprocessor systems, but multiple systems working together

- Usually sharing storage via a storage-area network (SAN)

Multiprogramming (batch system)

- Needed for efficiency

Timesharing (multitasking)

- Is logical extension in which CPU switches jobs so frequently that users can interact with each job while it is running, creating interactive computing