Specifications

	DK1	DK2	DK3	DK4
Audio Connectors				
Meter Connector	15-pole D-Sub	15-pole D-Sub	-	15-pole D-Sub
Analogue input	2 XLR input	2 XLR input	-	2 XLR input
AES input	3 BNC (AES3-4-2009)	3 BNC (AES3-4-2009)	-	3 BNC (AES3-4-2009)
Video Connectors				
SDI In	-	-	BNC 3G/HD/SD SDI	BNC 3G/HD/SD SDI
SDI Out	-	-	BNC 3G/HD/SD SDI (active loop through)	BNC 3G/HD/SD SDI (active loop through)
Bit Resolution	24 bit	24 bit	-	24 bit
Group Delay	1.75msec	1.75msec	-	1.75msec
Nominal input imp.	75 ohm	75 ohm	-	75 ohm
S-rate int. /ext.	48kHz	48kHz	48kHz	48kHz
Analogue Input				
Input type	Balanced (electronic)	Balanced (electronic)	-	Balanced (electronic)
Dynamic range	>103dB	>103dB	-	>103dB
Crosstalk	<96dB	<96dB	-	<96dB
SNR	typical 93dB relative to -1dBFS	typical 93dB relative to -1dBFS	-	typical 93dB relative to -1dBFS
Nominal input Imp.	>20kOhm	>20kOhm	-	>20kOhm
Maximum input level	24dBu	24dBu	-	24dBu
Freq. resp. 20Hz-20kHz	+/-0.3dB	+/-0.3dB	-	+/-0.3dB
Loudness				
Compliant with...	ITU BS1770-2, EBU R128, A/85, ARIB	ITU BS1770-2, EBU R128, A/85, ARIB	ITU BS1770-2, EBU R128, A/85, ARIB	ITU BS1770-2, EBU R128, A/85, ARIB
Reference Level digital	-12dBFS & -24dBFS	-12dBFS & -24dBFS	-12dBFS & -24dBFS	-12dBFS & -24dBFS
Dynamic gate level	-2LU dB to -20LU/Off	-2LU dB to -20LU/Off	-2LU dB to -20LU/Off	-2LU dB to -20LU/Off
Short term int. window	0 to 30 seconds	0 to 30 seconds	0 to 30 seconds	0 to 30 seconds
Num. Loudness	LRA	LRA	LRA	LRA
True Peak	Flying peak & Num.	Flying peak & Num.	Flying peak & Num.	Flying peak & Num.
Peak thrs. / hold time	-2dBFS / >0.5sec	-2dBFS / >0.5sec	-2dBFS / >0.5sec	-2dBFS / >0.5sec
Power				
Consumption	350mA	350mA	350mA	350mA
Power Supply	Plugtop, 100-240V, 5VDC, 500mA May be powered from Computer or USB hub	Plugtop, 100-240V, 5VDC, 500mA May be powered from Computer or USB hub	Plugtop, 100-240V, 5VDC, 500mA May be powered from Computer or USB hub	Plugtop, 100-240V, 5VDC, 500mA May be powered from Computer or USB hub

DK - Technologies