

AI-Assisted Coding

Lab Assignment=9.1

Roll no: 2403A510D1

Name: Likhitha Pothunuri

Batch no: 05

CSE 2nd year

Task 1:

Task: Use AI to add Google-style docstrings to all functions in a given Python script.

Prompt:

Add Google-style docstrings to all functions in the following Python script.

Each docstring must include:

- Function description
- Parameters with type hints
- Return values with type hints
- Example usage (without input/output examples)

Do not change the function logic.

Code Generated:

```
9.1.task1.py > ...
1  def example_function(param1: int, param2: str) -> bool:
2      """
3          Performs an example operation using param1 and param2.
4
5          Args:
6              param1 (int): The first parameter, an integer value.
7              param2 (str): The second parameter, a string value.
8
9          Returns:
10             bool: True if operation is successful, False otherwise.
11
12         Example:
13             result = example_function(5, "hello")
14         """
15         # ...existing code...
16         return True
17
18 # Call the function and print the output
19 result = example_function(5, "hello")
20 print(result)
```

Output:

```
[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\9.1.task1.py"
True

[Done] exited with code=0 in 0.154 seconds
```

Observation:

Function Purpose

- The function `example_function` is designed as a placeholder example.
- It takes two parameters (`param1: int` and `param2: str`) and returns a boolean value (`True` in this case).

Docstring Quality

- The docstring follows **Google-style formatting**.
- It clearly documents the function's purpose, parameters (with type hints), return type, and includes an example usage.
- This makes the code more **readable** and **maintainable**.

Code Behavior

- The function currently always returns `True`, regardless of the input values.
- No actual operation is performed using `param1` and `param2`.

Execution

- When the script runs, it calls `example_function(5, "hello")`.
- The result (`True`) is stored in `result` and printed to the console.

☑ In summary: The code demonstrates how to write and use a properly formatted **Google-style docstring**, but the function logic is only illustrative (returns a constant `True`).

Task 2 (Documentation – Inline Comments for ComplexLogic)

- Task: Use AI to add meaningful inline comments to a Python program explaining only complex logic parts

Prompt:

Add meaningful inline comments to the following Python script.

Requirements:

- Focus only on complex or non-intuitive logic.
- Do not add comments for obvious syntax (e.g., variable declarations, loops, or print statements).
- Ensure comments improve readability and maintainability.
- Do not change the code logic.

Code Generated:

```

task2.py > ...
1  def process_data(data: list) -> list:
2      # Filter out negative values (non-intuitive: only positive numbers are processed)
3      filtered = [x for x in data if x >= 0]
4
5      # Sort the filtered data in descending order (complex: reverse sorting)
6      sorted_data = sorted(filtered, reverse=True)
7
8      # Apply a transformation: square each number (non-obvious transformation)
9      transformed = [x ** 2 for x in sorted_data]
10
11     return transformed
12
13     # Example usage
14     numbers = [3, -1, 2, -7, 5]
15     result = process_data(numbers)
16     print(result)

```

Output:

```

[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\task2.py"
[25, 9, 4]

[Done] exited with code=0 in 0.177 seconds

```

Observation:

1. Function Purpose

- The function `process_data` takes a list of numbers as input and applies a sequence of transformations to produce a processed list.

2. Logic Steps

- **Filtering:** Removes all negative values, keeping only non-negative integers.
- **Sorting:** Orders the remaining numbers in descending order (`reverse=True`).
- **Transformation:** Squares each number in the sorted list.

3. Docstring/Comments Quality

- Inline comments clearly explain the reasoning behind non-obvious steps (e.g., filtering negatives, reverse sorting, squaring values).
- This improves **readability** and helps others understand why these steps are applied.

4. Execution

- Input: `numbers = [3, -1, 2, -7, 5]`
- Processing:
 - Filtered → `[3, 2, 5]`
 - Sorted (descending) → `[5, 3, 2]`
 - Squared → `[25, 9, 4]`
- Output → `[25, 9, 4]`

☑ **Summary:** The code is clean, with inline comments focusing only on tricky parts (filtering negatives, reverse sorting, squaring). The logic is straightforward yet well-documented, making it **readable and maintainable**.

Task 3 (Documentation – Module-Level Documentation)

- Task: Use AI to create a module-level docstring summarizing the purpose, dependencies, and main functions/classes of a Python file.

Prompt:

Write a module-level docstring for the following Python file.

Requirements:

- Place a single multi-line docstring at the top of the file.
- Summarize the overall purpose of the module.
- Mention any dependencies.
- Briefly describe the main functions and/or classes.
- Clearly explain functionality and usage without rewriting the entire code.

Code Generated:

```
task3.py > process_data
1  def process_data(data: list) -> list:
2
3      # Filter out negative values
4      filtered = [x for x in data if x >= 0]
5      # Sort the filtered data in descending order
6      sorted_data = sorted(filtered, reverse=True)
7      # Square each number in the sorted list
8      transformed = [x ** 2 for x in sorted_data]
9      return transformed
10
11  # Example usage
12  numbers = [3, -1, 2, -7, 5]
13  result = process_data(numbers)
14  print(result)  # Output: [25, 9, 4]
15
16
```

Output:

```
[Done] exited with code=0 in 0.133 seconds

[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\task3.py"
[25, 9, 4]

[Done] exited with code=0 in 0.108 seconds
```

Observation:

1. Function Purpose

- The function `process_data` processes a list of numbers through three main steps: filtering, sorting, and transformation.
- Its goal is to output squared values of only the non-negative numbers, arranged in descending order.

2. Logic Flow

- **Filter Step:** Removes all negative numbers from the input list ($x \geq 0$).
- **Sorting Step:** Sorts the remaining numbers in **descending order** using `reverse=True`.
- **Transformation Step:** Squares each number in the sorted list.

3. Code Quality

- Code is **clean and readable**.
- Inline comments explain each logical step, improving clarity.
- The transformation pipeline is efficient and Pythonic (list comprehensions + built-in sorting).

4. Execution Walkthrough

- Input: `numbers = [3, -1, 2, -7, 5]`
- Filtered: `[3, 2, 5]`
- Sorted: `[5, 3, 2]`
- Squared: `[25, 9, 4]`

☑ **Summary:** The function works correctly and demonstrates good use of Python features. The output matches the intended logic. One minor note: in your code comment, `# Output: [25, 9, 4]` is missing the closing bracket `]`.

Task 4 : (Documentation – Convert Comments to Structured Docstrings)

- Task: Use AI to transform existing inline comments into structured function docstrings following Google style

Prompt:

Convert the inline comments in the following Python code into structured Google-style function docstrings. Move relevant details from comments into docstrings, keep the meaning intact, and improve structure. Do not rewrite the function logic.

Code Generated:

```

task4.py > ...
1  def process_data(data: list) -> list:
2      """
3          Filters out negative values, sorts the filtered data in descending order,
4          and applies a transformation by squaring each number.
5
6          Args:
7              data (list): List of integers or floats.
8
9          Returns:
10             list: List of squared values, sorted in descending order.
11
12         Example:
13             result = process_data([4, -2, 0, 7, -5])
14         """
15         filtered = [x for x in data if x >= 0]
16         sorted_data = sorted(filtered, reverse=True)
17         transformed = [x ** 2 for x in sorted_data]
18         return transformed
19
20     # Example usage 1
21     numbers1 = [3, -1, 2, -7, 5]
22     result1 = process_data(numbers1)
23     print(result1) # Output: [25, 9, 4]
24
25     # Example usage 2
26     numbers2 = [4, -2, 0, 7, -5]
27     result2 = process_data(numbers2)
28     print(result2)

```

Output:

```

[Done] exited with code=0 in 0.095 seconds

[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\task4.py"
[25, 9, 4]
[49, 16, 0]

[Done] exited with code=0 in 0.095 seconds

```

Observation:

1. Function Purpose

- The function process_data takes a list of numbers and:
 1. Removes negative values.
 2. Sorts the remaining values in descending order.
 3. Squares each number and returns the transformed list.

2. Docstring Quality

- The function has a **Google-style docstring**, which is well-structured.
- It includes a **description**, **arguments**, **return type**, and an **example usage**.
- This makes the function self-explanatory and improves maintainability.

3. Logic Flow

- filtered: Keeps only non-negative numbers ($x \geq 0$).

- sorted_data: Sorts the filtered list in descending order.
- transformed: Squares each number in the sorted list.
- Returns the final transformed list.

4. Execution Walkthrough

- **Example 1**
 - Input: [3, -1, 2, -7, 5]
 - Filtered → [3, 2, 5]
 - Sorted → [5, 3, 2]
 - Squared → [25, 9, 4]
 - Output → [25, 9, 4]
- **Example 2**
 - Input: [4, -2, 0, 7, -5]
 - Filtered → [4, 0, 7]
 - Sorted → [7, 4, 0]
 - Squared → [49, 16, 0]
 - Output → [49, 16, 0]

☑ **Summary:** The code is clean, well-structured, and demonstrates excellent use of **Google-style docstrings**. The function is correct and works for multiple test case

Task 5: (Documentation – Review and Correct Docstrings)

- Task: Use AI to identify and correct inaccuracies in existing docstrings.

Prompt:

Review the following Python code and identify inaccuracies in existing docstrings. Rewrite each docstring so it correctly describes the current code behavior, following Google-style formatting. Do not change the function logic.

Code Generated:


```

task5.py > ...
1  def process_data(data: list) -> list:
2      """
3      Filters out negative values, sorts the filtered data in descending order,
4      and applies a transformation by squaring each number.
5
6      Args:
7      |   data (list): List of integers or floats.
8
9      Returns:
10     |   list: List of squared values, sorted in descending order.
11
12     Example:
13     |   result = process_data([4, -2, 0, 7, -5])
14     """
15     filtered = [x for x in data if x >= 0]
16     sorted_data = sorted(filtered, reverse=True)
17     transformed = [x ** 2 for x in sorted_data]
18     return transformed
19
20 # Example usage
21 numbers = [1, -3, 6, 0, -2]
22 result = process_data(numbers)
23 print(result) # Output: [36, 1, 0]

```

Output:

```

[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\task5.py"
[36, 1, 0]

[Done] exited with code=0 in 0.164 seconds

```

Observation:

1. Function Purpose

- The function `process_data` processes a list of numbers by:
 1. Removing negative values.
 2. Sorting the remaining values in **descending order**.
 3. Squaring each number and returning the transformed list.

2. Docstring Quality

- The docstring is **accurate** and follows **Google-style formatting**.
- It provides:
 - A clear description.
 - Arguments with type hints.
 - Return type with description.
 - An example usage.
- The docstring matches the function's actual behavior.

3. Logic Flow

- filtered: Keeps only non-negative numbers ($x \geq 0$).
- sorted_data: Sorts the filtered list in descending order.
- transformed: Squares each number.
- Returns the transformed list.

4. Execution Walkthrough

- Input: [1, -3, 6, 0, -2]
- Filtered → [1, 6, 0]
- Sorted (descending) → [6, 1, 0]
- Squared → [36, 1, 0]
- Output → [36, 1, 0]

☑ Summary:

- The code executes correctly and produces the expected output.
- The docstring is correct and well-structured; it does not require updates.
- The inline comment with expected output (# Output: [36, 1, 0]) is accurate.

Task 6 : (Documentation – Prompt Comparison Experiment)

Task: Compare documentation output from a vague prompt and a detailed prompt for the same Python `function`.

Prompt:

```
def process_data(data: list) -> list:
```

```
    """
```

```
    Processes a list of numbers by filtering out negative values, sorting the remaining
    numbers in descending order, and squaring each number.
```

```
    Args: data (list): List of integers or floats.
```

```
    Returns list: List of squared values, sorted in descending order.
```

```
    Example:
```

```
        result = process_data([4, -2, 0, 7, -5])
```

```
    """
```

```
    filtered = [x for x in data if x >= 0]
```

```
    sorted_data = sorted(filtered, reverse=True)
```

```
    transformed = [x ** 2 for x in sorted_data]
```

```
    return transformed
```

```
# Example usage
```

```
numbers = [4, -2, 0, 7, -5]
```

```
result = process_data(numbers)
```

```
print(result)
```

Code Generated:

```
task6.py > ...
1  def process_data(data: list) -> list:
2      """
3          Processes a list of numbers by filtering out negative values, sorting the remaining
4          numbers in descending order, and squaring each number.
5
6          Args:
7              data (list): List of integers or floats.
8
9          Returns:
10             list: List of squared values, sorted in descending order.
11
12         Example:
13             result = process_data([4, -2, 0, 7, -5])
14         """
15         filtered = [x for x in data if x >= 0]
16         sorted_data = sorted(filtered, reverse=True)
17         transformed = [x ** 2 for x in sorted_data]
18         return transformed
19
20 # Example usage
21 numbers = [4, -2, 0, 7, -5]
22 result = process_data(numbers)
23 print(result) # Output: [49, 16, 0]
```

Output:

```
[Done] exited with code=0 in 0.119 seconds

[Running] python -u "c:\Users\akshi\OneDrive\Desktop\AI_Assisted_Coding\task6.py"
[49, 16, 0]

[Done] exited with code=0 in 0.128 seconds
```

Observation:

1. Function Purpose

- The function `process_data` processes a list of numbers by:
 1. Removing all negative values.
 2. Sorting the non-negative values in **descending order**.
 3. Squaring each number and returning the transformed list.

2. Docstring Quality

- The docstring is **Google-style** and well-written.
- It includes:
 - A **clear description** of the function's behavior.
 - **Args** with type hints.
 - **Returns** with type hints.
 - An **example usage**.
- The docstring is accurate and aligns with the function's actual logic.

3. Logic Flow

- `filtered`: Keeps only numbers ≥ 0 .

- `sorted_data`: Sorts these numbers in descending order.
- `transformed`: Squares each sorted number.
- Returns the final transformed list.

4. Execution Walkthrough

- Input: [4, -2, 0, 7, -5]
- Step 1 (Filter): [4, 0, 7]
- Step 2 (Sort descending): [7, 4, 0]
- Step 3 (Square): [49, 16, 0]
- Output: [49, 16, 0]

5. Output

6. [49, 16, 0]

☒ Summary:

- The function works as intended and produces correct output.
- The docstring is **accurate, structured, and complete**.
- The example in the docstring matches the actual function behavior, making the code easy to understand and maintain.