```
Program – 1:- Implement three nodes point–to–point networks with duplex links between
them. Set the gueue size, vary the bandwidth, and find the number of packets dropped.
#Create Simulator
set ns [new Simulator]
#Open Trace file and NAM file set ntrace [open prog1.tr w]
$ns trace-all $ntrace
set namfile [open prog1.nam w]
$ns namtrace-all $namfile
#Finish Procedure proc Finish {} {
global ns ntrace namfile
#Dump all the trace data and close the files
$ns flush-trace close $ntrace close $namfile
#Execute the nam animation file exec nam prog1.nam &
#Show the number of packets dropped
exec echo "The number of packet drops is " & exec grep -c "^d" prog1.tr &
exit 0
}
#Create 3 nodes set n0 [$ns node] set n1 [$ns node] set n2 [$ns node]
#Label the nodes
$n0 label "TCP Source"
$n2 label "Sink"
#Set the color
$ns color 1 blue
#Create Links between nodes
#You need to modify the bandwidth to observe the variation in packet drop
$ns duplex-link $n0 $n1 1Mb 10ms DropTail
$ns duplex-link $n1 $n2 1Mb 10ms DropTail
#Make the Link Orientation
$ns duplex-link-op $n0 $n1 orient right
$ns duplex-link-op $n1 $n2 orient right
#Set Queue Size
#You can modify the queue length as well to observe the variation in packet drop
$ns queue-limit $n0 $n1 10
$ns queue-limit $n1 $n2 10
```

#Set up a Transport layer connection. set tcp0 [new Agent/TCP] \$ns attach-agent \$n0 \$tcp0 set sink0 [new Agent/TCPSink] \$ns attach-agent \$n2 \$sink0 \$ns connect \$tcp0 \$sink0

#Set up an Application layer Traffic set cbr0 [new Application/Traffic/CBR] \$cbr0 set type_ CBR \$cbr0 set packetSize_ 100 \$cbr0 set rate_ 1Mb \$cbr0 set random_ false \$cbr0 attach-agent \$tcp0

\$tcp0 set class_ 1

#Schedule Events \$ns at 0.0 "\$cbr0 start" \$ns at 5.0 "Finish"

#Run the Simulation \$ns run