# Copies, Conflicts and Broken Parses: How Corpus Defects Affect Retrieval-Augmented Claim Verification

**Likhith Venkata Sai Manikanta Nalla**
Independent researcher
likhith.nalla1@gmail.com

## Abstract

Retrieval-augmented systems inherit the quality of the collection they search, but the effect of specific defects is rarely measured in isolation. We inject four controlled defects into the SciFact corpus (near-duplicate copies, stale copies with flipped findings, broken parsing, and chunking) at 10–50% of the gold-evidence documents, and measure, claim by claim, how they change retrieval and the verdicts of four verifiers: two zero-shot LLMs (Qwen2.5 1.5B and 3B) and an NLI cross-encoder used off the shelf or fine-tuned. Results are repeated over five corruption seeds and three training seeds and replicated on Climate-FEVER. Copies push the gold document out of first place (dense recall@1 from 0.74 to 0.53 at 50% stale copies) but barely change verification, whereas broken parsing is almost invisible to retrieval yet costs correct answers for both LLMs and for the fine-tuned verifier on every seed. Flipped copies move the fine-tuned verifier towards CONTRADICT, and on one-sentence Climate-FEVER records cost it many correct answers (up to 55 lost against 14 gained) and make it more often confidently wrong; both LLMs largely ignore them. Single-sentence chunks make the fine-tuned verifier less accurate and more confident. Monitoring retrieval alone would rank these defects in the wrong order of harm.

## 1 Introduction

Retrieval-augmented generation (RAG; Lewis et al., 2020) answers a question from documents retrieved out of a collection, so its answers can be no better than that collection. Real collections are imperfect: documents are duplicated across sources, older versions sit next to newer ones that contradict them, PDF parsing truncates or scrambles text, and chunking splits documents into pieces of varying size. Robustness studies of RAG usually vary what reaches the reader, for instance by adding irrelevant or counterfactual passages to its context (Cuconasu et al., 2024; Chen et al., 2024; Xie et al., 2024), rather than the collection the retriever searches. Practitioners, however, control the collection, and need to know which of its defects are worth cleaning.

We ask how much each of four common defects, on its own, changes retrieval and the final answer. We use claim verification because it has labels for both the answer (does the evidence support or contradict the claim?) and the evidence (which documents), so a defect's effect can be traced from retrieval to the verdict. Defects are injected under control, one type and rate at a time, into an otherwise unchanged corpus, with every model, prompt and threshold held fixed, so any change in the results comes from the corpus. Our contributions:

- A seeded corruption tool for four defect types (near-duplicates, stale copies with flipped findings, broken parsing, chunking) that logs every change, and a pipeline that regenerates and verifies each corrupted corpus from its seed.
- Paired, claim-level measurements on SciFact (Wadden et al., 2020) for two retrievers, a reranker and four verifiers, repeated over five corruption seeds and three verifier training seeds, and replicated on Climate-FEVER (Diggelmann et al., 2020).
- Evidence that retrieval metrics rank the defects in the wrong order of harm, that stale copies matter only to verifiers that read their context closely, and that small chunks make a fine-tuned verifier confidently wrong.

All code, per-claim predictions, corruption manifests and fine-tuned models are public.[1]

[1] https://github.com/Likhithvenkatanalla/rag-dq-benchmark; archived at https://doi.org/10.5281/zenodo.23314458.

## 2 Related Work

**Robustness of retrieval-augmented models.** Language models are easily distracted by irrelevant context (Shi et al., 2023), use the middle of long contexts poorly (Liu et al., 2024), and can be trained to ignore irrelevant passages (Yoran et al., 2024). RGB (Chen et al., 2024) tests noise robustness, negative rejection and counterfactual robustness of RAG readers, and Cuconasu et al. (2024) find that random documents in the context can even help. These studies manipulate the reader's context directly; we manipulate the collection and let the retriever decide what reaches the reader.

**Knowledge conflicts.** Longpre et al. (2021) substitute entities in passages to create conflicts with a model's parametric knowledge, and Xie et al. (2024) show that LLMs readily accept coherent conflicting evidence. Our stale copies create conflicts *within* the collection: the original and a flipped copy are both retrievable, as when outdated and current versions of a document coexist.

**Duplicates and data quality.** Near-duplicates are pervasive in web-scale text and deduplication improves language-model training (Lee et al., 2022). Retrieval benchmarks such as BEIR (Thakur et al., 2021) evaluate retrievers across clean collections; we hold the task fixed and vary the collection's quality.

**Claim verification.** FEVER (Thorne et al., 2018), SciFact (Wadden et al., 2020) and Climate-FEVER (Diggelmann et al., 2020) pair claims with evidence and a verdict, which makes the path from evidence to answer measurable.

## 3 Setup

### 3.1 Data

**SciFact** pairs expert-written scientific claims with 5,183 abstracts. We evaluate on the 300 dev claims (124 SUPPORT, 64 CONTRADICT, 112 NEI); 188 have gold evidence, among 184 distinct gold abstracts. The 809 train claims, disjoint from dev, are used only for training and threshold tuning.

**Climate-FEVER** pairs real-world climate claims with five Wikipedia sentences each, labelled by annotators. We build a closed corpus from all 5,240 distinct evidence sentences (each a record titled with its article), close in size to SciFact, and drop the 154 DISPUTED claims, leaving 1,381 claims (654 SUPPORT, 253 CONTRADICT, 474 NEI). A claim's gold records are its evidence sentences labelled with the claim's own verdict (907 claims have at least one). No model is trained on Climate-FEVER.

### 3.2 Pipeline

**Retrieval.** BM25 (Robertson and Zaragoza, 2009) over whitespace tokens, and dense retrieval with BGE-small-en-v1.5 (Xiao et al., 2023) and exact cosine search (Johnson et al., 2019). Recall@$k$ is the share of a claim's gold records found in the top $k$, averaged over claims with evidence.

**Verification.** A verifier reads the claim with the top-3 dense-retrieved records and outputs SUPPORT, CONTRADICT or NEI. *Qwen-1.5B* and *Qwen-3B* are Qwen2.5-1.5B/3B-Instruct (Qwen Team, 2024), zero-shot with greedy decoding, instructed to answer with one word. *NLI zero-shot* is the cross-encoder `nli-deberta-v3-xsmall` (He et al., 2023) as released, and *NLI fine-tuned* is the same model fine-tuned for 3 epochs on 1,123 SciFact train pairs (gold abstracts with their labels; cited abstracts of claims without evidence and the top non-gold BM25 abstract of each claim with evidence as NEI), trained with three seeds. An NLI verifier scores each (claim, record) pair; the claim takes the higher of the maximum SUPPORT and CONTRADICT probabilities over its three records, or NEI if neither reaches a threshold tuned for macro-F1 on 20% of the train claims held out from training (never on dev).

**Reranking.** A MiniLM cross-encoder (Nogueira and Cho, 2019), as released or fine-tuned on SciFact train, reorders the dense top-10 before verification.

### 3.3 Defects

Each defect is applied to a share (10, 25 or 50%) of the gold-evidence records, so that it reaches the evaluated claims; claims and labels never change.

- **Duplicate** adds a near-copy of the record (one sentence dropped if there are more than two, about 5% of words deleted, one adjacent word pair swapped per sentence).
- **Stale** adds a copy whose directional findings are flipped by rule (*increased*↔*decreased*, *higher*↔*lower*, "is associated" → "is not associated", ...; for Climate-FEVER also *warming*↔*cooling*, *rise*↔*fall*, ...). Copies with

nothing to flip are identical to the original; we analyse flipped copies separately.

- **Parse** replaces the record with a broken parse: truncated at 30–60% of its length, sentences scrambled, or OCR-style character noise.
- **Chunk** splits every SciFact abstract into records of 1, 3 or 5 sentences (not applicable to one-sentence Climate-FEVER records).

A copy is a different document: retrieving it does not count as retrieving the gold record. A chunk counts as its parent abstract.

### 3.4 Statistics

All runs on a dataset share the same claims, so comparisons are paired: for each claim we record whether the answer went from right to wrong (*lost*) or wrong to right (*gained*) relative to the clean corpus, and report both counts with an exact McNemar test (McNemar, 1947). We run many such tests without correction, so we treat as findings only effects whose direction repeats across corruption seeds and, for the fine-tuned verifier, training seeds.

## 4 Results on SciFact

### 4.1 Clean baseline

Dense retrieval beats BM25 at every cut-off (recall@1 0.744 vs. 0.615; recall@10 0.957 vs. 0.883). Qwen-1.5B reaches 0.557 accuracy and 0.502 macro-F1 (majority class: 0.413 and 0.195) but answers SUPPORT for 200 of 300 claims. The fine-tuned NLI verifier reaches 0.650 / 0.680 / 0.667 for its three training seeds, each significantly above Qwen-1.5B (lost/gained 32/60, 36/73, 35/68; $p \leq 0.005$). Untuned, the NLI model reaches only 0.353. Doubling the LLM closes the gap: Qwen-3B reaches 0.667 accuracy and 0.655 macro-F1, significantly above Qwen-1.5B (34 lost, 67 gained; $p = 0.001$) and level with the fine-tuned verifier, without any training; its answers are spread evenly over the three labels (109 SUPPORT, 96 CONTRADICT, 95 NEI).

### 4.2 Retrieval

Copies push the gold abstract out of first place in proportion to their rate (Table 1, Figure 1) while recall@10 does not change: a copy usually sits just above its original. Over five corruption seeds, dense recall@1 at 50% falls to $0.584 \pm 0.019$ (duplicates) and $0.528 \pm 0.031$ (stale), against 0.744 clean. The fine-tuned reranker lifts clean recall@1 to 0.805 and recovers part of the duplicate loss but little of the stale loss: a flipped copy is as relevant to the claim as its original, so a relevance model cannot tell them apart. Broken parsing removes documents from BM25's reach (recall@10 0.845 at 50%) but barely affects dense retrieval, and chunking hurts BM25 but not dense retrieval.

| Corpus | BM25 | Dense | + rerank |
|---|---|---|---|
| clean | 0.615 | 0.744 | 0.805 |
| duplicate 10/25/50% | .594/.541/.463 | .689/.668/.604 | .774/.751/.644 |
| stale 10/25/50% | .583/.530/.466 | .691/.622/.551 | .752/.657/.571 |
| parse 10/25/50% | .615/.599/.578 | .744/.734/.739 | .795/.799/.758 |
| chunk 5/3/1 sent. | .583/.590/.520 | .749/.742/.762 | .803/.818/.784 |

Table 1: SciFact recall@1 (188 claims with evidence; corruption seed 0). Recall@10 is unchanged by copies (0.883 BM25, 0.957 dense).

| Setting | Dense R@1 | NLI acc. | Lost / gained |
|---|---|---|---|
| clean | 0.744 | 0.650 | – |
| dup. 10% | .704 (.015) | .649 (.003) | 3 / 1 |
| dup. 25% | .665 (.026) | .653 (.005) | 5 / 10 |
| dup. 50% | .584 (.019) | .657 (.009) | 7 / 18 |
| stale 10% | .696 (.004) | .647 (.009) | 8 / 3 |
| stale 25% | .624 (.011) | .646 (.010) | 16 / 10 |
| stale 50% | .528 (.031) | .649 (.005) | 23 / 22 |
| parse 10% | .744 (.004) | .643 (.007) | 11 / 1 |
| parse 25% | .736 (.008) | .641 (.006) | 18 / 4 |
| parse 50% | .733 (.010) | .631 (.006) | 41 / 13 |

Table 2: SciFact over five corruption seeds (mean, sd): dense recall@1, accuracy of the fine-tuned verifier (training seed 0), and claims lost / gained relative to clean, summed over the seeds.

### 4.3 Verification

Accuracy changes are small for most defects (Table 3, Figure 2), so we read them claim by claim.

**Broken parsing costs verification.** With five corruption seeds, the seed-0 fine-tuned verifier lost more correct answers than it gained in 14 of the 15 parse runs and gained more in none (Table 2): 41 lost against 13 gained over the five 50% corpora, 18 against 4 at 25%. No single run is significant at $p < 0.05$ (the largest has 12 lost, 4 gained), which is why repetition matters here: under no effect, a net loss on all five seeds has probability $1/32$ for each rate. Qwen-1.5B shows the same direction (8 lost, 0 gained at 50%, $p = 0.008$), as do all three training seeds on corruption seed 0. Qwen-3B, too, loses more than it gains at 25% (5 vs. 2) and 50% (13 vs. 7). Every verifier we tested is hurt by broken parsing in the same direction.





Figure 1: SciFact recall@1 by corruption level for BM25, dense retrieval and dense retrieval with the fine-tuned reranker (corruption seed 0).

| Corpus | Qwen-1.5B | NLI zero-shot | NLI fine-tuned |
|---|---|---|---|
| clean | 0.557 | 0.353 | 0.666 (.015) |
| dup. 10/25/50% | .543/.547/.557 | .360/.367/.353 | .670/.670/.677 |
| stale 10/25/50% | .553/.550/.560 | .353/.357/.347 | .672/.661/.656 |
| parse 10/25/50% | .550/.547/.530 | .357/.347/.340 | .664/.658/.647 |
| chunk 5/3/1 | .543/.573/.583 | .390/.353/.333 | .667/.631/.573 |

Table 3: SciFact verification accuracy (300 claims; corruption seed 0). Fine-tuned: mean over three training seeds (sd on clean).

**Single-sentence chunks hurt the fine-tuned verifier** , consistently across training seeds (0.573 mean accuracy; lost/gained 58/38, 65/32 and 64/34, $p = 0.052, 0.001, 0.003$). It was trained on whole abstracts; 5-sentence chunks do not hurt it, and neither Qwen model is hurt by chunking.

**Duplicates do not change verification** , despite their effect on retrieval: the gold abstract is still in the top 3 for nearly as many claims (gold-in-context rate 0.872 clean, 0.867 at 50%), and a near-copy carries the same evidence. Over five seeds the fine-tuned verifier gained slightly more answers than it lost at 25–50% (12 lost, 28 gained in total), consistent with no harm.

**Reranking barely changes verification.** Verifying from the fine-tuned reranker's top-3 moves accuracy by 0 to +2.3 points across the 13 corpora, with no run changing significantly: the gold abstract is usually already within the dense top-3, and its position there matters little to the verifier.

### 4.4 Conflicting evidence

To isolate genuinely conflicting evidence we keep only claims whose top-3 context held a stale copy whose findings were actually flipped, and compare them with the same claims on the clean corpus. At 50% on corruption seed 0, 78 claims qualify. The fine-tuned verifier changed its answer on 13, 19 and 16 of them (training seeds 0/1/2), and 11, 15 and 12 of those changes went to CONTRADICT; Qwen-1.5B changed 6 and moved 1 to CONTRADICT, consistent with its SUPPORT bias. Qwen-3B, despite matching the fine-tuned verifier's accuracy, behaves like the smaller LLM: it changed 8 of the 78 answers and moved 3 to CONTRADICT (4 lost, 4 gained), so its insensitivity is not a side effect of the smaller model's SUPPORT bias. Over five corruption seeds the pattern is stable: of 48 changed answers at 50%, 35 moved to CONTRADICT. Claims whose context held only unflipped copies never changed answer for the NLI verifier. Yet no verifier's accuracy changes significantly: the fine-tuned verifier is misled on some claims and helped on others (23 lost, 22 gained over five seeds at 50%), and flipped copies do not make it more often confidently wrong (55 such answers on these claims clean, 56 with stale copies). The count rose on two corruption seeds and fell on three, so the increase we reported earlier for a single seed was not robust.

### 4.5 Calibration

We give each NLI answer a confidence (for SUPPORT or CONTRADICT, the highest probability of that label over the three records; for NEI, one minus the highest SUPPORT or CONTRADICT probability) and compare it with correctness; the Qwen models give no probabilities. The fine-tuned verifier is overconfident even on clean data: mean confidence 0.75–0.80 against accuracy 0.65–0.68, expected calibration error (ECE; Guo et al., 2017) 0.14–0.18, and 8–11% of claims answered wrongly with confidence of at least 0.9 (*confidently wrong*). Copies and broken parses barely change this. Small chunks do: with 1-sentence records confidence rises while accuracy falls, ECE roughly doubles (0.31–0.32





Figure 2: SciFact verification accuracy by corruption level. The orange band spans the three fine-tuned training seeds; the green line is the seed-0 verifier on corruption seed 1 (its own clean value is 0.650).





Figure 3: SciFact: share of claims answered wrongly with confidence $\geq 0.9$ by the fine-tuned verifier (bar: mean of three training seeds; dots: seeds).

for all three training seeds) and 18–22% of claims are confidently wrong (Figure 3).

## 5 Replication on Climate-FEVER

Climate-FEVER differs from SciFact in ways that make it a demanding replication: records are single Wikipedia sentences, claims come from the web rather than from experts, and no verifier was trained on it. Retrieval is much harder (a gold sentence reaches the dense top-3 for 53% of claims with evidence, against 87% on SciFact), and both verifiers are weak: Qwen-1.5B reaches 0.508 accuracy (majority class 0.474) with NEI for only 89 claims, and the SciFact-trained NLI verifier transfers poorly, at 0.458 (0.450–0.468) and significantly below Qwen-1.5B for every training seed ($p \leq 0.039$). The findings that replicate are therefore the ones that do not depend on absolute accuracy (Table 4).

**Stale copies hurt the NLI verifier, much more than on SciFact.** At 25% and 50% each training seed lost far more correct answers than it gained (at 50%: 55/14, 46/16 and 48/15, all $p < 0.001$), and accuracy fell monotonically with the rate for every seed. On claims with a flipped copy in their top-3 (356 at 50%), the verifier changed 84–101 answers, about half of them to CONTRADICT, and became more often confidently wrong for all three seeds (98→119, 95→120, 79→107). Qwen-1.5B again barely reacted (26 lost, 27 gained). A one-sentence record leaves no other evidence to outweigh a flipped finding, which plausibly explains why the effect is stronger than on SciFact.

**Copies displace gold records without hurting verification.** Duplicates and stale copies lower the gold-in-top-3 rate by about four points at 50%, yet duplicates leave accuracy essentially unchanged (the fine-tuned verifier moves by at most 0.4 points; Qwen-1.5B even gains at 25%, 4 lost against 21 gained).

**Broken parsing has no consistent effect here.** With one-sentence records, a third of the parse corruptions (sentence scrambling) change nothing, and truncation leaves part of a short sentence; the lost/gained counts point in both directions across verifiers and seeds.

## 6 Discussion

**Retrieval metrics can rank defects in the wrong order.** On SciFact, duplicates and stale copies cause the largest drops in recall@1 but no reliable change in verification, because the verifier reads the top 3 and the gold abstract rarely leaves it. Broken parsing shows the opposite: retrieval barely notices it, yet it is the defect that most consistently costs correct answers, for both LLMs and for the fine-tuned verifier across all its training and corruption seeds, because the verifier receives a truncated or scrambled version of the right abstract. Monitoring retrieval alone would put these defects in the wrong order; answer-level evaluation on a corrupted copy of one's own collection is cheap and does not.

| | Retrieval | | Qwen-1.5B | | NLI fine-tuned (SciFact) | |
|---|---|---|---|---|---|---|
| Corpus | Gold in top-3 | Dense R@10 | Acc. | Lost / gained | Acc. (3 seeds) | Lost / gained at 50% (seeds 0/1/2) |
| clean | 0.534 | 0.522 | 0.508 | – | 0.458 | – |
| duplicate 10 / 25 / 50% | .526 / .517 / .494 | .515 / .499 / .486 | .511 / .520 / .516 | 5/9, 4/21, 21/33 | .459 / .457 / .456 | 29/24, 25/21, 24/24 |
| parse 10 / 25 / 50% | .531 / .515 / .504 | .509 / .495 / .475 | .510 / .511 / .506 | 3/6, 7/12, 21/19 | .457 / .452 / .458 | 38/32, 27/30, 28/31 |
| stale 10 / 25 / 50% | .528 / .516 / .496 | .516 / .502 / .489 | .509 / .511 / .508 | 4/6, 11/15, 26/27 | .453 / .446 / .433 | 55/14, 46/16, 48/15 |

Table 4: Climate-FEVER (1,381 claims; corruption seed 0). Gold in top-3: share of claims with evidence whose dense top-3 holds a gold sentence. Lost / gained: claims right on the clean corpus and wrong on the corrupted one, and the reverse.

**Whether conflicting evidence matters depends on the reader.** The fine-tuned NLI verifier reads each record closely and reacts to flipped copies: on SciFact it moves answers to CONTRADICT without a net loss, and on Climate-FEVER, where a record is one sentence, it loses many correct answers and becomes confidently wrong more often. Both zero-shot LLMs largely ignore the flipped copies, including Qwen-3B, which is as accurate as the fine-tuned verifier on clean SciFact. Relevance-based reranking does not help, since a flipped copy is as relevant as its original. Detecting version conflicts needs signals beyond relevance, such as dates, provenance, or deduplication before indexing.

**Chunk size interacts with the verifier's training.** The fine-tuned verifier, trained on whole abstracts, degrades on single sentences and grows more confident while doing so. Chunking should match the format a verifier was trained on, and a verifier's confidence should not be trusted outside that format.

## Limitations

Effects of a few claims out of 300 (SciFact) are within noise, and the McNemar $p$-values are not corrected for multiple comparisons; our findings rest on repetition across corruption seeds, training seeds, verifiers and datasets. Qwen-3B and the Climate-FEVER runs use one corruption seed. Stale copies are produced by rule-based word substitution, so they may read less naturally than real outdated documents, and some copies have nothing to flip (about 20% on SciFact, 32% on Climate-FEVER), which we handle by analysing flipped copies separately. Defects target gold-evidence records, which makes their effect on evaluated claims visible but does not model how defects are distributed in real collections. All models are small (BGE-small, Qwen2.5 up to 3B, DeBERTa-v3-xsmall) because every experiment ran on free CPU runners; larger readers may react differently, and we did not study generation beyond a one-word verdict.

## Ethics and Reproducibility Statement

SciFact and Climate-FEVER are public research datasets; they are downloaded from their official releases and not redistributed. All experiments ran on free CPU runners of GitHub Actions; the workflows that produced every number are in the repository, and each corrupted corpus is regenerated from its seed and checked against the committed manifest. Code was developed with AI assistance (Claude); every reported number comes from runs whose outputs are in the repository.

## References


Jiawei Chen, Hongyu Lin, Xianpei Han, and Le Sun. 2024. Benchmarking large language models in retrieval-augmented generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*.

Florin Cuconasu, Giovanni Trappolini, Federico Siciliano, Simone Filice, Cesare Campagnano, Yoelle Maarek, Nicola Tonellotto, and Fabrizio Silvestri. 2024. The power of noise: Redefining retrieval for RAG systems. In *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*.

Thomas Diggelmann, Jordan Boyd-Graber, Jannis Bulian, Massimiliano Ciaramita, and Markus Leippold. 2020. CLIMATE-FEVER: A dataset for verification of real-world climate claims. *arXiv preprint arXiv:2012.00614*.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. In *International Conference on Learning Representations (ICLR)*.

Jeff Johnson, Matthijs Douze, and Hervé Jégou. 2019. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3).

Katherine Lee, Daphne Ippolito, Andrew Nystrom, Chiyuan Zhang, Douglas Eck, Chris Callison-Burch, and Nicholas Carlini. 2022. Deduplicating training data makes language models better. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12.

Shayne Longpre, Kartik Perisetla, Anthony Chen, Nikhil Ramesh, Chris DuBois, and Sameer Singh. 2021. Entity-based knowledge conflicts in question answering. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Quinn McNemar. 1947. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2).

Rodrigo Nogueira and Kyunghyun Cho. 2019. Passage re-ranking with BERT. *arXiv preprint arXiv:1901.04085*.

Qwen Team. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

Stephen Robertson and Hugo Zaragoza. 2009. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4).

Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H. Chi, Nathanael Schärli, and Denny Zhou. 2023. Large language models can be easily distracted by irrelevant context. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*.

Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. BEIR: A heterogeneous benchmark for zero-shot evaluation of information retrieval models. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. 2018. FEVER: a large-scale dataset for fact extraction and VERification. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*.

David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. 2023. C-Pack: Packaged resources to advance general Chinese embedding. *arXiv preprint arXiv:2309.07597*.

Jian Xie, Kai Zhang, Jiangjie Chen, Renze Lou, and Yu Su. 2024. Adaptive chameleon or stubborn sloth: Revealing the behavior of large language models in knowledge conflicts. In *International Conference on Learning Representations (ICLR)*.

Ori Yoran, Tomer Wolfson, Ori Ram, and Jonathan Berant. 2024. Making retrieval-augmented language models robust to irrelevant context. In *International Conference on Learning Representations (ICLR)*.