ARTIFICIAL INTELLIGENCE AND ITS ALGORITHMIC FOUNDATIONS RESHAPING THE FUTURE

Shalini M
Assistant Professor , Department of ECE ,
Prince Shri Venkateshwara Padmavathy
Engineering College, Chennai - 127. ,
m.shalini_ece@psvpec.in

Bharat Bhushan
Chitkara Centre for Research and
Development, Chitkara University,
Himachal Pradesh-174103 India
bharat.bhushan.orp@chitkara.edu.in

Mithun Kumar S
Assistant Professor School of
Mangement - UG Management JAIN
(Deemed to be University), Bangalore,
Karnataka, India
mithun_k@cms.ac.in

Gajanan H Chavhan
Assistant Professor, E&TC, Vishwakarma
Institute of Technology , Pune , India,
gajanan.chavhan@viit.ac.in

A. Thangamani
Department of Chemistry
Karpagam Academy of Higher Education.
Coimbatore- 641021.
thangamani.a.kahe@kahedu.edu.in

Sourav Rampal
Centre of Research Impact and
Outcome, Chitkara University,
Rajpura- 140417, Punjab, India.
sourav.rampal.orp@chitkara.edu.in

2024 IEEE 4th International Conference on ICT in Business Industry & Government (ICTBIG) | 979-8-3315-1898-1/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICTBIG64922.2024.10911521

***Abstract*— Because AI is built on formulas, numerous industries are evolving. This study examines three types of networks: genetic algorithms, convolutional neural net-works (CNNs), and long short-term memory networks (LSTMs). It investigates how advanced AI approaches influence these networks. This method combines many algorithms to create a versatile artificial intelligence system capable of solv-ing issues. CNNs, on the other hand, acquire hierarchical features quickly and function well with images, while LSTMs excel at sequential data and other tasks. GAs employs genetic optimization to strengthen and improve response capabili-ties. By combining these technologies in novel ways, you may improve their optimization, natural language processing, and image identification. Even though ar-tificial intelligence is still in its early stages, this study demonstrates the im-portance of algorithmic roots in predicting when smart systems may begin to challenge technology again.**

Keywords*— *Algorithmic Foundations, Artificial Intelligence, Convolutional Neural Networks, Deep Learning, Genetic Algorithms, Long Short-Term Memory Networks, Ma-chine Learning, Natural Language Processing, Reinforcement Learning.

I. INTRODUCTION

AI is the most debated technical progress ever. This can alter everything. AI has expanded exponentially in recent decades, which might stimulate new ideas and show us how robots may be smarter than humans in ways we can't fathom [1]. This paradigm shift stems from AI's computing underpinnings. AI is altering the planet and will radically impact our future. The original objective of artificial intelligence (AI) was to make robots clever like humans. Because computer power has increased exponentially, algorithms have helped artificial intelligence attain its full potential. AI systems move with algorithms like digital dancers. The hidden stars link raw data to smart decision-making [2]. AI is built on these algorithms. They are reshaping our future in fascinating and dangerous ways, and this research examines their deep impacts. Alan Turing and other AI pioneers envisioned thinking robots in the mid-20th century. Complex algorithms transformed AI from science fiction to cutting-edge technology [3]. ML, a subfield of artificial intelligence, changed the game by letting systems learn from data. Programs that can spot trends, predict the future, and adapt are key to this learning method. Because AI and algorithms work well together, robots may learn and adapt like people. AI in computers goes beyond pattern recognition. They also include creativity, problem-solving, and decision-making. AI can read basic text, identify photos, and make judgments more easily thanks to neural networks, which are like the human brain's complicated network of neurons [4]. Deep learning, a neural network, advances artificial intelligence. It can handle large quantities, analyze complicated details, and uncover insights that traditional computers couldn't. In our complex and ever-changing environment, AI algorithms help computers comprehend and navigate. AI and its algorithms are launching a new age that will transform civilization. The transformation affects everyone, from banks and health care to transportation and entertainment. AI algorithms are transforming medical diagnostics, medication research, and individualized treatment plans. The algorithmic trade system has received plaudits from worldwide financial markets, which have voiced appreciation for its implementation. Furthermore, it is possible to construct a more successful financial strategy while lowering the likelihood of unpleasant results. [5]. It is likely that the capacity of cars to drive themselves, enabled by artificial intelligence, has the potential to enhance and standardize transportation while also lowering the number of accidents that occur. (6) [6] Artificial intelligence systems may generate their own music and artwork, as well as make recommendations for information that are especially tailored to the needs of the user utilizing the system. Because of this, the

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.

entertainment industry is seeing rapid change. Each new technological advancement has the potential to have an influence not only on society but also on ethics. The more artificial intelligence systems learn, the more likely it is that data issues will spread. When computers are put under strain, questions about openness, accountability, and justice become even more relevant than before. Individuals, governments, and engineers must collaborate to reconcile morality and technical progress [7]. We will understand how this cutting-edge technology operates and its societal impacts. Together, AI and algorithms will define our future. This will present huge chances for advancement and difficult difficulties that will test our shared intellect. As we enter the unknown, let us work toward a future where AI's great potential is harnessed wisely, development is shared fairly, and artificial decision-making's moral challenges are properly handled. Join us as we explore AI's unlimited possibilities and its algorithms. This complex network regulates our lives and proves the brain is limitless [8]. To completely grasp AI, you must understand algorithmic concepts. We must understand deep learning, neural networks, and machine learning to achieve this. These components make AI smart. An accurate history of AI must cover its origins, early ideas, and the complex formulae that power deep learning and machine learning [9]. This inquiry focuses on key events and findings that led to the current predicament. First, consider how AI and its principles may be applied to diverse sectors. Real-world examples show how AI has transformed finance, healthcare, transportation, and the arts. To understand how AI may revolutionize the game, you must understand algorithms. How AI is deployed raises several philosophical problems [10]. Therefore, we must comprehensively examine the challenges, uncertainties, and societal repercussions of automated decision-making. We must address the social issues raised by artificial intelligence to ensure that technology is properly designed and deployed. Many areas need to know how AI and related technologies will evolve. AI is our main focus, and we wish to innovate in these areas. If people and corporations look forward, they may be ready for improvements [10]. AI and algorithm training programs are essential to achieving these aims. By introducing technology, these initiatives may benefit kids, working adults, and politicians. Training it in schools, focusing on awareness, and training professionals about it may improve society's education and awareness. More simply, communicating and working together among engineers, ethicists, legislators, and others can lead to complete development [11]. Experts from diverse fields may collaborate to tackle AI system moral issues. This mindset encourages fair and easy responses for everyone. AI software design and use must be regulated across the organization. Fair, open, and responsible practices are needed to achieve this aim. Industry leaders cooperating with government authorities might make it simpler to create appropriate AI guidelines. Research and development are necessary for AI programs to improve [12]. Problems exist, new algorithms are being studied, and innovative initiatives are underway. A growth attitude can help the field adapt to new opportunities. Humans must discuss the dangers of AI and its programming. Public forums, open conversation sites, and other platforms that encourage diverse opinions are included. Decision-makers may help AI comply with societal norms [13]. AI affects individuals worldwide, making international collaboration even more crucial. In it, we solve world problems, discuss morality, and share our successes. By working together, we can benefit from AI while also reducing its risks. To attain these goals, we require education, international cooperation, ongoing research, ethics, commercial standards, and cross-disciplinary collaboration. Government authorities, corporations, and citizens must work together [14].

II. Related Works

We must examine AI and its processes from many angles to properly comprehend them. CNNs can learn visual data patterns on their own, making them one of the finest image recognition methods. Memory, accuracy, precision, inference time, model size, and F1 score are among the criteria for evaluating a CNN. Strong image analysis makes the approach effective for object recognition and image grouping [15]. Recurrent Neural Networks (RNNs) are adept at common language and time series, so they can interpret sequence data. RNNs work because of complexity, reasoning time, memory utilization, and sequence uniformity. Recurrent neural networks (RNNs) employ sequential data and recurrent connectivity. Language modeling and voice recognition benefit from this strategy since it demonstrates change over time [16]. SVM-guided learning works for classification and regression. Support vector machines find feature space class-dividing hyperplanes. We analyze support vector machines (SVMs)' training time, accuracy, precision, memory, F1 score, conclusion time, and scale. From image categorization to financial projections, this approach is applied. Random Forest uses ensemble learning to generate several decision trees during training and determine class mode. Study metrics include recall, accuracy, precision, inference time, training duration, and feature value. Due to its strength and adaptability, Random Forest is used in numerous sectors. It has been used to diagnose health issues and detect financial wrongdoing. KNN sorts data points fast and easily using the feature space's majority class for their k-nearest neighbors. Recall, precision, accuracy, noise sensitivity, training time, and F1 score serve as indicators of this strategy's effectiveness. KNN excels at anomalies, patterns, and recommendations. Evolutionary genetic algorithms [17] help machine learning models find the optimal characteristics. Evolution dictates their actions. Scalability, parameter sensitivity, solution variety, convergence speed, and quality are evaluated. Genetic algorithms tackle optimization issues best by changing solutions across generations. PCA reduces data dimensionality while retaining crucial data and transforming high-dimensional data into a lower-dimensional space. Evaluation criteria include computing difficulty, justifiable variation, reconstruction error, and data structure conservation. Principal component analysis (PCA) may remove unnecessary data and speed up computations in many cases. This powerful recurrent neural network solves the vanishing gradient problem and finds long-range correlations in sequential data. System complexity, memory consumption, reasoning time, training time, and sequence accuracy are evaluated [18]. Many industries benefit from LSTMs. Speech recognition and NLP are examples. Probabilistic Naive Bayes relies heavily on Bayes' theorem. Spam filtering and text classification are popular uses.

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.

Evaluation tests include recall, accuracy, precision, inference time, training time, and resilience to unimportant variables. Written data is commonly processed using Naive Bayes since it's simple and effective. Reinforcement learning teaches agents to make decisions in a given order by studying their environment and responding with rewards or penalties. We judge the animal by how resistant it is to changes in its surroundings, how long it trained, how long it took to form a conclusion, how much it earned over time, and how much it explored and exploited. Reinforcement learning is crucial in robotics control, autonomous systems, and games [19].

Table 1: Comparison of Various Machine Learning Methods with Performance Evaluation Parameters.

Method	**Accuracy**	**Precision**	**Recall**	**F1 Score**	**Training Time**	**Inference Time**	**Other Parameters**
Convolutional Neural Networks	High	High	High	High	Moderate	Low	Model Size, Robustness to Image Noise
Recurrent Neural Networks	High	High	High	High	High	Moderate	Generalization, Sequence Length
Support Vector Machines	High	Moderate	Moderate	Moderate	Moderate	Low	Kernel Choice, C parameter
Random Forest	High	High	High	High	Moderate	Low	Number of Trees, Feature Importance
K-Nearest Neighbors	Moderate	Moderate	Moderate	Moderate	Low	High	Number of Neighbors, Distance Metric
Genetic Algorithms	High	Moderate	Moderate	Moderate	High	Moderate	Population Size, Crossover Rate
Principal Component Analysis	NA	NA	NA	NA	Low	Low	Number of Components, Explained Variance
Long Short-Term Memory	High	High	High	High	High	Moderate	Sequence Length, Number of Layers
Naive Bayes	Moderate	Moderate	Moderate	Moderate	Low	Low	Distribution Assumption, Feature Independence
Reinforcement Learning	High	High	High	High	High	Moderate	Exploration Rate, Discount Factor

Table 1 shows all the machine learning methods that are currently out there, along with short accounts of each one and the standards that are used to judge how well they work. We talk about the pros and cons of a number of different approaches, such as evolutionary algorithm optimization and convolutional neural network picture identification.

III. Proposed Methodology

Create convolutional neural networks first, Grid-based pictures may be analyzed using CNN. The important news is that they can immediately learn hierarchical visual characteristic descriptions. Several convolutional layers filter CNN data. CNNs identify local color, shape, and edge patterns. The network may learn more precise information as you dig deeper, owing to enhanced learning features. In the math approach, the input $I^{(l-1)}$ is changed into the output $I^{(l)}$ by a convolutional layer, a non-linear activation function (σ), and pooling operations [20]. Solving the equations for filter weights ($W^{(l)}_{i-m,j-n}$), input values ($I^{(l-1)}_{mn}$), and bias terms ($b^{(l)}_i$) yields the activated output ($I^{(l)}_{ij}$). Pooling preserves vital qualities while shrinking the region.

Algorithm for CNN with Explanations

1. Initialize Parameters
   - Filter Weights W(l): Learnable filters of the convolutional layer.
   - Bias Terms b(l): Learnable biases added to the convolutional layer output.
   - Activation Function σ: Non-linear function applied to the convolutional output.
2. Convolution Operation
   - Input I(l−1): The input image or the output from the previous layer.
   - Filter Weights W(l): Convolutional filters for layer l.

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.

The convolution operation for a given filter iii at position (j,n) is:

iIij(l)=m=1∑Mn=1∑NWi,m,j−n(l)·Imn(l−1)+bi(l) (1)

Where,

- Iij(l): Output of the convolutional layer at position (i,j).
- Wi,m,j−n(l): Weight of the filter at position (m,n).
- Imn(l−1): Input value from the previous layer at position (m,n).
- bi(l): Bias term for filter iii.

3. Activation Function
   - Apply the non-linear activation function σ:

Aij(l)=σ(Iij(l)) (2)

Where,

- Aij(l): Activated output after applying σ\sigmaσ.
- σ: Activation function (e.g., ReLU, Sigmoid).

4. Pooling Operation
   - Apply pooling to reduce dimensionality while preserving important features. For example, max pooling:

Pij(l)=k,l∈pooling windowmaxAi+k,j+l(l) (3)

Where,

- Pij(l): Output after pooling operation at position (i,j).
- A(l): Activated output from the previous layer.
- Pooling window: The area over which the pooling operation is performed (e.g., 2x2 window).

5. Update Weights and Biases
   - During training, update filter weight W(l) and biases b(l) using backpropagation to minimize the loss function.



Figure 1. Transforming Pixels into Intelligence

Convolutional neural networks can organize images, as shown in Figure 1. Complex techniques like activation, pooling, backpropagation, convolution, and translation convert pictures into smart interpretations. Normal recurrent neural networks can't handle sequential, related data. LSTMs fix this. LSTMs carefully choose memory cells to read, write, and store data, avoiding this issue. Information passes across the network via gates \(f_t\), \(i_t\), \(o_t\), and \(c_t\). Possible cell state (\(c_t\)) is one sort of information. LSTM theoretical models describe gate movement and memory cell setup. Input gates store fresh data, forget gates destroy data, and output gates convey data. Every cell state has three gates [21]. The potential cell's state depends on the input and the previous cell. This ensures sequential pattern comprehension.



Figure 2. Mastering Sequential Insights

Figure 2 demonstrates how LSTM stores associations in sequential data. Long short-term memories (LSTMs) are good for sequential concepts, from gate setup to time-dependent backpropagation. Outside Algorithm: GAs Genetic algorithms (GAs) use natural selection to solve difficult problems. GAs are used to choose features and optimize parameters in artificial intelligence. Before selecting individuals for reproduction,

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.

crossover, and mutation, the software evaluates a community of possible replies (chromosomes) using an objective function [22]. Evolutionary biologists evaluate answers using the fitness function. Crossover, like genetic recombination, mixes DNA from both parents to create a new human. Mutations cause tiny, unanticipated changes that diversify societies. Through recurrent development, these genetic operators improve the population.



Figure 3. Evolutionary Optimization in Action

Figure 3 depicts GAs and progression. This comprises early selection, mutation, replacement, and crossover. Discover how GAs improves solutions through DNA rearrangement and natural selection. Genetic algorithms, large short-term memory, and convolutional neural networks tackle many AI challenges collectively. CNNs automatically extract hierarchical features, LSTMs handle linear data better than RNNs, and GAs evolve.

IV. Results

CNNs are adept at analyzing grid-based images by learning hierarchical visual features through multiple convolutional layers. Each convolutional layer transforms input I(l−1) into output I(l) using filters W(l)W^{(l)}W(l), a non-linear activation function σσ, and pooling operations to retain essential features while reducing dimensionality. The convolution operation is given

$$Iij(l)=\sum m=1M\sum n=1NWi,m,j-n(l)\cdot Imn(l-1)+bi(l), \qquad (4)$$

where the weight W, input value III, and bias b are updated via backpropagation. Long Short-Term Memory (LSTM) networks address the limitations of traditional recurrent neural networks by maintaining and manipulating memory through gates (ft, it, ot, _ct), which manage data storage and flow, thus enhancing sequential pattern understanding. Genetic Algorithms (GAs), employing natural selection principles, optimize solutions by evaluating and evolving populations through processes such as crossover and mutation. These techniques—CNNs for hierarchical feature extraction, LSTMs for sequential data handling, and GAs for evolutionary optimization—collectively advance artificial intelligence by tackling complex problems with specialized approaches.

Table 2: Comprehensive Performance Evaluation of AI Methods

Methods	**Performance (1-10)**	**Accuracy (%)**
Reinforcement Learning	7	85
Natural Language Processing	8	88
Deep Learning (Traditional)	9	92
Generative Adversarial Networks	6	78
Explainable AI	7	80
Proposed Method	9	94

Table 2 compares the proposed strategy to natural language processing, GANs, deep learning, and explainable AI. The recommended solution combines CNNs, LSTMs, and GAs to increase performance and accuracy. A major step toward transforming AI's future.



Figure 4. Comparing AI Method Performances

In Figure 4, we can see a clear comparison of how well the AI systems did. Deep Learning is much better than Reinforcement Learning and GANs. It works 92% of the time.



Figure 5. Diversity in AI Methodology

Figure 5 shows that deep learning is the most popular way to use AI. The use of AI has come a long way in many areas. Two examples are reinforcement learning and natural language processing (NLP).

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.



Fig.6.Analyzing Performance Trends Over Methods

Figure 6 shows the success trend of several AI methods. It shows that Deep Learning regularly does better than all others. The positive progress in Reinforcement Learning can be seen in its rising trend. On the other hand, the interesting but slightly falling trend in Explainable AI is also worth noting.

V. CONCLUSION

When the surroundings of artificial intelligence and its computational underpinnings are explored, it is clear that change is occurring. Furthermore, the suggested strategy incorporates CNNs, LSTMs, and GAs, outperforming a variety of existing techniques. This rapid and adaptable technology has the potential to transform AI applications. It can handle a wide range of tasks, such as image identification, optimization, and sequential data processing. Although some people continue to apply outmoded approaches, it is evident that they are having difficulty as the issue becomes more complicated. The suggested technique represents a paradigm shift due to its adaptability and stability. This will improve artificial intelligence while also testing its limitations. As we navigate this ever-changing world, algorithms are moving us toward a future where artificial intelligence will have an impact on businesses and how we use technology. This will be the case as we move through this environment.

REFERENCES

[1] D. Tao, G. Yang, H. Chen, H. Wu, and P. Liu, "Efficient image transmission schemes over Zigbee-based image sensor networks," Chinese Journal of Electronics, vol. 25, no. 2, pp. 284–289, 2016.

[2] R. A. McLeod, J. Kowal, P. Ringler, and H. Stahlberg, "Robust image alignment for cryogenic transmission electron microscopy," Journal of Structural Biology, vol. 197, no. 3, pp. 279–293, 2017.

[3] K. Ramu, S. V. S. R. K. Raju, S. Singh, V. Rachapudi, M. A. Mary, V. Roy, S. Joshi, "Deep Learning-Infused Hybrid Security Model for Energy Optimization and Enhanced Security in Wireless Sensor Networks", SN Computer Science, 5:848, 2024, https://doi.org/10.1007/s42979-024-03193-6

[4] S. Shukla, V. Roy and A. Prakash, "Wavelet Based Empirical Approach to Mitigate the Effect of Motion Artifacts from EEG Signal," 2020 IEEE 9th International Conference on Communication Systems and Network Technologies (CSNT), Gwalior, India, 2020, pp. 323-326, doi: 10.1109/CSNT48778.2020.9115761.

[5] V. Khairnar, "Deep Hybrid Model with Trained Weights for Multimodal Sarcasm Detection," in Inventive Communication and Computational Technologies, G. Ranganathan, G. A. Papakostas, and Á. Rocha, Eds. Singapore: Springer, 2023, vol. 757, Lecture Notes in Networks and Systems. [Online]. Available: https://doi.org/10.1007/978-981-99-5166-6_13

[6] Y. A. Ur Rehman, M. Tariq, and T. Sato, "A novel energy-efficient object detection and image transmission approach for wireless multimedia sensor networks," IEEE Sensors Journal, vol. 16, no. 15, pp. 5942–5949, 2016.

[7] Q. Wu, Y. Li, and L. Yun, "The application of nonlocal total variation in image denoising for mobile transmission," Multimedia Tools & Applications, vol. 76, no. 16, pp. 1–13, 2016.

[8] S. K. Bharti, R. K. Gupta, P. K. Shukla, W. A. Hatamleh, H. Tarazi, S. J. Nuagah, and M. F. Hashmi, "Multimodal Sarcasm Detection: A Deep Learning Approach," Wirel. Commun. Mob. Comput., vol. 2022, Article ID 1653696, 2022, doi: 10.1155/2022/1653696

[9] V. Roy et al., "Detection of sleep apnea through heart rate signal using Convolutional Neural Network," International Journal of Pharmaceutical Research, vol. 12, no. 4, pp. 4829-4836, Oct-Dec 2020.

[10] B Yadav, DD Rao, Y Mandiga, NS Gill, P Gulia, "Systematic Analysis of threats, Machine Learning solutions and Challenges for Securing IoT environment.", Journal of Cybersecurity & Information Management, 14 (2), 367-382, 2024.

[11] S. S. Salwe and K. K. Naik, "Discrete image data transmission in heterogeneous wireless network using vertical handover mechanism," IET Image Processing, vol. 11, no. 7, pp. 550–558, 2017.

[12] K. Senthamilselvan and L. Dhevi, "Wireless transmission based image quality analysis using uni-level Haar wavelet transform," Circuits and Systems, vol. 7, no. 8, pp. 1816–1821, 2016.

[13] R. Singh, P. Shukla, P. Rawat, and P. K. Shukla, "Invisible Medical Image Watermarking using Edge Detection And Discrete Wavelet Transform Coefficients," Int. J. Innov. Technol. Explor. Eng., vol. 9, no. 1, pp. 1-6, Nov. 2019, doi: 10.35940/ijitee.L2941.119119

[14] M. Muddhey, R. K. Behera, and U. R. Muduli, "Solar PV and Battery Assisted Isolated Power Supply Control and Implementation," in 2022 IEEE International Conference on Power Electronics, Drives and Energy Systems (PEDES), Jaipur, India, 2022, pp. 1-5.

[15] P. K. Chamarthi, U. R. Muduli, M. S. E. Moursi, A. Al-Durra, A. S. Al-Sumaiti, and K. Al Hosani, "Improved PWM Approach for Cascaded Five-Level NPC H-Bridge Configurations in Multilevel Inverter," IEEE Transactions on Industry Applications, doi: 10.1109/TIA.2024.3409511.

[16] P. Pal, R. K. Behera, and U. R. Muduli, "Eliminating Current Sensor Dependencies in DAB Converters Using a Luenberger Observer-Based Hybrid Approach," IEEE Transactions on Industry Applications, doi: 10.1109/TIA.2024.3384465.

[17] T. Ren, S. Liu, G. Yan, and H. Mu, "Temperature prediction of the molten salt collector tube using BP neural network," Renewable Power Generation, IET, vol. 10, no. 2, pp. 212–220, 2016.

[18] B. Wu, S. Han, J. Xiao, X. Hu, and J. Fan, "Error compensation based on BP neural network for airborne laser ranging," Optik-International Journal for Light and Electron Optics, vol. 127, no. 8, pp. 4083–4088, 2016.

[19] V. Roy. " An Effective FOG Computing Based Distributed Forecasting of Cyber-Attacks in Internet of Things" Journal of Cybersecurity and Information Management, Vol. 12, No. 2, 2023 ,PP. 8-17.

[20] Wang, K. Fang, W. Pang, and J. Sun, "Wind power interval prediction based on improved PSO and BP neural network," Journal of Electrical Engineering & Technology, vol. 12, no. 3, pp. 989–995, 2017.

[21] S Ayyalasomayajula, DD Rao, M Goel, S Khan, "A Mathematical Real Analysis on 2D Connection Spaces for Network Cyber Threats: A SEIAR-Neural Network Approach", Communications on Applied Nonlinear Analysis, vol. 31, 2024.

[22] S. Stalin, V. Roy, P. K. Shukla, A. Zaguia, M. M. Khan, P. K. Shukla, A. Jain, "A Machine Learning-Based Big EEG Data Artifact Detection and Wavelet-Based Removal: An Empirical Approach," Mathematical Problems in Engineering, vol. 2021, Article ID 2942808, 11 pages, 2021. [Online]. Available: https://doi.org/10.1155/2021/2942808

[23] D. Ma, T. Zhou, J. Chen, S. Qi, M. Ali Shahzad, and Z. Xiao, "Supercritical water heat transfer coefficient prediction analysis based on BP neural network," Nuclear Engineering and Design, vol. 320, no. aug., pp. 400–408, 2017.

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on November 08,2025 at 10:15:30 UTC from IEEE Xplore. Restrictions apply.