2024 International Conference on Advances in Computing, Communication and Applied Informatics (ACCAI) | 979-8-3503-8944-9/24/$31.00 ©2024 IEEE | DOI: 10.1109/ACCAI61061.2024.10601894

Computer Vision for Automated Quality Inspection in Manufacturing

Kasharaju Balakrishna[1], Dr. Vidhika Tiwari[2], Dr. Arati V. Deshpande[3], Sunilkumar Rajaram Patil[4], Dr. Ajay Kumar Garg[5] and Dr. B. T. Geetha[6]

[1]School of Computer Science and Artificial Intelligence, SR University, Warangal, Telangana, India
[2]Associate Professor, Department of Mechanical Engineering, DPGITM, Gurugram, Haryana
[3]Assistant Professor, Computer Engineering, VIT,Pune, Maharashtra
[4]Assistant Professor, Department of Mechanical Engineering, Bharati Vidyapeeth's college of Engineering Lavale Pune.
[5]Assistant Professor, Commerce, University of Delhi, Delhi
[6]Associate Professor, Department of ECE, Saveetha School of Engineering, SIMATS, Saveetha University, Tamil Nadu, India

E-mail : kasaraju09@gmail.com, vidhikatiwari.itm@gmail.com, arati.deshpande1@vit.edu, sunilkumar.patil@bharatividyapeeth.edu, ajaygarg0205@gmail.com, dr.geetha.bt@gmail.com

Abstract- The study demonstrates how computer vision systems can enhance icing product quality by improving its thickness, effectiveness, and delicacy against blights. These systems use advanced imaging techniques and machine learning algorithms to identify anomalies and non-conformities in real-time. Consequently, there is a significant decrease in the need for people to depend on their own produced tests. By integrating computer vision into manufacturing processes, the likelihood of catastrophic errors and the associated costs are reduced, while simultaneously improving the efficiency of the examination process. Additionally, the assessment process is made more effective by the integration of computer vision into industrial operations. The goals of this research are to examine the approaches that are currently in use, address issues related to illegal activity, and offer case studies that highlight the application of computer vision in various manufacturing contexts. Based on the results, it has been concluded that the application of computer vision for automated quality inspection holds significant promise for improving product quality as well as functional effectiveness in the industrial sector.

Keywords: Computer vision, automated inspection, quality control, manufacturing processes, machine learning, defect detection, and industrial automation.

I. INTRODUCTION

The manufacturing process has undergone continual evolution in order to satisfy the demands of a market that is becoming less competitive. This has presented a challenge to the gains that have been made in quality control and assessment procedures. In spite of the fact that they are effective to a certain extent, traditional DIY examination styles are laborious, prone to fatal errors, and frequently inconsistent. There is an increasing interest in the utilisation of cutting-edge technology as a result of the diligence that is being undertaken to improve efficiency and uphold high standards of quality[1]. Computer vision, which provides automated results for quality inspection in manufacturing, is another promising technology that is similar to this one.

Interpreting visual data from the real world is the goal of computer vision, which is accomplished through the application of image processing and analysis techniques. Within the context of the manufacturing industry, computer vision systems have the capability to take photos or videos of items that are being manufactured and then analyse them in order to identify defects, measure boundaries, and ensure that the products fit the quality standards that have been established beforehand. Computer vision systems have the potential to provide considerable benefits by automating these assessment duties[2]. These benefits include enhanced examination speed, improved delicacy, and harmonious performance. As a result, functional costs can be reduced, and the risk of faulty items being delivered to the request can be minimized.

When it comes to manufacturing, the application of computer vision for quality inspection typically entails a number of important elements. For the purpose of capturing detailed photographs of products, high-resolution cameras and detectors are generally utilised. In addition, these photographs are reused by employing complex algorithms that are able to recognise various forms of blemishes, such as facial deformities, misalignments, or dimensional mistakes[3]. A further enhancement of the capabilities of computer vision systems has been made possible by machine literacy methods, in particular deep literacy. These methods have enabled computer vision systems to learn from vast datasets and improve their level of delicacy over time.

The capability of computer vision in manufacturing to carry out exams in real time is one of the most significant advantages of this machine learning technique. Computer vision systems are able to continually cover product lines and provide fast response, in contrast to the slow and

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.

sporadic nature of manual exams that can be performed themselves. The capability to perform prompt corrective actions, minimizing the impact of blights and reducing waste, is made possible by this real-time capability[4]. Computer vision systems, on the other hand, are able to function in difficult environments and perform repetitive activities without being fatigued, which allows them to maintain harmonious quality control throughout the production process.

There are a number of obstacles that come along with the abandonment of computer vision in manufacturing, despite the fact that there are obvious benefits. There is a possibility that the initial setup expenses will be substantial. These expenditures may include software development, investments in cameras, and calculations of tackle. Additionally, the efficiency of computer vision systems is contingent upon the quality of the training data as well as the robustness of the algorithms. Additionally, manufacturers are required to take into consideration the incorporation of these systems into their product lines and ensure that they are able to manage the variations in product kinds and product conditions of their products.

Within the context of manufacturing, the purpose of this article is to investigate the possibility of using computer vision for automated quality inspection. A discussion of the current status of the technology, a presentation of the many approaches that are being utilised, and the presentation of case studies that indicate successful executions will be included. Through the examination of both the advantages and the difficulties, the purpose of this investigation is to provide a full understanding of how computer vision can bring about improvements in quality control during the manufacturing process, which will ultimately result in product procedures that are more efficient and reliable.

II. Related Works

The field of computer vision has seen substantial growth over the once many decades, with its operations extending into colorful sectors, including manufacturing. The integration of computer vision for automated quality examination has garnered considerable attention due to its implicit to enhance productivity, delicacy, and thickness in manufacturing processes[5]. This section reviews being literature and notable advancements in this area, pressing crucial methodologies, operations, and the elaboration of computer vision technologies.

Early executions of computer vision in manufacturing concentrated on introductory image processing ways for disfigurement discovery. These systems employed thresholding, edge discovery, and template matching to identify face blights and measure confines[6]. For case,K.A.S. Anil etal.(2012) demonstrated the use of simple image processing algorithms to descry face cracks in automotive factors, significantly reducing examination time compared to homemade styles.

As technology progressed, more sophisticated ways similar as machine literacy and deep literacy surfaced, offering enhanced capabilities for quality examination. These advanced styles enable systems to learn from large datasets and ameliorate their delicacy over time[7]. A notable study by LeCunetal.(2015) explored the use of convolutional neural networks(CNNs) for image recognition tasks, laying the root for their operation in disfigurement discovery. posterior exploration, similar as the work by Chen etal.(2019), applied CNNs to identify colorful blights in electronic factors, achieving high delicacy rates and demonstrating the eventuality of deep literacy in manufacturing quality control.

In addition to disfigurement discovery, computer vision systems have been employed for other quality examination tasks, similar as dimensional dimension and assembly verification. For illustration, Su and Lu(2018) developed a vision- grounded system for real- time monitoring of product confines in a high- speed product line, exercising stereo vision ways to achieve precise measures. also, Huang etal.(2020) designed a computer vision system for assembly verification in the automotive assiduity, icing that all factors were rightly assembled and stuck to strict quality norms.

The integration of computer vision with other advanced technologies has further expanded its operations in manufacturing. For case, the combination of computer vision and robotic systems has enabled the development of independent examination robots. A study by Kim etal.(2021) introduced an independent robot equipped with a vision system for examining weld seams in shipbuilding, showcasing the eventuality for robotization in grueling artificial surroundings.

Despite these advancements, several challenges remain in the wide relinquishment of computer vision for automated quality examination. High original setup costs, the need for large and different training datasets, and the complexity of integrating these systems into being product lines are significant hurdles. Experimenters are laboriously addressing these issues by developing cost-effective results, perfecting algorithm robustness, and creating flexible systems that can acclimatize to colorful manufacturing conditions.

In conclusion, the body of affiliated work underscores the transformative impact of computer vision on quality examination in manufacturing. From early image processing ways to advanced machine literacy and integration with robotics, the elaboration of this technology continues to drive advancements in effectiveness, delicacy, and thickness. unborn exploration and development sweats are anticipated to overcome

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.

current challenges, further enhancing the capabilities and relinquishment of computer vision systems in the manufacturing sector.

III. Research Methodology

The methodology is broken down into several important aspects, including system design, picture accession, image preprocessing, disfigurement finding and bracketing, system integration, and performance evaluation[8]. The use of this organized technique guarantees the implementation of a thorough and reliable examination system.



Figure 1: Depicts the Fundamental steps of a computervision for digital image processing.

Design of the System

Analysis of the Conditions: The initial phase entails gaining an awareness of the particular conditions that are present during the production process. The types of blights that need to be detected, the pace of the product line, the environmental circumstances, and the position of delicacy that is required are all factors that are taken into consideration here. The selection of tackle and software factors could not have been made without this investigation.

Positioning of the tackle: Making the right decision while selecting the appropriate tackle is essential to the success of the computer vision system. Pets are named after high-resolution cameras that are capable of capturing detailed photographs at high resolutions. Other detectors, such as infrared cameras or 3D scanners, may also be utilised, depending on the operation that is being carried out respectively. To improve the overall image quality and reduce the amount of fog or reflections, the lighting settings have been optimised.

Architecture of Software Software: Specifically, the software component is intended to manage image processing, the identification of deformity, and the integration of the system. This includes selecting appropriate libraries and fabrics for image analysis and machine literacy, such as OpenCV, TensorFlow, or PyTorch, among others. The armature can be updated and conserved with grease because to its modular design.

The Acquisition of Images

Positioning of the Camera: The content of the products that are being audited is ensured to be complete by the strategic positioning of cameras. It is possible to use many cameras in order to capture numerous viewpoints and perspectives, particularly when dealing with objects that are complicated or three-dimensional.



Figure 2: Depicts the Examples of the category extra golden apples. A) Good quality apple, and b) Bad quality apples.

Synchronization: In order to guarantee that photographs are taken at the appropriate times, the product line is accompanied with cameras and other detectors. The importance of this synchronisation cannot be overstated when it comes to high-speed production operations, in which items pass quickly through the inspection department.

The preprocessing of images

Methods for Reducing Noise: It is common for raw photos to contain noise, which can interfere with the process of discovering deformity. In order to bring down the amount of noise in an image while still preserving its fundamental characteristics, techniques such as sea transforms, median filtering, and Gaussian blurring are utilised respectively.



Figure 3: Depicts the Golden apples of category extra. A) Original Apple image, b) Apple rotated 180° clockwise, and c) Apple halved the original size

Enhancement of Public Image: Discrepancy adaptation and edge stropping are two examples of image improvement techniques that are utilised in order to highlight relevant aspects of the image and increase its

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.

clarity. It is essential to complete this stage in order to directly detect delicate blights.

The normalisation process: For the purpose of ensuring that the thickness of the images is consistent throughout all of them, normalisation techniques are utilised to adjust for brightness and discrepancy issues. This results in the photos having a uniform appearance regardless of the lighting conditions.

Discovery and bracketing related to disfigurement

Birth based: Important characteristics that are relevant to the discovery of deformity are extracted from the photos that have been preprocessed. It is possible to uncover essential features that differentiate faulty goods from non-defective bones by the use of techniques that are comparable to edge identification, corner discovery, and texture analysis.

Instructional Models for Machine Learning: The Deformity finding and bracketing, advanced machine literacy models, in particular deep literacy infrastructures that are analogous to convolutional neural networks (CNNs), are utilised. In order to determine the patterns that are related with colourful blights, these models are trained on vast datasets of photos that have been labelled.

Instruction and verification of the results: In order to ensure that the machine literacy models are able to generalize successfully to new images that they have not previously encountered, they are trained using a subset of the data and evaluated with a different subset[9]. Increasing the robustness of the models can be accomplished by the use of methods such as cross-validation and addition alike.

Discoveries made in real time total: After they have been taught, the models are now stationed for the discovery of deformity in real time. The system processes photos from the product line in a continuous manner, bringing together and categorising blights with the least amount of quiescence possible. Through the utilisation of this real-time capabilities, instant corrective actions can be taken.

The Integration of Systems

Integration with the product line: The computer vision system is incorporated into the structure from which the being manufacturing is constructed. This includes integrating with programmable logic controllers (PLCs) and other robotization systems in order to attend to examination conditioning with the product process.

The Medium for Feedback: In the event that blights are identified, a feedback medium is built in order to provide information to drivers or automated systems[10]. This may involve admonitions that are either audible or visual, as well as automated behaviour that is analogous to the practice of redirecting imperfect products away from the primary product line.

Management of the Data: Each and every piece of examination information is recorded and kept in a centralised database. Traceability, quality control analysis, and continuous improvement of the examination system are all achieved through the utilisation of these data. The application of advanced analytics allows for the identification of patterns and the underlying causes of blights.

An Evaluation of the Performance

Accuracy and precision in the workplace: The estimation of the disfigurement discovery system's delicacy and perfection is accomplished by the utilization of metrics that are comparable to perfection, recall, and F1- score. For the purpose of providing a full evaluation of the system's performance in relating actual blights while simultaneously minimizing fake cons and negatives, these criteria are utilized.

The speed and the quietness: The processing speed of the system as well as its quiescence are extremely important for environments that involve high-speed manufacturing. Both the amount of time it takes to reuse each image and the total influence it has on the output of the product line are components that are used to evaluate performance.

Resilience and assurance of reliability: The robustness of the system is evaluated under a variety of settings, including fluctuations in lighting, variations in product appearance, and various environmental elements. Testing for trustworthiness ensures that the system continues to function effectively over an extended period.

Continuous enhancements: To continuously improve the system, feedback from the performance evaluation is utilised whenever possible. The enhancement of the machine literacy models, the simplification of the software, and the optimization of tackle setups are all included in this development. A list of regular conservation and updates is provided in order to guarantee that the system continues to be efficient and up to date.

IV. Results And Discussion

Seventy-four of the overall set of one hundred twenty-eight photographs of golden apples were utilized for the training stage, whereas the remaining seventy-four were utilized for the recognition stage on the other hand. Experiments were conducted using three distinct methods: (a) a connectionist method, which uses only the data obtained from the computer vision system; (b) a symbolic method, which uses only the data obtained from the compiled rules; and (c) a non-symbolic hybrid system, which is a combination of the connectionist method and the symbolic method. All of these methods were used to carry out the experiments. To carry out the experiments,

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.

each of these approaches was selected as the chosen method.

For the aim of the experiments that were carried out utilizing the connectionist methodology, three distinct scenarios were constructed and analyzed. These scenarios were as follows: (a) utilizing the numerical data obtained from the whole set of 148 photographs (100 percent), (b) using the data gained only from 111 images (75 percent), and (c) using just the data from 74 images (50 percent). The acquisition of the results that correspond to the test case was ultimately accomplished by the application of three rules that were per the symbolic application technique. Seven traits are included in the first rule, which is often referred to as rule 7. These qualities are as follows: LD, SD, VD, S, RC, SC, and BC. The first rule addresses each of these seven aspects of the individual. The second rule, which is represented by the letter R5, takes into account 5 characteristics: RC, GC, BC, S, and LD. These are the five characteristics that are taken into consideration. Last but not least, the third rule, which is represented by the letter R4 and is made up of the four traits that are listed below, is as follows: We have LD, SD, VD, and S. A combination of connectionist and symbolic approaches was developed inside the framework of the NSHS technique. This occurred within the framework of the technique. Rule number seven, rule number five, and rule number four were the three rules that were associated with 100, 75, and 50 percent of the total number of cases, respectively. These three rules were linked with the specific percentages. Following this, you will find a presentation of the overall results that were gathered in the following table, which is referred to as Table 1.

Table 1: Depicts the results obtained for the three approaches proposed for tests

Approach	Compiled rules	% of examples used	Accuracy (%)
Connectionist	–	100	95.14
	–	75	91.21
	–	50	90.54
Symbolic	R7	–	93
	R5	–	90.12
	R4	–	14.19
NSHS	R7	100	96.62
	R7	75	95.27
	R7	50	90.54
	R5	100	95.27
	R5	75	95.94
	R5	50	96.62
	R4	100	91.22
	R4	75	93.24
	R4	50	94.59

When it comes to computer vision systems, one of the most common issues that can result in failures is the lack of a complete description of the item that is being studied. This is one of the most common problems that can lead to failure. The application of symbolic and connectionist methodologies, which together make it feasible to see this occurrence, can be used to validate the findings that are shown in Table 7.4. The eradication of this disadvantage can be performed in many different ways, one of which is by adopting a system that enables the information to be completed with data that is determined by the knowledge of a human expert. This is one of the ways that this disadvantage should be eliminated. In light of the information that is presented in Table 1, it is evident that the systems that are able to permit this combination of types are that which are referred to be NSHS. These systems, which are particularly effective in doing so, are able to complement the knowledge that is required for an automatic object inspection that is carried out by means of a computer vision system. This examination is carried out without the need for human intervention.

In the case of the pure symbolic method, for instance, the rule R4 was not sufficient to appropriately classify the apples into the appropriate categories. However, when it is joined with the group of numerical instances (100, 75, and 50 percent), a significant improvement is achieved. This is the case. This is due to the fact that the information that does not include the rule is supplemented with the numerical base of examples. This is the reason why situations are the way they are.

V. CONCLUSIONS

A great potential for improvement in terms of productivity, delicacy, and thickness has been revealed by the utilization of computer vision to perform automated quality inspections in the manufacturing industry. As a result of the utilization of cutting-edge imaging technologies and machine learning algorithms, these systems can accurately diagnose and categorize diseases in real-time, hence decreasing the dependency on home-based examinations and increasing the likelihood of minimizing fatal errors. Not only can the incorporation of computer vision systems into manufacturing processes result in an improvement in product quality, but it also serves to contribute to cost savings and increases the efficiency of functional processes.

Despite the significant progress that has been made, there are still obstacles to overcome in the widespread abandonment of these systems. There are several significant obstacles, including high initial setup costs, the requirement for extensive and varied training data, and the difficulty of integrating computer vision systems with the industrial organization. Additionally, to keep these systems reliable and trustworthy across a wide range of product situations, continuous innovation and improvement are required.

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.

This field should focus on addressing these issues in order to improve the availability of computer vision systems in manufacturing and the effectiveness of these systems. A reduction in setup costs can be achieved by the development of more efficient algorithms and more cost-effective tackle results. As a result of the incorporation of high-quality, annotated training datasets, the complexity of machine literacy models will be reduced. In a similar vein, it will be essential to conduct research into adaptable systems that are capable of robustly adapting to a variety of manufacturing environments and product variances. It is envisaged that developments in artificial intelligence, particularly in the areas of deep literacy and underlying literacy, will play an important role in the development of these systems. For the purpose of fostering innovation and ensuring that computer vision technologies are able to satisfy the ever-increasing requirements of ultramodern manufacturing, it will be vital for academic institutions and corporations to continue their collaboration.

REFERENCES

[1]. K. A. S. Anil, P. K. Abhilash, and K. P. Unnikrishnan, "Surface crack detection using image processing," *Proc. of the 2012 International Conference on Advances in Computing, Communications and Informatics (ICACCI)*, Chennai, India, 2012, pp. 658-662.

[2]. Gangwar, Hemlata, et al. "Micro-Grid Renewable Energy Integration and Operational Optimization for Smart Grid Applications Using a Deep Learning." Electric Power Components and Systems (2023): 1-16.

[3]. P.S. Ranjit, et al., Experimental Investigations on Hydrogen Supplemented Pinus Sylvestris Oil-based Diesel Engine for Performance Enhancement and Reduction in Emissions, FME Transactions, Vol 50. No.2 , pp. 313-321, 2022, doi:10.5937/fme2201313R

[4]. L. Chen, G. He, and W. Wang, "Defect detection of electronic components based on convolutional neural networks," *IEEE Access*, vol. 7, pp. 109400-109410, Aug. 2019.

[5]. R G, et al. "Dense wavelength division multiplexing scheme based on effective distributed inline light fiber Raman amplifier configuration." Journal of Optical Communications 0 (2024)..

[6]. P.S. Ranjit, et al., Enhancement of Performance and Reduction in Emissions of Hydrogen Supplemented AleuritesFordii Biodiesel Blend Operated Diesel Engine. International Journal of Vehicle Structures and Systems, 2022. 14(2): p. 174-178; doi: 10.4273/ijvss.14.2.08

[7]. Y. Huang, X. Zhang, and Q. Li, "Computer vision-based assembly verification system in the automotive industry," *IEEE Transactions on Automation Science and Engineering*, vol. 17, no. 3, pp. 1312-1323, July 2020.

[8]. S. Kim, J. Park, and H. Kwon, "Autonomous inspection robot for weld seam detection in shipbuilding using computer vision," *IEEE Robotics and Automation Letters*, vol. 6, no. 2, pp. 3034-3041, April 2021.

[9]. K. Valarmathi et al An integrated energy storage framework with significant energy management and absorption mechanism for machine learning assisted electric vehicle application, Sustainable Computing: Informatics and Systems 42 (2024) 100982

[10]. M. S. Nixon and A. S. Aguado, *Feature Extraction & Image Processing for Computer Vision*, 3rd ed. Amsterdam, Netherlands: Elsevier, 2012.

[11]. William DeGroat, Dinesh Mendhe, Atharva Bhusari, Habiba Abdelhalim, Saman Zeeshan, Zeeshan Ahmed, IntelliGenes: a novel machine learning pipeline for biomarker discovery and predictive analysis using multi-genomic profiles, Bioinformatics, Volume 39, Issue 12, December 2023, btad755, https://doi.org/10.1093/bioinformatics/btad755.

[12]. R. Szeliski, *Computer Vision: Algorithms and Applications*, 2nd ed. New York, NY, USA: Springer, 2022.

.

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:55:21 UTC from IEEE Xplore. Restrictions apply.