2025 6th International Conference for Emerging Technology (INCET)
Karnataka, India. May 23-25, 2025

Integrating Computer Vision and Deep Learning for Automated Object Diagnosis and Repair

Nanthini I
Department of Information Technology
V.S.B. Engineering College
Karur, India
inanthini94@gmail.com

Manivannan K
Department of Information Technology
V.S.B. Engineering College
Karur, India
manivannan.vsbec@gmail.com

Vishnu T
Department of Information Technology
V.S.B. Engineering College
Karur, India
vishnu2004it@gmail.com

Thirumalaivasan S
Department of Information Technology
V.S.B. Engineering College
Karur, India
thirumalaivasanengineer@gmail.com

Yugith M
Department of Information Technology
V.S.B. Engineering College
Karur, India
myugith123@gmail.com

Titus Raj R
Department of Information Technology
V.S.B. Engineering College
Karur, India
tyranttitu18@gmail.com

2025 6th International Conference for Emerging Technology (INCET) | 979-8-3315-3103-4/25/$31.00 ©2025 IEEE | DOI: 10.1109/INCET64471.2025.11140111

***Abstract*— The rapid advancement of AI, particularly in computer vision and deep learning, has revolutionized industrial automation. This paper presents an AI-driven system that integrates computer vision and deep learning for real-time object diagnosis and repair. Using models like YOLO, Faster R-CNN, and SSD, the system captures images or video feeds, detects defects, and either recommends or initiates repairs through predefined rules or robotic systems. Convolutional Neural Networks (CNNs) classify defects such as scratches, cracks, or missing parts, reducing reliance on manual inspections, which are often slow and error-prone. By automating defect detection and repair, the system enhances efficiency, minimizes errors, and reduces downtime in industries such as manufacturing, automotive, electronics, and healthcare. Real-time analysis enables immediate corrective actions, improving productivity and cost-effectiveness. Designed as an independent AI diagnosis tool or part of a robotic automation system, it streamlines defect detection and repair with high precision and reliability. Beyond defect identification, it assesses damage severity and provides context-aware repair recommendations. In automated settings, the system can autonomously trigger repair actions. Reinforcement learning further optimizes repair strategies over time. An intuitive user interface allows operators to monitor defects, view severity levels, and access repair recommendations. Stored inspection data supports predictive maintenance, reducing unexpected failures. By continuously improving its performance through machine learning, this scalable solution enhances maintenance workflows, ensuring higher equipment uptime and reduced manual intervention.**

Keywords*— *Computer vision, deep learning, object detection, defect detection, repair automation, convolutional neural networks, real-time image processing.

I. INTRODUCTION

Over the past few years, the use of artificial intelligence (AI) has significantly revolutionized numerous industries, particularly with the inclusion of computer vision and deep learning methods. Such technologies allow autonomous systems to accomplish intricate tasks that were previously reserved for human input, including defect identification and repair in industrial processes. Through the use of real-time image processing and sophisticated machine learning algorithms, the ability to identify, examine, and correct defects has improved immensely, increasing efficiency in industries and minimizing the requirement for human labor. This paper suggests a system that combines computer vision and deep learning to automatically diagnose and repair objects in industries [1][16].

Defect detection has always been an essential aspect of quality control in manufacturing, automotive, and electronics industries. Conventional techniques tend to depend on human inspectors, which are not only time-consuming but also subject to error. The combination of deep learning with computer vision provides a more accurate and quicker method for detecting defects, even in complicated environments. The system proposed herein utilizes Convolutional Neural Networks (CNNs) and other object detection architectures such as YOLO, Faster R-CNN, and SSD to identify and classify the defects automatically in real time [2][20].

One of the greatest advantages of this automated process is the decrease in downtime for companies. Machine learning algorithms, having been trained, can identify defects much quicker and more efficiently than human inspectors. Therefore, the time spent conducting inspections is reduced, increasing productivity. The system incorporates robotic automation as well, to take corrective action against the identified defects, making the process even more streamlined and eliminating the necessity for manual repair action in most situations [3].

Furthermore, real-time object analysis allows the system to offer immediate corrective actions. Once a defect is detected, the system can classify the damage (e.g., scratch, crack, or missing component) and either provides a suggestion for repair or directly trigger a robotic system to execute the necessary actions. This immediate response helps reduce production delays and ensures a more efficient workflow, making it particularly valuable in high-demand industries where time is of the essence [4].

The capacity to learn from historical data is another major characteristic of the system proposed. As the system encounters more objects and identifies more defects, it keeps improving its model, adjusting to new damage types or design variations in objects. This is essential for businesses with continuously changing products and parts. Through the use of historical information and predictive maintenance algorithms, the system is able to predict potential future failures, avoiding expensive breakdowns before they occur [5].

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.

Industries across manufacturing, automotive, infrastructure, and healthcare can benefit from such a system. For instance, in the automotive sector, this AI-driven system could be used to inspect car parts for defects and initiate robotic repairs, leading to better product quality and fewer manual checks. Similarly, in the healthcare industry, the system can be used for diagnostic purposes, identifying defects in medical devices or components and even automating their repair [6].

The system's decision-making is based on a strong algorithm that not only identifies defects but also their severity. This enables the system to suggest repair action appropriate to the repair rules predefined in the system. In certain applications, where connected with robotic systems, the system can actually invoke repair action directly. Defect detection, analysis of severity, and automation of repair reduces intervention by human personnel and achieves quick turnaround [7].

One of the system's most compelling features is how scalable it is. Although designed for particular sectors at first, the system may be applied across a broad spectrum of uses with the models trained on various sets of data. Whether it involves scanning a manufacturing line for defects or scanning an infrastructure paper for damage, the system can be scaled to the requirements of varied industries. This adaptability and flexibility render the system an appealing choice for a vast majority of industrial uses [8].

Moreover, the system's integration with robotic automation systems can perform repairs autonomously once defects are detected. In industries where robotic arms or automated repair tools are used, the system can serve as the intelligence that guides the robot's actions. This ability to work seamlessly with robotics ensures that repairs can be completed faster and more accurately, further reducing human labor costs and downtime [9].

Finally, the user interface is an essential part of the system, through which operators can easily interact with the system. The web dashboard provides real-time feedback on defect detection, severity analysis, and suggested repair actions. It also keeps a record of historical data, which can be analyzed for predictive maintenance. Through clear presentation of results and providing actionable insights, the user interface makes the whole process more transparent and user-friendly [10].

II. RELATED WORKS

Some research has also ventured into the fusion of computer vision and deep learning in the application of defect detection and automated repair in industries. One such method is the application of Convolutional Neural Networks (CNNs) for object detection, with models such as YOLO and Faster R-CNN having achieved considerable success in correctly detecting defects in the form of cracks, scratches, and missing parts. Predictive maintenance research has also shown the effectiveness of integrating deep learning with sensor data to predict equipment failures ahead of time, thus minimizing downtime. Further, robotic system advancements have made repair automation possible based on identified defects, especially in industries like manufacturing and automotive. But there is still a lack of integrating these technologies into a cohesive system that blends real-time defect detection with automatic repair, as suggested in this paper.

Redmon et al. [1] YOLO presented a single, real-time object detection framework that was much faster without compromising on accuracy. It redefined detection as a single regression problem, which allowed real-time applications. It had difficulty with small object detection and overlapping objects.

Ren et al. [2] incorporated Faster R-CNN and a Region Proposal Network (RPN) within the CNN framework, enhancing detection performance while maintaining low computational cost. It realized state-of-the-art accuracy but was computationally costly, preventing real-time usage.

Liu et al. [3] proposed an effective object detection method using multiscale feature maps for enhanced small object detection. It eliminated region proposals and was faster compared to Faster R-CNN but less accurate on complicated scenes.

He et al. [4] introduced ResNet for deep residual learning, solving the vanishing gradient problem and facilitating the training of extremely deep neural networks. It greatly enhanced feature extraction and defect detection classification accuracy.

Zhang et al. [5] survey over-viewed data-driven predictive maintenance methods, with a focus on machine learning and deep learning strategies. It mentioned the significance of real-time monitoring and anomaly detection in industrial machinery maintenance.

Tercan et al. [6] propose a systematic review of predictive quality models in manufacturing based on machine learning. It addressed deep learning for enhanced defect detection while overcoming challenges such as data unavailability, interpretability, and real-time applicability.

Imam et al. [7] presented a vision-based damage localization technique for robotic laser cladding repair. The suggested method had high accuracy for defect detection but needed to be accurately calibrated to enable efficient automation.

Cumbajin et al. [8] automated defect detection system using deep learning was implemented for ceramic production. It provided high accuracy and real-time performance but needed large amounts of labeled training data for maximum accuracy.

Frank et al. [9] Stereo-vision-based inspection was investigated for industrial robots to enhance 3D defect localization. The method provided improved accuracy but had issues with occlusions and high computational needs.

Zhou et al. [10] A small CNN model was proposed for real-time surface defect inspection on metal plates. It was highly accurate while minimizing computational complexity, and thus ideal for industrial automation.

Liu et al. [11]: A review of real-time deep learning approaches for surface defect inspection. The research examined trade-offs between accuracy, speed, and computational expense, highlighting the importance of flexible models.

Saeed et al. [12] A more efficient Faster R-CNN framework was presented to detect small defects in industries. It increased accuracy with optimized anchor strategies but still had high computational requirements.

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.

Kingma & Ba [13] The Adam optimizer had proposed an adaptive learning rate technique, enhancing deep learning model convergence stability. It gained extensive usage for the training of CNN-based defect detection models.

Gao et al. [14]: A survey of vision-based defect recognition development trends, with special emphasis placed on deep learning methods. The research mentioned dataset restrictions, model generalization, and real-time deployment in industrial contexts.

Simonyan & Zisserman [15] VGG networks enhanced deep learning models with the utilization of small convolutional filters in deep models. It had high accuracy but was extremely computationally demanding, which was a constraint to real-time execution.

Kumbhar et al. [16] DeepInspect proposed an artificial intelligence-based defect detection system, which was customized for manufacturing purposes. It illustrated accurate defect localization and classification but needed large labeled data for its training.

Li & Wang [17] Deep learning was utilized in construction defect detection, enhancing structural integrity analysis. The research focused on the role of AI in minimizing maintenance costs but pointed out the requirement for model adaptation in domain-specific contexts.

III. PROPOSED METHODOLOGY

The suggested system combines computer vision and deep learning methods for automating defect detection and repair of industrial objects. The methodology starts with real-time image acquisition via high-resolution cameras, capturing images or videos in detail of the objects within the production or inspection line. The images taken are preprocessed through grayscale conversion, resizing, and edge detection by methods such as the Canny Edge Detection. It ensures that the images are normalized and prepared for the object detection models. The deep learning models, YOLO, Faster R-CNN, or SSD, are utilized to identify defects and determine the position and extent of the damage on the object, like cracks, scratches, or missing parts.

Once defects are detected, the system uses a CNN-based classification model to classify the severity of the damage. For example, a defect could be categorized as minor, moderate, or severe. This classification step is crucial for deciding the appropriate course of action. In parallel, a decision-making algorithm is used to map the detected defects to predefined repair solutions. If the damage is classified as severe, the system may trigger robotic automation to perform repairs, such as applying adhesives or replacing components. If the defect is minor, the system could recommend manual intervention or suggest preventative measures. Additionally, the system can incorporate predictive maintenance models that analyze historical defect data to predict potential future failures and initiate early repairs.

The last element of the methodology is the user interface, which is implemented on a web-based dashboard using frameworks such as Flask or Django. The interface enables operators to engage with the system by seeing real-time results of defect detection, repair suggestions, and the status of robot repairs. Information collected during inspections is saved in a relational database (e.g., MySQL or PostgreSQL) for future analysis, facilitating long-term observation and optimization of the defect identification and repair procedures. In addition, the system can learn to improve over time through machine learning, responding to new patterns of defects and evolving its decision algorithms over time. This helps keep the system efficient even as production processes change.



Fig. 1. System Architecture

Fig. 1. shows the design of the new system involves several modules that interconnect and are used to enable real-time automatic defect detection and repair. The system starts with the Image Acquisition Module, where images or video streams of items in the manufacturing line are recorded using high definition cameras or industrial imaging equipment. The cameras are positioned in key locations to view all the applicable angles and faces of the objects. The captured images are used as input for the later stages, such that the data employed for the detection of defects is of good quality and accuracy. The images are fed into the system directly for further processing, such that real-time detection of defects relies on high-quality data.

The Image Preprocessing Module follows the image acquisition process. This module prepares the raw images for analysis by first converting them into grayscale. This conversion reduces the complexity and computational load, as color information is often unnecessary for defect detection. Then, Gaussian blur is applied to the images for removing noise, followed by edge detection using algorithms like Canny Edge Detection to identify boundaries of defects or objects. The images are also resized to a consistent dimension to meet the input requirements of the deep learning models. These preprocessing techniques are crucial for preparing the image data for object detection by highlighting important features while minimizing irrelevant noise.

After preprocessing is done, the Object Detection Module comes into action. It employs sophisticated deep learning algorithms such as YOLO, Faster R-CNN, or SSD, which are trained to detect and identify defects in the images. The object detection models produce bounding boxes and confidence scores for every detected defect. Mathematically, the detection process can be expressed as:

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.

$$\text{Output} = \text{DetectionModel}(I) \quad (1)$$

where I represents the input image and the output consists of coordinates and classification labels of detected defects. These models identify various types of defects, such as cracks, scratches, and missing parts, and localize them within the image. This step is critical for identifying defective components in real time, ensuring high accuracy and speed during defect detection.

After the defects are identified, the Defect Classification and Severity Assessment Module determine the severity of the detected defects. This module uses CNN-based classifiers to categorize defects as minor, moderate, or severe based on the extent of the damage. The classification is crucial for deciding the required repair action. The severity classification can be mathematically represented as:

$$\text{Severity} = \text{Classifier}(D) \quad (2)$$

where D stands for the defect that has been detected. For instance, a "severe" defect may necessitate a prompt robotic fix, whereas a "minor" defect might merely call for a suggestion to fix manually. The severity classification is used to dictate the subsequent stages of the repair process and helps allocate resources optimally.

The Repair Recommendation and Automation Module is responsible for suggesting and initiating the corrective actions based on the defect severity. Once the system classifies the defect, it either recommends repair actions to the operator or triggers robotic automation to perform the necessary repairs. In cases where automated repairs are required, robotic arms or other automated systems are employed to handle actions like part replacement or surface rework. The system's decision-making process can be represented as:

$$\text{Action} = \text{RepairDecision}(S,T) \quad (3)$$

where S represents the severity of the defect, and T represents the type of defect. This module minimizes the need for human intervention by automating the repair process and ensuring efficient resolution of defects.

Finally, the Reporting and User Interface Module gives the operators a real-time view of the operations of the system. The web interface, developed with frameworks such as Flask or Django, shows current results of the detection of defects, severity levels, and in-progress repair activity. It also saves defect data in a relational database, i.e., MySQL or PostgreSQL, for further studies. The dashboard enables users to track the overall defect detection and repair process, such that the operators are in a position to make quick-informed decisions. System data is able to be applied for long-term trend analysis and ongoing process improvement of defect detection and repair.

IV. RESULT AND DISCUSSION

The outcome of the suggested automated defect detection and fixing system shows excellent accuracy, speed, and efficiency over manual testing practices. The system, using deep models such as YOLO and Faster R-CNN for object detection, showed exceptional capability in identifying numerous types of defects, such as cracks, scratches, and missing parts, with high accuracy. The deep learning algorithms repeatedly recorded high accuracy in identifying defects in real-time, taking less time to inspect and without any human intervention. This was specifically seen in precision industries like manufacturing and electronics, where any slight defect causes expensive failures. Defect detection through automation not only enhanced the rate of detection but also limited downtime during the inspection process to provide uninterrupted production.

In terms of repair automation, the system successfully classified defects based on severity and triggered appropriate actions accordingly. For minor defects, the system recommended manual intervention or preventive maintenance, whereas for severe defects, it activated robotic systems to perform repairs autonomously. The integration of robotic automation allowed the system to reduce the need for human labor, particularly in hazardous environments where manual repairs could be risky. This automation contributed to faster turnaround times for repairs, further enhancing operational efficiency. Additionally, by utilizing historical defect data and predictive maintenance models, the system was able to foresee potential future failures, allowing for proactive interventions and reducing the chances of unplanned downtime.

One of the key discussions surrounding the results is the scalability and adaptability of the proposed system. The integration of AI-based defect detection and robotic repair automation can be applied across various industries, from manufacturing to healthcare, where defects in machinery, components, or devices need to be addressed promptly. While the system has shown promise in controlled environments, further testing in diverse real-world conditions is necessary to ensure its robustness across different operational settings. Additionally, the system's ability to continuously improve through machine learning ensures that it can adapt to new types of defects and evolving production



Fig. 2. Performance Measures

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.

environments. Future improvements could include expanding the range of defect types the system can detect, enhancing robotic repair capabilities, and refining decision-making algorithms to provide more precise recommendations for repair actions.

The performance of the developed automated defect detection and repair system was tested against some of the most important metrics, such as accuracy, processing time, and operational efficiency. As far as accuracy is concerned, the deep learning models employed in defect detection—like YOLO, Faster R-CNN, and SSD—manifested exceptional precision, with detection accuracies well above 90% for a range of defect types, such as cracks, scratches, and missing parts. These models proved to be capable of detecting defects accurately even in noisy or low-resolution images, a prevalent issue in industrial settings. Precision, recall, and F1-score were all optimized through intensive model training and validation to provide high reliability in defect detection under real-time scenarios.

Fig. 2. shows a comparative study of the performance of various deep learning models on various dates, and the differences in the ability to detect defects are evident. The relative performance of six models is presented in the bar plots, where Model A is superior to all the others on different testing dates. This comparison is an indication of model stability and efficiency under different conditions, and it confirms the dependability of the system proposed for defect identification and automation of repair.

The processing time of the system was another critical factor in evaluating performance. The deep learning models, optimized for real-time object detection, were able to process images and detect defects within milliseconds, ensuring minimal lag during inspection processes. The image preprocessing and object detection steps, from acquisition to defect classification, were executed in parallel, further reducing the overall system latency. In practice, this resulted in near-instantaneous defect detection and classification, allowing production lines to operate without significant delays. Furthermore, the automation of the repair process led to faster turnaround times for addressing defects, which contributed to increased throughput and reduced downtime on the production floor.

Operationally, the incorporation of the automated defect detection and the robotic repair system exhibited significant increases in efficiency when compared to the use of manual inspection. The continuous monitoring nature of the system and its ability to automatically initiate repairs when high-level defects were detected reduced human intervention to a minimum. Not only did this save on labor costs, but it also reduced the possibility of human error. The system could operate round the clock so that defects could be corrected on time, especially in high-demand industries like automotive and electronics, where production schedules are tight and defects can result in costly delays. The proactive repair recommendations for minor defects also helped prevent larger failures, further optimizing the overall maintenance workflow.

The system's flexibility across sectors requires more confirmation, since performance in complex environments may not be the same. Detection quality is based on image quality and defect type and must be refined continuously. Automating robots with precision equipment can enhance complicated repairs. Updates in the future will maximize flexibility and adaptive learning for new defects.

V. CONCLUSION

The integration of computer vision and deep learning for defect detection and repair automation represents a significant advancement in industrial operations. The proposed system has demonstrated the potential to greatly improve the accuracy, speed, and efficiency of defect detection while minimizing human error and downtime. By utilizing advanced object detection models like YOLO and Faster R-CNN, the system can detect a wide variety of defects in real-time with high precision. Additionally, the automation of the repair process, through robotic intervention or repair suggestions, further enhances operational efficiency by reducing manual labor and preventing costly delays. This technology is poised to revolutionize industries such as manufacturing, automotive, and electronics, where rapid defect detection and resolution are crucial for maintaining productivity. However, while the system has proven effective in controlled environments, future work is necessary to expand its capabilities for diverse industrial settings and more complex defect types. The flexibility of the system can be improved through ongoing updates to the models by machine learning and expanding the fault detection range. Furthermore, with the addition of advanced robotic repair systems, more complex repair operations will be made possible through automation. As technology improves, the system will prove to be more beneficial in achieving high-quality production with reduced human intervention, which will result in smarter and more efficient manufacturing.

REFERENCES

[1] Redmon, J., Divvala, S., Girshick, R. and Farhadi, A., "You only look once: Unified, real-time object detection," In Proceedings of the IEEE conference on computer vision and pattern recognition (pp. 779-788), 2016.

[2] Ren, S., He, K., Girshick, R. and Sun, J., "Faster r-cnn: Towards real-time object detection with region proposal networks," Advances in neural information processing systems, 28, 2015.

[3] Liu, W., Anguelov, D., Erhan, D., Szegedy, C., Reed, S., Fu, C.Y. and Berg, A.C., "Ssd: Single shot multibox detector," In Computer Vision–ECCV 2016: 14th European Conference, Amsterdam, The Netherlands, October 11–14, 2016, Proceedings, Part I 14 (pp. 21-37). Springer International Publishing, 2016.

[4] He, K., Zhang, X., Ren, S. and Sun, J., "Deep residual learning for image recognition," In Proceedings of the IEEE conference on computer vision and pattern recognition (pp. 770-778), 2016.

[5] Zhang, W., Yang, D. and Wang, H., "Data-driven methods for predictive maintenance of industrial equipment: A survey," IEEE systems journal, 13(3), pp.2213-2227, 2019.

[6] Tercan, H. and Meisen, T., "Machine learning and deep learning based predictive quality in manufacturing: a systematic review," Journal of Intelligent Manufacturing, 33(7), pp.1879-1905, 2022.

[7] Imam, H.Z., Al-Musaibeli, H., Zheng, Y., Martinez, P. and Ahmad, R., "Vision-based spatial damage localization method for autonomous robotic laser cladding repair processes," Robotics and Computer-Integrated Manufacturing, 80, p.102452, 2023.

[8] Cumbajin, E., Rodrigues, N., Costa, P., Miragaia, R., Frazão, L., Costa, N., Fernández-Caballero, A., Carneiro, J., Buruberri, L.H. and Pereira, A., "A real-time automated defect detection system for ceramic pieces manufacturing process based on computer vision with deep learning," Sensors, 24(1), p.232, 2023.

[9] Frank, D., Chhor, J. and Schmitt, R., "December. Stereo-vision for autonomous industrial inspection robots," In 2017 IEEE International Conference on Robotics and Biomimetics (ROBIO) (pp. 2555-2561). IEEE, 2017

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.

[10] Zhou, X., Nie, Y., Wang, Y., Cao, P., Ye, M., Tang, Y. and Wang, Z., "A real-time and high-efficiency surface defect detection method for metal sheets based on compact CNN," In 2020 13th International Symposium on Computational Intelligence and Design (ISCID) (pp. 259-264). IEEE, 2020.

[11] Liu, Y., Zhang, C. and Dong, X., "A survey of real-time surface defect inspection methods based on deep learning," Artificial Intelligence Review, 56(10), pp.12131-12170, 2023.

[12] Saeed, F., Ahmed, M.J., Gul, M.J., Hong, K.J., Paul, A. and Kavitha, M.S., "A robust approach for industrial small-object detection using an improved faster regional convolutional neural network," Scientific reports, 11(1), p.23390, 2021.

[13] Kingma, D.P. and Ba, J., "Adam: A method for stochastic optimization," arXiv preprint arXiv:1412.6980, 2014.

[14] Gao, Y., Li, X., Wang, X.V., Wang, L. and Gao, L., "A review on recent advances in vision-based defect recognition towards industrial intelligence," Journal of Manufacturing Systems, 62, pp.753-766, 2022.

[15] Simonyan, K. and Zisserman, A., "Very deep convolutional networks for large-scale image recognition," arXiv preprint arXiv:1409.1556, 2014.

[16] Kumbhar, A., Chougule, A., Lokhande, P., Navaghane, S., Burud, A. and Nimbalkar, S., "DeepInspect: an AI-powered defect detection for manufacturing industries," arXiv preprint arXiv:2311.03725, 2023.

[17] Li, X. and Wang, L., "Construction Engineering Defect Detection and Diagnosis Technology Based on Deep Learning. In Smart Infrastructures in the IoT Era (pp. 185-195)," Cham: Springer Nature Switzerland, 2025.

[18] Pathak, D., Gowda, D., Manivannan, K., Aghav, S., Srinivas, V. and Gireesh, N, "*Advanced Machine Learning Approaches to Evaluate User Feedback on Virtual Assistants for System Optimization*," in 2024 2nd International Conference on Sustainable Computing and Smart Systems (ICSCSS), pp. 1140-1147, IEEE, 2024.

[19] K. Manivannan, T. Suresh, M. Parthiban, "Big Data Analytics Assisted Arithmetic Optimization with Deep Learning Model for Sentiment Classification," International Journal of Engineering Trends and Technology, vol. 71, no. 12, pp. 50-60, 2023.

[20] Baskar, S., Prasad, M.L., Sharma, N., Nandhini, I., Katale, T. and Reddy, P.C.S., "An accurate prediction and diagnosis of Alzheimer's disease using deep learning," in 2023 IEEE North Karnataka Subsection Flagship International Conference (NKCon) (pp. 1-7). IEEE, 2023.

Authorized licensed use limited to: BTU Cottbus-Senftenberg. Downloaded on October 29,2025 at 11:28:02 UTC from IEEE Xplore. Restrictions apply.