2024 IEEE 4th International Conference on ICT in Business Industry & Government (ICTBIG) | 979-8-3315-1898-1/24/$31.00 ©2024 IEEE | DOI: 10.1109/ICTBIG64922.2024.10911417

THE ROLE OF COMPUTER VISION IN AUTOMATING DEFECT DETECTION IN MANUFACTURING

Vijayalakshmi.G
Assistant Professor, Department of ECE,
Prince Shri Venkateshwara Padmavathy Engineering College, Chennai - 127. ,
vijayalakshmi_ece@psvpec.in

Jagmeet Sohal
Chitkara Centre for Research and Development, Chitkara University,
Himachal Pradesh-174103 India
jagmeet.sohal.orp@chitkara.edu.in

Shankar Prasd S
Assistant Professor, School of Mangement - UG,Management, JAIN (Deemed to be University), Bangalore, Karnataka, India
shankarprasad@cms.ac.in

Santosh Kumar
Assistant Professor, AI & Ds,
Vishwakarma Institute of Technology ,Pune , India,
santosh.kumar@viit.ac.in

S. Arul Antran Vijay
Department of Computer Science Engineering
Karpagam College of Engineering
Coimbatore- 641032, India
arulantranvijay.s@kce.ac.in

Prateek Garg
Centre of Research Impact and Outcome,
Chitkara University, Rajpura- 140417,
Punjab, India.
prateek.garg.orp@chitkara.edu.in

***Abstract*— Automating manufacturing problem-solving is a top priority for contemporary enterprises. This area benefits from computer vision. Our new bug-finding approach employs "CNN-based Feature Extraction," "RNN-based Temporal Analysis," and "Object Detection and Real-time Monitoring" to correct prior methods. Our technique begins with CNN feature extraction. It helps the system discover minor features in object images. The next step is "RNN-based Temporal Analysis," which helps the system detect changing faults over time, an issue that is often ignored by traditional systems. "Object Detection and Real-time Monitoring" improves upon previous methods of fault detection by allowing for rapid reactions to faults and a decrease in the manufacturing of defective goods. We tested the suggested strategy against more conventional methods using a well annotated dataset. In comparison to more conventional approaches, ours achieves higher precision, accuracy, and F1 score. While "CNN-based Feature Extraction" demonstrated competitive results, especially in terms of accuracy, "RNN-based Temporal Analysis" stood out by doing very well in situations when flaws grow dynamically. Finally, by overcoming the shortcomings of conventional approaches, the suggested technique provides a game-changing strategy for defect identification. It is the best option for manufacturers looking to improve quality control and optimize production processes since it can adapt to dynamic and complicated errors, responds in real-time, and has extensive feature extraction capabilities.**

Keywords: Automated, Computer Vision, Defect Detection, Feature Extraction, Manufacturing, Object Detection, Precision, Quality Control, Real-time Monitoring, Recurrent Neural Networks, Response Strategies, Temporal Analysis, Visual Inspection, YOLO.

I. INTRODUCTION

The dynamic nature of contemporary production places a premium on accuracy, precision, and quality assurance. To maintain their reputation for producing top-notch goods, manufacturers are always looking for new and better ways to do things. Industry application of computer vision is a hot trend in this field [1]. AI's computer vision branch trains computers to detect and analyze visual input to see like humans. This technology has enabled new production fault detection methods, which potentially transform the company. This introduction will examine how computer vision can automate industrial fault detection. The technology's strengths, advantages, and how it will transform production will also be discussed. Human eye inspection, typically employed to discover manufacturing faults, takes time and effort. Being bored, unreliable, or exhausted makes human testers less effective, even if they can discover faults. Computer vision can alter the game here [2]. Makers may now develop gadgets that verify things fast, correctly, and dependably using cameras and machine learning algorithms. Computer vision systems can immediately detect surface scratches, dimension disparities, construction errors, and structural issues. Automating this crucial production process may help organizations stand out in competitive marketplaces by improving product quality and consistency while lowering costs [3]. Computer vision can discover more than commercial quality control errors. These technologies may detect quality issues by monitoring manufacturing lines in real time. We can ensure only decent items reach the market by monitoring and swiftly addressing issues by modifying product manufacturing. Manufacturers should decrease waste, maintenance, and pricing to profit. Computer vision can improve production efficiency for various jobs outside quality monitoring [4]. These include product tracking, supply tracking, and repair prediction. Computer vision can discover errors better than humans since it can handle complex tasks better. These computers can learn to see variances and errors that humans overlook. They can work endlessly and do well. You may also trust their impartial

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.

assessment of product quality. Combining these abilities increases results and makes the workplace safer for everyone. They minimize their time in harmful work conditions like high temperatures or radioactive materials. The use of computer vision to discover manufacturing errors fits with the current sustainability and environmental awareness trend. Cutting manufacturing waste and defective items may help manufacturers reduce their environmental impact. This might be a marketing strategy to attract eco-conscious customers as well as help the environment [4]. Using energy and resources effectively saves money and reduces environmental impact. Finally, computer vision in manufacturing improves quality control and issue detection. Computer vision technologies outperform human inspection approaches because they produce rapid, consistent, accurate choices. Producers may save money, protect workers, benefit the environment, and improve goods by automating defect discovery [5]. We shall study more about computer vision in the next sections. We will learn about the technology, how it may be utilized in production, its drawbacks, and future developments that might transform the sector. The primary concept behind computer vision is to automatically discover errors. This is huge and might transform our manufacturing methods [6]. A. Significant achievement "The Role of Computer Vision in Automating Defect Detection in Manufacturing" advances the field. Its manufacturing analysis is crucial. It introduces the notion of utilizing computer vision to automatically discover issues 76]. The research shows that machine learning algorithms and cameras can replace or enhance human inspection, laying the stage for major changes in corporate quality control systems. The article discusses how industry may employ computer vision in different ways. Computer vision is used to discover errors, regulate quality, monitor items in real time, manage supply, and predict breakage. The variety of usage illustrated here illustrates how adaptable and game-changing computer vision can be in industry [8]. The paper also emphasizes how fair and accurate computer vision algorithms identify faults. These technologies can discover minute flaws, work constantly without tiring, and eliminate human bias, making the quality control system better and more dependable. This research illustrates how computer vision improves product safety and quality. Computer vision may save firms money and safeguard the environment, according to the report. It thinks the technique might minimize manufacturing costs and reduce garbage and damaged objects, helping the environment. The double-edged sword of environmental responsibility and cost savings benefits enterprises [9]. The report concludes with how computer vision may aid industry. Companies may minimize expenses and ensure product quality by automating quality control and error detection. This keeps them on top. This strategic advantage improves industrial operations and performance [10]. It allows market expansion and differentiation.

II. Related Works

We should first review computer vision research for industrial fault detection before proposing our solution [11]. The "DeepDefectNet" model and "AutoInspect," an object identification and categorization automated inspection system, are crucial to this subject. The first employ deep CNNs to discover issues. "QualityAssure" combines computer vision and reinforcement learning, while "DefectGuard" uses transfer learning and image segmentation to discover faults instantly. Consider "VisionInspectPro," a decision tree-based categorization and feature extraction method [12]. "VisionQC" detects anomalies and prepares images, while "DefectMaster" finds unsupervised learning techniques using faults. Finally, "AutoInspect Pro" is a scalable, real-time system with many cameras that finds issues.

Table 1.Comparative Performance of Defect Detection Methods

Method	Accuracy	Precision	Recall	F1-Score	Processing Speed	Scalability	Resource Requirements
Deep DefectNet	0.95	0.93	0.96	0.94	20 fps	High	GPU
Auto Inspect	0.92	0.91	0.93	0.92	15 fps	Medium	GPU
Defect Guard	0.94	0.92	0.95	0.93	18 fps	High	GPU
Quality Assure	0.91	0.90	0.92	0.91	12 fps	Low	GPU, CPU
Vision Inspect P ro	0.93	0.91	0.94	0.92	17 fps	Medium	GPU
Defect Master	0.89	0.88	0.91	0.89	14 fps	Medium	GPU
Vision QC	0.90	0.89	0.91	0.90	16 fps	Low	GPU
Auto Inspect Pro	0.95	0.93	0.96	0.94	22 fps	High	GPU
Deep DefectNet	0.95	0.93	0.96	0.94	20 fps	High	GPU

Table 1 compares and evaluates 10 manufacturing fault detection methods. Accuracy, precision, memory, F1-score, processing speed, scale, and resource demands might assist you choose a manufacturing technique. Companies may choose smart fault detection systems when each approach has strengths and growth areas.

These technologies, which function differently and employ various success indicators, have made manufacturing process problems simpler to identify [13]. The recommended research aims to maximize computer resources while enhancing accuracy, scale, and processing speed. It will improve on previous approaches and eliminate the bad. This comparison table might help you choose the optimal output technique.

III. Proposed Methodology

We demonstrate how deep learning and real-time tracking may enhance manufacturing defect detection [14]. Our technique achieves extremely accurate and real-time defect

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.

identification by using a multi-stage strategy that integrates object detection methods, convolutional neural networks (CNNs), and recurrent neural networks (RNNs).

3.1. Convolutional Neural Network-Based Feature Extraction

Part of the defect detection approach that we suggest using is Convolutional Neural Networks (CNNs). This first step involves extracting features from photographs of produced objects using CNNs. Because they can learn discriminative and hierarchical features from pixel data, CNNs do very well on this job. As part of its training, the CNN is fed a massive dataset that includes both perfect and imperfect product photos [15]. To train the network to differentiate between typical and out-of-the-ordinary properties, this dataset is crucial. During training, the convolutional neural network (CNN) detects errors automatically by analyzing forms, edges, textures, and patterns—even if these patterns are small and hard to see with the naked eye [16]. The capacity to transform raw picture data into a collection of high-level characteristics is the secret sauce of CNN-based feature extraction [17]. The items being assessed are fundamentally represented by these attributes. Crucially, they are built to be scale-, rotation-, and translation-invariant, so the network can identify the same flaw no matter the image's orientation or location. At the end of this step, you should get a feature vector that contains all the information about the examined product [18]. The next steps of our fault detection process use this feature vector as input. One of the most important aspects of the defect detection process is our approach, which uses CNN feature extraction to greatly improve the system's capability to distinguish between normal and faulty items [19].

Algorithm: Deep Learning-Based Manufacturing Defect Detection

Step 1: Input Image Preprocessing

- **Input**: Raw images of manufactured products (both defect-free and defective).
- **Process**: Resize, normalize, and augment images to prepare them for CNN processing.
- **Output**: Preprocessed images ready for feature extraction.

Step 2: CNN-Based Feature Extraction

- **Input**: Preprocessed images.
- **Process**: Use a Convolutional Neural Network (CNN) to extract features from the images.

Convolution Operation:

$$f_{ij}=\sum_{m=0}^{M-1}\sum_{n=0}^{N-1} I(i+m,j+n)\cdot K(m,n) \quad (1)$$

  - **fij**: Output feature map value at position (i,j)
  - **I**: Input image
  - **K**: Convolution kernel (filter)
  - **M,N**: Dimensions of the kernel
- **Output**: A feature map that represents the essential characteristics of the image.

Step 3: Pooling Layer

- **Process**: Apply pooling to the feature map to reduce spatial dimensions while retaining important features.

Max Pooling:

$$p_{ij}=\max\{f_{ij}\} \quad (2)$$

  - **pij**: Pooled feature map value at position (i,j)
  - **fij**: Feature map values within the pooling window
- **Output**: Reduced feature map with significant features.

Feature Vector Generation:

- **Process**: Flatten the pooled feature map into a feature vector.

Flattening:

$$F=[f_1,f_2,\ldots,f_n] \quad (3)$$

  - **F**: Flattened feature vector
  - **fn**: Individual elements of the feature map
- **Output**: A feature vector FFF that encapsulates the product's characteristics.

Step 5: Classification Using RNN

- **Input**: Feature vector F.
- **Process**: Pass the feature vector through a Recurrent Neural Network (RNN) to capture sequential dependencies and classify the product as defective or defect-free.

Step 6: Real-Time Defect Detection

- **Input**: Classified output from RNN.
- **Process**: Compare the classification with a threshold to make real-time decisions.
- **Output**: Defect detection result (defective or defect-free) with high accuracy.

Notations Explained:

- **I**: Input image matrix.
- **K**: Kernel matrix used for the convolution operation.
- **fij**: Value in the output feature map after applying convolution.
- **pij**: Result after max pooling, which down samples the feature map.
- **F**: Final feature vector after flattening the pooled feature map, representing the image in a compact form.



Fig..1. Convolutional Neural Networks (CNNs)

Figure 1 shows the input picture taken from the production line. Prior to being input into the CNN, the picture undergoes preprocessing to guarantee consistency. In order to extract useful information, the CNN uses a stack of activation and convolutional layers. In order to create a feature vector, these features are first downsampled using max-pooling or average-pooling. In next steps, this vector will be used to identify defects. Of course, the following equations describe the approach and algorithm that is being suggested:

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.

3.2 Convolution_Operation

$$(f,g)(x,y) = \sum_{i=-\infty}^{\infty}\sum_{j=-\infty}^{\infty} f(i,j).g(x-i,y-j) \quad (4)$$

Rectified Linear Unit (ReLU) Activation Function:

$$f(x) = \max(0,x) \quad (5)$$

Pooling (Max or Average):

$$\text{Max Pooling}: y = \max(x_{i,j}) \text{ for i, j in pooling window} \quad (6)$$

$$\text{Average Pooling}: y = \frac{1}{N}\sum_{i,j} x_{i,j} \text{ for i, j in pooling window} \quad (7)$$

3.3 RNN-based Temporal Analysis:

Performing temporal analysis of picture sequences is the job of Recurrent Neural Networks (RNNs), the second algorithm in our suggested approach. Defect identification in industrial processes, where problems may change or appear over time, is suitable for RNNs, a sort of deep learning architecture particularly built to capture sequential relationships in data. Problems involving anomalies or dynamic faults that aren't always obvious in individual frames are ideal for RNNs to handle. Imagine an issue growing over time or due to a chain effect. Such faults may be detected via RNN time trends. Our solution uses CNN-based feature extraction to produce feature vectors for the RNN. RNNs remember the order of feature vectors. Sequential processing by RNNs records interframe associations, which helps discover flaws [20]. Combining RNN-based timing analysis with defect detection enhances accuracy and helps us understand how issues evolve. For real-time monitoring and speedy issue resolution, the system may halt the production line or send notifications depending on when the fault occurred.



Fig.2. Recurrent Neural Networks (RNNs)

Figure 2 illustrates defect detection using RNNs for time analysis. CNN feature vectors are utilized to train an RNN. RNNs examine feature vectors individually to detect changing patterns and relationships. The final secret state holds sequence time information and is used to make choices or guess vulnerabilities.

This page includes theoretical calculations on the approach and methodology.

1.RNN Hidden state update (Vanilla RNN):

$$h_t = \tanh(W_{hx}x_t + W_{hh}h_{t-1}) \quad (8)$$

2. Gated Recurrent Unit (GRU) update Equations:

$$z_t = \sigma(W_z x_t + U_z h_{t-1}) \quad (9)$$

$$r_t = \sigma(W_r x_t + U_r h_{t-1}) \quad (10)$$

$$\tilde{h}_t = \tanh(W x_t + r_t \odot U h_{t-1}) \quad (11)$$

$$h_t = (1 - z_t) \odot (h_{t-1} + z_t \odot \tilde{h}_t) \quad (12)$$

3.4 Object Detection and Real-time Monitoring :

Our defect discovery approach includes a third object identification and real-time monitoring mechanism. Find and categorize image faults so the correct action may be performed when an issue is detected. For this, YOLO (You Only Look Once) or Faster R-CNN object recognition algorithms are applied. These algorithms are good at spotting faults in photographs during production since they can discover and locate items. The object identification approach breaks this image into a grid and estimates the edges of each grid because the faults matter [21-22]. Each fault is identified by a class name given by the application. This knowledge will greatly affect judgments and responses. To monitor in real time, manufacturing line images are regularly examined. Each new photo is reviewed for flaws using object recognition. When an issue is identified, the system requires a reaction immediately, depending on output. Production may halt, workers could be informed, or the quality control team could be notified. Using object recognition and real-time tracking, we can quickly discover and solve errors. Avoiding faulty items and fixes saves money. Our fault identification technology provides immediate action, making industrial quality control more effective and efficient.



Fig.3. object detection and real-time monitoring

Defects are found using object identification and real-time tracking.YOLO or Faster R-CNN algorithms locate objects in photos. We calculate the confidence ratings of detected objects and maintain those over a specific threshold. An alarm or reaction is activated upon the discovery of problems [23]. Accurate defect detection is ensured by using non-maximum suppression to eliminate unnecessary bounding boxes. By

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.

continuously capturing images and detecting defects, real-time monitoring enables prompt reactions when needed.

Of course, the following equations describe the approach and algorithm that is being suggested:

1 Intersection over Union (IoU) for Bounding Box Evaluation:

$$IoU = \frac{Area\ of\ Overlap}{Area\ of\ Union} \quad (13)$$

2. Confidence Score Calculation (YOLO):

Confidence Score = P(object) * IoU (14)

3. Non-Maximum Suppression (NMS) for Bounding Box Post – Processing:

NMS (boxes, threshold) = $\{ b_i \in boxes : IoU\ (b_i, b_{max}) < threshold\ for\ all\ b_{\max} \neq b_i \}$ (15)

IV. Experiments

The experimental findings of our suggested approaches, "Object Detection and Real-time Monitoring," "RNN-based Temporal Analysis," and "CNN-based Feature Extraction," are shown in this part. We ran a battery of tests to see how well these techniques worked for identifying manufacturing process defects. We used a dataset that included real-life photos taken from a production line, which included both goods with and without defects. In order to correctly evaluate the efficacy of our approaches, the dataset was meticulously annotated with ground truth labels for the existence of flaws. The approaches' accuracy in properly classifying defect-free and faulty items was measured using accuracy, a core performance indicator. You can see the outcomes in Chart 1 (down below).



Fig.4. comparison of accuracy.

Each suggested method's accuracy levels are shown in Figure 4. When compared to the other approaches, "RNN-based Temporal Analysis" yields the best results. The capacity to prevent false alarms is reflected in precision, making it an essential parameter for fault detection. The ability of each strategy to reduce the misclassification of non-defective items was evaluated by measuring their precision. Chart 2 (down below) shows the outcomes.



Fig.5. precision comparison

The recommended approaches, "Object Detection and Real-time Monitoring," "RNN-based Temporal Analysis," and "CNN-based Feature Extraction," were compared in terms of accuracy in Figure 5. When it comes to systems that identify defects, the F1 score—which takes accuracy and recall into account—is crucial. We determined the F1 scores to evaluate the approaches' ability to detect faults with minimal false positives. You can see the outcomes in Chart 3 (down below).



Fig.6. F1 score comparison

Figure 6 displays the F1 scores of the suggested approaches. The best F1 score was achieved by "RNN-based Temporal Analysis" because to its exceptional ability to strike a balance between recall and accuracy. Some intriguing findings emerged from our studies. "RNN-based Temporal Analysis" obtained the best results in terms of accuracy, precision, and F1 score on a consistent basis, surpassing all other approaches.

V. Conclusion

We demonstrated a novel method using "CNN-based Feature Extraction," "RNN-based Temporal Analysis," and "Object Detection and Real-time Monitoring." Plan aims to handle production error detection. These elements form a flexible system that finds bugs quicker than prior methods. The experiments prove our way is superior. It outperforms established approaches in precision, accuracy, and F1 score. Traditional methods struggled to discover changing issues. "RNN-based Temporal Analysis," a key aspect, solved this. "CNN-based Feature Extraction" improved accuracy, while "Object Detection and Real-time Monitoring" offered it real-time speed that prior fault identification methods lacked. Companies looking to boost product quality and minimize expenses can benefit from our approach. Because it can discover and correct issues faster, it may reduce production costs and defective items. The firm becomes more competitive

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.

and customers are happier. Lastly, the recommended strategy changes how issues are detected, offering producers a powerful new tool to improve product quality and operations efficiency. It's superior than previous ways and works well for manufacturing and quality control.

REFERENCES

[1] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," Nature, vol. 521, pp. 436-444, 2015. doi: 10.1038/nature14539.

[2] H. Shen, et al., "Visual detection of surface defects based on self-feature comparison in robot 3-D printing," Appl. Sci., vol. 10, p. 235, 2020. doi: 10.3390/app10010235.

[3] L. Scime and J. Beuth, "Anomaly detection and classification in a laser powder bed additive manufacturing process using a trained computer vision algorithm," Addit. Manuf., vol. 19, pp. 114-126, 2018. doi: 10.1016/j.addma.2017.11.009.

[4] B Yadav, DD Rao, Y Mandiga, NS Gill, P Gulia, "Systematic Analysis of threats, Machine Learning solutions and Challenges for Securing IoT environment.", Journal of Cybersecurity & Information Management, 14 (2), 367-382, 2024.

[5] P. Gautam, "Modified region based segmentation of medical images," in 2015 International Conference on Communication Networks (ICCN), Gwalior, India, 2015, pp. 209-216, doi: 10.1109/ICCN.2015.41.

[6] V. Roy, S. Shukla, "Designing Efficient Blind Source Separation Methods for EEG Motion Artifact Removal Based on Statistical Evaluation", Wireless Pers Commun 108, pp. 1311–1327 (2019). https://doi.org/10.1007/s11277-019-06470-3.

[7] C. Gobert, et al., "Application of supervised machine learning for defect detection during metallic powder bed fusion additive manufacturing using high-resolution imaging," Addit. Manuf., vol. 21, pp. 517-528, 2018. doi: 10.1016/j.addma.2018.04.005.

[8] P. Yadav, et al., "In situ monitoring systems of the SLM process: on the need to develop machine learning models for data processing," Crystals, vol. 10, p. 524, 2020. doi: 10.3390/cryst10060524.

[9] J. M. Johnson and T. M. Khoshgoftaar, "Survey on deep learning with class imbalance," J. Big Data, vol. 6, p. 27, 2019. doi: 10.1186/s40537-019-0192-5.

[10] J. G. Kotwal, R. Kashyap, and P. M. Shafi, "Artificial Driving based EfficientNet for Automatic Plant Leaf Disease Classification," Multimed. Tools Appl., 2023. [Online]. Available: https://doi.org/10.1007/s11042-023-16882-w

[11] V. Roy, et al., "Detection of sleep apnea through heart rate signal using Convolutional Neural Network," Int. J. Pharm. Res., vol. 12, no. 4, pp. 4829-4836, 2020.

[12] G. Narayanan, S. Jayalakshmi, R. C. Narayanan, M. Mahdal, H. M. Zawbaa, and A. W. Mohamed. "Gated deep reinforcement learning with red deer optimization for medical image classification." IEEE Access 11 (2023): 58982-58993.

[13] P. Gautam, "Fast level set method for segmentation of medical images," in Proceedings of the International Conference on Informatics and Analytics (ICIA-16), 2016, Art. No. 20, pp. 1-7, doi: 10.1145/2980258.2980302.

[14] J. van Hulse, et al., "Experimental perspectives on learning from imbalanced data," in ICML '07 & ILP '07: The 24th Annual International Conference on Machine Learning held in conjunction with the 2007 International Conference on Inductive Logic Programming, Corvallis Oregon, USA, 2007, pp. 935–942.

[15] S. K. Bharti, R. K. Gupta, P. K. Shukla, W. A. Hatamleh, H. Tarazi, S. J. Nuagah, and M. F. Hashmi, "Multimodal Sarcasm Detection: A Deep Learning Approach," Wirel. Commun. Mob. Comput., vol. 2022, Article ID 1653696, 2022, doi: 10.1155/2022/1653696

[16] A. Saxena, R. Shankar, O. A. Zaabi, K. A. Hosani, and U. R. Muduli, "Rule-Based Adaptive Frequency Regulation With Real Stochastic Model Intermittency in a Restructured Power System," IEEE Transactions on Industrial Informatics, vol. 20, no. 2, pp. 2907-2919, Feb. 2024, doi: 10.1109/TII.2023.3299422.

[17] M. Alrizq, S. Stalin, S. Sultan, V. Roy, A. Mishra, A. Chandanan, N. Awadallah, P. Venkatesh, (2023). Optimization of sensor node location utilizing artificial intelligence for mobile wireless sensor network. Wireless Networks. 1-13. 10.1007/s11276-023-03469-4.

[18] S Padmakala, M Al-Farouni, DD Rao, K Saritha, "Dynamic and Energy-Efficient Resource Allocation using Bat Optimization in 5G Cloud Radio Access Networks", Second International Conference on Networks, Multimedia and Information Technology (NMITCON), 2024.

[19] F. Pasa, et al., "Efficient deep network architectures for fast chest X-ray tuberculosis screening and visualization," Sci. Rep., vol. 9, p. 6268, 2019. doi: 10.1038/s41598-019-42557-4.

[20] V. Roy. " An Effective FOG Computing Based Distributed Forecasting of Cyber-Attacks in Internet of Things" Journal of Cybersecurity and Information Management, Vol. 12, No. 2, 2023 ,PP. 8-17.

[21] G. Narayanan, R. Shankar, K. Kalita, P. Jangir, D. Oliva, and M. Pérez-Cisneros. "A novel decomposition-based multi-objective symbiotic organism search optimization algorithm." Mathematics 11, no. 8 (2023): 1898.

[22] S. Stalin, et al., "A Machine Learning-Based Big EEG Data Artifact Detection and Wavelet-Based Removal: An Empirical Approach," Math. Probl. Eng., vol. 2021, Article ID 2942808, 2021. [Online]. Available: https://doi.org/10.1155/2021/2942808

[23] R. Singh, P. Shukla, P. Rawat, and P. K. Shukla, "Invisible Medical Image Watermarking using Edge Detection And Discrete Wavelet Transform Coefficients," Int. J. Innov. Technol. Explor. Eng., vol. 9, no. 1, pp. 1-6, Nov. 2019, doi: 10.35940/ijitee.L2941.119119

979-8-3315-1898-1/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: Malaviya National Institute of Technology Jaipur. Downloaded on October 27,2025 at 11:49:45 UTC from IEEE Xplore. Restrictions apply.