

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT

on

BIG DATA ANALYTICS (20CS6PEBDA)

Submitted by

LIKITHA B (1BM19CS079)

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

May-2023 to July-2023

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “**BIG DATA ANALYTICS**” carried out by **LIKITHA B (1BM19CS079)**, who is a bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2023. The Lab report has been approved as it satisfies the academic requirements in respect of a Big Data Analytics - (20CS6PEBDA) work prescribed for the said degree.

Rajeshwari Madli
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Jyothi S Nayak
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

Sl. No.	Experiment Title	Page No.
1	Cassandra Lab Program 1: - Employee Database	4
2	Cassandra Lab Program 2: - Library Database	8
3	MongoDB- CRUD Demonstration	11

4	Hadoop Installation	18
5	Hadoop Commands	19
6	Hadoop Program: Average Temperature	21
7	Hadoop Program: Word Count	28
8	Hadoop Program: Join Operation	39
9	Scala Program	47
10	Scala Program: Word Count	48

Course Outcome

CO1	Apply the concept of NoSQL, Hadoop or Spark for a given task
CO2	Analyze the Big Data and obtain insight using data analytics mechanisms.
CO3	Design and implement big data applications by applying NoSQL, Hadoop or Spark

1 Perform the following DB operations using Cassandra.

1. Create a keyspace by name Employee

2. Create a column family by name

Employee-Info with attributes

Emp_Id Primary Key, Emp_Name,

Designation, Date_of_Joining, Salary, Dept_Name

3. Insert the values into the table in batch

4. Update Employee name and Department of Emp-Id 121

5. Sort the details of Employee records based on salary

6. Alter the schema of the table Employee_Info to add a column Projects which stores a set of

Projects done by the corresponding Employee.

7. Update the altered table to add project names.

8. Create a TTL of 15 seconds to display the values of Employees.

```
cqlsh:employee> CREATE KEYSPACE employee WITH REPLICATION={ 'class' : 'SimpleStrategy',  
'replication_factor' : 1}; cqlsh:employee>
```

```
USE employee;
```

```
cqlsh:employee> create table employee_info(emp_id int PRIMARY KEY, emp_name text,  
... designation text, date_of_joining timestamp, salary double PRIMARY KEY, dept_name text);
```

```
cqlsh:employee> CREATE TABLE employee_info(emp_id int, emp_name text, designation text, date_of_joining  
timestamp, salary double, dept_name text, PRIMARY KEY(emp_id, salary));
```

```
cqlsh:employee> BEGIN BATCH INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
... VALUES(100,'John','MANAGER','2021-09-11',30000,'TESTING');
```

```
... INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
... VALUES(111,'Tom','ASSOCIATE','2021-06-22',25000,'DEVELOPING');
```

```
... INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
... VALUES(121,'Elsa','MANAGER','2021-03-30',35000,'HR');
```

```
... INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
... VALUES(115,'Chris','ASSISTANT','2021-12-30',20000,'DEVELOPING');
```

... INSERT INTO

... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)

... VALUES(105,'Sarah','ASSOCIATE','2021-06-25',25000,'TESTING');

... APPLY BATCH; cqlsh:employee> SELECT

* FROM employee_info

... ;

emp_id	salary	date_of_joining	dept_name	designation	emp_name
_____+	+	+
105	25000	2021-06-24 18:30:00.000000+0000	TESTING	ASSOCIATE	Sarah
111	25000	2021-06-21 18:30:00.000000+0000	DEVELOPING	ASSOCIATE	Tom
121	35000	2021-03-29 18:30:00.000000+0000	HR	MANAGER	Elsa
115	20000	2021-12-29 18:30:00.000000+0000	DEVELOPING	ASSISTANT	Chris
100	30000	2021-09-10 18:30:00.000000+0000	TESTING	MANAGER	John

(5 rows)

cqlsh:employee> UPDATE employee_info SET emp_name = 'Jessica', dept_name = 'DEVELOPING' WHERE emp_id = 121;

cqlsh:employee> UPDATE employee_info SET emp_name = 'Jessica', dept_name = 'DEVELOPING' WHERE emp_id = 121 AND salary = 35000;

cqlsh:employee> SELECT * FROM employee_info ;

emp_id	salary	date_of_joining	dept_name	designation	emp_name
_____+	+	+
105	25000	2021-06-24 18:30:00.000000+0000	TESTING	ASSOCIATE	Sarah
111	25000	2021-06-21 18:30:00.000000+0000	DEVELOPING	ASSOCIATE	Tom
121	35000	2021-03-29 18:30:00.000000+0000	DEVELOPING	MANAGER	Jessica
115	20000	2021-12-29 18:30:00.000000+0000	DEVELOPING	ASSISTANT	Chris

100 | 30000 | 2021-09-10 18:30:00.000000+0000 | TESTING | MANAGER | John

(5 rows)

```
cqlsh:employee> SELECT * FROM employee_info WHERE emp_id in (105, 111, 121, 115, 100) order by salary; cqlsh:employee> paging off Disabled Query paging.
```

```
cqlsh:employee> SELECT * FROM employee_info WHERE emp_id in (105, 111, 121, 115, 100) order by salary;
```

emp_id	salary	date_of_joining	dept_name	designation	emp_name
115	20000	2021-12-29 18:30:00.000000+0000	DEVELOPING	ASSISTANT	Chris
105	25000	2021-06-24 18:30:00.000000+0000	TESTING	ASSOCIATE	Sarah
111	25000	2021-06-21 18:30:00.000000+0000	DEVELOPING	ASSOCIATE	Tom
100	30000	2021-09-10 18:30:00.000000+0000	TESTING	MANAGER	John
121	35000	2021-03-29 18:30:00.000000+0000	DEVELOPING	MANAGER	Jessica

(5 rows)

```
cqlsh:employee> ALTER TABLE employee_info ADD projects text; cqlsh:employee>
```

```
UPDATE employee_info SET projects = 'Chat App' WHERE emp_id = 111;
```

```
cqlsh:employee> UPDATE employee_info SET projects = 'Chat App' WHERE emp_id = 111 and salary = 25000;
```

```
cqlsh:employee> UPDATE employee_info SET projects = 'Discord Bot' WHERE emp_id = 115 and salary = 20000;
```

```
cqlsh:employee> UPDATE employee_info SET projects = 'Campus Portal' WHERE emp_id = 105 and salary = 25000;
```

```
cqlsh:employee> UPDATE employee_info SET projects = 'YouTube Downloader' WHERE emp_id = 100 and salary = 30000;
```

```
cqlsh:employee> UPDATE employee_info SET projects = 'Library Management System ' WHERE emp_id = 121 and salary = 35000;
```

```
cqlsh:employee> SELECT * FROM employee_infor
```

... ;

```
cqlsh:employee> SELECT * FROM employee_info ;
```

emp_id	salary	date_of_joining	dept_name	designation	emp_name	projects
105	25000	2021-06-24 18:30:00.000000+0000	TESTING	ASSOCIATE	Sarah	Campus Portal
111	25000	2021-06-21 18:30:00.000000+0000	DEVELOPING	ASSOCIATE	Tom	Chat App
121	35000	2021-03-29 18:30:00.000000+0000	DEVELOPING	MANAGER	Jessica	Library Management System
115	20000	2021-12-29 18:30:00.000000+0000	DEVELOPING	ASSISTANT	Chris	Discord Bot
100	30000	2021-09-10 18:30:00.000000+0000	TESTING	MANAGER	John	YouTube Downloader

(5 rows)

```
cqlsh:employee> INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
...
```

```
... ;
```

```
cqlsh:employee> INSERT INTO
```

```
... employee_info(emp_id,emp_name,designation,date_of_joining,salary,dept_name)
```

```
... VALUES(110,'SAM','ASSOCIATE','2021-01-11',28000,'TESTING') USING TTL 15; cqlsh:employee>
```

```
SELECT TTL(emp_name) from employee_info WHERE emp_id = 110;
```

```
ttl(emp_name)
```

```
-----
```

(1 rows)

```
cqlsh:employee> SELECT * FROM employee_info;
```

emp_id	salary	date_of_joining	dept_name	designation	emp_name	projects
_____++			+_____+	
.....+					+	
105	25000	2021-06-24 18:30:00.000000+0000	TESTING	ASSOCIATE	Sarah	Campus Portal
111	25000	2021-06-21 18:30:00.000000+0000	DEVELOPING	ASSOCIATE	Tom	Chat App
121	35000	2021-03-29 18:30:00.000000+0000	DEVELOPING	MANAGER	Jessica	Library Management System
115	20000	2021-12-29 18:30:00.000000+0000	DEVELOPING	ASSISTANT	Chris	Discord Bot
100	30000	2021-09-10 18:30:00.000000+0000	TESTING	MANAGER	John	YouTube Downloader

(5 rows)

2. Perform the following DB operations using Cassandra.

1. Create a keyspace by name Library

2. Create a column family by name Library-Info with attributes

Stud_Id Primary Key, Counter_value of type Counter, Stud_Name,

Book-Name, Book-Id, Date_of_issue

3. Insert the values into the table in batch

4. Display the details of the table created and increase the value of the counter

5. Write a query to show that a student with id 112 has taken a book “BDA” 2 times.

6. Export the created column to a csv file

7. Import a given csv dataset from local file system into Cassandra column family

```
cqlsh:library> CREATE KEYSPACE library WITH replication = {'class': 'SimpleStrategy','replication_factor':1};  
cqlsh:library> USE library ;
```

```
cqlsh:library> CREATE TABLE Library_info(stud_id int, stud_name text, book_name text, book_id text,  
date_of_issue timestamp, counter_value counter, PRIMARY KEY(stud_id,stud_name, book_name, book_id,  
date_of_issue));
```

```
cqlsh:library> BEGIN COUNTER BATCH
```

```
... UPDATE library_info set counter_value +=1 where stud_id = 111 and stud_name = 'Manoj' and  
book_name = 'Operations Research' and book_id = '56TXT' and date_of_issue = '2021-09-12';
```

```
... UPDATE library_info set counter_value +=1 where stud_id = 112 and stud_name = 'Kamal' and  
book_name = 'Engineering Mathematics-3' and book_id = '5ERW4' and date_of_issue = '2021-04-10';
```

```
... UPDATE library_info set counter_value +=1 where stud_id = 113 and stud_name = 'Mahesh' and  
book_name = 'Robinson Crusoe' and book_id = '34EDC' and date_of_issue = '2021-02-01';
```

```
... UPDATE library_info set counter_value +=1 where stud_id = 114 and stud_name = 'Raj' and book_name  
= 'Engineering Drawing' and book_id = '123ER' and date_of_issue = '2021-04-03';
```

```
... APPLY BATCH;
```

```
cqlsh:library> SELECT * FROM library_info ;
```

stud_id	stud_name	book_name	book_id	date_of_issue	counter_value
114	Raj	Engineering Drawing	123ER	2021-04-02 18:30:00.000000+0000	1
111	Manoj	Operations Research	56TXT	2021-09-11 18:30:00.000000+0000	1
113	Mahesh	Robinson Crusoe	34EDC	2021-01-31 18:30:00.000000+0000	1
112	Kamal	Engineering Mathematics-3	5ERW4	2021-04-09 18:30:00.000000+0000	1

(4 rows)

```
cqlsh:library> UPDATE library_info set counter_value += 1 where stud_id = 112 and stud_name = 'Kamal' and
book_name = 'Engineering Mathematics-3' and book_id = '5ERW4' and date_of_issue = '2021-04-09';

cqlsh:library> SELECT * FROM library_info ;
```

stud_id	stud_name	book_name	book_id	date_of_issue	counter_value
114	Raj	Engineering Drawing	123ER	2021-04-02 18:30:00.000000+0000	1
111	Manoj	Operations Research	56TXT	2021-09-11 18:30:00.000000+0000	1
113	Mahesh	Robinson Crusoe	34EDC	2021-01-31 18:30:00.000000+0000	1
112	Kamal	Engineering Mathematics-3	5ERW4	2021-04-09 18:30:00.000000+0000	2

```
cqlsh:library> copy library_info(stud_id,stud_name, book_name, book_id, date_of_issue,counter_value) to
'library_info.csv' ;
```

Using 11 child processes

Starting copy of library.library_info with columns [stud_id, stud_name, book_name, book_id, date_of_issue, counter_value].

Processed: 6 rows; Rate: 39 rows/s; Avg. rate: 39 rows/s 6

rows exported to 1 files in 0.165 seconds.

```
cqlsh:library> copy library_info(stud_id,stud_name, book_name, book_id, date_of_issue,counter_value) from
'library_info.csv' ;
```

Using 11 child processes

Starting copy of library.library_info with columns [stud_id, stud_name, book_name, book_id, date_of_issue, counter_value].

Processed: 6 rows; Rate: 10 rows/s; Avg. rate: 15 rows/s 6

rows imported from 1 files in 0.392 seconds (0 skipped).

3. MongoDB- CRUD Demonstration

bmsce@bmsce-Precision-T1700:~\$ mongo

MongoDB shell version v3.6.8 connecting

to: mongodb://127.0.0.1:27017

Implicit session: session { "id" : UUID("d66acdb3-8482-417d-8b75-d65dae4b53ee") }

MongoDB server version: 3.6.8

> use Student switched

to db Student

> db.createCollection("student");

{ "ok" : 1 }

> db.Student.insert({_id:1,StudName:"Megha",Grade:"vii",Hobbies:"InternetSurfing"});

WriteResult({ "nInserted" : 1 })

> db.Student.update({_id:3,StudName:"Ayan",Grade:"vii"},{\$set:{Hobbies:"skating"}},{upsert:true});

WriteResult({ "nMatched" : 0, "nUpserted" : 1, "nModified" : 0, "_id" : 3 })

> db.Student.find({StudName:"Ayan"});

{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }

> db.Student.find({}, {StudName:1,Grade:1,_id:0});

{ "StudName" : "Megha", "Grade" : "vii" }

{ "Grade" : "vii", "StudName" : "Ayan" }

```
> db.Student.find({Grade:{Seq:'vii'}}).pretty();
```

```
{  
  
  "_id" : 1,  
  "StudName" : "Megha",  
  "Grade" : "vii",  
  "Hobbies" : "InternetSurfing"  
}
```

```
{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
```

```
> db.Student.find({Grade:{Seq:'vii'}});
```

```
{ "_id" : 1, "StudName" : "Megha", "Grade" : "vii", "Hobbies" : "InternetSurfing" }
```

```
{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
```

```
> db.Student.find({Grade:{Seq:'vii'}}).pretty();
```

```
{  
  
  "_id" : 1,  
  "StudName" : "Megha",  
  "Grade" : "vii",  
  "Hobbies" : "InternetSurfing"  
}
```

```
{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
```

```
> db.Student.find({Hobbies:{$in:['Chess','Skating']}}).pretty();
```

```
> db.Student.find({Hobbies:{$in:['Skating']}}).pretty();
```

```
> db.Student.find({Hobbies:{$in:['skating']}}).pretty();
```

```
{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
```

```
> db.Student.find({StudName:/^M/}).pretty();
```

```
{  
  
  "_id" : 1,  
  "StudName" : "Megha",  
  "Grade" : "vii",  
  "Hobbies" : "InternetSurfing"  
}
```

```
> db.Student.find({StudName:/e/}).pretty();
```

```
{  
  
  "_id" : 1,  
  "StudName" : "Megha",  
  "Grade" : "vii",  
  "Hobbies" : "InternetSurfing"  
}
```

```
> db.Student.count();
```

```
2
```

```
> db.Student.find().sort({StudName:-1}).pretty();
```

```
{  
  
  "_id" : 1,  
  "StudName" : "Megha",  
  "Grade" : "vii",  
  "Hobbies" : "InternetSurfing"  
}
```

```
{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
```

```

> db.Student.save({StudName:"Vamsi",Greade:"vi"})
WriteResult({ "nInserted" : 1 })

> db.Students.update({_id:4},{ $set:{Location:"Network"}})
WriteResult({ "nMatched" : 0, "nUpserted" : 0, "nModified" : 0 })

> db.Students.update({_id:4},{ $unset:{Location:"Network"}})
WriteResult({ "nMatched" : 0, "nUpserted" : 0, "nModified" : 0 })

> db.Student.find({_id:1},{StudName:1,Grade:1,_id:0});
{ "StudName" : "Megha", "Grade" : "vii" }

> db.Student.find({Grade:{ $ne:'VII'}}).pretty();
{
  "_id" : 1,
  "StudName" : "Megha",
  "Grade" : "vii",
  "Hobbies" : "InternetSurfing"
}

{ "_id" : 3, "Grade" : "vii", "StudName" : "Ayan", "Hobbies" : "skating" }
{
  "_id" : ObjectId("6253f413e88b8c9e787b194e"),
  "StudName" : "Vamsi",
  "Grade" : "vi"
}

> db.Student.find({StudName:/s$/}).pretty();

> db.Students.update({_id:3},{ $set:{Location:null}})
WriteResult({ "nMatched" : 0, "nUpserted" : 0, "nModified" : 0 })

> db.Students.count()

```

```

0
> db.Students.count({Grade:"VII"})
0
> db.Student.find({Grade:"VII"}).limit(3).pretty();
> db.Student.update({_id:3},{ $set:{Location:null}})
WriteResult({ "nMatched" : 1, "nUpserted" : 0, "nModified" : 1 })
> db.Student.count({Grade:"VII"})
0
> db.Students.count({Grade:"vii"})
0
> db.Student.count()
3
> db.Student.count({Grade:"vii"})
2
> db.Student.find({Grade:"vii"}).limit(3).pretty();
{
  "_id" : 1,
  "StudName" : "Megha",
  "Grade" : "vii",
  "Hobbies" : "InternetSurfing"
}{
  "_id" : 3,
  "Grade" : "vii",
  "StudName" : "Ayan",
  "Hobbies" : "skating",
  "Location" : null
}

```

```

> db.Student.find().sort({StudName:1}).pretty();
{
  "_id" : 3,
  "Grade" : "vii",
  "StudName" : "Ayan",
  "Hobbies" : "skating",
  "Location" : null
}
{
  "_id" : 1,
  "StudName" : "Megha",
  "Grade" : "vii",
  "Hobbies" : "InternetSurfing"
}
{
  "_id" : ObjectId("6253f413e88b8c9e787b194e"),
  "StudName" : "Vamsi",
  "Grade" : "vi"
}

> db.Student.find().skip(2).pretty()
{
  "_id" : ObjectId("6253f413e88b8c9e787b194e"),
  "StudName" : "Vamsi",
  "Grade" : "vi"
}

```



```

> db.food.insert( { _id:1, fruits:['grapes','mango','apple']; } )
2022-04-11T15:05:51.894+0530 E QUERY [thread1] SyntaxError: missing ] after element list @(shell):1:57

> db.food.insert({_id:1,fruits:['grapes','mango','apple']})
WriteResult({ "nInserted" : 1 })

> db.food.insert({_id:2,fruits:['grapes','mango','cherry']})
WriteResult({ "nInserted" : 1 })

> db.food.insert({_id:3,fruits:['banana','mango']})
WriteResult({ "nInserted" : 1 })

> db.food.find({fruits:['grapes','mango','apple']}).pretty();
{ "_id" : 1, "fruits" : [ "grapes", "mango", "apple" ] }

> db.food.find({'fruits.1':'grapes'})
> db.food.find({"fruits":{"$size:2}})
{ "_id" : 3, "fruits" : [ "banana", "mango" ] }

> db.food.find({_id:1},{"fruits":{"$slice:2}})
{ "_id" : 1, "fruits" : [ "grapes", "mango" ] }

> db.food.find({fruits:$all:["mango","grapes"]})
{ "_id" : 1, "fruits" : [ "grapes", "mango", "apple" ] }
{ "_id" : 2, "fruits" : [ "grapes", "mango", "cherry" ] }

> db.food.update({_id:3},{ $set:{"fruits.1":"apple"}})
WriteResult({ "nMatched" : 1, "nUpserted" : 0, "nModified" : 1 })

> db.food.update({_id:2},{ $push:{price:{grapes:80,mango:200,cherry:100}}})
WriteResult({ "nMatched" : 1, "nUpserted" : 0, "nModified" : 1 })

>db.Customers.insert({_custID:1,AcctBal:'100000',AcctType:"saving"});
WriteResult({ "nInserted" : 1 })

> db.Customers.aggregate({$group:{_id:"$custID",TotAccBal:{$sum:"$AccBal"}}});

```

```
{ "_id" : null, "TotAccBal" : 0 }
```

```
db.Customers.aggregate({$match:{AcctType:"saving"}},{ $group:{_id:"$custID",TotAccBal:{$sum:"$AccBal"}}});
```

```
{ "_id" : null, "TotAccBal" : 0 }
```

```
db.Customers.aggregate({$match:{AcctType:"saving"}},{ $group:{_id:"$custID",TotAccBal:{$sum:"$AccBal"}}},{ $match:{TotAccBal:{$gt:1200}}});
```

4. Screenshot of Hadoop installed

```
Microsoft Windows [Version 10.0.22000.739]
(c) Microsoft Corporation. All rights reserved.

C:\WINDOWS\system32>start-all.cmd
This script is Deprecated. Instead use start-dfs.cmd and start-yarn.cmd
starting yarn daemons
C:\WINDOWS\system32>jps
7072 DataNode
13492 Jps
15844 ResourceManager
16196 NameNode
1388 NodeManager

C:\WINDOWS\system32>hdfs dfs -ls -R /
drwxr-xr-x  - khush supergroup          0 2022-06-27 14:09 /input
drwxr-xr-x  - khush supergroup          0 2022-06-21 09:03 /input/inputtest
-rw-r--r--  1 khush supergroup        21 2022-06-21 09:03 /input/inputtest/output.txt
-rw-r--r--  1 khush supergroup        21 2022-06-21 08:19 /input/sample.txt
-rw-r--r--  1 khush supergroup        21 2022-06-27 14:09 /input/sample2.txt
drwxr-xr-x  - khush supergroup          0 2022-06-21 13:30 /test
-rw-r--r--  1 khush supergroup        19 2022-06-21 13:30 /test/sample.txt

C:\WINDOWS\system32>hadoop version
Hadoop 3.3.3
Source code repository https://github.com/apache/hadoop.git -r d37586cbda38c338d9fe481adda5a05fb516f71
Compiled by stevel on 2022-05-09T16:36Z
Compiled with protoc 3.7.1
From source with checksum eb96dd4a797b6989ae0cdb9db6efc6
This command was run using /C:/hadoop-3.3.3/share/hadoop/common/hadoop-common-3.3.3.jar

C:\WINDOWS\system32>
```

5. Execution of HDFS Commands for interaction with Hadoop Environment.

```
hduser@bmsce-Precision-T1700:~$ start-all.sh
```

```
hduser@bmsce-Precision-T1700:~$ jps
```

```
7184 NodeManager
```

```
6851 ResourceManager
```

```
6692 SecondaryNameNode
```

```
6313 NameNode
```

```
7306 Jps
```

```
6479 DataNode
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -mkdir /1BM19CS167
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /
```

```
Found 5 items
```

```
drwxr-xr-x - hduser supergroup      0 2022-06-01 09:30 /1BM19CS167
```

```
drwxr-xr-x - hduser supergroup      0 2022-05-31 09:58 /abcde
```

```
drwxr-xr-x - hduser supergroup      0 2022-05-31 10:04 /abcdef
```

```
drwxrwxr-x - hduser supergroup      0 2019-08-01 16:19 /tmp
```

```
drwxr-xr-x - hduser supergroup      0 2019-08-01 16:03 /user
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -put /home/hduser/Desktop/Welcome.txt /1BM19CS167/WC.txt
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -cat /1BM19CS167/WC.txt
```

```
Science in our Daily Lives
```

```
As I have mentioned earlier Science has got many changes in our lives. First of all, transportation is easier now.
```

With the help of Science it now easier to travel long distances. Moreover, the time of traveling is also reduced. Various high-speed vehicles are available these days. These vehicles have totally changed. The phase of our society. Science upgraded steam engines to electric engines. In earlier times people were traveling with cycles. But now everybody travels on motorcycles and cars. This saves time and effort. And this is all possible with the help of Science.

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -get /1BM19CS167/WC.txt /home/hduser/Desktop/WWC.txt
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -put /home/hduser/Desktop/Welcome.txt /1BM19CS167/WC2.txt
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -getmerge /1BM19CS167/WC.txt /1BM19CS167/WC2.txt /home/hduser/Desktop/Merge.txt
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -getfacl /1BM19CS167/
```

```
# file: /1BM19CS167
```

```
# owner: hduser #
```

```
group: supergroup
```

```
user::rwx group::r-x
```

```
other::r-x
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -copyToLocal /1BM19CS167/WC.txt /home/hduser/Desktop
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -mv /1BM19CS167 /1bm19cs167
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /
```

```
Found 5 items
```

```
drwxr-xr-x - hduser supergroup      0 2022-06-01 10:03 /1bm19cs167
```

```
drwxr-xr-x - hduser supergroup      0 2022-05-31 09:58 /abcde
```

```
drwxr-xr-x - hduser supergroup    0 2022-05-31 10:04 /abcdef
```

```
drwxrwxr-x - hduser supergroup    0 2019-08-01 16:19 /tmp drwxr-
```

```
xr-x - hduser supergroup    0 2019-08-01 16:03 /user
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /1bm19cs167
```

Found 2 items

```
-rw-r--r-- 1 hduser supergroup      1812 2022-06-01 09:39 /1bm19cs167/WC.txt
```

```
-rw-r--r-- 1 hduser supergroup      607 2022-06-01 10:03 /1bm19cs167/WC2.txt
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -cp /1bm19cs167 /1BM19CS167
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /
```

Found 6 items

```
drwxr-xr-x - hduser supergroup    0 2022-06-01 10:15 /1BM19CS167
```

```
drwxr-xr-x - hduser supergroup    0 2022-06-01 10:03 /1bm19cs167
```

```
drwxr-xr-x - hduser supergroup    0 2022-05-31 09:58 /abcde
```

```
drwxr-xr-x - hduser supergroup    0 2022-05-31 10:04 /abcdef
```

```
drwxrwxr-x - hduser supergroup    0 2019-08-01 16:19 /tmp
```

```
drwxr-xr-x - hduser supergroup    0 2019-08-01 16:03 /user
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /1BM19CS167
```

Found 2 items

```
-rw-r--r-- 1 hduser supergroup      1812 2022-06-01 10:15 /1BM19CS167/WC.txt
```

```
-rw-r--r-- 1 hduser supergroup      607 2022-06-01 10:15 /1BM19CS167/WC2.txt
```

6. Create a Map Reduce program to

a) find average temperature for each year from the NCDC data set.

b) find the mean max temperature for every month

AverageDriver

```
package temp; import org.apache.hadoop.fs.Path; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Job; import
org.apache.hadoop.mapreduce.lib.input.FileInputFormat; import
org.apache.hadoop.mapreduce.lib.output.FileOutputFormat; public
class AverageDriver { public static void main(String[] args) throws
Exception { if (args.length != 2) {
System.err.println("Please Enter the input and output parameters");
System.exit(-1);
}
Job job = new Job();
job.setJarByClass(AverageDriver.class);
job.setJobName("Max temperature");
FileInputFormat.addInputPath(job, new Path(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));
job.setMapperClass(AverageMapper.class);
job.setReducerClass(AverageReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}
```

AverageMapper

```
package temp; import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Mapper;
public class AverageMapper extends Mapper<LongWritable, Text, Text, IntWritable> { public
static final int MISSING = 9999;

public void map(LongWritable key, Text value, Mapper<LongWritable, Text, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int
temperature;

String line = value.toString(); String year =
line.substring(15, 19); if (line.charAt(87) == '+') {
temperature = Integer.parseInt(line.substring(88, 92));
} else {
temperature = Integer.parseInt(line.substring(87, 92));
}


String quality = line.substring(92, 93);
if (temperature != 9999 && quality.matches("[01459]")) context.write(new
Text(year), new IntWritable(temperature));
}
}
```

AverageReducer

```

package temp; import java.io.IOException;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Reducer;
public class AverageReducer extends Reducer<Text, IntWritable, Text, IntWritable> {
    public void reduce(Text key, Iterable<IntWritable> values, Reducer<Text, IntWritable, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int max_temp =
0;
int count = 0; for (IntWritable
value : values) { max_temp +=
value.get(); count++;
}
context.write(key, new IntWritable(max_temp / count));
}
}

```



```

c:\hadoop_new\sbin>hdfs dfs -cat /tempAverageOutput/part-r-00000
1901    46
1949    94
1950     3

```

MeanMaxDriver.class

```

package meanmax; import org.apache.hadoop.fs.Path; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Job; import
org.apache.hadoop.mapreduce.lib.input.FileInputFormat; import
org.apache.hadoop.mapreduce.lib.output.FileOutputFormat; public
class MeanMaxDriver { public static void main(String[] args) throws
Exception { if (args.length != 2) {

```



```

System.err.println("Please Enter the input and output parameters");
System.exit(-1);
}
Job job = new Job();
job.setJarByClass(MeanMaxDriver.class);
job.setJobName("Max temperature");
FileInputFormat.addInputPath(job, new Path(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));
job.setMapperClass(MeanMaxMapper.class);
job.setReducerClass(MeanMaxReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
System.exit(job.waitForCompletion(true) ? 0 : 1);
} }
M
ea
n
M
ax
M
ap
pe
r.c
las
s

```

```
package meanmax;
```

```

import      java.io.IOException;      import
org.apache.hadoop.io.IntWritable;    import
org.apache.hadoop.io.LongWritable;   import
org.apache.hadoop.io.Text;           import
org.apache.hadoop.mapreduce.Mapper;

public class MeanMaxMapper extends Mapper<LongWritable, Text, Text, IntWritable> {
    public static final int MISSING = 9999;

    public void map(LongWritable key, Text value, Mapper<LongWritable, Text, Text,
    IntWritable>.Context context) throws IOException, InterruptedException { int
    temperature;

    String line = value.toString(); String month =
    line.substring(19, 21); if (line.charAt(87) == '+') {
    temperature = Integer.parseInt(line.substring(88, 92));
    } else {
    temperature = Integer.parseInt(line.substring(87, 92));
    }

    String quality = line.substring(92, 93); if (temperature != 9999 &&
    quality.matches("[01459]")) context.write(new Text(month), new
    IntWritable(temperature));
    }
}

```

MeanMaxReducer.class

```

package meanmax; import java.io.IOException;
import      org.apache.hadoop.io.IntWritable;

```

```

import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Reducer;

public class MeanMaxReducer extends Reducer<Text, IntWritable, Text, IntWritable> {

    public void reduce(Text key, Iterable<IntWritable> values, Reducer<Text, IntWritable, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int max_temp =
0; int total_temp = 0; int count = 0;


    int days = 0; for (IntWritable
value : values) {

        int temp = value.get(); if
(temp > max_temp)

            max_temp = temp;
        count++; if (count == 3) {
            total_temp += max_temp;
            max_temp = 0;
            count = 0; days++;
        }
    }

    context.write(key, new IntWritable(total_temp / days));
}
}

```



A terminal window showing a command to cat a file from HDFS. The command is: `c:\hadoop_new\sbin>hdfs dfs -cat /tempMaxOutput/part-r-00000`. The output is a list of 12 lines, each with a number from 01 to 12 followed by a value. The values are: 44, 17, 111, 194, 256, 278, 317, 283, 211, 156, 89, 117.

01	44
02	17
03	111
04	194
05	256
06	278
07	317
08	283
09	211
10	156
11	89
12	117

7. For a given Text file, Create a Map Reduce program to sort the content in an alphabetic order listing only top 10 maximum occurrences of words.

```
//Driver Code package  
wordCount;  
import java.io.IOException;  
import org.apache.hadoop.conf.Configured; import  
org.apache.hadoop.fs.Path; import  
org.apache.hadoop.io.IntWritable; import  
org.apache.hadoop.io.Text; import  
org.apache.hadoop.mapred.FileInputFormat; import  
org.apache.hadoop.mapred.FileOutputFormat;  
  
import org.apache.hadoop.mapred.JobClient;  
import org.apache.hadoop.mapred.JobConf;  
import org.apache.hadoop.util.Tool;  
import org.apache.hadoop.util.ToolRunner;  
  
public class WCDriver extends Configured implements Tool {  
    public int run(String args[]) throws IOException  
    {  
        if (args.length < 2)  
        {  
            System.out.println("Please give valid inputs"); return  
            -1;  
        }  
    }  
}
```

```

        JobConf conf = new JobConf(WCDriver.class);
        FileInputFormat.setInputPaths(conf, new Path(args[0]));
        FileOutputFormat.setOutputPath(conf, new Path(args[1]));
        conf.setMapperClass(WCMapper.class);
        conf.setReducerClass(WCReducer.class);
        conf.setMapOutputKeyClass(Text.class);
        conf.setMapOutputValueClass(IntWritable.class);
        conf.setOutputKeyClass(Text.class);
        conf.setOutputValueClass(IntWritable.class);
        JobClient.runJob(conf);
        return 0;
    }

    // Main Method
    public static void main(String args[]) throws Exception
    {

        int exitCode = ToolRunner.run(new WCDriver(), args);
        System.out.println(exitCode);
    }
}

//Mapper Code package
wordCount;    import
java.io.IOException;

import org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.LongWritable; import
org.apache.hadoop.io.Text; import

```

```

org.apache.hadoop.mapred.MapReduceBase; import
org.apache.hadoop.mapred.Mapper;
import org.apache.hadoop.mapred.OutputCollector;

import org.apache.hadoop.mapred.Reporter;

public class WCMapper extends MapReduceBase implements Mapper<LongWritable,Text, Text, IntWritable> {
    // Map function
    public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable> output, Reporter
rep) throws IOException
    {

        String line = value.toString(); //
        Splitting the line on spaces for
        (String word : line.split(" "))
        {

            if (word.length() > 0)
            {

                output.collect(new Text(word), new IntWritable(1));
            }
        }
    }
}

//Reducer Code

package wordCount;

```

```

import java.io.IOException; import java.util.Iterator;
import org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.MapReduceBase; import
org.apache.hadoop.mapred.OutputCollector; import
org.apache.hadoop.mapred.Reducer;
import org.apache.hadoop.mapred.Reporter;

public class WCReducer extends MapReduceBase implements Reducer<Text,IntWritable, Text, IntWritable> {
    // Reduce function
    public void reduce(Text key, Iterator<IntWritable> value, OutputCollector<Text, IntWritable>
output,Reporter rep) throws IOException
    {

        int count = 0;
        // Counting the frequency of each words while
        (value.hasNext())
        {

            IntWritable i = value.next(); count
            += i.get();

        }

        output.collect(key, new IntWritable(count));
    }
}
//Hadoo
p
Comman
ds

```

```
hduser@bmsce-Precision-T1700:~$ start-all.sh
```

This script is Deprecated. Instead use start-dfs.sh and start-yarn.sh

Starting namenodes on [localhost] hduser@localhost's password:

localhost: namenode running as process 10473. Stop it first.

hduser@localhost's password:

localhost: datanode running as process 10644. Stop it first.

Starting secondary namenodes [0.0.0.0] hduser@0.0.0.0's

password:

0.0.0.0: secondarynamenode running as process 10857. Stop it first.

starting yarn daemons resourcemanager running as process 9796.

Stop it first. hduser@localhost's password: localhost: nodemanager

running as process 10160. Stop it first.

```
hduser@bmsce-Precision-T1700:~$ jps
```

```
10160 NodeManager
```

```
7441 org.eclipse.equinox.launcher_1.5.600.v20191014-2022.jar
```

```
9796 ResourceManager
```

```
12692 org.eclipse.equinox.launcher_1.5.600.v20191014-2022.jar
```

```
10644 DataNode
```

```
10857 SecondaryNameNode
```

```
10473 NameNode
```

```
15100 Jps
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -ls /
```

Found 10 items

```
drwxr-xr-x - hduser supergroup      0 2019-10-23 09:52 /gou
```

```
drwxr-xr-x - hduser supergroup      0 2019-10-23 10:33 /har
```



```
drwxr-xr-x - hduser supergroup      0 2022-06-14 10:50 /input
drwxr-xr-x - hduser supergroup      0 2019-10-23 09:58 /output1
drwxr-xr-x - hduser supergroup      0 2019-10-23 15:57 /output2
drwxr-xr-x - hduser supergroup      0 2022-06-15 10:27 /rgs
drwxr-xr-x - hduser supergroup      0 2019-10-23 11:09 /stud
drwxr-xr-x - hduser supergroup      0 2019-10-23 15:50 /testing
drwxrwxr-x - hduser supergroup       0 2019-10-23 11:24 /tmp
drwxr-xr-x - hduser supergroup      0 2019-08-01 16:03 /user
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -mkdir /1BM19CS167
```

```
hduser@bmsce-Precision-T1700:~$ hadoop fs -copyFromLocal /home/hduser/Desktop/sample.txt
/1BM19CS167/test.txt
```

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -cat /1BM19CS167/test.txt
```

```
hi how are you how is your job how is your family how is your brother
how is your sister
```

```
hduser@bmsce-Precision-T1700:~$ hadoop jar /home/hduser/Documents/wordCount.jar
wordCount.WCDriver /1BM19CS167/test.txt /1BM19CS167/output
```

```
22/06/15 10:27:53 INFO Configuration.deprecation: session.id is deprecated. Instead, use dfs.metrics.session-
id
```

```
22/06/15 10:27:53 INFO jvm.JvmMetrics: Initializing JVM Metrics with processName=JobTracker, sessionId=
```

```
22/06/15 10:27:53 INFO jvm.JvmMetrics: Cannot initialize JVM Metrics with processName=JobTracker,
sessionId= - already initialized
```

```
22/06/15 10:27:53 WARN mapreduce.JobSubmitter: Hadoop command-line option parsing not performed.
Implement the Tool interface and execute your application with ToolRunner to remedy this.
```

```
22/06/15 10:27:53 INFO mapred.FileInputFormat: Total input paths to process : 1
```

```
22/06/15 10:27:53 INFO mapreduce.JobSubmitter: number of splits:1
```

22/06/15 10:27:53 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_local1115189753_0001

22/06/15 10:27:53 INFO mapreduce.Job: The url to track the job: http://localhost:8080/

22/06/15 10:27:53 INFO mapred.LocalJobRunner: OutputCommitter set in config null

22/06/15 10:27:53 INFO mapreduce.Job: Running job: job_local1115189753_0001

22/06/15 10:27:53 INFO mapred.LocalJobRunner: OutputCommitter is org.apache.hadoop.mapred.FileOutputCommitter

22/06/15 10:27:53 INFO mapred.LocalJobRunner: Waiting for map tasks

22/06/15 10:27:53 INFO mapred.LocalJobRunner: Starting task: attempt_local1115189753_0001_m_000000_0

22/06/15 10:27:53 INFO mapred.Task: Using ResourceCalculatorProcessTree : []

22/06/15 10:27:53 INFO mapred.MapTask: Processing split: hdfs://localhost:54310/rgs/test.txt:0+89

22/06/15 10:27:53 INFO mapred.MapTask: numReduceTasks: 1

22/06/15 10:27:54 INFO mapred.MapTask: (EQUATOR) 0 kvi 26214396(104857584)

22/06/15 10:27:54 INFO mapred.MapTask: mapreduce.task.io.sort.mb: 100

22/06/15 10:27:54 INFO mapred.MapTask: soft limit at 83886080

22/06/15 10:27:54 INFO mapred.MapTask: bufstart = 0; bufvoid = 104857600

22/06/15 10:27:54 INFO mapred.MapTask: kvstart = 26214396; length = 6553600

22/06/15 10:27:54 INFO mapred.MapTask: Map output collector class = org.apache.hadoop.mapred.MapTask\$MapOutputBuffer 22/06/15 10:27:54 INFO mapred.LocalJobRunner:

22/06/15 10:27:54 INFO mapred.MapTask: Starting flush of map output

22/06/15 10:27:54 INFO mapred.MapTask: Spilling map output

22/06/15 10:27:54 INFO mapred.MapTask: bufstart = 0; bufend = 169; bufvoid = 104857600

22/06/15 10:27:54 INFO mapred.MapTask: kvstart = 26214396(104857584); kvend = 26214320(104857280); length = 77/6553600

22/06/15 10:27:54 INFO mapred.MapTask: Finished spill 0

22/06/15 10:27:54 INFO mapred.Task: Task:attempt_local1115189753_0001_m_000000_0 is done. And is in the process of committing

22/06/15 10:27:54 INFO mapred.LocalJobRunner: hdfs://localhost:54310/rgs/test.txt:0+89 22/06/15 10:27:54 INFO mapred.Task: Task 'attempt_local1115189753_0001_m_000000_0' done.

22/06/15 10:27:54 INFO mapred.LocalJobRunner: Finishing task:
attempt_local1115189753_0001_m_000000_0

22/06/15 10:27:54 INFO mapred.LocalJobRunner: map task executor complete.

22/06/15 10:27:54 INFO mapred.LocalJobRunner: Waiting for reduce tasks

22/06/15 10:27:54 INFO mapred.LocalJobRunner: Starting task: attempt_local1115189753_0001_r_000000_0

22/06/15 10:27:54 INFO mapred.Task: Using ResourceCalculatorProcessTree : []

22/06/15 10:27:54 INFO mapred.ReduceTask: Using ShuffleConsumerPlugin:
org.apache.hadoop.mapreduce.task.reduce.Shuffle@1bc68cd5

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: MergerManager: memoryLimit=334338464,
maxSingleShuffleLimit=83584616, mergeThreshold=220663392, ioSortFactor=10,
memToMemMergeOutputsThreshold=10

22/06/15 10:27:54 INFO reduce.EventFetcher: attempt_local1115189753_0001_r_000000_0 Thread started:
EventFetcher for fetching Map Completion Events

22/06/15 10:27:54 INFO reduce.LocalFetcher: localfetcher#1 about to shuffle output of map
attempt_local1115189753_0001_m_000000_0 decomp: 211 len: 215 to MEMORY

22/06/15 10:27:54 INFO reduce.InMemoryMapOutput: Read 211 bytes from map-output for
attempt_local1115189753_0001_m_000000_0

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: closeInMemoryFile -> map-output of size: 211,
inMemoryMapOutputs.size() -> 1, commitMemory -> 0, usedMemory -> 211

22/06/15 10:27:54 INFO reduce.EventFetcher: EventFetcher is interrupted.. Returning 22/06/15
10:27:54 INFO mapred.LocalJobRunner: 1 / 1 copied.

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: finalMerge called with 1 in-memory map-outputs and 0
on-disk map-outputs

22/06/15 10:27:54 INFO mapred.Merger: Merging 1 sorted segments

22/06/15 10:27:54 INFO mapred.Merger: Down to the last merge-pass, with 1 segments left of total size: 205
bytes

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: Merged 1 segments, 211 bytes to disk to satisfy reduce
memory limit

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: Merging 1 files, 215 bytes from disk

22/06/15 10:27:54 INFO reduce.MergeManagerImpl: Merging 0 segments, 0 bytes from memory into reduce

22/06/15 10:27:54 INFO mapred.Merger: Merging 1 sorted segments

22/06/15 10:27:54 INFO mapred.Merger: Down to the last merge-pass, with 1 segments left of total size: 205 bytes

22/06/15 10:27:54 INFO mapred.LocalJobRunner: 1 / 1 copied.

22/06/15 10:27:54 INFO mapred.Task: Task:attempt_local1115189753_0001_r_000000_0 is done. And is in the process of committing

22/06/15 10:27:54 INFO mapred.LocalJobRunner: 1 / 1 copied.

22/06/15 10:27:54 INFO mapred.Task: Task attempt_local1115189753_0001_r_000000_0 is allowed to commit now

22/06/15 10:27:54 INFO output.FileOutputCommitter: Saved output of task 'attempt_local1115189753_0001_r_000000_0' to
hdfs://localhost:54310/rgs/output/_temporary/0/task_local1115189753_0001_r_000000

22/06/15 10:27:54 INFO mapred.LocalJobRunner: reduce > reduce

22/06/15 10:27:54 INFO mapred.Task: Task 'attempt_local1115189753_0001_r_000000_0' done.

22/06/15 10:27:54 INFO mapred.LocalJobRunner: Finishing task: attempt_local1115189753_0001_r_000000_0

22/06/15 10:27:54 INFO mapred.LocalJobRunner: reduce task executor complete.

22/06/15 10:27:54 INFO mapreduce.Job: Job job_local1115189753_0001 running in uber mode : false

22/06/15 10:27:54 INFO mapreduce.Job: map 100% reduce 100%

22/06/15 10:27:54 INFO mapreduce.Job: Job job_local1115189753_0001 completed successfully

22/06/15 10:27:54 INFO mapreduce.Job: Counters: 38

File System Counters

FILE: Number of bytes read=8614

FILE: Number of bytes written=510599

FILE: Number of read operations=0

FILE: Number of large read operations=0

FILE: Number of write operations=0

HDFS: Number of bytes read=178

HDFS: Number of bytes written=69

HDFS: Number of read operations=13

HDFS: Number of large read operations=0

HDFS: Number of write operations=4

Map-Reduce Framework

Map input records=5

Map output records=20

Map output bytes=169

Map output materialized bytes=215

Input split bytes=87

Combine input records=0

Combine output records=0

Reduce input groups=10

Reduce shuffle bytes=215

Reduce input records=20

Reduce output records=10

Spilled Records=40

Shuffled Maps =1

Failed Shuffles=0

Merged Map outputs=1

GC time elapsed (ms)=1

CPU time spent (ms)=0

Physical memory (bytes) snapshot=0

Virtual memory (bytes) snapshot=0

Total committed heap usage (bytes)=471859200

Shuffle Errors

BAD_ID=0

CONNECTION=0

IO_ERROR=0

WRONG_LENGTH=0

WRONG_MAP=0

WRONG_REDUCE=0

File Input Format Counters

Bytes Read=89

File Output Format Counters

Bytes Written=69

0

```
hduser@bmsce-Precision-T1700:~$ hdfs dfs -cat /1BM19CS167/output/part-00000
```

are 1

brother 1

family 1

hi 1

how 5

is 4

job 1

sister 1

you 1 your 4

8. Create a Map Reduce program to demonstrating join operation

```
// JoinDriver.java import org.apache.hadoop.conf.Configured; import
org.apache.hadoop.fs.Path; import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.*; import
org.apache.hadoop.mapred.lib.TextInputFormat; import
org.apache.hadoop.util.*; public class JoinDriver extends Configured
implements Tool { public static class KeyPartitioner implements
Partitioner<TextPair, Text> {
@Override
public void configure(JobConf job) {}
```

@Override

```
public int getPartition(TextPair key, Text value, int numPartitions) {  
    return (key.getFirst().hashCode() & Integer.MAX_VALUE) %  
    numPartitions;  
}  
}
```

@Override

```
public int run(String[] args) throws Exception { if  
(args.length != 3) {  
    System.out.println("Usage: <Department Emp Strength input>  
<Department Name input> <output>"); return  
-1;  
}  
JobConf conf = new JobConf(getConf(), getClass()); conf.setJobName("Join 'Department  
Emp Strength input' with 'Department Nameinput'");  
Path AInputPath = new Path(args[0]); Path  
BInputPath = new Path(args[1]); Path  
outputPath = new Path(args[2]);  
MultipleInputs.addInputPath(conf, AInputPath, TextInputFormat.class,  
Posts.class);  
MultipleInputs.addInputPath(conf, BInputPath, TextInputFormat.class,  
User.class);  
FileOutputFormat.setOutputPath(conf, outputPath);  
conf.setPartitionerClass(KeyPartitioner.class);  
conf.setOutputValueGroupingComparator(TextPair.FirstComparator.class
```

```

); conf.setMapOutputKeyClass(TextPair.class);
conf.setReducerClass(JoinReducer.class);
conf.setOutputKeyClass(Text.class); JobClient.runJob(conf); return 0;
}
public static void main(String[] args) throws Exception { int
exitCode = ToolRunner.run(new JoinDriver(), args);
System.exit(exitCode);
}
}

```

```

// JoinReducer.java import
java.io.IOException;
import java.util.Iterator;
import
org.apache.hadoop.io.Text
; import
org.apache.hadoop.mapre
d.*; public class
JoinReducer extends
MapReduceBase
implements
Reducer<TextPair, Text,
Text,
Text> {
@Override

```



```

public void reduce (TextPair key, Iterator<Text> values, OutputCollector<Text, Text>output, Reporter reporter)
throws IOException
{
    Text nodeId = new Text(values.next()); while
    (values.hasNext()) {
        Text node = values.next();
        Text outValue = new Text(nodeId.toString() + "\t\t" + node.toString()); output.collect(key.getFirst(),
        outValue);
    }
}

```

```

// User.java import
java.io.IOException;
import java.util.Iterator;
import org.apache.hadoop.conf.Configuration;
import org.apache.hadoop.fs.FSDataInputStream;
import
org.apache.hadoop.fs.FSDataOutputStream;
import org.apache.hadoop.fs.FileSystem; import
org.apache.hadoop.fs.Path; import
org.apache.hadoop.io.LongWritable;

import org.apache.hadoop.io.Text; import org.apache.hadoop.mapred.*; import
org.apache.hadoop.io.IntWritable; public class User extends MapReduceBase
implements Mapper<LongWritable, Text, TextPair,
Text> {
@Override

```

```

public void map(LongWritable key, Text value, OutputCollector<TextPair, Text> output,
Reporter reporter) throws IOException
{
String valueString = value.toString();
String[] SingleNodeData = valueString.split("\t"); output.collect(new
TextPair(SingleNodeData[0], "1"), new
Text(SingleNodeData[1]));
}}
//Posts.java
import java.io.IOException; import
org.apache.hadoop.io.*; import
org.apache.hadoop.mapred.*;
public class Posts extends MapReduceBase implements Mapper<LongWritable, Text, TextPair,
Text> {
@Override
public void map(LongWritable key, Text value, OutputCollector<TextPair, Text> output,
Reporter reporter) throws IOException
{
String valueString = value.toString(); String[]
SingleNodeData = valueString.split("\t");
output.collect(new TextPair(SingleNodeData[3], "0"), new
Text(SingleNodeData[9]));
}}
// TextPair.java import java.io.*; import org.apache.hadoop.io.*;
public class TextPair implements WritableComparable<TextPair> {
private Text first; private
Text second; public

```

```

TextPair() { set(new Text(),
new Text());
}
public TextPair(String first, String second) { set(new
Text(first), new Text(second));
}
public TextPair(Text first, Text second) { set(first,
second);
}
public void set(Text first, Text second) {
this.first = first;
this.second = second;
}
public Text getFirst() { return
first;
}
public Text getSecond() { return
second;
}
@Override
public void write(DataOutput out) throws IOException
{ first.write(out); second.write(out);
}
@Override
public void readFields(DataInput in) throws IOException {
first.readFields(in); second.readFields(in);
}

```

```

@Override
public int hashCode() {
    return first.hashCode() * 163 + second.hashCode();
}

@Override
public boolean equals(Object o) {
    if (o instanceof TextPair) { TextPair
        tp = (TextPair) o;
        return first.equals(tp.first) && second.equals(tp.second);
    }
    return false;
}

@Override
public String toString() {
    return first + "\t" + second;
}

@Override
public int compareTo(TextPair tp) {
    int cmp = first.compareTo(tp.first);
    if (cmp != 0) { return cmp;
    }
    return second.compareTo(tp.second);
}

// ^^ TextPair
// vv TextPairComparator

public static class Comparator extends WritableComparator { private static final
    Text.Comparator TEXT_COMPARATOR = new Text.Comparator(); public
    Comparator() { super(TextPair.class);

```

```

}

@Override

public int compare(byte[] b1, int s1, int l1,
byte[] b2, int s2, int l2) { try {
int firstL1 = WritableUtils.decodeVIntSize(b1[s1]) + readVInt(b1, s1);
int firstL2 = WritableUtils.decodeVIntSize(b2[s2]) + readVInt(b2, s2);
int cmp = TEXT_COMPARATOR.compare(b1, s1, firstL1, b2, s2, firstL2);
if (cmp != 0) {
return cmp;
}
return TEXT_COMPARATOR.compare(b1, s1 + firstL1, l1 - firstL1,
b2, s2 + firstL2, l2 - firstL2); } catch
(IOException e) { throw new
IllegalArgumentException(e);
}}
} static
{
WritableComparator.define(TextPair.class, new Comparator());
}

public static class FirstComparator extends WritableComparator {
private static final Text.Comparator TEXT_COMPARATOR = new Text.Comparator();
public FirstComparator() { super(TextPair.class);
}

@Override

public int compare(byte[] b1, int s1, int l1,
byte[] b2, int s2, int l2) { try {

```

```

int firstL1 = WritableUtils.decodeVIntSize(b1[s1]) + readVInt(b1, s1);
int firstL2 = WritableUtils.decodeVIntSize(b2[s2]) + readVInt(b2, s2);
return TEXT_COMPARATOR.compare(b1, s1, firstL1, b2, s2, firstL2);
} catch (IOException e) { throw new
IllegalArgumentException(e);
}}

@Override public int compare(WritableComparable a,
WritableComparable b) { if (a instanceof TextPair && b instanceof
TextPair) {
return ((TextPair) a).first.compareTo(((TextPair) b).first);
}
return super.compare(a, b);
}
}}

```

```

hduser@bmsce-Precision-T1700:/home/bmsce$ hdfs dfs -cat /join/output/*
A11      Finance      50
B12      HR              100
C13      Manufacturing    250
Dept_ID  Dept_Name          Total_Employee

```


9. Program to print word count on scala shell and print “Hello world” on scala IDE

```

val data=sc.textFile("sparkdata.txt") data.collect;
val splitdata = data.flatMap(line => line.split(" "));
splitdata.collect;
val mapdata = splitdata.map(word => (word,1));
mapdata.collect;    val    reducedata    =
mapdata.reduceByKey(_+_);
reducedata.collect;

```

```
Spark session available as 'spark'.
Welcome to

 version 2.4.8

Using Scala version 2.11.12 (OpenJDK 64-Bit Server VM, Java 1.8.0_232)
Type in expressions to have them evaluated.
Type :help for more information.

scala> val data=sc.textFile("sample.txt")
data: org.apache.spark.rdd.RDD[String] = sample.txt MapPartitionsRDD[1] at textFile at <console>:24

scala> data.collect;
res0: Array[String] = Array(hi how are you, how is your job, how is your family, how is your brother, how is your sister)

scala> val splitdata = data.flatMap(line => line.split(" "));
splitdata: org.apache.spark.rdd.RDD[String] = MapPartitionsRDD[2] at flatMap at <console>:25

scala> splitdata.collect;
res1: Array[String] = Array(hi, how, are, you, how, is, your, job, how, is, your, family, how, is, your, brother, how, is, your, sister)

scala> val mapdata = splitdata.map(word => (word,1));
mapdata: org.apache.spark.rdd.RDD[(String, Int)] = MapPartitionsRDD[3] at map at <console>:25

scala> mapdata.collect;
res2: Array[(String, Int)] = Array((hi,1), (how,1), (are,1), (you,1), (how,1), (is,1), (your,1), (job,1), (how,1), (is,1), (your,1), (family,1), (how,1), (is,1), (your,1), (brother,1), (how,1), (is,1), (your,1), (sister,1))

scala> val reducedata = mapdata.reduceByKey(_+_);
reducedata: org.apache.spark.rdd.RDD[(String, Int)] = ShuffledRDD[4] at reduceByKey at <console>:25

scala> reducedata.collect;
res3: Array[(String, Int)] = Array((are,1), (brother,1), (is,4), (sister,1), (family,1), (how,5), (job,1), (you,1), (hi,1), (your,4))

scala>
```


10. Using RDD and FlAMap count how many times each word appears in a file and write out a list of words whose count is strictly greater than 4 using Spark

```
val textFile = sc.textFile("/home/bhoom/Desktop/wc.txt")

val counts = textFile.flatMap(line => line.split(" ")).map(word => (word, 1)).reduceByKey(_ +
_) import scala.collection.immutable.ListMap val
sorted=ListMap(counts.collect.sortWith(_._2 > _._2):_*)// sort in descending order based on
values println(sorted) for((k,v)<-sorted)

{
if(v>4)
{
print(k+",")
print(v) println()
}
}
```

```

 version 2.4.8

Using Scala version 2.11.12 (OpenJDK 64-Bit Server VM, Java 1.8.0_232)
Type in expressions to have them evaluated.
Type :help for more information.

scala> val textFile = sc.textFile("sample.txt")
textFile: org.apache.spark.rdd.RDD[String] = sample.txt MapPartitionsRDD[1] at textFile at <console>:24

scala> val counts = textFile.flatMap(line => line.split(" ")).map(word => (word, 1)).reduceByKey(_ + _)
counts: org.apache.spark.rdd.RDD[(String, Int)] = ShuffledRDD[4] at reduceByKey at <console>:25

scala> import scala.collection.immutable.ListMap
import scala.collection.immutable.ListMap

scala> val sorted=ListMap(counts.collect.sortWith(_._2 > _. _2):_*)// sort in descending order based
sorted: scala.collection.immutable.ListMap[String,Int] = Map(how -> 5, is -> 4, your -> 4, are -> 1, brother -> 1, sister -> 1, family -> 1, job -> 1, you -> 1, hi
-> 1)

scala> println(sorted)
Map(how -> 5, is -> 4, your -> 4, are -> 1, brother -> 1, sister -> 1, family -> 1, job -> 1, you -> 1, hi -> 1)

scala> for((k,v)<-sorted)
| {
| {
Display all 689 possibilities? (y or n)
| {
| if(v>4)
| {
| print(k+",")
| print(v)
| println()
| }
| }
| }
how,5

```