

SPRINT 1: Project Scaffold — Another Mother Marketplace

Complete Build Prompt for AI Coding Agent

Build a Next.js 14 (App Router) project called “another-mother” with the following exact specifications. Create every file listed below. Do not skip any file. Test that `npm run dev` starts without errors.

1. INITIALISE PROJECT

Run these commands in terminal:

```
npx create-next-app@latest another-mother --typescript --tailwind --eslint --app --src-dir
  ↳ --import-alias "@/*" --use-npm

cd another-mother

npm install @supabase/supabase-js zustand react-hook-form zod @hookform/resolvers framer-motion
  ↳ lucide-react clsx tailwind-merge

npm install -D @types/node
```

2. TAILWIND CONFIG (Custom Theme)

File: `tailwind.config.ts`

```
import type { Config } from "tailwindcss";

const config: Config = {
  content: [
    "./src/pages/**/*.jsx,tsx,mdx",
    "./src/components/**/*.jsx,tsx,mdx",
    "./src/app/**/*.jsx,tsx,mdx",
  ],
  theme: {
    extend: {
      colors: {
        navy: {
          50: "#f5f5f8",
          100: "#e5e5ec",
          200: "#cbcbd9",
          300: "#a5a5b8",
          400: "#7a7a94",
          500: "#5a5a78",
          600: "#3d3d5c",
          700: "#2a2a45",
          800: "#1a1a2e", // Primary background
          900: "#0f0f1a",
        },
      },
    },
  },
  pink: {
```

```

    50: "#fdf2f8",
    100: "#fce7f3",
    200: "#fbcfe8",
    300: "#f9a8d4",
    400: "#f472b6", // Primary accent
    500: "#ec4899",
    600: "#db2777",
  },
  cyan: {
    50: "#ecfeff",
    100: "#cffffe",
    200: "#a5f3fc",
    300: "#67e8f9",
    400: "#22d3ee", // Secondary accent
    500: "#06b6d4",
  },
},
fontFamily: {
  sans: ["Inter", "system-ui", "sans-serif"],
  display: ["Playfair Display", "serif"],
},
borderRadius: {
  "2x1": "1rem",
  "3x1": "1.5rem",
},
animation: {
  "slide-up": "slideUp 0.3s ease-out",
  "fade-in": "fadeIn 0.2s ease-out",
  "pulse-soft": "pulseSoft 2s infinite",
},
keyframes: {
  slideUp: {
    "0%": { transform: "translateY(20px)", opacity: "0" },
    "100%": { transform: "translateY(0)", opacity: "1" },
  },
  fadeIn: {
    "0%": { opacity: "0" },
    "100%": { opacity: "1" },
  },
  pulseSoft: {
    "0%, 100%": { opacity: "1" },
    "50%": { opacity: "0.7" },
  },
},
},
},
plugins: [],
};

export default config;

```

3. GLOBAL CSS

File: src/app/globals.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;

@import url('https://fonts.googleapis.com/css2?
  ↪ family=Inter:wght@300;400;500;600;700&family=Playfair+Display:wght@600;700&display=swap');

@layer base {
  html {
    -webkit-tap-highlight-color: transparent;
  }

  body {
    @apply bg-navy-50 text-navy-900 antialiased;
    font-family: 'Inter', system-ui, sans-serif;
  }

  /* Safe area support for mobile */
  .pb-safe {
    padding-bottom: env(safe-area-inset-bottom, 0px);
  }

  .pt-safe {
    padding-top: env(safe-area-inset-top, 0px);
  }
}

@layer components {
  .gradient-brand {
    @apply bg-gradient-to-r from-pink-400 to-cyan-400;
  }

  .card-shadow {
    @apply shadow-sm shadow-navy-100/50;
  }
}
```

4. SUPABASE CLIENT SETUP

File: src/lib/supabase.ts

```
import { createClient } from '@supabase/supabase-js';

const supabaseUrl = process.env.NEXT_PUBLIC_SUPABASE_URL!;
```

```

const supabaseAnonKey = process.env.NEXT_PUBLIC_SUPABASE_ANON_KEY!;

export const supabase = createClient(supabaseUrl, supabaseAnonKey, {
  auth: {
    persistSession: true,
    autoRefreshToken: true,
    detectSessionInUrl: true,
  },
});

// Type-safe database helper
export type Database = typeof supabase;

```

5. ZUSTAND AUTH STORE

File: src/stores/authStore.ts

```

import { create } from "zustand";
import { persist } from "zustand/middleware";
import { supabase } from "@/lib/supabase";

export type UserType = "family" | "provider" | "admin";

export interface User {
  id: string;
  email: string;
  type: UserType;
  firstName: string;
  onboardingCompleted: boolean;
}

interface AuthState {
  user: User | null;
  isLoading: boolean;
  isAuthenticated: boolean;

  setUser: (user: User | null) => void;
  setLoading: (loading: boolean) => void;
  logout: () => Promise<void>;
  checkSession: () => Promise<void>;
}

export const useAuthStore = create<AuthState>()(
  persist(
    (set, get) => ({
      user: null,
      isLoading: true,
      isAuthenticated: false,

      setUser: (user) =>

```

```

    set({
      user,
      isAuthenticated: !!user,
      isLoading: false,
    }),

    setLoading: (loading) => set({ isLoading: loading }),

    logout: async () => {
      await supabase.auth.signOut();
      set({ user: null, isAuthenticated: false, isLoading: false });
    },

    checkSession: async () => {
      const {
        data: { session },
        error,
      } = await supabase.auth.getSession();

      if (error || !session) {
        set({ user: null, isAuthenticated: false, isLoading: false });
        return;
      }

      // Fetch user profile from your profiles table
      const { data: profile } = await supabase
        .from("users")
        .select("id, email, user_type, first_name, onboarding_completed")
        .eq("id", session.user.id)
        .single();

      if (profile) {
        set({
          user: {
            id: profile.id,
            email: profile.email,
            type: profile.user_type as UserType,
            firstName: profile.first_name,
            onboardingCompleted: profile.onboarding_completed,
          },
          isAuthenticated: true,
          isLoading: false,
        });
      } else {
        set({ user: null, isAuthenticated: false, isLoading: false });
      }
    },
  })),
{
  name: "another-mother-auth",
  partialize: (state) => ({

```

```

        user: state.user,
      }},
    }
  )
};

```

6. UI STORE (Toast + Navigation State)

File: src/stores/uiStore.ts

```

import { create } from "zustand";

export interface Toast {
  id: string;
  message: string;
  type: "success" | "error" | "info";
  duration?: number;
}

interface UIState {
  bottomNavVisible: boolean;
  toasts: Toast[];

  showToast: (toast: Omit<Toast, "id">) => void;
  dismissToast: (id: string) => void;
  setBottomNavVisible: (visible: boolean) => void;
}

export const useUIStore = create<UIState>((set) => ({
  bottomNavVisible: true,
  toasts: [],

  showToast: (toast) => {
    const id = Math.random().toString(36).substring(7);
    set((state) => ({ toasts: [...state.toasts, { ...toast, id }] }));
    setTimeout(() => {
      set((state) => ({
        toasts: state.toasts.filter((t) => t.id !== id),
      }));
    }, toast.duration || 4000);
  },

  dismissToast: (id) =>
    set((state) => ({
      toasts: state.toasts.filter((t) => t.id !== id),
    })),

  setBottomNavVisible: (visible) => set({ bottomNavVisible: visible }),
}));

```

7. SHARED UI COMPONENTS

7.1 ScreenShell (Safe area + scroll container)

File: src/components/layout/ScreenShell.tsx

```
"use client";

import { ReactNode } from "react";
import { motion } from "framer-motion";

interface ScreenShellProps {
  children: ReactNode;
  className?: string;
  animate?: boolean;
}

export function ScreenShell({ children, className = "", animate = true }: ScreenShellProps) {
  const content = (
    <div
      className={`flex flex-col h-screen h-[100dvh] overflow-hidden bg-navy-50 ${className}`}
    >
      <div className="flex-1 overflow-y-auto overscroll-y-contain pt-safe">
        {children}
      </div>
    </div>
  );

  if (!animate) return content;

  return (
    <motion.div
      initial={{ opacity: 0 }}
      animate={{ opacity: 1 }}
      exit={{ opacity: 0 }}
      transition={{ duration: 0.2 }}
      className="h-screen h-[100dvh]"
    >
      {content}
    </motion.div>
  );
}
```

7.2 PrimaryButton

File: src/components/actions/PrimaryButton.tsx

```
"use client";

import { ReactNode } from "react";
```

```

import { motion } from "framer-motion";

interface PrimaryButtonProps {
  children: ReactNode;
  onClick?: () => void;
  disabled?: boolean;
  type?: "button" | "submit";
  className?: string;
  size?: "sm" | "md" | "lg";
}

export function PrimaryButton({
  children,
  onClick,
  disabled = false,
  type = "button",
  className = "",
  size = "md",
}: PrimaryButtonProps) {
  const sizeClasses = {
    sm: "px-4 py-2 text-sm",
    md: "px-6 py-3 text-base",
    lg: "px-8 py-4 text-lg",
  };

  return (
    <motion.button
      whileTap={{ scale: disabled ? 1 : 0.97 }}
      type={type}
      onClick={onClick}
      disabled={disabled}
      className={`
        w-full rounded-2xl font-semibold text-white
        bg-gradient-to-r from-pink-400 to-cyan-400
        hover:from-pink-500 hover:to-cyan-500
        active:from-pink-600 active:to-cyan-600
        disabled:opacity-50 disabled:cursor-not-allowed
        transition-all duration-200
        shadow-lg shadow-pink-400/25
        ${sizeClasses[size]}
        ${className}
      `}
    >
      {children}
    </motion.button>
  );
}

```

7.3 SecondaryButton

File: src/components/actions/SecondaryButton.tsx


```

"use client";

import { ReactNode } from "react";
import { motion } from "framer-motion";

interface SecondaryButtonProps {
  children: ReactNode;
  onClick?: () => void;
  disabled?: boolean;
  className?: string;
}

export function SecondaryButton({ children, onClick, disabled = false, className = "" }:
  ↪ SecondaryButtonProps) {
  return (
    <motion.button
      whileTap={{ scale: disabled ? 1 : 0.97 }}
      onClick={onClick}
      disabled={disabled}
      className={`
        w-full rounded-2xl font-semibold text-navy-700
        border-2 border-navy-200 bg-white
        hover:bg-navy-50 hover:border-navy-300
        active:bg-navy-100
        disabled:opacity-50 disabled:cursor-not-allowed
        transition-all duration-200
        px-6 py-3
        ${className}
      `}
    >
      {children}
    </motion.button>
  );
}

```

7.4 Toast Component

File: src/components/feedback/Toast.tsx

```

"use client";

import { motion, AnimatePresence } from "framer-motion";
import { useUIStore } from "@/stores/uiStore";
import { X, CheckCircle, AlertCircle, Info } from "lucide-react";

export function ToastContainer() {
  const { toasts, dismissToast } = useUIStore();

  return (
    <div className="fixed top-4 left-4 right-4 z-50 flex flex-col gap-2 pointer-events-none">

```

```

<AnimatePresence>
  {toasts.map((toast) => (
    <motion.div
      key={toast.id}
      initial={{ opacity: 0, y: -20, scale: 0.95 }}
      animate={{ opacity: 1, y: 0, scale: 1 }}
      exit={{ opacity: 0, y: -20, scale: 0.95 }}
      className={`
        pointer-events-auto
        flex items-center gap-3 px-4 py-3 rounded-2xl shadow-lg
        ${
          toast.type === "success"
            ? "bg-green-50 border border-green-200 text-green-800"
            : toast.type === "error"
            ? "bg-red-50 border border-red-200 text-red-800"
            : "bg-navy-50 border border-navy-200 text-navy-700"
        }
      `}
    >
      {toast.type === "success" && <CheckCircle size={20} className="text-green-500 shrink-0" />}
      {toast.type === "error" && <AlertCircle size={20} className="text-red-500 shrink-0" />}
      {toast.type === "info" && <Info size={20} className="text-navy-500 shrink-0" />}
      <p className="text-sm font-medium flex-1">{toast.message}</p>
      <button
        onClick={() => dismissToast(toast.id)}
        className="p-1 rounded-full hover:bg-black/5 transition-colors"
      >
        <X size={16} />
      </button>
    </motion.div>
  ))}
</AnimatePresence>
</div>
);
}

```

8. HOME SCREEN (“Hello Another Mother”)

File: src/app/page.tsx

```

import { ScreenShell } from "@/components/layout/ScreenShell";
import { PrimaryButton } from "@/components/actions/PrimaryButton";
import { SecondaryButton } from "@/components/actions/SecondaryButton";
import { Heart, Shield, Users, ArrowRight } from "lucide-react";
import Link from "next/link";

export default function HomePage() {
  return (
    <ScreenShell animate={false}>

```

```

{ /* Hero Section */}
<div className="flex-1 flex flex-col justify-center px-6 py-12">
  { /* Logo / Brand Mark */}
  <div className="mb-8">
    <div className="w-16 h-16 rounded-2xl gradient-brand flex items-center justify-center mb-6
      ↪ shadow-lg shadow-pink-400/30">
      <Heart size={32} className="text-white" fill="white" />
    </div>
    <h1 className="font-display text-4xl font-bold text-navy-900 leading-tight mb-3">
      Another
    <br />
    <span className="gradient-brand bg-clip-text text-transparent">
      Mother
    </span>
  </h1>
  <p className="text-lg text-navy-500 leading-relaxed">
    The village rebuilt.
    <br />
    Trusted mums helping local families.
  </p>
</div>

{ /* Trust Signals */}
<div className="space-y-3 mb-10">
  <div className="flex items-center gap-3 text-sm text-navy-600">
    <div className="w-8 h-8 rounded-full bg-pink-50 flex items-center justify-center">
      <Shield size={16} className="text-pink-500" />
    </div>
    <span>Police checked & WWCC verified</span>
  </div>
  <div className="flex items-center gap-3 text-sm text-navy-600">
    <div className="w-8 h-8 rounded-full bg-cyan-50 flex items-center justify-center">
      <Users size={16} className="text-cyan-500" />
    </div>
    <span>Local mums, not strangers</span>
  </div>
  <div className="flex items-center gap-3 text-sm text-navy-600">
    <div className="w-8 h-8 rounded-full bg-green-50 flex items-center justify-center">
      <Heart size={16} className="text-green-500" />
    </div>
    <span>Safe payments held until job is done</span>
  </div>
</div>

{ /* CTAs */}
<div className="space-y-3">
  <Link href="/register" className="block">
    <PrimaryButton size="lg">
      <span className="flex items-center justify-center gap-2">
        Get Started
        <ArrowRight size={20} />
      </span>
    </PrimaryButton>
  </Link>

```

```

        </span>
      </PrimaryButton>
    </Link>

    <Link href="/login" className="block">
      <SecondaryButton>I already have an account</SecondaryButton>
    </Link>
  </div>

  { /* Subtle footer */ }
  <p className="text-xs text-navy-400 text-center mt-8">
    Currently serving Paddington, Red Hill & surrounds.
    <br />
    More suburbs coming soon.
  </p>
</div>
</ScreenShell>
);
}
```

9. PWA MANIFEST

File: public/manifest.json

```
{
  "name": "Another Mother",
  "short_name": "AnotherMother",
  "description": "The village rebuilt — trusted mum-to-mum support",
  "start_url": "/",
  "display": "standalone",
  "background_color": "#ffffff",
  "theme_color": "#1a1a2e",
  "orientation": "portrait",
  "icons": [
    {
      "src": "/icon-192x192.png",
      "sizes": "192x192",
      "type": "image/png",
      "purpose": "any maskable"
    },
    {
      "src": "/icon-512x512.png",
      "sizes": "512x512",
      "type": "image/png",
      "purpose": "any maskable"
    }
  ]
}
```

10. ENVIRONMENT VARIABLES TEMPLATE

File: .env.local (add to .gitignore — never commit this)

```
# Supabase
NEXT_PUBLIC_SUPABASE_URL=https://your-project.supabase.co
NEXT_PUBLIC_SUPABASE_ANON_KEY=your-anon-key
SUPABASE_SERVICE_ROLE_KEY=your-service-role-key

# Stripe (test mode)
NEXT_PUBLIC_STRIPE_PUBLISHABLE_KEY=pk_test_...
STRIPE_SECRET_KEY=sk_test_...
STRIPE_WEBHOOK_SECRET=whsec_...

# App
NEXT_PUBLIC_APP_URL=http://localhost:3000
```

11. NEXT.JS CONFIG

File: next.config.js

```
/** @type {import('next').NextConfig} */
const nextConfig = {
  images: {
    domains: ["cdn.anothermother.com.au", "localhost"],
  },
  experimental: {
    // Enable if needed for advanced features
  },
};

module.exports = nextConfig;
```

12. ROOT LAYOUT

File: src/app/layout.tsx

```
import type { Metadata, Viewport } from "next";
import "./globals.css";
import { ToastContainer } from "@components/feedback/Toast";

export const metadata: Metadata = {
  title: "Another Mother — The village rebuilt",
  description:
    "Trusted mum-to-mum marketplace. School pickups, meal prep, childcare, and more. Verified local  

    ⇨ mothers helping Australian families.",
  keywords: ["mum marketplace", "childcare", "school pickup", "family support", "Australia"],
```

```

    authors: [{ name: "Another Mother" }],
    openGraph: {
      title: "Another Mother",
      description: "The village rebuilt. Trusted mums helping local families.",
      type: "website",
    },
  },
};

export const viewport: Viewport = {
  width: "device-width",
  initialScale: 1,
  maximumScale: 1,
  userScalable: false,
  themeColor: "#1a1a2e",
};

export default function RootLayout({
  children,
}: {
  children: React.ReactNode;
}) {
  return (
    <html lang="en-AU">
      <head>
        <link rel="manifest" href="/manifest.json" />
        <link rel="apple-touch-icon" href="/icon-192x192.png" />
        <meta name="apple-mobile-web-app-capable" content="yes" />
        <meta name="apple-mobile-web-app-status-bar-style" content="black-translucent" />
      </head>
      <body className="min-h-screen bg-navy-50">
        <ToastContainer />
        {children}
      </body>
    </html>
  );
}

```

13. PLACEHOLDER PAGES (So routing doesn't break)

Create these minimal pages so links work:

File: src/app/login/page.tsx

```

import { ScreenShell } from "@/components/layout/ScreenShell";

export default function LoginPage() {
  return (
    <ScreenShell>
      <div className="px-6 py-12">

```

```

    <h1 className="text-2xl font-bold text-navy-900 mb-4">Welcome back</h1>
    <p className="text-navy-500">Login form coming in Sprint 3...</p>
  </div>
</ScreenShell>
);
}

```

File: src/app/register/page.tsx

```

import { ScreenShell } from "@/components/layout/ScreenShell";

export default function RegisterPage() {
  return (
    <ScreenShell>
      <div className="px-6 py-12">
        <h1 className="text-2xl font-bold text-navy-900 mb-4">Join Another Mother</h1>
        <p className="text-navy-500">Registration coming in Sprint 3...</p>
      </div>
    </ScreenShell>
  );
}

```

14. VERIFICATION CHECKLIST

After running `npm run dev`, confirm:

- `http://localhost:3000` loads without errors
- Home screen shows: logo, headline, 3 trust signals, 2 buttons
- “Get Started” button is pink-to-cyan gradient
- “I already have an account” is white with border
- Typography uses Inter (body) and Playfair Display (headline)
- Background is soft navy-50 (not white)
- No horizontal scroll on mobile viewport (375px)
- Buttons are full-width with rounded-2xl corners
- No console errors in browser DevTools
- `manifest.json` is accessible at `/manifest.json`

INSTRUCTIONS FOR AI AGENT

1. Create ALL files above exactly as specified
2. Run `npm run dev` and fix any errors until it starts cleanly
3. Take a screenshot of the home page and describe what you see
4. If any file fails to create or any error occurs, stop and report it
5. Do not add extra dependencies beyond what’s listed in step 1
6. Do not modify the design tokens (colours, fonts, radii) — these are brand-critical

NEXT SPRINT PREVIEW

Sprint 2: Supabase schema migration + TypeScript types from your PostgreSQL schema doc Sprint 3: Auth flow (register/login/logout) with email + password Sprint 4: Family profile creation wizard