

Users

Users are pretty straightforward. They represent people (or bots) using the e621 site.

GET Endpoints

List

List users, filtering by a given set of parameters. If no parameters are given you will get a listing of all users.

Base URL is `https://e621.net/user/index.json`

Parameters

- **id** - ID of the user to list (effectively the same as *show*)
- **name** - String to match partial or all of a user's name against
- **level** - Permission level the returned users have. Can be one of the following:
 - **0** - Unactivated
 - **10** - Blocked
 - **20** - Member
 - **30** - Privileged
 - **33** - Contributor
 - **34** - Former Staff
 - **35** - Janitor
 - **40** - Mod
 - **50** - Admin
- **order** - Order to sort the user data retrieved by. Can be one of the following:
 - **name** - Username, based on unicode chars (ascending)
 - **posts** - Number of posts the user has made (descending)
 - **deleted** - Number of deleted posts the user has made (descending)
 - **taggedits** - Number of tag edits the user has made (descending)
 - **posts** - Number of posts the user has made (descending)
 - **date** - The date the user joined, from most recent to least
 - **record** - User's record score (descending)

Typical Response Example

```
[
  {
    name: string,
    id: number
    level: e621UserLevels,
    created_at: string,
    avatar_id: number,
    stats:
    {
      post_count: number,
      del_post_count: number,
      edit_count: number,
      favorite_count: number,
      wiki_count: number,
      forum_post_count: number,
      note_count: number,
      comment_count: number,
      blip_count: number,
      set_count: number,
      pool_update_count: number,
      pos_user_records: number,
      neutral_user_records: number,
      neg_user_records: number
    },
    artist_tags: string[]
  },
  // ...
]
```

[Example JSON Request + Response \(https://e621.net/user/index.json?name=purple&level=20&order=date\)](https://e621.net/user/index.json?name=purple&level=20&order=date)

[Example XML Request + Response \(https://e621.net/user/index.xml?name=purple&level=20&order=date\)](https://e621.net/user/index.xml?name=purple&level=20&order=date)

Show

Get a user's information by ID. If an ID is not given you will get the information of the user you are logged in as through the APIs

Base URL is `https://e621.net/user/show.json`

Parameters

- **id** - ID of the user to retrieve

Typical Response Example

```
{
  name: string,
  id: number
  level: e621UserLevels,
  created_at: string,
  avatar_id: number,
  stats:
  {
    post_count: number,
    del_post_count: number,
    edit_count: number,
    favorite_count: number,
    wiki_count: number,
    forum_post_count: number,
    note_count: number,
    comment_count: number,
    blip_count: number,
    set_count: number,
    pool_update_count: number,
    pos_user_records: number,
    neutral_user_records: number,
    neg_user_records: number
  },
  artist_tags: string[]
}
```

[Example JSON Request + Response \(https://e621.net/user/show.json\)](https://e621.net/user/show.json)

[Example XML Request + Response \(https://e621.net/user/show.xml\)](https://e621.net/user/show.xml)

POST Endpoints

NONE