

Blips

Blips are a unique type. They are like *comments* but don't relate to a specific post. They are also unlike *forum* posts as they aren't created around a user-generated topic.

You can check them out yourself [here \(https://e621.net/blip/index\)](https://e621.net/blip/index).

GET Endpoints

List

List a set of blips. If you give no parameters, you will get the most recent blips

Base URL is `https://e621.net/blip/index.json`

Parameters

- **name** - Return blips made by a user with the matching name (must be exact match)
- **body** - Return blips that match a given string in the message body
- **page** - The page number to return
- **limit** - Number of records per page to return. Limit cannot be set over 100
- **status** - Type of blips to retrieve. Can be `hidden`, `active` or `any`. Note that whether or not you can see other user's hidden blips is affected by your permission levels
- **response_to** - Returns blips which are in response to the blip with the given ID

Typical Response Example

```
[
  {
    body: string,
    user: string,
    user_id: number,
    id: number,
    response: number
  },
  // ...
]
```

[Example JSON Request + Response \(https://e621.net/blip/index.json\)](https://e621.net/blip/index.json)

[Example XML Request + Response \(https://e621.net/blip/index.xml\)](https://e621.net/blip/index.xml)

Show

Show a blip by ID

Base URL is `https://e621.net/blip/show.json`

Parameters

`id` parameter is **required**

- **id** - The ID of the blip to retrieve

Typical Response Example

```
{
  body: string,
  user: string,
  user_id: number,
  id: number,
  response: number
}
```

[Example JSON Request + Response \(https://e621.net/blip/show.json?id=1234\)](https://e621.net/blip/show.json?id=1234)

[Example XML Request + Response \(https://e621.net/blip/show.xml?id=1234\)](https://e621.net/blip/show.xml?id=1234)

POST Endpoints

Create

Create a blip

Base URL is `https://e621.net/blip/create.json`

POST Parameters

`body` parameter is **required**

- **blip[body]** - The blip's body text
- **blip[response]** - Blip ID that the new blip is in response to (optional)

Example POST Object

```
{
  "blip[body]": 123456,
  "blip[response]": 56789
}
```

Response

Response object should look similar to the object below. ? representing a response property that may or may not be returned

```
success: boolean,
reason?: string,
message?: string
```

Hide

Hide a blip by ID

Base URL is `https://e621.net/blip/hide.json`

Note: This does not effect the API-facing endpoints and is typically only done from a user's perspective

POST Parameters

`id` is **required**

- **id** - ID of the blip to hide

Example POST Object

```
{
  "id": 123456
}
```

Response

Response object should look similar to the object below. ? representing a response property that may or may not be returned

```
success: boolean,
reason?: string,
message?: string
```

Unhide

Unhide a blip by ID

Base URL is `https://e621.net/blip/unhide.json`

Note: This does not effect the API-facing endpoints and is typically only done from a user's perspective

POST Parameters

id is required

- **id** - ID of the blip to unhide

Example POST Object

```
{
  "id": 123456
}
```

Response

Response object should look similar to the object below. ? representing a response property that may or may not be returned

```
success: boolean,
reason?: string,
message?: string
```

Update

Update a blip by ID

Base URL is `https://e621.net/blip/update.json`

POST Parameters

id and **body** are required

- **id** - ID of the blip to update
- **blip[body]** - The new body of the blip

Example POST Object

```
{
  "id": 123456,
  "blip[body]": "this is the new body"
}
```

Response

Response object should look similar to the object below. ? representing a response property that may or may not be returned

```
success: boolean,
reason?: string,
message?: string
```