

Introduction to databases

Iniziato venerdì, 11 giugno 2021, 23:08

Stato Completato

Terminato sabato, 12 giugno 2021, 00:56

Tempo impiegato 1 ora 48 min.

Valutazione Non ancora valutato

Domanda 1

Risposta errata

Punteggio ottenuto
0,00 su 1,00

The primary key of a table

- ☐ (a) may not be composite
- ☒ (b) may not be composed of a single element ✖
- ☐ (c) none of the answers are correct
- ☐ (d) must be unique but it might not be minimal
- ☐ (e) must be referenced by a foreign key

La risposta corretta è: none of the answers are correct

Domanda 2

Risposta corretta

Punteggio ottenuto
1,00 su 1,00

The HTML statement:

```
<select name = "course">  
  <option value = "23ACIPL"> Mathematical analysis II </option>  
  <option value = "08CKRPL"> Statistics </option>  
  <option value = "14AFQPL" selected> Databases </option>  
</ Select>
```

- ☐ (a) It isn't correct because the value attribute only accepts integers
- ☐ (b) Creates a set of checkboxes
- ☐ (c) Creates a set of radio buttons
- ☐ (d) Creates a drop-down list where the default value is Mathematical Analysis II
- ☒ (e) None of the other answers is correct ✓

La risposta corretta è: None of the other answers is correct

Domanda 3

Risposta errata

Punteggio ottenuto
0,00 su 1,00

A transaction has the property of durability if

-
- ☐ (a) it makes modifications permanent immediately after the transaction has ended
 - ☐ (b) it takes the system from a valid state to another valid state
 - ☐ (c) none of the answers are correct
 - ☒ (d) all of the operations composing it are either completed, or they are undone, as if they had never been executed ✗
 - ☐ (e) it is executed on the system at the same time as other transactions as if it were the only one being executed

La risposta corretta è: it makes modifications permanent immediately after the transaction has ended

Domanda 4


Completo

Punteggio max.:
4,00**Given the following relational tables:**GUEST (GID, FirstName, LastName, BirthDate)HOTEL (HID, Name, City, Region, #Stars)STAY (GID, HID, StartDate, EndDate)

Select the name and the surname of guests born after 1990/01/01 who have stayed only in hotels located in the Piedmont region.

Assignment for the exercise:

The following query tree graphically represents the requested algebraic query. You are requested to indicate, for each box in the query tree (i.e., A, B, C, D, E, F, G, H and I box), the relational table or the corresponding algebraic operator. Use the text box below to provide your solution. Note: each box in the query tree is associated with only one relational table or one algebraic operator.



A | STAY1

B | SELECTION(DateOfBirth> 1990/01/01)

C| NATURAL JOIN

D| HOTEL

E | STAY2

F | SELECTION (Region<>"Piedmont")

G | NATURAL JOIN

H | LEFT ANTI JOIN

I | PROJECTION (Name, Surname)

Draft Solution

A. STAY1

B. Selection: BirthDate>1990/01/01

C. Theta-join: STAY1.GID=GUEST.GID or natural join

D. HOTEL

E. STAY2

F. Selection: Region <> 'Piedmont'

G. Theta-join: STAY2.HID=HOTEL.HID or natural join

H. Anti semi-join / ANTI-join: GUEST.GID=STAY2.GID

I. Projection: FirstName, LastName

Domanda 5

Completo

Punteggio max.:
3,00**Given the following relational tables**

```
Person (SSN, Name, Surname, DateOfBirth, Gender)
SerologicalTest (CodT, CommercialName, Brand, Reliability)
Building(CodB, City, Province Region, MaxCapacity)
UndergoTest (SSN, CodT, Date, CodB, Outcome)
```

Write the following query in the SQL language:

Find the name and surname of the male persons (Gender = "Male") who have never undergone serological tests with a positive outcome (Outcome = "Positive") in a building located in the city of Turin.

Assignment for the exercise

Use the text box below to provide your solution.

```
SELECT Name, Surname
FROM Person
WHERE Gender="Male"
      AND SSN NOT IN
      (SELECT SSN
      FROM UndergoTest U, Building B
      WHERE   U.CodB=B.CodB AND U.Outcome="Positive" AND B.City="Turin"
      )
```

Draft solution:

```
SELECT DISTINCT Name, Surname
FROM Person
WHERE SSN NOT IN (
      SELECT SSN
      FROM UndergoTest UT, Building B
      WHERE UT.CodB = B.CodB AND
            Outcome = "Positive" AND
            City = "Turin"
) AND Gender = "Male";
```

Domanda 6

Completo

Punteggio max.:
3,00**Given the following relational tables**

```
Person (SSN, Name, Surname, DateOfBirth, Gender)
SerologicalTest (CodT, CommercialName, Brand, Reliability)
Building(CodB, City, Province Region, MaxCapacity)
UndergoTest (SSN, CodT, Date, CodB, Outcome)
```

Write the following query in the SQL language:

For each serological test brand, find the brand and the overall number of tests undergone from May 1st, 2020 to June 30th, 2020 to persons who have undergone at least two tests with the outcome "Positive" of that brand.

Assignment for the exercise

Use the text box below to provide your solution.

```
SELECT Brand, SSN, COUNT(*)
FROM   SerologicalTest S, UndergoTest U
WHERE  Date>="2020/05/01" AND Date<="2020/06/30"
      AND U.CodT= S.CodT
      AND (U.SSN, S.Brand) IN
      (SELECT Brand, SSN
       FROM UndergoTest U1, SerologicalTest S1
       WHERE U1.CodT=S1.CodT
            AND U1.Outcome="Positive"
       GROUP BY U1.SSN, S1.Brand
       HAVING COUNT(*)>=2
      )
GROUP BY S.Brand, U.SSN
```

DRAFT SOLUTION**Sol 1: with correlation condition**

```
SELECT Brand, COUNT(*)
FROM SerologicalTest ST, UndergoTest UT
WHERE ST.CodT = UT.CodT AND Date >= 01/05/2020 AND Date <=
30/06/2020
AND SSN IN (
    Select SSN
    From UndergoTest UT2, SerologicalTest ST2
    where ST2.CodT = UT2.CodT and outcome='positive'
        and ST2.Brand = ST.Brand
    group by SSN
    having COUNT(*) > 1)
GROUP BY Brand
```

Sol 2: with tuple constructor

```
SELECT Brand, COUNT(*)
FROM SerologicalTest ST, UndergoTest UT
```

```
WHERE ST.CodT = UT.CodT AND Date >= 01/05/2020 AND Date <=
30/06/2020)
AND (SSN, Brand) IN (
Select SSN, Brand
    From UndergoTest UT2, SerologicalTest ST2
    where ST2.CodT = UT2.CodT and outcome='positive'
    group by SSN, Brand
    having COUNT(*) > 1)
GROUP BY Brand
```

Sol 3: with table function

```
SELECT Brand, COUNT(*)
FROM SerologicalTest ST, UndergoTest UT,
    (Select SSN, Brand
    From UndergoTest UT2, SerologicalTest ST2
    where ST2.CodT = UT2.CodT and outcome='positive'
    group by SSN, Brand
    having COUNT(*) > 1)AS TableTestBrand
WHERE ST.CodT = UT.CodT AND Date >= 01/05/2020 AND Date <=
30/06/2020)
AND TableTestBrand.Brand = ST.Brand AND TableTestBrand.SSN=UT.SSN
GROUP BY Brand
```

Domanda 7

Completo

Punteggio max.:
5,00**Given the following relational tables**

```
Person (SSN, Name, Surname, DateOfBirth, Gender)
SerologicalTest (CodT, CommercialName, Brand, Reliability)
Building(CodB, City, Province Region, MaxCapacity)
UndergoTest (SSN, CodT, Date, CodB, Outcome)
```

Write the following query in the SQL language:

Considering only the buildings located in the Piedmont region (Region = "Piedmont"), find the dates of June 2020 at which the overall number of tests made in that building is maximal.

Assignment for the exercise

Use the text box below to provide your solution.

```
SELECT B.CodB, Date, COUNT(*)
FROM UndergoTest U , Building B
WHERE Region="Piedmont" AND Date<="2020/06/30" AND Date>="2020/06/01"
      AND U.CodB= B.CodB
GROUP BY B.CodB, U.Date
HAVING COUNT(*)=
      (SELECT MAX(Counter)
      FROM ( SELECT COUNT(*) AS Counter
            FROM UndergoTest U1
            WHERE AND U1.Date<="2020/06/30" AND U1.Date>="2020/06/01"
                  AND U1.CodB=B.CodB
            GROUP BY U1.CodB, U1.Date
            )
      )
)
```

Draft solution:

```
SELECT Date, B.CodB
FROM UndergoTest UT, Building B
WHERE Date >= 01/06/2020 AND Date <= 30/06/2020 AND
      UT.CodB = B.CodB AND
      Region = "Piedmont" AND
GROUP BY Date, B.CodB
HAVING COUNT (*) = (SELECT MAX(Test#)
                    FROM (SELECT Date, B1.CodB, COUNT(*) as
Test#
                        FROM UndergoTest UT1, Building B1
                        WHERE Date >= 01/06/2020 AND
                              Date <= 30/06/2020 AND
                              UT1.CodB = B1.CodB AND
                              Region = "Piedmont" AND
                        GROUP BY Date, B1.CodB) AS TF
                    WHERE TF.CodB=B.CodB
                    ) ;
```


Domanda 8

Completo

Punteggio max.:
4,00**Describe the Entity-Relationship diagram addressing the following specifications.**

You are requested to design the database for the management of company relocations.

The database must contain a list of vans suitable for relocations. The vans are identified by their plate, and they are characterized by their model, and by their volume in cubic meters if known. Of all the vans, some are authorized to transport special materials, and only for such vans, a list with the certifications of the special materials known to be allowed has to be stored.

The database must contain a list of warehouses, identified by a code and characterized by their address and the name of the company to which they belong.

You are requested to keep track of all the relocations made. The relocations are identified by the date and by the van with which they are made, and they are characterized by the name of the driver who carries it out. Each relocation is also characterized by the departure warehouse and departure time, and by the arrival warehouse and arrival time.

Indications for solving the exercise

Use the text box below to report the ER diagram in text form. Alternatively, you can use the drawing box to graphically represent the ER diagram.

ENTITY-father: VAN

Internal ID: Plate

Attribute : Model, Volume(0,1)

ENTITY-childer: SPECIAL

Attribute: Certification(1,N)

ENTITY: WAREHOUSE

Internal ID: Code

Attribute: Address, CompanyName

ENTITY: RELOCATION

Internal ID: Date

External ID: CodeVan

Attribute: DriverName, WarehouseDeparture, WarehouseArrival, TimeDeparture, TimeArrival

BINARY RELATION: IS

VAN (0,1) - SPECIAL(1,1)

BINARY RELATION: FROM

RELOCATION (1,N) - WAREHOUSE (0, N)

Relocation(WarehouseDeparture) REFERENCES Warehouse(Code)

BINARY RELATION: TO

RELOCATION (1,N) - WAREHOUSE (0,N)

Relocation(WarehouseArrival) REFERENCES Warehouse(Code)

Entity VAN

ID: Plate

model, volume (0,1)

HIERARCHY (p,e)

children entity SPECIAL

certificationList (1,N)

Entity RELOCATION

internal ID interno: date

external ID: VAN's ID

driver, departureTime, arrivalTime (alternatively, the times can be added to the relationships RELOCATION-WAREHOUSE)

Entity WAREHOUSE

ID: WarehouseCode

address, companyName

Relazione CARRIED_OUT: VAN(0,N) – RELOCATION(1,1)

Relazione FROM: RELOCATION(1,1) – WAREHOUSE(0,N)

Relazione TO: RELOCATION(1,1) – WAREHOUSE(0,N)

Domanda 9

Completo

Punteggio max.:
3,00**Describe the Entity-Relationship diagram addressing the following specifications.**

You are requested to design the database for the management of van repairs.

The database must contain a list of vans identified by their plate and characterized by the year of registration. Among the various types of vans, the capacity of the battery is known for those equipped with an electric motor.

The database must also include the list of repair shops, identified by a unique code and characterized by their address.

The repair shops can be in partnership with some companies. For each partner company, its VAT number, name, and possibly the list of telephone numbers are known. Note that each company can be in partnership with multiple repair shops and you are requested to keep track only of those companies having a partnership.

You are also requested to keep track of the repairs carried out over time on each van. The date, cost and duration in hours are known for each repair. Note that a van can undergo multiple repairs on the same day but in different repair shops. A repair shop can carry out at most one repair for the same van on the same day.

Indications for solving the exercise

Use the text box below to report the ER diagram in text form. Alternatively, you can use the drawing box to graphically represent the ER diagram.

ENTITY-Father: VAN

Internal ID: Plate

Attribute: YearOfRegistration, Type

ENTITY-Children: ELECTRIC-VAN

Attribute: CapacityOfBattery

ENTITY: SHOP-REPAIR

Internal ID: Code

Attribute: Address

ENTITY: COMPANY

Internal ID: VATNumber

Attribute: Name, ListOfNumber(0,N)

ENTITY: REPAIRS

Internal ID: Date

External ID: CodeVan, VATNumber

Attribute: Duration, Cost

BINARY-RELATION: IsElectric

VAN(0,1)- ELECTRIC-VAN(1,1)

BINARY-RELATION: HasPartnership
SHOP-REPAIR(0,N)- COMPANY(0,N)

BINARY-RELATION: HasRepair
VAN(0,N) - REPAIRS(1,1)

BINARY-RELATION: DoRepair
SHOP-REPAIR(0,N)- REPAIRS(1,1)

Entity VAN

ID: Plate

- registrationYear

HIERARCHY (p,e)

children entity ELECTRIC

- batteryCapacity

Entity REPAIR_SHOP

ID: ShopCode

- address

Entity COMPANY

ID: VATnumber

- name, phoneNumbers (0,N)

Relationship PARTNERSHIP: REPAIR_SHOP(0,N) – COMPANY(1,N)

Relationship REPAIR: REPAIR_SHOP(0,N) – VAN(0,N) – TIME(1,N), attributes: price, duration


(alternatively, REPAIR entity with external IDs from repair_shop and van, and internal id: date)

Entity TIME

ID: date

Domanda 10

Completo

Punteggio max.:
3,00**Given the following Entity-Relationship diagram**

You are required to:

- Provide a normalized relational logical schema for the same database (N.B. It is not mandatory to report the restructured E-R diagram)
- Define referential integrity constraints for 2 relationships of your choice among those defined in the conceptual schema

Assignment

Use the text box below to provide your solution.

Author(author_id, name, surname)Book(ISBN, title, price, num_pages)Clerk(clerk_id, name)Customer(customer_id, phone_number)Non_Private(customer_id, vat_number)Private(customer_id, name, surname)Buy(Customer_id, clerk_id, isbn)Written_by(isbn, author_id)

1) Written_by(isbn) REFERENCES Book(isbn)

Written_by(author_id) REFERENCES Author(author_id)

2) Buy(customer_id) REFERENCES Customer(customer_id)

Buy(clerk_id) REFERENCES Clerk(clerk_id)

Buy(isbn) REFERENCES Book(ISBN)

AUTHOR(author_id, name, surname)

BOOK(ISBN, title, num_pages, price)

CUSTOMER(customer_id, phone_number*, type, name*, surname*, vat_number*)

CLERK(clerk_id, name)

BUY(customer_id, clerk_id, ISBN)

WRITTEN_BY(author_id, ISBN)

1) WRITTEN_BY (author_id) REFERENCES AUTHOR(author_id)

WRITTEN_BY (ISBN) REFERENCES BOOK(ISBN)

2) BUY(customer_id) REFERENCES CUSTOMER(customer_id)

BUY (clerk_id) REFERENCES CLERK(clerk_id)

BUY (ISBN) REFERENCES BOOK(ISBN)

Domanda 11

Completo

Punteggio max.:
3,00**The following relational schema is given (primary keys are underlined):**

MARKET_BASKET (BasketCode, ItemCode, NumberOfPieces)
ITEM_PRICE (ItemCode, CostPerPiece)
BASKET_TOTALPRICE_NOTIFICATION (RequestCode, BasketCode, TotalBasketCost)
LOYALTY_CARDS (LoyaltyCardCode, TotalAmount)
REQUEST_FOR_CALCULATION_OF_TOTALBASKETPRICE (RequestCode, BasketCode, LoyaltyCardCode)

Write the trigger to manage the following activities on an online shopping site. The calculation of the total cost of a market basket is requested (insertion of a record in the REQUEST_FOR_CALCULATION_OF_TOTALBASKETPRICE table).

The calculation of the total price of the basket must consider the items in the basket, the number of pieces per item, and the one-piece price of each item. The MARKET_BASKET table contains, for each basket, the items contained in the basket and the number of pieces per item. The ITEM_PRICE table contains the one-piece price of each item.

Once the total price of the market basket has been computed, a new record must be inserted in the BASKET_TOTALPRICE_NOTIFICATION table with the calculated information. Then, the total amount for the customer who requested the calculation of the market basket price must be updated in the LOYALTY_CARDS table (attribute LoyaltyCardCode in the REQUEST_FOR_CALCULATION_OF_TOTALBASKETPRICE table).

Indications for carrying out the exercise

*Given the following incomplete solution of the trigger, you are asked to complete **Part A** in bold by specifying the body of the trigger. Use the text box below to provide your solution.*

create or replace trigger CalculationOfTotalBasketPrice
after insert on REQUEST_FOR_CALCULATION_OF_TOTALBASKETPRICE
for each row
Part A

DECLARE

TotalCostXXX Number;

BEGIN

SELECT Sum(IP.CostPerPiece * MB.NumberOfPiece) INTO TotalCostXXX
FROM MARKET_BASKET MB, ITEM_PRICE IP
WHERE MB.ItemCode= IP.ItemCode AND MB.BasketCode=:NEW.BasketCode;

INSERT INTO BASKET_TOTALPRICE_NOTIFICATION
VALUES(:NEW.RequestCode, :NEW.BasketCode, TotalCostXXX);

UPDATE LOYALTY_CARDS


```
WHERE LoyaltyCardCode= :NEW.LoyaltyCardCode
```

```
SET TotalAmount= TotalAmount+TotalCostXXX;
```

Draft Solution - Part A:

```
declare
```

```
X number;
```

```
begin
```

```
select SUM(NumberOfPieces*CostPerItem) INTO X
```

```
from MARKET_BASKET MB,ITEM_PRICE IP
```

```
where BasketCode = :NEW.BasketCode AND MB.ItemCode = IP.ItemCode;
```

```
INSERT INTO BASKET_TOTALPRICE_NOTIFICATION (RequestCode, BasketCode,  
TotalBasketPrice) values (:New.RequestCode, :NEW.ItemCode, X);
```

```
UPDATE LOYALTY_CARDS
```

```
SET TotalAmount = TotalAmount + X
```

```
WHERE LoyaltyCardCode = :NEW.LoyaltyCardCode;
```

```
END;
```