The StormWarden® Diesel Generator System

A StormWarden® Diesel Generator System is a great choice for off-grid power production or as an emergency power backup system for your critical pumpsets. Our engines are known for their reliability and low maintenance, giving you peace of mind. StormWarden generators are well equipped under the hood, powered by a refined three or four-cylinder industrial engine that you can always depend on. With earth leakage protection to Australian standards and fully equipped with fail-safe engine protection, the generator is as safe as it is dependable.



Perfect for any application requiring a 415V backup power supply, a StormWarden® Diesel Generator can be specified to suit your exact pump power needs, and will guarantee peace of mind for years to come.

Selection

Our range of Diesel Generators is available in three power classes, from 11kVA right up to 50kVA, meaning we've definitely got a model to suit your 415V generator needs.

Be sure to advise your Aline sales representative of the specific pumps installed along with details regarding your on-grid power supply to ensure the best selection.

The table below provides an approximate overview for selections on a per-pump basis. These are indicative only and we require a pre-sale call to determine your exact needs.

Pump KW	kVA Required		
	Single Pump	Dual Pumps	Triplex Pumps
0.75 kW	11	11	11
1.1 kW	11	11	11
1.5 kW	11	17	17
2.2 kW	17	17	22
3.7 kW	22	30	30
5.5 kW	30	50	50

StormWarden® Diesel Genset

Overview



stormwarden
the storm defence back up system

Specifications

Specifications	11kVA	17kVA
Prime Power	9kW / 11kVA 415 Volts 16Amps	13.6kW / 17kVA 415V 24Amps
Standby Power	9.4kW / 11.4kVA	15kW / 18.7kVA
Engine	OEM 3 Cylinder Diesel	OEM 4 Cylinder Diesel
RPM	1500/min	1500/min
Cooling Method	Water Cooled	Water Cooled
Starter System	12 volt Electric - Battery Included	12 volt Electric - Battery Included
Controller	• 2 Wire / Remote Start Capable • Over Temperature Protection • Over Current Protection • Low Oil Protection	• 2 Wire / Remote Start Capable • Over Temperature Protection • Over Current Protection • Low Oil Protection
Safety Systems	• Battery Isolator • Emergency Stop • Failsafe Shutdown Fuel Solenoid	• Battery Isolator • Emergency Stop • Failsafe Shutdown Fuel Solenoid
Noise Level	65 dBA at 7 metres	63 dBA at 7 metres
Fuel Tank Capacity	60 Litres (-/c Fuel Gauge)	95 Litres (-/c Fuel Gauge)
Running Time	27 Hours cont (prime load)	23 Hours cont (prime load)
Chassis Enclosure	• Lockable • Sound Deadening Throughout • Weather-Resistant Coating • Stainless Steel Fittings • External Use	• Lockable • Sound Deadening Throughout • Weather-Resistant Coating • Stainless Steel Fittings • External Use
ATS (Mains Failure)	Easy Connect Plug (ATS Optional)	Easy Connect Plug (ATS Optional)
Single Phase Outlets	3 x 15 Amp IP66	3 x 15 Amp IP66
Three Phase Outlets	1 x 20 Amp IP66	1 x 20 Amp IP66
Hardwire Terminals	Yes	Yes
Dimensions	141 L x 72 W x 111 H cm	167 L x 76 W x 117 H cm

Automatic Transfer Switch (ATS)

An ATS allows safe switching between your mains supply (primary source) and your standby Generator supply (secondary source) whilst ensuring both sources cannot be connected simultaneously thanks to the generator switch.



Design	Modular Steel
Controller	Smartgen HAT600 ATS Controller
Starting Method	2 Wire Trigger / Auto / Manual
Switching Method	Automatic (Mains Sensing) / Manual
Connection	ATS to Generator - ATS Lead Supplied
Switching Delay	0-60 Seconds (Mains Loss)
Generator Start Delay	0-90 Seconds (Generator Start/Stop)
Security	Key Lockable Cabinet
Safety	Padlock Isolation
Phase Voltage	Single, Two & Three Phase Available

StormWarden® Diesel Genset

Specifications

stormwarden
the storm defence back up system

22kVA	**30kVA**	50**kVA**
18kW / 22kVA 415Volts 31Amps	24kW / 30kVA 415Volts 42Amps	40kW / 50kVA 415Volts 69Amps
20kW / 24kVA	26kW / 33kVA	44kW / 55kVA
OEM 4 Cylinder Diesel	OEM 4 Cylinder Diesel Turbo	OEM 4 Cylinder Diesel
1500/min	1500/min	1500/min
Water Cooled	Water Cooled	Water Cooled
12 volt Electric - Battery Included	12 volt Electric - Battery Included	24 volt Electric - Battery Included
• 2 Wire / Remote Start Capable • Over Temperature Protection • Over Current Protection • Low Oil Protection	• 2 Wire / Remote Start Capable • Over Temperature Protection • Over Current Protection • Low Oil Protection	• 2 Wire / Remote Start Capable • Over Temperature Protection • Over Current Protection • Low Oil Protection
• Battery Isolator • Emergency Stop • Failsafe Shutdown Fuel Solenoid	• Battery Isolator • Emergency Stop • Failsafe Shutdown Fuel Solenoid	• Battery Isolator • Emergency Stop • Failsafe Shutdown Fuel Solenoid
65 dBA at 7 metres	63 dBA at 7 metres	67 dBA at 7 metres
120 Litres (-/c Fuel Gauge)	165 Litres (-/c Fuel Gauge)	270 Litres (-/c Fuel Gauge)
24 Hours cont (prime load)	25 Hours cont (prime load)	27 Hours cont (prime load)
• Lockable • Sound Deadening Throughout • Weather-Resistant Coating • Stainless Steel Fittings • External Use	• Lockable • Sound Deadening Throughout • Weather-Resistant Coating • Stainless Steel Fittings • External Use	• Lockable • Sound Deadening Throughout • Weather-Resistant Coating • Stainless Steel Fittings • External Use
Easy Connect Plug (ATS Optional)	Easy Connect Plug (ATS Optional)	Easy Connect Plug (ATS Optional)
2 x 15 Amp IP66	2 x 15 Amp IP66	1 x 15 Amp IP66
1 x 20 Amp IP66 1 x 32 Amp IP66	1 x 20 Amp IP66 1 x 32 Amp IP66	1 x 20 Amp IP66 2 x 32 Amp IP66
Yes	Yes	Yes
167 L x 76 W x 117 H cm	187 L x 80 W x 122 H cm	221 L x 95 W x 152 H cm



stormwarden
the storm defence back up system