

DATA SHEET

SURFACE-MOUNT CERAMIC MULTILAYER CAPACITORS

General purpose

Class 1, NP0

16 V TO 250 V

0.22 pF to 100 nF

RoHS compliant & Halogen Free



YAGEO

Product Specification – May 14, 2025 V.2.1



SCOPE

This specification describes NP0 series chip capacitors with lead-free terminations.

APPLICATIONS

- Consumer electronics for example
 - Tuners
 - Television receivers
 - All types of cameras
- Telecommunications
- Data processing

FEATURES

- Supplied in tape on reel
- Nickel-barrier end termination
- RoHS compliant
- Halogen Free compliant
- MSL class: level I

ORDERING INFORMATION - GLOBAL PART NUMBER, PHYCOMP CTC & I2NC

All part numbers are identified by the series, size, tolerance, TC material, packing style, voltage, process code, termination and capacitance value.

YAGEO BRAND ordering code**GLOBAL PART NUMBER (PREFERRED)**

CC XXXX X X NP0 X BN XXX
 (1) (2) (3) (4) (5)

(1) SIZE – INCH BASED (METRIC)

0201 (0603)
 0402 (1005)
 0603 (1608)
 0805 (2012)
 1206 (3216)
 1210 (3225)
 1812 (4532)

(2) TOLERANCE

B = ± 0.1 pF
 C = ± 0.25 pF
 D = ± 0.5 pF
 F = $\pm 1\%$
 G = $\pm 2\%$
 J = $\pm 5\%$
 K = $\pm 10\%$

(3) PACKING STYLE

R = Paper/PE taping reel; Reel 7 inch
 K = Blister taping reel; Reel 7 inch
 P = Paper/PE taping reel; Reel 13 inch
 F = Blister taping reel; Reel 13 inch
 C = Bulk case

(4) RATED VOLTAGE

7 = 16 V
 8 = 25 V
 9 = 50 V
 0 = 100 V
 A = 200 V
 Y = 250 V

(5) CAPACITANCE VALUE

2 significant digits+number of zeros
 The 3rd digit signifies the multiplying factor, and letter R is decimal point
 Example: 121 = $12 \times 10^1 = 120$ pF

CONSTRUCTION

The capacitor consists of a rectangular block of ceramic dielectric in which a number of interleaved metal electrodes are contained. This structure gives rise to a high capacitance per unit volume.

The inner electrodes are connected to the two end terminations and finally covered with a layer of plated tin (NiSn). The terminations are lead-free. A cross section of the structure is shown in Fig.1.




Fig. 1 Surface mounted multilayer ceramic capacitor construction

DIMENSION

Table I For outlines see fig. 2

| TYPE | L ₁ (mm) | W (mm) | T (MM) | L ₂ / L ₃ (mm) | | L ₄ (mm) |
|------|---------------------|------------|----------------------------|--------------------------------------|------|---------------------|
| | | | | min. | max. | min. |
| 0201 | 0.6 ±0.03 | 0.3±0.03 | 0.3±0.03 | 0.10 | 0.20 | 0.20 |
| 0402 | 1.0 ±0.05 | 0.5 ±0.05 | 0.5 ±0.05 | 0.15 | 0.35 | 0.30 |
| 0603 | 1.6 ±0.10 | 0.8 ±0.10 | 0.8 ±0.10 | 0.20 | 0.60 | 0.40 |
| 0805 | 2.0 ±0.10 | 1.25 ±0.10 | 0.6 ±0.10 | 0.25 | 0.75 | 0.70 |
| | 2.0 ±0.20 | 1.25 ±0.20 | 0.85 ±0.10 | | | |
| | | | 1.25 ±0.20 | | | |
| 1206 | | | 0.6 ±0.10 | 0.25 | 0.75 | 1.40 |
| | | | 0.85 ±0.10 | | | |
| | 3.2 ±0.15 | 1.6 ±0.15 | 0.85 ±0.10 | | | |
| | | | 0.85 ± 0.10 ⁽¹⁾ | | | |
| | 3.2 ±0.30 | 1.6 ±0.20 | 1.25 ±0.20 | | | |
| 1210 | | | 1.6 ±0.20 | 0.25 | 0.75 | 1.40 |
| | 3.2 ±0.30 | 1.6 ±0.30 | 1.6 ±0.30 | | | |
| | 3.2 ±0.20 | 2.5 ±0.20 | 0.85 ±0.10 | | | |
| | | | 1.25 ±0.20 | | | |
| 1808 | | | 1.6 ±0.20 | 0.25 | 0.75 | 2.20 |
| | | | 2.0 ±0.20 | | | |
| | 4.5 ±0.40 | 2.0 ±0.30 | 1.25 ±0.20 | | | |
| 1812 | | | 0.85 ±0.10 | 0.25 | 0.75 | 2.20 |
| | | | 1.25 ±0.20 | | | |
| | 4.5 ±0.40 | 3.2 ±0.30 | 1.25 ±0.20 | | | |
| 2020 | | | 1.60 ±0.20 | 0.25 | 0.75 | 3.40 |
| | | | 2.0 ±0.20 | | | |
| 2020 | 5.7 ±0.40 | 5.0 ±0.30 | 2.0 ±0.20 | 0.25 | 0.75 | 3.40 |

NOTE

1. Dimension for size 1206, 12nF to 33nF, 25V to 100V.

OUTLINES

For dimension see Table I




Fig. 2 Surface mounted multilayer ceramic c

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 2 Sizes from 0201 to 0402

| CAP. | 0201 | | | 0402 | | | |
|---------|----------|----------|----------|----------|----------|----------|----------|
| | 25 V | 50 V | 100 V | 16 V | 25 V | 50 V | 100 V |
| 0.22 pF | 0.3±0.03 | 0.3±0.03 | | | | | |
| 0.47 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 0.82 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.0 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.2 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.5 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.8 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 2.2 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 2.7 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 3.3 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 3.9 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 4.7 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 5.6 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 6.8 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 8.2 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 10 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 12 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 15 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 18 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 22 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 27 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 33 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 39 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 47 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 56 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 68 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 82 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 100 pF | 0.3±0.03 | 0.3±0.03 | 0.3±0.03 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |

NOTE

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 3 Sizes from 0603

| CAP. | 0603 | | | | |
|---------|---------|---------|---------|---------|---------|
| | 25 V | 50 V | 100 V | 200 V | 250 V |
| 0.22 pF | | | | | |
| 0.47 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 0.82 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 1.0 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 1.2 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 1.5 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 1.8 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 2.2 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 2.7 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 3.3 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 3.9 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 4.7 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 5.6 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 6.8 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 8.2 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 10 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 12 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 15 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 18 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 22 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 27 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 33 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 39 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 47 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 56 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 68 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 82 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 100 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |

NOTE

- Values in shaded cells indicate thickness class in mm
- Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0**Table 4** Sizes from 0201 to 0402 (continued)

| CAP. | 0402 | | | |
|--------|----------|----------|----------|----------|
| | 16 V | 25 V | 50 V | 100 V |
| 120 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 150 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 180 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 220 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 270 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 330 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 390 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 470 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 560 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 680 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 820 pF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.0 nF | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 | 0.5±0.05 |
| 1.2 nF | | | | |
| 1.5 nF | | | | |
| 1.8 nF | | | | |
| 2.2 nF | | | | |
| 2.7 nF | | | | |
| 3.3 nF | | | | |
| 3.9 nF | | | | |
| 4.7 nF | | | | |
| 5.6 nF | | | | |
| 6.8 nF | | | | |
| 8.2 nF | | | | |
| 10 nF | | | | |
| 12 nF | | | | |
| 15 nF | | | | |
| 18 nF | | | | |
| 22 nF | | | | |
| 33 nF | | | | |

NOTE

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 5 Sizes from 0603

| CAP. | 0603 25 V | 50 V | 100 V | 200 V | 250 V |
|--------|--------------|---------|---------|---------|---------|
| 120 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 150 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 180 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 220 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 270 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 330 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 390 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 470 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 560 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 680 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 |
| 820 pF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 1.0 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 1.2 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 1.5 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 1.8 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 2.2 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 2.7 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 3.3 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 3.9 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 4.7 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 5.6 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 6.8 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 8.2 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 10 nF | 0.8±0.1 | 0.8±0.1 | 0.8±0.1 | | |
| 12 nF | | | | | |
| 15 nF | | | | | |
| 18 nF | | | | | |
| 22 nF | | | | | |
| 33 nF | | | | | |

NOTE

- Values in shaded cells indicate thickness class in mm
- Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 6 Sizes from 0805 to 1206

| CAP. | 0805 | | | | | 1206 | | | | |
|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| | 25 V | 50 V | 100 V | 200 V | 250 V | 25 V | 50 V | 100 V | 200 V | 250 V |
| 0.22 pF | | | | | | | | | | |
| 0.47 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 0.82 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 1.0 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 1.2 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 1.5 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 1.8 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 2.2 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 2.7 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 3.3 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 3.9 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 4.7 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 5.6 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 6.8 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 8.2 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 10 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 12 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 15 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 18 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 22 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 27 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 33 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 39 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 47 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 56 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 68 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 82 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 100 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |

NOTE

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-I2 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 7 Sizes from 1210

| CAP. | 1210 | | | | |
|---------|----------|----------|----------|----------|----------|
| | 25 V | 50 V | 100 V | 200 V | 250 V |
| 0.22 pF | | | | | |
| 0.47 pF | | | | | |
| 0.82 pF | | | | | |
| 1.0 pF | | | | | |
| 1.2 pF | | | | | |
| 1.5 pF | | | | | |
| 1.8 pF | | | | | |
| 2.2 pF | | | | | |
| 2.7 pF | | | | | |
| 3.3 pF | | | | | |
| 3.9 pF | | | | | |
| 4.7 pF | | | | | |
| 5.6 pF | | | | | |
| 6.8 pF | | | | | |
| 8.2 pF | | | | | |
| 10 pF | | | | | |
| 12 pF | | | | | |
| 15 pF | | | | | |
| 18 pF | | | | | |
| 22 pF | | | | | |
| 27 pF | | | | | |
| 33 pF | | | | | |
| 39 pF | | | | | |
| 47 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 56 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 68 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 82 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 100 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |

NOTE

- Values in shaded cells indicate thickness class in mm
- Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 8 Sizes from 0805 to 1206

| CAP. | 0805 | | | | | 1206 | | | | |
|--------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| | 25 V | 50 V | 100 V | 200 V | 250 V | 25 V | 50 V | 100 V | 200 V | 250 V |
| 120 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 150 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 180 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 220 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 270 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 330 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 390 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 470 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 560 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 680 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 |
| 820 pF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.85±0.1 | 0.85±0.1 |
| 1.0 nF | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.85±0.1 | 0.85±0.1 |
| 1.2 nF | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.85±0.1 | 0.85±0.1 |
| 1.5 nF | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 0.85±0.1 | 0.85±0.1 |
| 1.8 nF | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 1.25±0.2 | 1.25±0.2 |
| 2.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 1.25±0.2 | 1.25±0.2 |
| 2.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 0.6±0.1 | 0.6±0.1 | 0.6±0.1 | 1.25±0.2 | 1.25±0.2 |
| 3.3 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 1.25±0.2 | 1.25±0.2 |
| 3.9 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | 1.25±0.2 | 1.25±0.2 |
| 4.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 5.6 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 6.8 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 8.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 10 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 12 nF | | | | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 15 nF | | | | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 18 nF | | | | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 22 nF | | | | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 33 nF | | | | | | 0.85±0.1 | 0.85±0.1 | 0.85±0.1 | | |
| 47 nF | | | | | | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 56 nF | | | | | | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 68 nF | | | | | | 1.60±0.2 | 1.60±0.2 | 1.60±0.2 | | |
| 82 nF | | | | | | 1.60±0.2 | 1.60±0.2 | 1.60±0.2 | | |
| 100 nF | | | | | | 1.60±0.2 | 1.60±0.2 | 1.60±0.2 | | |

NOTE

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 9 Sizes from 1210

| CAP. | 1210 25 V | 50 V | 100 V | 200 V | 250 V |
|--------|--------------|----------|----------|----------|----------|
| 120 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 150 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 180 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 220 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 270 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 330 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 390 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 470 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 560 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 680 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 820 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.0 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.5 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.8 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 2.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 2.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 3.3 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 3.9 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 4.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 5.6 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 6.8 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 8.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 10 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 12 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 15 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | | |
| 18 nF | 1.60±0.2 | 1.60±0.2 | 1.60±0.2 | | |
| 22 nF | 1.60±0.2 | 1.60±0.2 | 1.60±0.2 | | |
| 33 nF | | | | | |
| 47 nF | 1.60±0.2 | 1.60±0.2 | | | |
| 56 nF | | | | | |
| 68 nF | | | | | |
| 82 nF | | | | | |
| 100 nF | | | | | |

NOTE

- Values in shaded cells indicate thickness class in mm
- Capacitance value of non E-12 series is on request

CAPACITANCE RANGE & THICKNESS FOR NP0

Table 10 Sizes 1812

| CAP. | 1812 50 V | 100 V | 200 V | 250 V |
|--------|--------------|----------|----------|----------|
| 10 pF | | | | |
| 12 pF | | | | |
| 15 pF | | | | |
| 18 pF | | | | |
| 22 pF | | | | |
| 27 pF | | | | |
| 33 pF | | | | |
| 39 pF | | | | |
| 47 pF | | | | |
| 56 pF | 1.25±0.2 | | | |
| 68 pF | 1.25±0.2 | | | |
| 82 pF | 1.25±0.2 | | | |
| 100 pF | 1.25±0.2 | | | |
| 120 pF | 1.25±0.2 | | | |
| 150 pF | 1.25±0.2 | | | |
| 180 pF | 1.25±0.2 | | | |
| 220 pF | 1.25±0.2 | | | |
| 270 pF | 1.25±0.2 | | | |
| 330 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 390 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 470 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 560 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 680 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 820 pF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.5 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 1.8 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 2.2 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 2.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 3.3 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 3.9 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 4.7 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 |
| 5.6 nF | 1.25±0.2 | 1.25±0.2 | 1.25±0.2 | |
| 6.8 nF | 1.25±0.2 | 1.25±0.2 | | |
| 8.2 nF | 1.25±0.2 | 1.25±0.2 | | |
| 10 nF | 1.25±0.2 | 1.25±0.2 | | |
| 12 nF | 1.25±0.2 | 1.25±0.2 | | |
| 15 nF | 1.25±0.2 | 1.25±0.2 | | |
| 18 nF | 1.25±0.2 | 1.25±0.2 | | |
| 22 nF | 1.25±0.2 | 1.25±0.2 | | |
| 33 nF | 1.25±0.2 | | | |

NOTE

1. Values in shaded cells indicate thickness class in mm
2. Capacitance value of non E-12 series is on request

PAPER/PE TAPE SPECIFICATION




Table 1 Dimensions of paper/PE tape for relevant chip size; see Fig.3

| SIZE | SYMBOL | Unit: mm | | | | | | | | | |
|----------|----------------|----------------|----------|-----------|------------|-------------------------------|----------------|----------------|-----------------|--------------------------|---------------------------|
| CODE | A ₀ | B ₀ | W | E | F | P ₀ ⁽¹⁾ | P ₁ | P ₂ | ØD ₀ | K ₀ | T |
| 01005 | 0.24 ±0.03 | 0.45 ±0.03 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.05 | 2.0 ±0.05 | 2.0 ±0.05 | 1.50 ±0.1 | 0.24 ± 0.03 | 0.36 ± 0.01 |
| 0201 | 0.39 ±0.06 | 0.70 ±0.06 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.05 | 2.0 ±0.05 | 2.0 ±0.05 | 1.55 ±0.03 | 0.38 ± 0.05 | (0.47 / 0.55)±0.10 |
| 0402 | 0.70 ±0.15 | 1.21 ±0.12 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.05 | 2.0 ±0.05 | 2.0 ±0.05 | 1.50 ±0.1 | 0.75 / 0.60)±0.10 | (0.85 / 0.70)±0.10 |
| 0603 | 1.05 ±0.14 | 1.86 ±0.13 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 1.05 / 0.95 / 0.75)±0.10 | (1.15 / 1.05 / 0.85)±0.10 |
| 0805 | 1.50 ±0.15 | 2.26 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 1.05 / 0.95 / 0.75)±0.10 | (1.15 / 1.05 / 0.85)±0.10 |
| 1206 | 1.90 ±0.15 | 3.50 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 0.95 / 0.75)±0.10 | (1.05 / 0.85)± 0.10 |
| 4 × 0402 | 1.50 ±0.15 | 2.26 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 1.05 / 0.95 / 0.75)±0.10 | (1.15 / 1.05 / 0.85)±0.10 |
| 4 × 0603 | 1.90 ±0.15 | 3.50 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 0.95 / 0.75)±0.10 | (1.05 / 0.85)±0.10 |
| 0508 | 1.50 ±0.15 | 2.26 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 1.05 / 0.95 / 0.75)±0.10 | (1.15 / 1.05 / 0.85)±0.10 |
| 0612 | 1.90 ±0.15 | 3.50 ±0.20 | 8.0 ±0.2 | 1.75 ±0.1 | 3.50 ±0.05 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.50 ±0.1 | 0.95 / 0.75)±0.10 | (1.05 / 0.85)±0.10 |

NOTE

1. P₀ pitch tolerance over any 10 pitches is ±0.2 mm
2. 4 × 0402 stands for 0508 array
3. 4 × 0603 stands for 0612 array

BLISTER TAPE SPECIFICATION

For dimension see Table 4




Fig. 4 Blister tape

Table 12 Dimensions of blister tape for relevant chip size; see Fig.4

| SIZE CODE | SYMBOL | | | | | | | | | | | | | | | Unit: mm | |
|--------------|----------------|------|----------------|------|----------------|------|------------|-----------|-----------|-----------------|-----------------|-------------------------------|----------------|----------------|----------------|----------|--|
| | A ₀ | | B ₀ | | K ₀ | | W | E | F | ØD ₀ | ØD ₁ | P ₀ ⁽²⁾ | P ₁ | P ₂ | T ₂ | | |
| | Min. | Max. | Min. | Max. | Min. | Max. | | | | | | | | | Min. | Max. | |
| 0805 | 1.29 | 1.65 | 2.09 | 2.60 | 1.25 | 1.62 | 8.1 ±0.20 | 1.75 ±0.1 | 3.5 ±0.05 | 1.5 +0.1/-0.0 | 1 +0.1/-0.0 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.30 | 1.67 | |
| 1206 | 1.65 | 2.12 | 3.30 | 3.75 | 1.22 | 2.15 | 8.1 ±0.20 | 1.75 ±0.1 | 3.5 ±0.05 | 1.5 +0.1/-0.0 | 1 +0.1/-0.0 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.27 | 2.20 | |
| 1210 | 2.55 | 3.02 | 3.31 | 3.88 | 0.97 | 2.92 | 8.1 ±0.20 | 1.75 ±0.1 | 3.5 ±0.05 | 1.5 +0.1/-0.0 | 1 +0.1/-0.0 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.02 | 2.97 | |
| 1808 | 2.05 | 2.55 | 4.80 | 5.45 | 1.30 | 2.45 | 12.1 ±0.20 | 1.75 ±0.1 | 5.5 ±0.05 | 1.5 +0.1/-0.0 | 1.5 +0.1/-0.0 | 4.0 ±0.10 | 4.0 ±0.10 | 2.0 ±0.05 | 1.35 | 2.50 | |
| 1812 | 3.35 | 3.75 | 4.70 | 5.33 | 0.70 | 2.40 | 12.1 ±0.20 | 1.75 ±0.1 | 5.5 ±0.05 | 1.5 +0.1/-0.0 | 1.5 +0.1/-0.0 | 4.0 ±0.10 | 8.0 ±0.10 | 2.0 ±0.05 | 0.75 | 2.45 | |
| 2220 | 5.12 | 5.32 | 5.84 | 6.04 | 1.28 | 1.48 | 12.0 ±0.20 | 1.75 ±0.1 | 5.5 ±0.05 | 1.5 +0.1/-0.0 | 1.5 +0.1/-0.0 | 4.0 ±0.10 | 8.0 ±0.10 | 2.0 ±0.05 | 1.33 | 1.53 | |

NOTE

1. Typical capacitor displacement in pocket
2. P_0 pitch tolerance over any 10 pitches is $\pm 0.2 \text{ mm}$

REEL SPECIFICATION




Table 13 Reel dimensions; see Fig.5

| TAPE WIDTH | SYMBOL | | | | Unit: mm |
|-----------------|----------|----------|----------------|----------------|--------------------|
| | A | N | C | W ₁ | W _{2max.} |
| 8 (Ø178 mm/7") | 178 ±1.0 | 60 ±1.0 | 13 +0.50/-0.20 | 9.4 ±1.5 | 14.4 |
| 8 (Ø330 mm/13") | 330 ±1.0 | 100 ±1.0 | 13 +0.50/-0.20 | 9.0 ±0.2 | 14.4 |
| 12 (Ø178 mm/7") | 178 ±1.0 | 60 ±1.0 | 13 +0.50/-0.20 | 13.4 ±1.5 | 18.4 |

PROPERTIES OF REEL

Material: polystyrene

Surface resistance: <10¹⁰ X/sq.

THICKNESS CLASSES AND PACKING QUANTITY

Table 14

| SIZE CODE | THICKNESS CLASSIFICATION | TAPE WIDTH QUANTITY PER REEL | Ø180 MM / 7 INCH | | Ø330 MM / 13 INCH | | QUANTITY PER BULK CASE |
|-----------|--------------------------|---------------------------------|------------------|----------------|-------------------|---------|---------------------------|
| | | | Paper/PE | Blister | Paper/PE | Blister | |
| 0201 | 0.3 ±0.03 mm | 8 mm | 15,000 | --- | 50,000 | --- | --- |
| 0402 | 0.5 ±0.05 mm | 8 mm | 10,000 | --- | 50,000 | --- | 50,000 |
| 0603 | 0.8 ±0.1 mm | 8 mm | 4,000 | --- | 15,000 | --- | 15,000 |
| 0805 | 0.6 ±0.1 mm | 8 mm | 4,000 | --- | 20,000 | --- | 10,000 |
| | 0.85 ±0.1 mm | 8 mm | 4,000 | --- | 15,000 | --- | 8,000 |
| | 1.25 ±0.2 mm | 8 mm | --- | 3,000 | --- | 10,000 | 5,000 |
| 1206 | 0.6 ±0.1 mm | 8 mm | 4,000 | --- | 20,000 | --- | --- |
| | 0.85 ±0.1 mm | 8 mm | 4,000 | --- | 15,000 | --- | --- |
| | 1.00 / 1.15 ±0.1 mm | 8 mm | --- | 3,000 | --- | 10,000 | --- |
| | 1.25 ±0.2 mm | 8 mm | --- | 3,000 | --- | 10,000 | --- |
| | 1.6 ±0.15 mm | 8 mm | --- | 2,500 | --- | 10,000 | --- |
| | 1.6 ±0.2 mm | 8 mm | --- | 2,000 | --- | 8,000 | --- |
| 1210 | 0.6 / 0.7 ±0.1 mm | 8 mm | --- | 4,000 | --- | 15,000 | --- |
| | 0.85 ±0.1 mm | 8 mm | --- | 4,000 | --- | 10,000 | --- |
| | 1.15 ±0.1 mm | 8 mm | --- | 3,000 | --- | 10,000 | --- |
| | 1.15 ±0.15 mm | 8 mm | --- | 3,000 | --- | 10,000 | --- |
| | 1.25 ±0.2 mm | 8 mm | --- | 3,000 | --- | --- | --- |
| | 1.5 ±0.1 mm | 8 mm | --- | 2,000 | --- | --- | --- |
| | 1.6 / 1.9 ±0.2 mm | 8 mm | --- | 2,000 | --- | --- | --- |
| | 2.0 ±0.2 mm | 8 mm | --- | 2,000 1,000 | --- | --- | --- |
| | 2.5 ±0.2 mm | 8 mm | --- | 1,000 500 | --- | --- | --- |
| 1808 | 1.15 ±0.15 mm | 12 mm | --- | 3,000 | --- | --- | --- |
| | 1.25 ±0.2 mm | 12 mm | --- | 3,000 | --- | --- | --- |
| | 1.35 ±0.15 mm | 12 mm | --- | 2,000 | --- | --- | --- |
| | 1.5 ±0.1 mm | 12 mm | --- | 2,000 | --- | --- | --- |
| | 1.6 ±0.2 mm | 12 mm | --- | 2,000 | --- | --- | --- |
| | 2.0 ±0.2 mm | 12 mm | --- | 2,000 | --- | --- | --- |
| 1812 | 0.6 / 0.85 ±0.1 mm | 12 mm | --- | 2,000 | --- | --- | --- |
| | 1.15 ±0.1 mm | 12 mm | --- | 1,000 | --- | --- | --- |
| | 1.25 ±0.2 mm | 12 mm | --- | 1,000 | --- | --- | --- |
| | 1.5 ±0.1 mm | 12 mm | --- | 1,000 | --- | --- | --- |
| | 1.6 ±0.2 mm | 12 mm | --- | 1,000 | --- | --- | --- |
| | 2.0 ±0.2 mm | 12 mm | --- | 1,000 | --- | --- | --- |
| | 2.5 ±0.2 mm | 12 mm | --- | 500 | --- | --- | --- |



ELECTRICAL CHARACTERISTICS

NP0 DIELECTRIC CAPACITORS; NISN TERMINATIONS

Unless otherwise stated all electrical values apply at an ambient temperature of 20±1 °C, an atmospheric pressure of 86 to 106 kPa, and a relative humidity of 63 to 67%.

Table 15

| DESCRIPTION | VALUE |
|---|---|
| Capacitance range | 0.22 pF to 100 nF |
| Capacitance tolerance | |
| C < 10 pF | ±0.1 pF, ±0.25 pF, ±0.5 pF |
| C ≥ 10 pF | ±1%, ±2%, ±5%, ±10% |
| Dissipation factor (D.F.) | |
| C < 30 pF | ≤ 1 / (400 + 20C) |
| C ≥ 30 pF | ≤ 0.1 % |
| Insulation resistance after 1 minute at U _r (DC) | R _{ins} ≥ 10 GΩ or R _{ins} × C _r ≥ 500 seconds whichever is less |
| Maximum capacitance change as a function of temperature (temperature characteristic/coefficient): | ±30 ppm/°C |
| Operating temperature range: | −55 °C to +125 °C |






Fig. 8 Typical tan δ as a function of temperature

SOLDERING RECOMMENDATION

Table I6

| SOLDERING METHOD | SIZE 0201 | 0402 | 0603 | 0805 | 1206 | ≥ 1210 |
|------------------|-----------|------|------|------|------|--------|
| Reflow | ○ | ○ | ○ | ○ | ○ | ○ |
| Wave | --- | --- | ○ | ○ | ○ | --- |

TESTS AND REQUIREMENTS

Table 17 Test procedures and requirements

| TEST | TEST METHOD | PROCEDURE | REQUIREMENTS |
|---------------------------------------|-----------------|--|----------------------------------|
| Mounting | IEC 60384-21/22 | 4.3 The capacitors may be mounted on printed-circuit boards or ceramic substrates | No visible damage |
| Visual inspection and dimension check | | 4.4 Any applicable method using × 10 magnification | In accordance with specification |
| Capacitance | | 4.5.1 Class I: f = 1 MHz for C ≤ 1 nF, measuring at voltage 1 V _{rms} at 20 °C f = 1 KHz for C > 1 nF, measuring at voltage 1 V _{rms} at 20 °C | Within specified tolerance |
| Dissipation factor (D.F.) | | 4.5.2 Class I: f = 1 MHz for C ≤ 1 nF, measuring at voltage 1 V _{rms} at 20 °C f = 1 KHz for C > 1 nF, measuring at voltage 1 V _{rms} at 20 °C | In accordance with specification |
| Insulation resistance | | 4.5.3 At U _r (DC) for 1 minute | In accordance with specification |
| Temperature coefficient | | 4.6 Capacitance shall be measured by the steps shown in the following table. The capacitance change should be measured after 5 min at each specified temperature stage. | Class I: Δ C/C: ±30ppm |

| Step | Temperature(°C) |
|------|------------------------|
| a | 25±2 |
| b | Lower temperature±3 °C |
| c | 25±2 |
| d | Upper Temperature±2 °C |
| e | 25±2 |

(1) Class I

Temperature Coefficient shall be calculated from the formula as below

$$\text{Temp, Coefficient} = \frac{C2 - C1}{C1 \times \Delta T} \times 10^6 \text{ [ppm/°C]}$$

C1: Capacitance at step c
C2: Capacitance at 125 °C
ΔT: 100°C (=125°C -25 °C)

(2) Class II

Capacitance Change shall be calculated from the formula as below

$$\Delta C = \frac{C2 - C1}{C1} \times 100\%$$

C1: Capacitance at step c
C2: Capacitance at step b or d

| TEST | TEST METHOD | PROCEDURE | REQUIREMENTS |
|--------------------------------------|---------------------|--|--|
| Adhesion | 4.7 | A force applied for 10 seconds to the line joining the terminations and in a plane parallel to the substrate | Force size \geq 0603: 5N size = 0402: 2.5N size = 0201: 1N |
| Bond strength of plating on end face | 4.8 | Mounting in accordance with IEC 60384-22 paragraph 4.3 Conditions: bending 1 mm at a rate of 1 mm/s, radius jig 5 mm | No visible damage $\Delta C/C$ Class I: NP0: within $\pm 1\%$ or 0.5 pF whichever is greater |
| Resistance to soldering heat | IEC 60384-21/22 4.9 | Precondition: 150 $\pm 0/-10$ °C for 1 hour, then keep for 24 ± 1 hours at room temperature Preheating: for size \leq 1206: 120 °C to 150 °C for 1 minute Preheating: for size $>$ 1206: 100 °C to 120 °C for 1 minute and 170 °C to 200 °C for 1 minute Solder bath temperature: 260 ± 5 °C Dipping time: 10 ± 0.5 seconds Recovery time: 24 ± 2 hours | Dissolution of the end face plating shall not exceed 25% of the length of the edge concerned $\Delta C/C$ Class I: NP0: within $\pm 0.5\%$ or 0.5 pF whichever is greater D.F. within initial specified value R_{ins} within initial specified value |
| Solderability | 4.10 | Preheated the temperature of 80 °C to 140 °C and maintained for 30 seconds to 60 seconds. 1. Temperature: 235 ± 5 °C / Dipping time: 2 ± 0.5 s 2. Temperature: 245 ± 5 °C / Dipping time: 3 ± 0.5 s (lead free) Depth of immersion: 10mm | The solder should cover over 95% of the critical area of each termination |
| Rapid change of temperature | 4.11 | Preconditioning: 150 $\pm 0/-10$ °C for 1 hour, then keep for 24 ± 1 hours at room temperature 5 cycles with following detail: 30 minutes at lower category temperature 30 minutes at upper category temperature Recovery time 24 ± 2 hours | No visual damage $\Delta C/C$ Class I: NP0: within $\pm 1\%$ or 1 pF whichever is greater D.F. meet initial specified value R_{ins} meet initial specified value |

| TEST | TEST METHOD | PROCEDURE | REQUIREMENTS | | | | | | | | | | |
|---------------------------|-----------------|---|--|-----|--------|-------------|----------|-------------|----------|-------------|-------|-------------|---|
| Damp heat with U_r load | IEC 60384-21/22 | <div>4.13</div> <div><div><div>1. Preconditioning, class 2 only: 150 +0/-10 °C /1 hour, then keep for 24 ±1 hour at room temp</div><div>2. Initial measure: Spec: refer to initial spec C, D, IR</div><div>3. Damp heat test: 500 ±12 hours at 40 ±2 °C; 90 to 95% R.H. 1.0 U_r applied.</div><div>4. Recovery: Class I: 6 to 24 hours</div><div>5. Final measure: C, D, IR</div></div><div>P.S. If the capacitance value is less than the minimum value permitted, then after the other measurements have been made the capacitor shall be preconditioned according to “IEC 60384 4.1” and then the requirement shall be met.</div></div> | <div>No visual damage after recovery</div> <div>$\Delta C/C$ Class I: NP0: within ±2% or 1 pF whichever is greater D.F. Class I: NP0: ≤ 2 × specified value R_{ins} Class I: NP0: ≥ 2,500 MΩ or $R_{ins} \times C_r \geq 25s$ whichever is less</div> | | | | | | | | | | |
| Endurance | | <div>4.14</div> <div><div><div>1. Preconditioning, class 2 only: 150 +0/-10 °C /1 hour, then keep for 24 ±1 hour at room temp</div><div>2. Initial measure: Spec: refer to initial spec C, D, IR</div><div>3. Endurance test: Temperature: NP0: 125 °C Specified stress voltage applied for 1,000 hours: Applied 2.0 × U_r for general product.</div><div>4. High voltage series follows with below stress condition:</div></div><table><tr><th>Voltage</th><th>NPO</th></tr><tr><td>≤ 100V</td><td>2.0 × U_r</td></tr><tr><td>200/250V</td><td>1.5 × U_r</td></tr><tr><td>500/630V</td><td>1.3 × U_r</td></tr><tr><td>≥ 1KV</td><td>1.2 × U_r</td></tr></table><div>* NP0, 0603, 100V, 5.1nF to 10nF, apply voltage : 1.5 × U_r</div><div><div>5. Recovery time: 24 ±2 hours</div><div>6. Final measure: C, D, IR</div></div><div>P.S. If the capacitance value is less than the minimum value permitted, then after the other measurements have been made the capacitor shall be preconditioned according to “IEC 60384 4.1” and then the requirement shall be met.</div></div> | Voltage | NPO | ≤ 100V | 2.0 × U_r | 200/250V | 1.5 × U_r | 500/630V | 1.3 × U_r | ≥ 1KV | 1.2 × U_r | <div>No visual damage</div> <div>$\Delta C/C$ Class I: NP0: within ±2% or 1 pF whichever is greater D.F. Class I: NP0: ≤ 2 × specified value R_{ins} Class I: NP0: ≥ 4,000 MΩ or $R_{ins} \times C_r \geq 40s$ whichever is less</div> |
| Voltage | NPO | | | | | | | | | | | | |
| ≤ 100V | 2.0 × U_r | | | | | | | | | | | | |
| 200/250V | 1.5 × U_r | | | | | | | | | | | | |
| 500/630V | 1.3 × U_r | | | | | | | | | | | | |
| ≥ 1KV | 1.2 × U_r | | | | | | | | | | | | |
| Voltage proof | IEC 60384-1 | <div>4.6</div> <div><div>Specified stress voltage applied for 1 minute</div><div>$U_r \leq 100$ V: series applied 2.5 U_r</div><div>100 V < $U_r \leq 200$ V series applied (1.5 U_r + 100)</div><div>200 V < $U_r \leq 500$ V series applied (1.3 U_r + 100)</div><div>$U_r > 500$ V: 1.3 U_r</div><div>I: 7.5 mA</div></div> | No breakdown or flashover | | | | | | | | | | |

REVISION HISTORY

| REVISION | DATE | CHANGE NOTIFICATION | DESCRIPTION |
|------------|---------------|---------------------|---|
| Version 21 | May 14, 2025 | - | - Add 1206, 12nF to 82nF, 100V |
| Version 20 | Mar. 11, 2025 | - | - Add 1206, 100nF, 100V |
| Version 19 | Jan. 29, 2024 | - | - Add 100 V to 250 V product range |
| Version 19 | Jan. 29, 2024 | - | - Add 100 V to 250 V product range |
| Version 18 | Jun. 14, 2023 | - | - Update 1206/12nF to 47nF dimension |
| Version 17 | Jul. 29, 2019 | - | - Update 0805/10nF dimension |
| Version 16 | Mar. 7, 2017 | - | - 0805 L4 spec updated |
| Version 15 | Nov. 21, 2016 | - | - Product range updated |
| Version 14 | Jul. 22, 2016 | - | - Add 0805/8.2nF and 10nF/ 16V to 50V, T=1.25mm |
| Version 13 | May. 16, 2016 | - | - Product range updated |
| Version 12 | Feb. 16, 2016 | - | - Product range updated |
| Version 11 | Sep. 11, 2014 | - | - Product range updated |
| Version 10 | Feb. 18, 2014 | - | - Product range updated |
| Version 9 | Jun. 17, 2013 | - | - Product range updated |
| Version 8 | Aug 05, 2011 | - | - Dimension updated |
| Version 7 | Jun 14, 2011 | - | - Size 1210 T=1.0mm SPQ added - Dimension updated |
| Version 6 | Jan 06, 2011 | - | - Dimension updated |
| Version 5 | Dec 29, 2010 | - | - Dimension updated |
| Version 4 | Nov 23, 2010 | - | - Dimension updated |
| Version 3 | Apr 20, 2010 | - | - The statement of "Halogen Free" on the cover added - Dimension updated |
| Version 2 | Oct 26, 2009 | - | - Typo updated |
| Version 1 | Jun 02, 2009 | - | - 12NC code updated |
| Version 0 | Apr 15, 2009 | - | - New datasheet for general purpose NP0 series with RoHS compliant - Replace the "16V to 50V" part of pdf files: NP0_16V_7, NP0_16V-to-100V_6, NP0_25V_7, NP0_50-to-500V_11 - Combine 0201 from pdf files: UP-NP0X5RX7RY5V_0201_6.3-to-50V_2 and UY-NP0X5RX7RY5V_0201_6.3-to-50V_2 - Define global part number - Description of "Halogen Free compliant" added - Test method and procedure updated |

LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, "YAGEO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial, automotive, and/or COTS grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.