

THE TALKING HANDS

A Comprehensive Survey and Framework for Real-Time Multilingual Sign Language Recognition with Integrated Natural Language

Processing

1st A. Shri Poornima

Department of Artificial Intelligence and Data Science
National Engineering College
Kovilpatti, India
2217019@nec.edu.in

2nd A. Sonali Mitra

Department of Artificial Intelligence and Data Science
National Engineering College
Kovilpatti, India
2217020@nec.edu.in

3rd R. Yuvanithi

Department of Artificial Intelligence and Data Science
National Engineering College
Kovilpatti, India
2217024@nec.edu.in

Abstract—Persistent communication asymmetries between the hearing-impaired community and the general population constitute a significant barrier to social inclusion, a challenge that is further exacerbated in linguistically diverse regions. To address this, we introduce "The Talking Hands," an end-to-end real-time translation framework that synergizes computer vision, deep learning, and computational linguistics to convert manual gestures into synthesized speech. The proposed system deploys advanced webcam-based hand tracking algorithms to robustly localize and identify both unimanual and bimanual gestures across a spectrum of sign languages. These gesture sequences are analyzed using Convolutional Neural Networks (CNNs) trained on comprehensive datasets comprising both alphabet and word-level lexicon. Distinct from conventional recognition-only approaches, this framework couples gesture classification with adaptive machine learning models for enhanced contextual understanding. Deployed as a browser-based web application, the system eliminates the requisite for local software installation, thereby ensuring ubiquitous accessibility across varying device form factors. The system's high-fidelity processing capabilities are designed to augment social interaction for individuals with auditory impairments. Furthermore, recognized gesture tokens are processed by a Long Short-Term Memory (LSTM) based Natural Language Processing (NLP) module, which reconstructs grammatically coherent sentences. These sentences are subsequently converted into audio via a multilingual Text-to-Speech (TTS) engine, supporting output in English, Hindi, Tamil, and Russian, with configurable voice profiles. This holistic platform aims to foster inclusive communication ecosystems and facilitate seamless interaction across multiple linguistic modalities.

Index Terms—Sign Language Recognition, Deep Learning, Computer Vision, Assistive Technology, Real-Time Translation, Convolutional Neural Networks, Gesture Recognition, Accessibility.

I. Introduction

Automatic Sign Language Recognition (SLR) represents a critical technological intervention for dismantling

communication barriers between the Deaf and Hard-of-Hearing (DHH) community and the hearing population. By facilitating seamless interaction, SLR technologies promote greater equity and inclusion within social, educational, and professional environments. Sign languages—encompassing distinct systems such as Indian Sign Language (ISL), Chinese Sign Language (CSL), Russian Sign Language (RSL), Pakistani Sign Language (PSL), and American Sign Language (ASL)—are complex, fully-formed linguistic systems defined by unique hand configurations, facial expressions, and syntactic rules. This functional gap significantly constrains the participation of DHH individuals in virtual meetings and digital collaborative spaces.

The development of real-time translation architectures capable of interpreting multiple sign languages and converting them into spoken or written text can profoundly expand the communicative horizons for DHH users. This paper provides a survey of significant contributions to the field of SLR and introduces a novel integrated framework designed to recognize signs, generate grammatically accurate sentences, and produce multilingual speech output. The overarching objective is to mitigate communication hurdles in diverse linguistic settings, ensuring that technology serves as a bridge for universal human interaction.

II. Related Work

A. Historical Development of Sign Language Recognition

The trajectory of Sign Language Recognition (SLR) research over the past two decades reflects a transition from heuristic-based methods to data-driven learning paradigms. Early methodologies were predominantly reliant on handcrafted features, employing techniques such as skin-color segmentation, background subtraction, and geometric shape analysis to isolate and identify static hand

979-8-3315-8715-4/26/\$31.00 © 2026 IEEE

postures [1], [5], [9]. To address the spatiotemporal nature of signing, researchers subsequently adopted probabilistic models, specifically Hidden Markov Models (HMMs) and Dynamic Time Warping (DTW). These approaches provided a mathematical framework for modeling sequential gestures and handling variations in signing speed [3], [11], [16]. While these foundational methods demonstrated the feasibility of SLR, they exhibited significant fragility when exposed to real-world variables. Performance often degraded substantially under varying illumination, signer inter-variability, and cluttered backgrounds, limiting their deployment in unconstrained environments [7], [12].

B. Vision-Based Approaches

The integration of machine learning marked a significant evolution in vision-based SLR. Initial efforts utilized classical classifiers such as Support Vector Machines (SVMs), k-Nearest Neighbors (k-NN), and Random Forests, which operated on manually extracted feature vectors representing hand shape and motion trajectories [4], [13], [15].

III. LITERATURE SURVEY

A. Deep Learning for Static and Dynamic Gesture Recognition

Deep learning has fundamentally altered the SLR landscape by removing the bottleneck of manual feature engineering. For static gesture recognition, deep CNN architectures such as AlexNet, VGGNet, and ResNet have achieved high accuracy benchmarks on standard datasets [3], [9], [11], [18]. In the realm of dynamic gesture recognition, which necessitates the analysis of motion over time, 3D CNNs and hybrid CNN-LSTM models have proven effective in capturing spatiotemporal features [10], [13]. However, the efficacy of these models is heavily contingent on the volume and diversity of training data. Consequently, sign languages with limited digital resources, such as ISL, continue to present recognition challenges, as the lack of extensive annotated data hinders the training of deep models that generalize well [5].

B. Sequence Modeling with RNNs, LSTMs, and Transformers

Since sign language conveys meaning through ordered sequences of gestures, accurate temporal modeling is indispensable. Recurrent Neural Networks (RNNs) and Long Short-Term Memory (LSTM) networks have been extensively deployed to process sequential video data and model the transitions between frames [3], [11].

C. Comparative Analysis of Reviewed Works

The evolution of SLR can be summarized through the following developmental stages:

- 1) Handcrafted Features: Offered interpretability but lacked robustness against noise [4], [7], [9].
- 2) Classical Machine Learning: Improved classification but struggled with complex temporal dynamics [1], [6], [12].

- 3) Deep Learning Classifiers: CNNs provided a leap in accuracy but introduced high data dependency [3], [9], [11].
- 4) Real-Time Frameworks: Lightweight landmark-based systems enable real-time use, though comprehensive multilingual support remains an active research frontier [13].

IV. PROPOSED WORK

A. System Overview and Novel Contributions

"The Talking Hands" is engineered as a real-time interpretation framework for Indian Sign Language (ISL), designed with scalability for other sign languages. The system architecture integrates computer vision for gesture acquisition, deep learning for classification, and NLP for sentence construction. MediaPipe is utilized for robust tracking of unimanual and bimanual signs, which are analyzed by a deep learning model trained on a diverse ISL dataset. An integrated NLP module refines the recognized glosses into grammatically correct text, which is then converted into spoken output in English, Hindi, and Tamil via a customizable TTS engine. The system is delivered as a lightweight web application using HTML, CSS, JavaScript, and Python Flask, ensuring low-latency performance without client-side installation.




Fig. 1. Evolution of Sign Language Recognition Approaches

B. Dataset Collection and Preprocessing Pipeline

- 1) Data Overview: To ensure system robustness, we aggregated multiple publicly available datasets covering

Indian, Chinese, Pakistani, Russian, and American Sign Languages. These datasets contain both static images for isolated signs and video sequences for continuous gestures.

TABLE I
Dataset Summary for Sign Language Recognition

Dataset Name	Size
ISL Words Dataset (Kaggle)	250+ images
ISL Alphabet Dataset (Kaggle)	36K images
NationalCSL-DP (Figshare)	25K videos
PSL Alphabet Dataset (Kaggle)	26 letters
Russian Sign Alphabet Dataset (Kaggle)	1.5K images
ASL Alphabet Dataset (Kaggle)	87K images
WLASL Dataset (Kaggle)	annotated videos

2) Preprocessing Pipeline: A rigorous preprocessing workflow was implemented to optimize data for training. Images and videos were organized by label, with metadata used to isolate gesture segments in videos. Advanced landmark detection extracted 21 key points per hand, which were normalized to ensure scale invariance. Samples with poor tracking were filtered out. To prevent overfitting, data augmentation techniques—including rotation, scaling, and flipping—were applied. The processed data was serialized into optimized files for rapid access.

C. Real-Time Gesture Detection and Tracking using MediaPipe

The system employs MediaPipe for efficient, low-latency gesture tracking via standard webcams. MediaPipe processes video frames to detect hands and extract 21 3D landmarks (x, y, z coordinates) per hand, capturing pose and motion. For two-handed gestures, landmarks from both hands are concatenated to model spatial relationships. Unique identifiers are assigned to each hand to maintain temporal consistency. The extracted landmark sequences are fed into the classification model, where temporal architectures like LSTMs and GRUs enable the recognition of dynamic gestures. This landmark-based approach ensures scalability and real-time performance.

D. CNN-Based Gesture Classification Framework

The classification framework integrates MediaPipe landmark extraction with deep learning inference. The core recognition is performed by temporal models (LSTM/GRU) that analyze landmark sequences to identify sign patterns. By combining efficient per-frame extraction with sequential modeling, the system maintains high frame rates (>25 FPS), ensuring a responsive user experience.

E. NLP-Based Sentence Formation using LSTM

Raw recognition outputs often consist of disjointed glosses. To convert these into natural language, an embedded LSTM-based NLP module is employed. This module transforms recognized gloss sequences into grammatically coherent sentences. The process involves mapping gesture sequences to vectorized embeddings in a predefined




Fig. 2. System Architecture of the Talking Hands

lexicon. The LSTM network, trained on paired gloss-sentence examples, learns the syntactic mappings required for translation. During inference, the model generates sentences word-by-word. Post-processing refines the output for grammar and punctuation, bridging the gap between sign syntax and spoken language structure (English, Hindi, Tamil).

F. Multilingual Text-to-Speech (TTS)

The final pipeline stage is the multilingual TTS module, converting NLP-generated text into audio. Supporting English, Hindi, and Tamil, the TTS engine allows users to select voice characteristics. The system uses pre-loaded language models to ensure near-instantaneous audio generation.

V. COMPARATIVE EVALUATION FRAMEWORK

A. Performance Metrics and Evaluation Criteria

To rigorously assess the system, we utilized a comprehensive set of quantitative and qualitative metrics covering recognition accuracy, NLP quality, responsiveness, and speech naturalness.

TABLE II
Module-wise Performance: Talking Hands Framework

Module	Technique	Metric	Result vs Baseline
Gesture Recognition	MediaPipe+CNN	Accuracy	96.2% vs YOLOv8 (95.1%)
Sentence Formation	LSTM-NLP	BLEU	28.4 vs Rule-based (22.1)
Speech Synthesis	Multi-TTS	Latency	185ms vs Festival (320ms)
Real-time	Browser	FPS	25 vs Desktop (18 FPS)

1. Gesture Recognition Metrics:




Fig. 3. Text-to-Speech (TTS) pipeline

- Accuracy: The percentage of correctly classified gestures.
 - Precision and Recall: Metrics indicating exactness and completeness in identifying gesture classes.
 - F1-Score: The harmonic mean of precision and recall.
 - Confusion Matrix: A breakdown of classification errors to identify misclassified gestures.
2. Sentence Formation Metrics (NLP):
- BLEU Score: Similarity between system-generated sentences and reference translations.
 - Grammar Accuracy: Percentage of grammatically correct output sentences.
 - Sequence Completion Rate: The ability to construct complete sentences from partial inputs.
3. Speech Generation Metrics (TTS):
- Latency: Delay between text generation and audio output.
 - Intelligibility: Subjective ratings of speech clarity.
 - Language Accuracy: Verification of correct language/voice selection.
4. System-Level Performance:
- Frame Rate (FPS): Real-time processing capability.
 - Computational Efficiency: CPU/GPU resource utilization.
 - Robustness Testing: Performance under varying lighting and backgrounds.
5. Benchmarking: The system was benchmarked against existing ISL methods and sign-to-speech frameworks. Re-

sults indicate that the landmark-based approach yields superior accuracy for dynamic gestures. The LSTM-NLP module enhances sentence coherence, evidenced by competitive BLEU scores. The system consistently operates with latencies under 200ms and frame rates above 25 FPS, validating its real-time suitability.

VI. CHALLENGES AND LIMITATIONS

While integrating LSTMs and NLP effectively bridges the gap to spoken language, challenges persist. The scarcity of standardized datasets for languages like ISL limits generalization. Furthermore, while performance is strong in controlled settings, robustness degrades in real-world scenarios with poor lighting or occlusion, highlighting the need for adaptive architectures.

VII. CONCLUSION

Sign Language Recognition has matured from simple handcrafted features to sophisticated deep learning models capable of interpreting complex gestures. By supporting multiple languages and offering real-time speech output, this system represents a significant step towards dismantling communication barriers for the Deaf and Hard-of-Hearing community.

References

- [1] B. A. Albahdal and M. A. Al-Hamadi, "Vision-Based Sign Language Recognition Systems: A Review and Open Research Challenges," *Mathematical Problems in Engineering*, vol. 2024, p. 1487500, 2024.
- [2] W. Xue, J. Liu, S. Yan, Y. Zhou, T. Yuan, and Q. Guo, "Alleviating Data Insufficiency for Chinese Sign Language Recognition," *Visual Intelligence*, vol. 1, article 26, 2023.
- [3] H. Xu, Y. Zhang, Z. Yang, H. Yan, and X. Wang, "RF-CSign: A Chinese Sign Language Recognition System Based on Large Kernel Convolution and Normalization-Based Attention," *IEEE Access*, vol. 11, pp. 30712–30725, 2023.
- [4] M. A.-Al-Wadud et al., "Sign Language Recognition with Deep Learning: A Review," *Electronics*, vol. 11, no. 11, p. 1780, 2022.
- [5] Y. Wang, Z. Liang, and H. Zhang, "Multi-Modal Fusion for Sign Language Recognition in Real-Time Applications," *Sensors*, vol. 21, no. 17, p. 5843, 2021.
- [6] S. Z. Gurbuz et al., "American Sign Language Recognition Using RF Sensing," *IEEE Sensors Journal*, vol. 21, no. 3, pp. 3763–3775, 2021.
- [7] S. R. Agarwal, S. B. Agrawal, and A. M. Latif, "Sentence Formation in NLP Engine on the Basis of Indian Sign Language Using Hand Gestures," *Int. J. Adv. Res. Comput. Commun. Eng.*, vol. 10, no. 10, 2021.
- [8] M. Sharma, R. Singh, and S. K. Sahu, "Real-Time Indian Sign Language Recognition Using Deep Learning," *Procedia Computer Science*, vol. 167, pp. 2481–2490, 2020.
- [9] D. Kelly, J. McDonald, and C. Markham, "A Framework for Continuous Multimodal Sign Language Recognition," in *Proc. IEEE ICIP*, 2020, pp. 3105–3109.
- [10] K. K. Tripathi, S. P. Ghrera, and R. Kumar, "Deep Learning-Based Hand Gesture Recognition for Sign Language: A Comprehensive Review," in *Proc. ComPE*, 2020, pp. 217–222.
- [11] E. M. Hurroo and M. Elham, "Sign Language Recognition System Using CNN and Computer Vision," *Int. J. Eng. Res. Technol.*, vol. 9, no. 5, pp. 1234–1240, 2020.
- [12] Y. Yu et al., "Exploration of Chinese Sign Language Recognition Using Wearable Sensors Based on Deep Belief Net," *IEEE J. Biomed. Health Inform.*, vol. 24, no. 5, pp. 1310–1320, 2020.
- [13] M. M. Rahman et al., "RF-Based American Sign Language Recognition," *IEEE Trans. Human-Machine Syst.*, vol. 50, no. 6, pp. 523–535, 2020.

- [14] S. D. Roy, A. Choudhury, and R. Paul, "Indian Sign Language Recognition Using YOLOv3 and CNN," *Procedia Computer Science*, vol. 143, pp. 987–994, 2018.
- [15] M. V. Karthick, S. L. Tripathy, and M. M. Naidu, "Real-Time Sign Language Recognition Using Optimized CNN," in *Proc. ACM Multimedia*, 2018, pp. 1543–1550.
- [16] M. A. A. Dewan, A. A. Hossain, and M. M. Rahman, "Vision-Based Continuous Bangla Sign Language Recognition with HMM," in *Universal Access in Human-Computer Interaction*, 2018, pp. 226–235.
- [17] K. S. Krishnan and S. A. Kumar, "Gesture Recognition in Sign Language Using Convolutional Neural Networks," in *Proc. Int. Conf. Adv. Computing and Applications*, 2017, pp. 55–62.
- [18] R. Rastgoo, K. Nakisa, and M. B. Zadeh, "Sign Language Recognition: A Deep Survey," in *Proc. ICMLC*, 2017, pp. 93–100.
- [19] A. Li, X. Chen, and X. Zhang, "Sign-Component-Based Framework for Chinese Sign Language Recognition Using Accelerometer and sEMG Data," *IEEE Trans. Biomed. Eng.*, vol. 59, no. 1, pp. 1–11, 2012.
- [20] B. Garcia and S. Alarcon, "Real-Time American Sign Language Recognition with Convolutional Neural Networks," *Stanford Univ. Tech. Rep.*, 2016.