

Company 1	Project Name			Logo 2
Close Out Sheet				
PSD-HUC-118	MRU Barge Campaign Post Shutdown Phase CRA			Due Date: 2021-04-10
Activity	Node	Facility	Priority	
		BRG-CPP		
Project Phase			Guideword	
MRU Integration Project Post-Shutdown Phase				
Causes				
<p>1. Unfavourable weather conditions - High winds, heavy rain</p> <p>2. Work duration approaching monsoon season</p>				
Safeguards				
None				
Consequences				
<p>N2 purging operations stopped (unplanned) during adsorbent filling activities</p> <p>Adsorbent - Pyrophoric materials (Puraspec 1178 / 5199) - Self-healing material leading to potential fire</p> <p>- Source of ignition at live platform leading to increased risk of fire and explosion, in event of gas leaks, resulting in personnel injuries / fatalities, major asset and environmental impact.</p>				
Initial risk		Residual Risk		
None		None		
Recommendations/ Actions				
<p>To ensure adequate space is available at site to temporarily store cat cans, in event when filling activity is required to be stopped (unplanned) due to adverse weather conditions or emergency conditions requiring personnel to muster.</p> <p>To then reflect in work pack - designated cat can storage area on MRU Gas / Condensate modules and requirement to move cat can to storage area.</p>				

Response		
None		
Remarks	Actionee	
Attachments		
Organisation	MMHE	Signature: Date:
Disipline and Subdisipline	Commissioning	Signature: Date:
COMPANY COMMENTS		Status
		<input type="checkbox"/> Agree
		<input type="checkbox"/> Agree with comments
		<input type="checkbox"/> Disagree
		<input type="checkbox"/> To be followed
COMPANY Lead Discipline:	Signature:	Date:
COMPANY Lead Safety:	Signature:	Date:
COMPANY Rep (Engineering Coordinator):	Signature:	Date:
<small>The information contained in this document is the proprietary to North Oil Company. It must not be reproduced, stored, disclosed to any third party or used for any purpose not authorized by North Oil Company. Printed documents are uncontrolled and considered as "for information only". Reference should always be made to the on-line EDMS for the updated version</small>		