

Using **plantR** to Manage Animal Taxonomy with the CTFB Backbone

Carlos Eduardo Pinto* Renato A. Ferreira de Lima†

10 dezembro 2025

Contents

| | | |
|-----|---------------------------------------------------------|---|
| 1 | Installing plantR | 1 |
| 2 | A practical example | 2 |
| 3 | Preparing names using <code>fixSpecies()</code> | 2 |
| 3.1 | Internal functions | 3 |
| 4 | Validating taxon names using <code>prepSpecies()</code> | 3 |
| 4.1 | Internal functions | 4 |
| 5 | Validating family names using <code>prepFamily()</code> | 5 |
| 6 | Brief code summary | 5 |
| 7 | Citation | 6 |

1 Installing **plantR**

Install the packages from GitHub if needed and load **plantR**.

```
if (!requireNamespace("remotes"))  
  install.packages("remotes")  
library(remotes)  
  
if (!requireNamespace("plantR"))  
  install_github("LimaRAF/plantR")  
  
if (!requireNamespace("plantRdata"))  
  install_github("LimaRAF/plantRdata")  
  
library(plantR)
```

*Departamento de Ciências Biológicas, ESALQ, Universidade de São Paulo

†Departamento de Ciências Biológicas, ESALQ, Universidade de São Paulo, <https://github.com/LimaRAF>

2 A practical example

We will start with a small list of **names of animal species** that includes common issues (misspellings, synonyms, wrong capitalization, invalid names). We will save it in an objects called **names**:

```
names <- c(
  "Apis mellifera Linnaeus, 1758",      # name accepted with author
  "Apis melifera",                     # misspelling
  "Apis cf. mellifera",                 # open nomenclature
  "Ancyloscelis armatus",               # synonym of Ancyloscelis apiformis (Fabricius, 179
  "Centris aenea",                      # name accepted without author
  "Centris rufa",                       # synonym of Centris aenea Lepeletier, 1841
  "Centris Rhodoprocta Moure & Seabra, 1960", # wrong capitalization
  "Lutjanus purpureus",                 # synonym of Lutjanus campechanus (Poey, 1860)
  "Parotocinclus amazonensis",          # invalid in CTFB; no synonym for this name
  "Panthera onca",                      # name accepted without author
  "Solenopsis bicolor (Emery, 1906)",    # name accepted with author
  "Eucopricus columbi MacLeay, 1819",    # synonym of Sulcophanaeus columbi (MacLeay, 1819)
  "Eucopricus sp.1"                     # incomplete identification
)
```

3 Preparing names using fixSpecies()

`fixSpecies()` formats and cleans names (notation, casing, authorship split, notation flags). It accepts either a character vector or a data frame (default `scientificName` column).

```
names_fixed <- fixSpecies(names)
names_fixed[, -c(2,4)]
```

```
#>      scientificName      scientificName.new
#> 1      Apis mellifera Linnaeus, 1758      Apis mellifera
#> 2      Apis melifera                      Apis melifera
#> 3      Apis cf. mellifera                  Apis mellifera
#> 4      Ancyloscelis armatus                Ancyloscelis armatus
#> 5      Centris aenea                      Centris aenea
#> 6      Centris rufa                      Centris rufa
#> 7      Centris Rhodoprocta Moure & Seabra, 1960      Centris rhodoprocta
#> 8      Lutjanus purpureus                  Lutjanus purpureus
#> 9      Parotocinclus amazonensis          Parotocinclus amazonensis
#> 10     Panthera onca                      Panthera onca
#> 11     Solenopsis bicolor (Emery, 1906)      Solenopsis bicolor
#> 12     Eucopricus columbi MacLeay, 1819      Eucopricus columbi
#> 13     Eucopricus sp.1                    Eucopricus sp.1
#>      scientificNameStatus
#> 1      name_w_authors
#> 2      possibly_ok
#> 3      conferre
#> 4      possibly_ok
#> 5      possibly_ok
#> 6      possibly_ok
#> 7      name_w_wrong_case|name_w_authors
```

```
#> 8                possibly_ok
#> 9                possibly_ok
#> 10               possibly_ok
#> 11               name_w_authors
#> 12               name_w_authors
#> 13               indet
```

3.1 Internal functions

For this specific list, some functions may not change anything (which is fine). The goal is to illustrate correct usage of the internal functions on the **same** input vector of names.

```
fixIndet(names)      # detects undetermined names (e.g., "sp.", "indet")
fixCase(names)       # fixes casing (e.g., "Centris Rhodoprocta")
fixAuthors(names)    # splits taxon and author names, if present
```

4 Validating taxon names using prepSpecies()

Next, validate names against the CTFB backbone (ctfbNames) from plantRdata by loading it into the Global Environment and passing it to db.

```
# load the CTFB backbone (ctfbNames) into the Global Environment
utils::data("ctfbNames", package = "plantRdata")
```

```
# validate against CTFB
names_valid <- prepSpecies(
  names_fixed,
  tax.names = c("scientificName.new", "scientificNameAuthorship.new"),
  db = ctfbNames)
```

```
names_valid[, -c(2,3,4,9,11)]
```

```
#>                scientificName                scientificNameStatus
#> 1      Apis mellifera Linnaeus, 1758                name_w_authors
#> 2                Apis melifera                possibly_ok
#> 3                Apis cf. mellifera                conferre
#> 4      Ancyloscelis armatus                possibly_ok
#> 5                Centris aenea                possibly_ok
#> 6                Centris rufa                possibly_ok
#> 7 Centris Rhodoprocta Moure & Seabra, 1960 name_w_wrong_case|name_w_authors
#> 8                Lutjanus purpureus                possibly_ok
#> 9      Parotocinclus amazonensis                possibly_ok
#> 10               Panthera onca                possibly_ok
#> 11      Solenopsis bicolor (Emery, 1906)                name_w_authors
#> 12      Eucopricus columbi MacLeay, 1819                name_w_authors
#> 13               Eucopricus sp.1                indet
#> suggestedFamily      suggestedName suggestedAuthorship      tax.notes
#> 1      Apidae      Apis mellifera      Linnaeus, 1758      name accepted
#> 2      Apidae      Apis mellifera      Linnaeus, 1758      name misspelled
#> 3      Apidae      Apis mellifera      Linnaeus, 1758      name accepted
```

```

#> 4      Apidae      Ancyloscelis apiformis      (Fabricius, 1793)      replaced synonym
#> 5      Apidae      Centris aenea      Lepeletier, 1841      name accepted
#> 6      Apidae      Centris aenea      Lepeletier, 1841      replaced synonym
#> 7      Apidae      Centris rhodoprocta      Moure & Seabra, 1960      name accepted
#> 8      Lutjanidae    Lutjanus campechanus      (Poey, 1860)      replaced synonym
#> 9      Loricariidae Parotocinclus amazonensis      Garavello, 1977      synonym not replaced
#> 10     Felidae      Panthera onca      (Linnaeus, 1758)      name accepted
#> 11     Formicidae    Solenopsis bicolor      (Emery, 1906)      name accepted
#> 12     Scarabaeidae  Sulcophanaeus columbi      (MacLeay, 1819)      replaced synonym
#> 13     Scarabaeidae  Sulcophanaeus      d'Olsoufieff, 1924      replaced synonym
#>      scientificNameFull
#> 1      Apis mellifera Linnaeus, 1758
#> 2      Apis mellifera Linnaeus, 1758
#> 3      Apis mellifera Linnaeus, 1758
#> 4      Ancyloscelis apiformis (Fabricius, 1793)
#> 5      Centris aenea Lepeletier, 1841
#> 6      Centris aenea Lepeletier, 1841
#> 7      Centris rhodoprocta Moure & Seabra, 1960
#> 8      Lutjanus campechanus (Poey, 1860)
#> 9      Parotocinclus amazonensis Garavello, 1977
#> 10     Panthera onca (Linnaeus, 1758)
#> 11     Solenopsis bicolor (Emery, 1906)
#> 12     Sulcophanaeus columbi (MacLeay, 1819)
#> 13     Sulcophanaeus d'Olsoufieff, 1924

```

Tip 1: for large name lists, consider altering the argument `split.letters`, `parallel`, and `cores`. The minimal fuzzy similarity is controlled by `sug.dist`.

Tip 2: The maximum distance in fuzzy matching (defaults to 10%) is controlled by the argument `sug.dist`.

4.1 Internal functions

`nameMatching()` is the internal function used for exact and fuzzy matching. Below, we demonstrate it using the same names (reference names are the “accepted/standardized” targets):

```

input_names <- c(
  "Apis mellifera Linnaeus, 1758",
  "Apis mellifica",
  "Ancyloscelis apiformis",
  "Centris aenea",
  "Lutjanus purpureus",
  "Parotocinclus amazonensis",
  "Eucopricus columbi MacLeay, 1819"
)

ref_names <- c(
  "Apis mellifera Linnaeus, 1758",
  "Ancyloscelis apiformis (Fabricius, 1793)",
  "Centris aenea",
  "Centris rhodoprocta Moure & Seabra, 1960",
  "Lutjanus campechanus (Poey, 1860)",
  "Panthera onca",

```

```

"Coelonertus baridioides Solari & Solari, 1906",
"Solenopsis bicolor (Emery, 1906)",
"Sulcophanaeus columbi (MacLeay, 1819)"
)

nameMatching(input_names, ref_names)

#> [1] 1 1 2 3 5 NA 9

```

5 Validating family names using prepFamily()

plantR contains an internal dictionary of valid family names which can be used via the function `prepFamily()`. Currently, valid family names are available only for plants. But a similar procedure will be included for animals in the near future. So, for now, the function does not change the input family names.

```

names_valid <- prepFamily(names_valid,
  fam.name = "suggestedFamily",
  spp.name = "scientificName.new",
  kingdom = "animalia",
  db = ctfbNames)

```

6 Brief code summary

A compact two-step workflow (CTFB-only):

```

# 1) Standardize
names_fixed <- fixSpecies(names)

# 2) Validate against the CTFB backbone
utils::data("ctfbNames", package = "plantRdata")
names_valid <- prepSpecies(
  names_fixed,
  tax.names = c("scientificName.new", "scientificNameAuthorship.new"),
  db = ctfbNames
)

names_valid[, c("scientificName.new", "scientificNameFull", "tax.notes")]

```

| #> | scientificName.new | scientificNameFull | tax.notes |
|-------|---------------------------|-------------------------------------------|----------------------|
| #> 1 | Apis mellifera | Apis mellifera Linnaeus, 1758 | name accepted |
| #> 2 | Apis melifera | Apis mellifera Linnaeus, 1758 | name misspelled |
| #> 3 | Apis mellifera | Apis mellifera Linnaeus, 1758 | name accepted |
| #> 4 | Ancyloscelis armatus | Ancyloscelis apiformis (Fabricius, 1793) | replaced synonym |
| #> 5 | Centris aenea | Centris aenea Lepeletier, 1841 | name accepted |
| #> 6 | Centris rufa | Centris aenea Lepeletier, 1841 | replaced synonym |
| #> 7 | Centris rhodoprocta | Centris rhodoprocta Moure & Seabra, 1960 | name accepted |
| #> 8 | Lutjanus purpureus | Lutjanus campechanus (Poey, 1860) | replaced synonym |
| #> 9 | Parotocinclus amazonensis | Parotocinclus amazonensis Garavello, 1977 | synonym not replaced |
| #> 10 | Panthera onca | Panthera onca (Linnaeus, 1758) | name accepted |

| | | | |
|-------|--------------------|---------------------------------------|------------------|
| #> 11 | Solenopsis bicolor | Solenopsis bicolor (Emery, 1906) | name accepted |
| #> 12 | Eucopricus columbi | Sulcophanaeus columbi (MacLeay, 1819) | replaced synonym |
| #> 13 | Eucopricus sp.1 | Sulcophanaeus d'Olsoufieff, 1924 | replaced synonym |

Or, even simpler, using the wrapper `formatTax()`:

```
names_df <- data.frame(scientificName = names)
names_df_valid <- formatTax(names_df,
                             db = ctfbNames,
                             kingdom = "animalia")
```

7 Citation

If you use **plantR**, please cite it as:

Lima, R.A.F., Sánchez-Tapia, A., Mortara, S.R., ter Steege, H., Siqueira, M.F. (2021). *plantR*: An R package and workflow for managing species records from biological collections. *Methods in Ecology and Evolution* 14(2): 332–339. <https://doi.org/10.1101/2021.04.06.437754>

And please also cite the taxonomic backbones that you used:

Boeger, W., & Valim, M. P. (2024). Brazilian Zoology Group 2023 (version 1.1) [Data set]. Zenodo. <https://doi.org/10.5281/zenodo.10498290>