

AVALON HLP 150**HEAVY DUTY HYDRAULIC OIL****DESCRIPTION**

Veedol Avalon HLP 150 is premium grade heavy duty hydraulic oil for use in industrial hydraulic systems which require anti-wear protection.

Veedol Avalon HLP 150 provides good thermal and oxidative stability leading to longer service life.

PERFORMANCE SPECIFICATIONS

Meets & exceeds the performance requirements of

- IS : 11656-1986 (Reaffirmed 1991)
- IS : 10522-1983 (Reaffirmed 1993)
- DIN 51524-2
- Eaton M-2950-S & I-286-S3,
- ISO 11158
- SAE MS 1004
- ASTM D6158

APPLICATIONS

Recommended for high pressure hydraulic systems and also for systems of lightly loaded gears, variable speed units and bearings.

FEATURES/BENEFITS

- Excellent hydrolytic and oxidative stability.
- Outstanding anti-wear protection.
- Excellent rust & corrosion protection.
- Good filterability characteristics.
- Excellent water separability.

CHARACTERISTICS

Test Parameter	Test Method	Typical Value
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	150
Viscosity Index	ASTM D 2270	98
Flash Point, (COC) °C	ASTM D 92	250
Pour Point, °C	ASTM D 97	-12