

Modular Analysis

Joonhyup Lee

April 5, 2024

1 Syntax and Semantics

1.1 Abstract Syntax

Identifiers	x	\in	Var	
Expression	e	\rightarrow	$x \mid \lambda x.e \mid e e$	λ -calculus
			$e \bowtie e$	linked expression
			ε	empty module
			$x = e ; e$	(recursive) binding

Figure 1: Abstract syntax of the language.

1.2 Operational Semantics

Environment	σ	\in	Env	
Location	ℓ	\in	Loc	
de Bruijn Index	n	\in	\mathbb{N}	
Value	v	\in	$\text{Val} \triangleq \text{Env} + \text{Var} \times \text{Expr} \times \text{Env}$	
Weak Value	w	\in	$\text{WVal} \triangleq \text{Val} + \underline{\text{Val}}$	
Environment	σ	\rightarrow	\bullet	empty stack
			$(x, w) :: \sigma$	weak value binding
			$(x, \ell) :: \sigma$	free location binding
			$(x, n) :: \sigma$	bound location binding
Value	v	\rightarrow	σ	exported environment
			$\langle \lambda x.e, \sigma \rangle$	closure
Weak Value	w	\rightarrow	v	value
			$\mu.v$	recursive value

Figure 2: Definition of the semantic domains.

				$\sigma \vdash e \Downarrow v$
ID	RECID	FN	APP	
$\frac{\sigma(x) = v}{\sigma \vdash x \Downarrow v}$	$\frac{\sigma(x) = \mu.v}{\sigma \vdash x \Downarrow v^{\mu.v}}$	$\frac{}{\sigma \vdash \lambda x.e \Downarrow \langle \lambda x.e, \sigma \rangle}$	$\frac{\sigma \vdash e_1 \Downarrow \langle \lambda x.e, \sigma_1 \rangle \quad \sigma \vdash e_2 \Downarrow v_2}{\sigma \vdash e_1 e_2 \Downarrow v}$	
LINK	EMPTY	BIND		
$\frac{\sigma \vdash e_1 \Downarrow \sigma_1 \quad \sigma_1 \vdash e_2 \Downarrow v}{\sigma \vdash e_1 \bowtie e_2 \Downarrow v}$	$\frac{}{\sigma \vdash \varepsilon \Downarrow \bullet}$	$\frac{\ell \notin \text{FLoc}(\sigma) \quad (x, \ell) :: \sigma \vdash e_1 \Downarrow v_1}{\sigma \vdash x = e_1 ; e_2 \Downarrow (x, \mu. \text{\tiny ℓ} v_1) :: \sigma_2}$		

Figure 3: The big-step operational semantics.

We use the locally nameless representation, and enforce that all values be *locally closed*. As a consequence, the big-step operational semantics will be *deterministic*, no matter what ℓ is chosen in the Bind rule.

1.3 Reconciling with Conventional Backpatching

Environment	σ	\in	$\text{MEnv} \triangleq \text{Var} \xrightarrow{\text{fin}} \text{Loc}$	
Memory	m	\in	$\text{Mem} \triangleq \text{Loc} \xrightarrow{\text{fin}} \text{MVal}$	
Allocated set	L	\subseteq	Loc	
Value	v	\in	$\text{MVal} \triangleq \text{MEnv} + \text{Var} \times \text{Expr} \times \text{MEnv}$	
Environment	σ	\rightarrow	\bullet	empty stack
			$(x, \ell) :: \sigma$	location binding
Value	v	\rightarrow	σ	exported environment
			$\langle \lambda x.e, \sigma \rangle$	closure

Figure 4: Definition of the semantic domains with memory.

$\sigma, m, L \vdash e \Downarrow v, m', L'$

$$\begin{array}{c}
 \text{ID} \\
 \frac{\sigma(x) = \ell \quad m(\ell) = v}{\sigma, m, L \vdash x \Downarrow v, m, L} \quad \text{FN} \quad \frac{}{\sigma, m, L \vdash \lambda x.e \Downarrow \langle \lambda x.e, \sigma \rangle, m, L} \\
 \\
 \text{APP} \\
 \frac{\sigma, m, L \vdash e_1 \Downarrow \langle \lambda x.e, \sigma_1 \rangle, m_1, L_1 \quad \sigma, m_1, L_1 \vdash e_2 \Downarrow v_2, m_2, L_2 \quad \ell \notin \text{dom}(m_2) \cup L_2 \quad (x, \ell) :: \sigma_1, m_2[\ell \mapsto v_2], L_2 \vdash e \Downarrow v, m', L'}{\sigma, m, L \vdash e_1 e_2 \Downarrow v, m', L'} \\
 \\
 \text{LINK} \quad \frac{\sigma, m, L \vdash e_1 \Downarrow \sigma_1, m_1, L_1 \quad \sigma_1, m_1, L_1 \vdash e_2 \Downarrow v, m', L'}{\sigma, m, L \vdash e_1 \bowtie e_2 \Downarrow v, m', L'} \quad \text{EMPTY} \quad \frac{}{\sigma, m, L \vdash \varepsilon \Downarrow \bullet, m, L} \\
 \\
 \text{BIND} \\
 \frac{\ell \notin \text{dom}(m) \cup L \quad (x, \ell) :: \sigma, m, L \cup \{\ell\} \vdash e_1 \Downarrow v_1, m_1, L_1 \quad (x, \ell) :: \sigma, m_1[\ell \mapsto v_1], L_1 \vdash e_2 \Downarrow \sigma_2, m', L'}{\sigma, m, L \vdash x = e_1; e_2 \Downarrow (x, \ell) :: \sigma_2, m', L'}
 \end{array}$$

Figure 5: The big-step operational semantics with memory.

$w \sim_f v, m$

$$\begin{array}{c}
 \text{EQ-NIL} \quad \frac{}{\bullet \sim_f \bullet} \quad \text{EQ-CONSFREE} \quad \frac{\ell \notin \text{dom}(f) \quad \ell \notin \text{dom}(m) \quad \sigma \sim_f \sigma'}{(x, \ell) :: \sigma \sim_f (x, \ell) :: \sigma'} \quad \text{EQ-CONSBIND} \quad \frac{f(\ell) = \ell' \quad \ell' \in \text{dom}(m) \quad \sigma \sim_f \sigma'}{(x, \ell) :: \sigma \sim_f (x, \ell') :: \sigma'} \\
 \\
 \text{EQ-CONSWVAL} \quad \frac{m(\ell') = v' \quad w \sim_f v' \quad \sigma \sim_f \sigma'}{(x, w) :: \sigma \sim_f (x, \ell') :: \sigma'} \quad \text{EQ-CLOS} \quad \frac{\sigma \sim_f \sigma'}{\langle \lambda x.e, \sigma \rangle \sim_f \langle \lambda x.e, \sigma' \rangle} \quad \text{EQ-REC} \quad \frac{L \text{ finite} \quad m(\ell') = v' \quad \forall \ell \notin L, v^\ell \sim_{f[\ell \mapsto \ell']} v'}{\mu.v \sim_f v'}
 \end{array}$$

Figure 6: The equivalence relation between weak values in the original semantics and values in the semantics with memory. $f \in \text{Loc} \xrightarrow{\text{fin}} \text{Loc}$ tells what the free locations in w that were *opened* should be mapped to in memory. m is omitted for brevity.

The semantics in Figure 3 makes sense due to similarity with a conventional backpatching semantics as presented in Figure 5. We have defined a relation \sim that satisfies:

$$\sim \subseteq \text{WVal} \times (\text{MVal} \times \text{Mem} \times \mathcal{P}(\text{Loc})) \quad \bullet \sim (\bullet, \emptyset, \emptyset)$$

and the following theorem:

Theorem 1.1 (Equivalence of semantics). For all $\sigma \in \text{Env}, \sigma' \in \text{MEnv} \times \text{Mem} \times \mathcal{P}(\text{Loc}), v \in \text{Val}, v' \in \text{MVal} \times \text{Mem} \times \mathcal{P}(\text{Loc})$, we have:

$$\begin{aligned} \sigma \sim \sigma' \text{ and } \sigma \vdash e \Downarrow v &\Rightarrow \exists v' : v \sim v' \text{ and } \sigma' \vdash e \Downarrow v' \\ \sigma \sim \sigma' \text{ and } \sigma' \vdash e \Downarrow v' &\Rightarrow \exists v : v \sim v' \text{ and } \sigma \vdash e \Downarrow v \end{aligned}$$

The definition for $w \sim (\sigma, m, L)$ is:

$$w \sim_{\perp} (\sigma, m) \text{ and } \text{FLoc}(w) \subseteq L$$

where the definition for \sim_f is given in Figure 6.

The proof of Theorem 1.1 uses some useful lemmas, such as:

Lemma 1.1 (Free locations not in f are free in memory).

$$w \sim_f v', m \Rightarrow m|_{\text{FLoc}(w) - \text{dom}(f)} = \perp$$

Lemma 1.2 (Equivalence is preserved by extension of memory).

$$w \sim_f v', m \text{ and } m \sqsubseteq m' \text{ and } m'|_{\text{FLoc}(w) - \text{dom}(f)} = \perp \Rightarrow w \sim_f v', m$$

Lemma 1.3 (Equivalence only cares about f on free locations).

$$w \sim_f v', m \text{ and } f|_{\text{FLoc}(w)} = f'|_{\text{FLoc}(w)} \Rightarrow w \sim_{f'} v', m$$

Lemma 1.4 (Extending equivalence on free locations).

$$w \sim_f v', m \text{ and } \ell \notin \text{dom}(f) \text{ and } \ell \notin \text{dom}(m) \Rightarrow \forall u', w \sim_{f[\ell \mapsto \ell]} v', m[\ell \mapsto u']$$

Lemma 1.5 (Substitution of values).

$$w \sim_f v', m \text{ and } f(\ell) = \ell' \text{ and } m(\ell') = u' \text{ and } u \sim_{f-\ell} u', m \Rightarrow w[u/\ell] \sim_{f-\ell} v', m$$

Lemma 1.6 (Substitution of locations).

$$w \sim_f v', m \text{ and } \ell \in \text{dom}(f) \text{ and } \nu \notin \text{FLoc}(w) \Rightarrow w[\nu/\ell] \sim_{f \circ (\nu \leftrightarrow \ell)} v', m$$

2 Generating and Resolving Events

Now we formulate the semantics for generating events.

Event	E	\rightarrow	Init	initial environment
			Read(E, x)	read event
			Call(E, v)	call event
Environment	σ	\rightarrow	...	
			[E]	answer to an event
Value	v	\rightarrow	...	
			E	answer to an event

Figure 7: Definition of the semantic domains with events. All other semantic domains are equal to Figure 2.

We extend how to read weak values given an environment.

$$\begin{aligned} \bullet(x) &\triangleq \perp & ((x', \ell) :: \sigma)(x) &\triangleq (x = x'?\ell : \sigma(x)) \\ [E](x) &\triangleq \text{Read}(E, x) & ((x', w) :: \sigma)(x) &\triangleq (x = x'?w : \sigma(x)) \end{aligned}$$

Then we need to add only one rule to the semantics in Figure 3 for the semantics to incorporate events.

$$\frac{\text{APPEVENT} \quad \sigma \vdash e_1 \Downarrow E \quad \sigma \vdash e_2 \Downarrow v}{\sigma \vdash e_1 e_2 \Downarrow \text{Call}(E, v)}$$

Now we need to formulate the *concrete linking* rules. The concrete linking rule $\sigma_0 \times w$, given an answer σ_0 to the Init event, resolves all events within w to obtain a set of final results.

Concrete linking makes sense because of the following theorem. First define:

$$\text{eval}(e, \sigma) \triangleq \{v \mid \sigma \vdash e \Downarrow v\} \quad \text{eval}(e, \Sigma) \triangleq \bigcup_{\sigma \in \Sigma} \text{eval}(e, \sigma) \quad \sigma_0 \times W \triangleq \bigcup_{w \in W} (\sigma_0 \times w)$$

Then the following holds:

$$\begin{array}{c}
\boxed{\times \in \text{Env} \rightarrow \text{Event} \rightarrow \mathcal{P}(\text{Val})} \\
\sigma_0 \times \text{Init} \triangleq \{\sigma_0\} \\
\sigma_0 \times \text{Read}(E, x) \triangleq \{v_+ | \sigma_+ \in \sigma_0 \times E \wedge \sigma_+(x) = v_+\} \\
\quad \cup \{v_+^{\mu.v_+} | \sigma_+ \in \sigma_0 \times E \wedge \sigma_+(x) = \mu.v_+\} \\
\sigma_0 \times \text{Call}(E, v) \triangleq \{v'_+ | \langle \lambda x.e, \sigma_+ \rangle \in \sigma_0 \times E \wedge v_+ \in \sigma_0 \times v \wedge (x, v_+) :: \sigma_+ \vdash e \Downarrow v'_+\} \\
\quad \cup \{\text{Call}(E_+, v_+) | E_+ \in \sigma_0 \times E \wedge v_+ \in \sigma_0 \times v\} \\
\boxed{\times \in \text{Env} \rightarrow \text{Env} \rightarrow \mathcal{P}(\text{Env})} \\
\sigma_0 \times \bullet \triangleq \{\bullet\} \\
\sigma_0 \times (x, \ell) :: \sigma \triangleq \{(x, \ell) :: \sigma_+ | \sigma_+ \in \sigma_0 \times \sigma\} \\
\sigma_0 \times (x, w) :: \sigma \triangleq \{(x, w_+) :: \sigma_+ | w_+ \in \sigma_0 \times w \wedge \sigma_+ \in \sigma_0 \times \sigma\} \\
\sigma_0 \times [E] \triangleq \{\sigma_+ | \sigma_+ \in \sigma_0 \times E\} \cup \{[E_+] | E_+ \in \sigma_0 \times E\} \\
\boxed{\times \in \text{Env} \rightarrow \text{Val} \rightarrow \mathcal{P}(\text{Val})} \\
\sigma_0 \times \langle \lambda x.e, \sigma \rangle \triangleq \{\langle \lambda x.e, \sigma_+ \rangle | \sigma_+ \in \sigma_0 \times \sigma\} \\
\boxed{\times \in \text{Env} \rightarrow \text{WVal} \rightarrow \mathcal{P}(\text{WVal})} \\
\sigma_0 \times \mu.v \triangleq \{\mu. \setminus^\ell v_+ | \ell \notin \text{FLoc}(v) \cup \text{FLoc}(\sigma_0) \wedge v_+ \in \sigma_0 \times v^\ell\}
\end{array}$$

Figure 8: Definition for concrete linking.

Theorem 2.1 (Soundness of concrete linking). Given $e \in \text{Expr}, \sigma \in \text{Env}, v \in \text{Val}$,

$$\forall \sigma_0 \in \text{Env} : \text{eval}(e, \sigma_0 \times \sigma) \subseteq \sigma_0 \times \text{eval}(e, \sigma)$$

The proof of Theorem 2.1 uses some useful lemmas, such as:

Lemma 2.1 (Linking distributes under substitution). Let σ_0 be the external environment that is linked with locally closed weak values w and u . For all $\ell \notin \text{FLoc}(\sigma_0)$, we have:

$$\forall w_+, u_+ : w_+ \in \sigma_0 \times w \wedge u_+ \in \sigma_0 \times u \Rightarrow \{u_+ \leftarrow \ell\} w_+ \in \sigma_0 \times \{u \leftarrow \ell\} w$$

Lemma 2.2 (Linking is compatible with reads). Let σ_0 be the external environment that is linked with some environment σ . Let v be the value obtained from reading x from σ . Let $\text{unfold} : \text{WVal} \rightarrow \text{Val}$ be defined as:

$$\text{unfold}(\mu.v) \triangleq v^{\mu.v} \quad \text{unfold}(v) \triangleq v$$

Then for all $\sigma_+ \in \sigma_0 \times \sigma$, we have:

$$\exists w_+ \in \text{WVal} : \sigma_+(x) = w_+ \wedge \text{unfold}(w_+) \in \sigma_0 \times v$$

3 CFA

Program point	p	\in	$\mathbb{P} \triangleq \{\text{finite set of program points}\}$
Labelled expression	pe	\in	$\mathbb{P} \times \text{Expr}$
Labelled location	ℓ^p	\in	$\mathbb{P} \times \text{Loc}$
Collecting semantics	t	\in	$\mathbb{T} \triangleq \mathbb{P} \rightarrow \mathcal{P}(\text{Env} + \text{Env} \times \text{Val})$
Labelled expression	pe	\rightarrow	$\{p : e\}$
Expression	e	\rightarrow	$x \mid \lambda x. pe \mid pe \mid pe \times pe \mid \varepsilon \mid x = pe; pe$

Step : $\mathbb{T} \rightarrow \mathbb{T}$

$$\text{Step}(t) \triangleq \bigcup_{p \in \mathbb{P}} \text{step}(t, p)$$

step : $(\mathbb{T} \times \mathbb{P}) \rightarrow \mathbb{T}$

$$\begin{aligned}
\text{step}(t, p) &\triangleq [p \mapsto \{(\sigma, v) \mid \sigma \in t(p) \text{ and } \sigma(x) = v\}] && \text{when } \{p : x\} \\
&\cup [p \mapsto \{(\sigma, v^{\mu.v}) \mid \sigma \in t(p) \text{ and } \sigma(x) = \mu.v\}] \\
\text{step}(t, p) &\triangleq [p \mapsto \{(\sigma, \langle \lambda x. p', \sigma \rangle) \mid \sigma \in t(p)\}] && \text{when } \{p : \lambda x. p'\} \\
\text{step}(t, p) &\triangleq [p_1 \mapsto \{\sigma \in \text{Env} \mid \sigma \in t(p)\}] && \text{when } \{p : p_1 \ p_2\} \\
&\cup [p_2 \mapsto \{\sigma \in \text{Env} \mid \sigma \in t(p)\}] \\
&\cup \bigcup_{\sigma \in t(p)} \bigcup_{(\sigma, \langle \lambda x. p', \sigma_1 \rangle) \in t(p_1)} [p' \mapsto \{(x, v_2) :: \sigma_1 \mid (\sigma, v_2) \in t(p_2)\}] \\
&\cup [p \mapsto \bigcup_{\sigma \in t(p)} \bigcup_{(\sigma, \langle \lambda x. p', \sigma_1 \rangle) \in t(p_1)} \bigcup_{(\sigma, v_2) \in t(p_2)} \{(\sigma, v) \mid ((x, v_2) :: \sigma_1, v) \in t(p')\}] \\
&\cup [p \mapsto \bigcup_{\sigma \in t(p)} \{(\sigma, \text{Call}(E_1, v_2)) \mid (\sigma, E_1) \in t(p_1) \text{ and } (\sigma, v_2) \in t(p_2)\}] \\
\text{step}(t, p) &\triangleq [p_1 \mapsto \{\sigma \mid \sigma \in t(p)\}] && \text{when } \{p : p_1 \times p_2\} \\
&\cup [p_2 \mapsto \bigcup_{\sigma \in t(p)} \{\sigma_1 \mid (\sigma, \sigma_1) \in t(p_1)\}] \\
&\cup [p \mapsto \bigcup_{\sigma \in t(p)} \bigcup_{(\sigma, \sigma_1) \in t(p_1)} \{(\sigma, v_2) \mid (\sigma_1, v_2) \in t(p_2)\}] \\
\text{step}(t, p) &\triangleq [p \mapsto \{(\sigma, \bullet) \mid \sigma \in t(p)\}] && \text{when } \{p : \varepsilon\} \\
\text{step}(t, p) &\triangleq [p_1 \mapsto \bigcup_{\sigma \in t(p)} \{(x, \ell^{p_1}) :: \sigma \mid \ell \notin \text{FLoc}(\sigma)\}] && \text{when } \{p : x = p_1; p_2\} \\
&\cup [p_2 \mapsto \bigcup_{\sigma \in t(p)} \{(x, \mu. \ell^{p_1} v_1) :: \sigma \mid ((x, \ell^{p_1}) :: \sigma, v_1) \in t(p_1)\}] \\
&\cup [p \mapsto \bigcup_{\sigma \in t(p)} \bigcup_{((x, \ell^{p_1}) :: \sigma, v_1) \in t(p_1)} \{(\sigma, (x, \mu. \ell^{p_1} v_1) :: \sigma_2) \mid ((x, \mu. \ell^{p_1} v_1) :: \sigma, \sigma_2) \in t(p_2)\}]
\end{aligned}$$

The proof tree t computed by

$$t \triangleq \text{lfp}(\lambda t. \text{Step}(t) \cup t_{\text{init}}) \quad \text{where } t_{\text{init}} = [p_0 \mapsto \{\sigma_0\}]$$

contains all derivations of the form $\sigma_0 \vdash p_0 \Downarrow v_0$ for some v_0 . That is, (σ, v) is contained in $t_0(p)$ if and only if $\sigma \vdash p \Downarrow v$ must be contained in a valid derivation for the judgment $\sigma_0 \vdash p_0 \Downarrow v_0$.

Abstract event	$E^\#$	\in	$\text{Event}^\#$
Abstract environment	$\sigma^\#$	\in	$\text{Env}^\# \triangleq (\text{Var} \xrightarrow{\text{fin}} \mathcal{P}(\mathbb{P})) \times \mathcal{P}(\text{Event}^\#)$
Abstract closure	$\langle \lambda x. p, p' \rangle$	\in	$\text{Clos}^\# \triangleq \text{Var} \times \mathbb{P} \times \mathbb{P}$
Abstract value	$v^\#$	\in	$\text{Val}^\# \triangleq \text{Env}^\# \times \mathcal{P}(\text{Clos}^\#)$
Abstract semantics	$t^\#$	\in	$\mathbb{T}^\# \triangleq \mathbb{P} \rightarrow \text{Env}^\# \times \text{Val}^\#$
Abstract event	$E^\#$	\rightarrow	$\text{Init}^\# \mid \text{Read}^\#(p, x) \mid \text{Call}^\#(p, p)$

The concretization function γ that sends an element of $\mathbb{T}^\#$ to \mathbb{T} is defined as:

$$\gamma(t^\#) \triangleq \lambda p. \{\sigma \mid \sigma \leq (t^\#(p).1, t^\#)\} \cup \{(\sigma, v) \mid v \leq (t^\#(p).2, t^\#)\}$$

where \leq is the concretization relation that is inductively defined in Figure 9.

$\sigma \leq_f (\sigma^\#, t^\#)$

$\frac{\text{CONC-NIL}}{\bullet \leq \sigma^\#}$	$\frac{\text{CONC-ENIL}}{E \leq (\sigma^\#, \emptyset)} \quad [E] \leq \sigma^\#$	$\frac{\text{CONC-CONSLOC}}{p \in \sigma^\#.1(x) \quad \sigma \leq \sigma^\#} \quad (x, \ell^p) :: \sigma \leq \sigma^\#$	$\frac{\text{CONC-CONSWVAL}}{p \in \sigma^\#.1(x) \quad w \leq t^\#(p).2 \quad \sigma \leq \sigma^\#} \quad (x, w) :: \sigma \leq \sigma^\#$
--	---	---	--

$w \leq (v^\#, t^\#)$

$\frac{\text{CONC-CLOS}}{\langle \lambda x.p, p' \rangle \in v^\#.2 \quad \sigma \leq t^\#(p').1} \quad \langle \lambda x.p, \sigma \rangle \leq v^\#$	$\frac{\text{CONC-REC}}{L \text{ finite} \quad \forall \ell \notin L, v^{\ell^p} \leq t^\#(p).2 \text{ and } v^{\ell^p} \leq v^\#} \quad \mu.v \leq v^\#$
--	---

$\frac{\text{CONC-INIT}}{\text{Init}^\# \in v^\#.1.2} \quad \text{Init} \leq v^\#$	$\frac{\text{CONC-READ}}{\text{Read}^\#(p, x) \in v^\#.1.2 \quad [E] \leq t^\#(p).1} \quad \text{Read}(E, x) \leq v^\#$	$\frac{\text{CONC-CALL}}{\text{Call}^\#(p_1, p_2) \in v^\#.1.2 \quad E \leq t^\#(p_1).2 \quad v \leq t^\#(p_2).2} \quad \text{Call}(E, v) \leq v^\#$
--	---	--

Figure 9: The concretization relation between weak values and abstract values. $t^\#$ is omitted.

Now the abstract semantic function can be given.

$\text{Step}^\# : \mathbb{T}^\# \rightarrow \mathbb{T}^\#$

$$\text{Step}^\#(t^\#) \triangleq \bigsqcup_{p \in \mathbb{P}} \text{step}^\#(t^\#, p)$$

$\text{step}^\# : (\mathbb{T}^\# \times \mathbb{P}) \rightarrow \mathbb{T}^\#$

$$\begin{aligned} \text{step}^\#(t^\#, p) &\triangleq [p \mapsto \bigsqcup_{p' \in t^\#(p).1.1(x)} (\perp, t^\#(p').2)] && \text{when } \{p : x\} \\ &\sqcup [p \mapsto (\perp, ([], \{\text{Read}^\#(p, x)\}, \emptyset))] && \text{if } t^\#(p).1.2 \neq \emptyset \\ \text{step}^\#(t^\#, p) &\triangleq [p \mapsto (\perp, (\perp, \{\langle \lambda x.p', p \rangle\}))] && \text{when } \{p : \lambda x.p'\} \\ \text{step}^\#(t^\#, p) &\triangleq [p_1 \mapsto (t^\#(p).1, \perp)] && \text{when } \{p : p_1 p_2\} \\ &\sqcup [p_2 \mapsto (t^\#(p).1, \perp)] \\ &\sqcup \bigsqcup_{\langle \lambda x.p', p'' \rangle \in t^\#(p_1).2.2} [p' \mapsto (t^\#(p'').1 \sqcup ([x \mapsto \{p_2\}], \emptyset), \perp)] \\ &\sqcup [p \mapsto \bigsqcup_{\langle \lambda x.p', _ \rangle \in t^\#(p_1).2.2} (\perp, t^\#(p').2)] \\ &\sqcup [p \mapsto (\perp, ([], \{\text{Call}^\#(p_1, p_2)\}, \emptyset))] && \text{if } t^\#(p_1).2.1.2 \neq \emptyset \\ \text{step}^\#(t^\#, p) &\triangleq [p_1 \mapsto (t^\#(p).1, \perp)] && \text{when } \{p : p_1 \bowtie p_2\} \\ &\sqcup [p_2 \mapsto (t^\#(p_1).2.1, \perp)] \\ &\sqcup [p \mapsto (\perp, t^\#(p_2).2)] \\ \text{step}^\#(t^\#, p) &\triangleq \perp && \text{when } \{p : \varepsilon\} \\ \text{step}^\#(t^\#, p) &\triangleq [p_1 \mapsto (t^\#(p).1 \sqcup ([x \mapsto \{p_1\}], \emptyset), \perp)] && \text{when } \{p : x = p_1; p_2\} \\ &\sqcup [p_2 \mapsto (t^\#(p).1 \sqcup ([x \mapsto \{p_1\}], \emptyset), \perp)] \\ &\sqcup [p \mapsto (\perp, (t^\#(p_2).2.1 \sqcup ([x \mapsto \{p_1\}], \emptyset), \emptyset))] \end{aligned}$$

The abstract proof tree $t^\#$ computed by

$$t^\# \triangleq \text{lfp}(\lambda t^\#. \text{Step}^\#(t^\#) \sqcup t_{\text{init}}^\#) \quad \text{where } t_{\text{init}} \subseteq \gamma(t_{\text{init}}^\#)$$

is a sound abstraction of t .

Now we define a sound linking operator that abstracts \bowtie . Assume we have

$$\sigma_0 \leq (\sigma_0^\#, t_0^\#) \quad t \subseteq \gamma(t^\#)$$

we define:

$$\sigma_0 \bowtie t \triangleq \lambda p. (\sigma_0 \bowtie t(p))$$

We want to define $\times^\#$ so that the following holds:

$$\sigma_0 \times t \subseteq \gamma((\sigma_0^\#, t_0^\#) \times^\# t^\#)$$

This is defined by

$$(\sigma_0^\#, t_0^\#) \times^\# t^\# \triangleq \text{lfp}(\lambda t_+^\#. \text{Step}^\#(t_+^\#) \sqcup \text{Link}^\#(\sigma_0^\#, \mathbf{E}(t^\#), t_+^\#) \sqcup t_0^\# \sqcup \mathbf{V}(t^\#))$$

where

$$\mathbf{E}(t^\#) \in \mathbb{P} \rightarrow \mathcal{P}(\text{Event}^\#)^2 \quad \mathbf{V}(t^\#) \in \mathbb{T}^\# \quad \text{Link}^\#(\sigma^\#, \mathcal{E}, t^\#) \in \mathbb{T}^\#$$

are defined by

$$\mathbf{E}(t^\#) \triangleq \lambda p. (t^\#(p).1.2, t^\#(p).2.1.2) \quad \mathbf{V}(t^\#) \triangleq \lambda p. ((t^\#(p).1.1, \emptyset), ((t^\#(p).2.1.1, \emptyset), t^\#(p).2.2))$$

and

$$\text{Link}^\#(\sigma^\#, \mathcal{E}, t^\#) \triangleq \bigsqcup_{E^\# \in \mathcal{E}(p).1} \text{link}_1^\#(\sigma^\#, E^\#, t^\#, p) \sqcup \bigsqcup_{E^\# \in \mathcal{E}(p).2} \text{link}_2^\#(\sigma^\#, E^\#, t^\#, p)$$

where

$$\text{link}_1^\#(\sigma^\#, E^\#, t^\#, p) \in \mathbb{T}^\# \quad \text{link}_2^\#(\sigma^\#, E^\#, t^\#, p) \in \mathbb{T}^\#$$

are defined by

$$\begin{aligned} \text{link}_1^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq [p \mapsto (\sigma^\#, \perp)] && \text{when } E^\# = \text{Init}^\# \\ \text{link}_1^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq [p \mapsto \bigsqcup_{p'' \in t^\#(p').1.1(x)} (t^\#(p'').2.1, \perp)] && \text{when } E^\# = \text{Read}^\#(p', x) \\ &\sqcup [p \mapsto (([], \{\text{Read}^\#(p, x)\}), \perp)] && \text{if } t^\#(p).1.2 \neq \emptyset \\ \text{link}_1^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq \bigsqcup_{\langle \lambda x.p', p'' \rangle \in t^\#(p_1).2.2} [p' \mapsto (t^\#(p'').1 \sqcup ([x \mapsto \{p_2\}], \emptyset), \perp)] && \text{when } E^\# = \text{Call}^\#(p_1, p_2) \\ &\sqcup [p \mapsto \bigsqcup_{\langle \lambda x.p', _ \rangle \in t^\#(p_1).2.2} (t^\#(p').2.1, \perp)] \\ &\sqcup [p \mapsto (([], \{\text{Call}^\#(p_1, p_2)\}), \perp)] && \text{if } t^\#(p_1).2.1.2 \neq \emptyset \\ \text{link}_2^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq [p \mapsto (\perp, (\sigma^\#, \emptyset))] && \text{when } E^\# = \text{Init}^\# \\ \text{link}_2^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq [p \mapsto \bigsqcup_{p'' \in t^\#(p').1.1(x)} (\perp, t^\#(p'').2)] && \text{when } E^\# = \text{Read}^\#(p', x) \\ &\sqcup [p \mapsto (\perp, (([], \{\text{Read}^\#(p, x)\}), \emptyset))] && \text{if } t^\#(p).1.2 \neq \emptyset \\ \text{link}_2^\#(\sigma^\#, E^\#, t^\#, p) &\triangleq \bigsqcup_{\langle \lambda x.p', p'' \rangle \in t^\#(p_1).2.2} [p' \mapsto (t^\#(p'').1 \sqcup ([x \mapsto \{p_2\}], \emptyset), \perp)] && \text{when } E^\# = \text{Call}^\#(p_1, p_2) \\ &\sqcup [p \mapsto \bigsqcup_{\langle \lambda x.p', _ \rangle \in t^\#(p_1).2.2} (\perp, t^\#(p').2)] \\ &\sqcup [p \mapsto (\perp, (([], \{\text{Call}^\#(p_1, p_2)\}), \emptyset))] && \text{if } t^\#(p_1).2.1.2 \neq \emptyset \end{aligned}$$

Lemma 3.1 (Substitution of values).

$$w \leq (v^\#, t^\#) \text{ and } u \leq (t^\#(p).2, t^\#) \Rightarrow w[u/\ell^p] \leq (v^\#, t^\#)$$

Lemma 3.2 (Sound step[#]).

$$\forall p, t, t^\# : t \subseteq \gamma(t^\#) \Rightarrow \text{step}(t, p) \cup t \subseteq \gamma(\text{step}^\#(t^\#, p) \sqcup t^\#)$$

Lemma 3.3 (Sound Step[#]).

$$\forall t_{\text{init}}, t^\# : t_{\text{init}} \subseteq \gamma(t^\#) \text{ and } \text{Step}^\#(t^\#) \sqsubseteq t^\# \Rightarrow \text{lfp}(\lambda t. \text{Step}(t) \cup t_{\text{init}}) \subseteq \gamma(t^\#)$$

Lemma 3.4 (Sound Link[#]). For each $\sigma_0, \sigma_0^\#, t_0^\#, t, t^\#, t_+^\#$, if:

1. $\sigma_0 \leq (\sigma_0^\#, t_0^\#)$
2. $t \subseteq \gamma(t^\#)$
3. $\text{Step}^\#(t_+^\#) \sqcup \text{Link}^\#(\sigma_0^\#, \mathbf{E}(t^\#), t_+^\#) \sqcup t_0^\# \sqcup \mathbf{V}(t^\#) \sqsubseteq t_+^\#$

we have:

$$\forall w, w_+ \in \sigma_0 \times w, p : [w \in t(p) \Rightarrow w_+ \leq (t_+^\#(p).1, t_+^\#)] \text{ and } [(_, w) \in t(p) \Rightarrow w_+ \leq (t_+^\#(p).2, t_+^\#)]$$