

WR-90 flexible waveguide

The WR-90 flexible waveguide (R100 · WG16) covers 8.2–12.5 GHz. We build it twistable and seamless, with the flanges and length you need.

SIZE DATA

Operating band	8.2–12.5 GHz
Designations	WR-90 · R100 · WG16
Inner section a × b	22.86 × 10.16 mm
Code	TLFX-100
Overall A × B	27.9 × 13.8 mm
Corrugation root C × D	23.9 × 9.4 mm
Pitch P	2.0 mm
Tolerance	± 0.20 mm
Standard length	300 · 600 · 900 · 1,000 · 1,200 mm
Material	Brass OT 80 UNI 4897

Inner section a × b: standard EIA values. The other dimensions come from the Tecnolambro dimension table.

ELECTRICAL DATA · TWISTABLE

Return loss 300 mm	28.3 dB
Return loss 600 mm	26.4 dB
Return loss 1000 mm	25.7 dB
Attenuation	0.42 dB/m
CW power	1,000 W
Peak power	210 kW

ELECTRICAL DATA · SEAMLESS

VSWR 600 mm	1.07
Attenuation	0.30 dB/m
CW power	3,000 W
Peak power	180 kW


FLANGES

UBR100

PBR100

PDR100

TECHNICAL DRAWING



Indicative data: final values are stated in the quote.

Request a quote: tecnolambro.it/shop · +39 375 577 1084

Tecnolambro S.a.s. di Pasquini Marco & C. · Via degli Spinedi 20, 27010 Miradolo Terme (PV) · info@tecnolambro.it · +39 375 577 1084

ISO 9001:2015 · ISO 14001:2015



Size page