

Course project

Kim Hammar

7 dec 2015

Revision History

Revision	Date	Author(s)	Description
0.1	07.12.15	KH	First draft
0.2	13.12.15	KH	Error correction

Contents

1	Abstract	3
2	Task specification	4
2.1	Sub-assignment 1. A Single-User Information System for NOG	4
2.2	Sub-assignment 2. A Multi-User Information System for NOG	4
2.3	Sub-assignment 3. Chat Rooms for NOG	4
3	Platform	5
4	Software and technologies used	5
5	The application	6
5.1	Sub-assignment 1. A Single-User Information System for NOG	6
5.1.1	Functionality	6
5.1.2	Protocols used	6
5.1.3	GUI	6
5.1.4	Architecture	10
5.1.5	Load-testing	10
5.2	Sub-assignment 2. A Multi-User Information System for NOG	13
5.2.1	Functionality	13
5.2.2	Protocols used	14
5.2.3	GUI	14
5.2.4	Architecture	15
5.2.5	Load-testing	15
5.3	Sub-assignment 3. Chat Rooms for NOG	17
5.3.1	Functionality	17
5.3.2	Protocols used	17
5.3.3	GUI	18
5.3.4	Architecture	21
6	Documentation	21

1 Abstract

Course project in a course on Network programming in Java [1], carried out at Royal Institute of Technology, Stockholm.

2 Task specification

You are “hired” by JEM inc (Java Enterprise Microsystems Inc.) to design and develop the distributed application software (clients and servers) for the NOG (Nordic Olympic Games) event.

The NOG information system should allow storing, retrieving and updating personal information about NOG participants. The system should also be able to provide statistical information about participants. The system is to be developed in two version(1) a single-user version; (2) a multi-user version. You should also develop a NOG virtual meeting place. The NOG virtual meeting place is Internet based software which offers remotely located users to communicate and share information represented as textual, image or audio files.

2.1 Sub-assignment 1. A Single-User Information System for NOG

Develop a distributed application in Java that allows storing, retrieving and updating information about participants of NOG. The application should consist of a client with a user interface and a server. In this assignment we assume a **single user** semantics for the application, i.e It's not required to support coherency of multiple copies of participant records which may be cached by multiple client at the same time.

2.2 Sub-assignment 2. A Multi-User Information System for NOG

Develop a multi-user application, similar to the solution developed in sub-assignment 1. In this version a multi-user semantic is required. Many users can fetch the participants-data at the same time and when one user updates his local-cache of the data, the change need to be replicated among all clients connected in order to prevent them from using stale data.

2.3 Sub-assignment 3. Chat Rooms for NOG

Develop a distributed “building of chat rooms”.

3 Platform

The platform used for the development-process, benchmarks and tests is a computer running Xubuntu 14.04 LTS, CPU: Intel(R) Core(TM) i7-4790 CPU @ 3.60GHz

Java version: 1.7.0_79 (OpenJDK version 7 update 79).

4 Software and technologies used

- Java Remote Method Invocation (java.rmi package)
- Java Persistence API (javax.persistence package)
- JDBC (java.sql package)
- Java Swing (javax.swing package)
- Java Socket (java.net package)
- PostgreSQL 9.3.9
- Apache JMeter

5 The application

5.1 Sub-assignment 1. A Single-User Information System for NOG

5.1.1 Functionality

Distributed java application that allows storing and updating information about participants in NOG. The server is using the HTTP protocol and only supports GET and PUT methods (PUT For storing and GET for fetching). The server is multithreaded but doesnt provide any multi-user semantics in the likes of keeping consistent data among clients (hence the minimized protocol of GET/PUT).

The client is a simple http-client atached with a GUI developed with Java Swing.

5.1.2 Protocols used

- HTTP
 - PUT/GET methods.

5.1.3 GUI




Figure 1: Screenshot of the startframe of the application

The screenshot shows a web application window titled "NOG Informationssystem". Inside, there is a "Menu" bar at the top. Below it, the title "Participants in NOG" is centered. There are two buttons: "Edit selected row" and "Delete selected row". Below these is a "Search:" label followed by a text input field. The main content is a table with 8 columns: Id, Name, Gender, Country, birthday, height, weight, and sport. The table contains 15 rows of data. Below the table are navigation buttons: "<", ">", "first", and "last". At the bottom, there is a "Filtering form:" with labels for ID, Name, Gender, Country, Birthday, Height, Weight, and Sport, each followed by a text input field. At the bottom of the form are "apply filter" and "clear" buttons.

Id	Name	Gender	Country	birthday	height	weight	sport
50511	Salminen, L...	F	Sweden	1975/03/05	169.0	67.0	Alpine Skiing
50012	Bergendal, ...	M	Sweden	1971/05/15	181.0	85.0	Alpine Skiing
50013	Karlsson, Ja...	M	Sweden	1971/01/12	173.0	70.0	Alpine Skiing
50551	Malmgren, ...	F	Sweden	1974/01/31	165.0	62.0	Speedskating
50552	Millberg, Su...	F	Sweden	1979/10/17	167.0	63.0	Speedskating
50531	Nirmark, A...	F	Sweden	1975/03/01	176.0	89.0	Cross Coun...
50042	Norberg, M...	M	Sweden	1978/10/11	179.0	72.0	Skijumping
50532	Nurminen, ...	F	Sweden	1972/11/07	167.0	59.0	Cross Coun...
50553	Odevall, Kat...	F	Sweden	1974/12/08	164.0	63.0	Speedskating
50021	Ohlsson, Lars	M	Sweden	1972/09/12	191.0	78.0	Biathlon
50542	Persson, Ca...	F	Sweden	1978/08/07	161.0	50.0	Skijumping
50043	Pettersson, ...	M	Sweden	1974/07/21	185.0	70.0	Skijumping
50542	Ramstedt, E...	F	Sweden	1970/04/20	170.0	62.0	Skijumping

Figure 2: Screenshot of the mainPanel of the application





Figure 3: Screenshot of the statisticsPanel of the application



The screenshot shows a window titled "Edit Participant" with a standard Windows-style title bar (minimize, maximize, close buttons). The window content displays the title "Edit participant: Bergendal, Christer ID:50012" in a bold font. Below this, there are seven labeled text input fields arranged vertically: "Name" (containing "Bergendal, Christer"), "Gender" (containing "M"), "Country" (containing "Sweden"), "Birthday" (containing "1971/00/15"), "Height" (containing "181.0"), "Weight" (containing "85.0"), and "Sport" (containing "Alpine Skiing"). At the bottom left of the form area is a button labeled "Save edit".

Field	Value
Name	Bergendal, Christer
Gender	M
Country	Sweden
Birthday	1971/00/15
Height	181.0
Weight	85.0
Sport	Alpine Skiing

Figure 4: Screenshot of the EditPanel of the application

5.1.4 Architecture




Figure 5: Class diagram over the application architecture.

5.1.5 Load-testing

These tests have been done on my local machine so It isn't a real proof of how the application would hold under huge loads in production but we can still see some interesting results. My main purpose with this load test was to see how well the multi-threaded semantics is working in reality. Since the test-environment is on a machine with 7 cores, we can expect that the throughput would be higher when there is multiple clients sending requests concurrently.

Without latency simulation

No. threads	No. requests	Throughput/sec	(KB/sec)
1Thread	100	990.099	17579.091
2Threads	100	1470.588	26110.122
4Threads	100	1886.792	33499.779
10Threads	100	2631.579	46723.376
TOTAL	400	1486.989	26401.313

Table 2: Load-test for http-server




Figure 6: Throughput/sec for different number of threads

The result show that 10 threads gave more than doubled the throughput compared to 1 thread. But it wasn't the result I expected. I expected a linear growth in throughput with respect to number of threads until we reach ≈ 7 threads (which is the maximum number of threads that can run in parallel on the test-machine) where the throughput would stabilize around some value.

With latency simulation

Since the server was running on my local machine it barely was'nt any latency between the requests at all, I figured that was the reason the tests did'nt match my expectations. To simulate network-latency that might occur outside of the test-environment I added a 200 millisecond delay at the server while handling the requests and re-did the tests to see what effect it gave.

No. threads	No. requests	Throughput/sec	(KB/sec)
1Thread	100	4.946	87.817
2Threads	100	9.870	175.253
4Threads	100	19.685	349.505
10Threads	100	49.189	873.334
TOTAL	400	10.672	189.486

Table 3: Load-test for http-server with latency simulation




Figure 7: Throughput/sec for different number of threads

As can be seen from the benchmark-results with the latency-simulation, the throughput is much lower, obviously.

What's interesting here is the throughput gains we get by having multiple threads issuing the requests in parallel, we can see that 10 threads issuing GET-requests in semi-parallel give ≈ 10 times higher throughput/sec than 1 thread.

5.2 Sub-assignment 2. A Multi-User Information System for NOG

5.2.1 Functionality

A multi-user distributed application that allows storing, fetching and updating (delete, edit, add) participants data. The server is developed with Java RMI and the persistence layer is developed with JPA (Java Persistence API). The underlying database is PostgreSQL.

The server is multithreaded (with java rmi) and provides functionality to let many user at a time update and have local copies of the data where every update will be replicated among every other user that is connected.

The client is a simple Java RMI client with a Java Swing GUI.

5.2.2 Protocols used

Custom developed protocol for remote method calls between server and client.

Server-interface:

- getParticipants
- putParticipants
- addParticipant
- deleteParticipant
- editParticipant

Client-interface:

- updateParticipants

5.2.3 GUI

Same GUI as for sub-assignment 1.

5.2.4 Architecture




Figure 8: Class diagram over the application architecture.

5.2.5 Load-testing

The loadtesting done for this assignment is of another nature than the tests done for sub-assignment 1. Here i have created a custom LoadTesting class for issuing remote method-calls to the RMI-server all method-calls is done single-threaded. An important note here is that all of these functions contains database interaction, so besides the Java RMI server these tests also depend on the database-layer which is in PostgreSQL. Just like for the load-testing done on the sub-assignment 1 http-server, number of calls done for each method is 100.

Method	No. calls	Time (s)
getParticipants	100	0.926
addParticipant	100	0.293
deleteParticipant	100	0.110
deleteParticipant	100	0.211

Table 4: Performance-test for rmi-server




Figure 9: Benchmark results.

The result is not very suprising, *getParticipant* is by far the method that takes the most time and *deleteParticipant* takes the least.

This was not a sophisticated load-test but we can still see that the rmi-server is alot slower than the http-server in sub-assignment 1, if we convert the data in the table above we can get that the rmi-server can handle 100 calls for *getParticipants* in ≈ 0.92 seconds. In comparison with the load-test

result from sub-assignment 1 (the single-threaded version) which could handle ≈ 990 GET-requestst of the participants, the rmi-server is way slower. The fact that the rmi-server is slower than the http-server is not suprising since the http-server simply reads from a tsv file while the rmi-server goes through many more steps: conversion from relational data to object-data with the ORM, compile psql-commands down to sql etc. but I did'nt expect the differencies to be this big.

5.3 Sub-assignment 3. Chat Rooms for NOG

5.3.1 Functionality

Distributed chat application for NOG users. The server is deveoped with java RMI and provides functionality for users to create/destroy/add chat-rooms, to Direct-Message other users and to block users.

The client is developed with java-rmi and is attached with a GUI developed with java Swing.

5.3.2 Protocols used

Custom developed protocol for remote method calls between server and client.

Server-interface:

- getClient
- registerClient
- deRegisterClient
- getChatRooms
- addChatRoom
- sendMessage
- joinChat
- destroyChatRoom
- leaveChatRoom
- privateChatRoom

Client-interface:

- updateClients
- updateChatRooms

- updateChat
- chatRoomDestroyed
- BlockClient
- unBlockClient
- getBlockedList

5.3.3 GUI




Figure 10: Screenshot of the startframe of the application




Figure 11: Screenshot of the MainPanel of the application




Figure 12: Screenshot of the MainPanel of the application

References

- [1] Royal Institute of Technology. Network programming in java. <https://www.kth.se/social/course/ID2212/>, 2015. [Online; accessed 7-Dec-2015].