

NYCU DL

Lab1 - Backpropagation

TA 高宗霖

March 21, 2023

Outline

- Recap
- Lab Objective
- Lab Description
- Scoring Criteria
- Importance Date
- Demo format

Recap

Recap - Build a Network

- Model

```
class simple(nn.Module):  
    def __init__(self, num_hidden):  
        self.layer1 = nn.Sequential(  
            nn.Linear(2, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.layer2 = nn.Sequential(  
            nn.Linear(num_hidden, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.flatten = nn.Linear(num_hidden, 1)  
  
    def forward(self, x):  
        h1 = self.layer1(x)  
        h2 = self.layer2(h1)  
        out = self.flatten(h2)  
        return out
```

Linear

Sigmoid

Linear


Sigmoid

Fully connected Layer

Recap - Forward

- Model


```
class simple(nn.Module):  
    def __init__(self, num_hidden):  
        self.layer1 = nn.Sequential(  
            nn.Linear(2, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.layer2 = nn.Sequential(  
            nn.Linear(num_hidden, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.flatten = nn.Linear(num_hidden, 1)  
  
    def forward(self, x):  
        h1 = self.layer1(x)  
        h2 = self.layer2(h1)  
        out = self.flatten(h2)  
        return out
```



Recap - Backpropagation

- Model

```
class simple(nn.Module):  
    def __init__(self, num_hidden):  
        self.layer1 = nn.Sequential(  
            nn.Linear(2, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.layer2 = nn.Sequential(  
            nn.Linear(num_hidden, num_hidden),  
            nn.Sigmoid()  
        )  
  
        self.flatten = nn.Linear(num_hidden, 1)  
  
    def forward(self, x):  
        h1 = self.layer1(x)  
        h2 = self.layer2(h1)  
        out = self.flatten(h2)  
        return out
```




Recap - Backpropagation

- Model

```
class simple(nn.Module):  
    def __init__(self, num_hidden):  
        self.layer1 = nn.Sequential(  
            nn.Linear(2, num_hidden),  
            nn.Sigmoid()  
        )
```

```
loss.backward()
```


```
def forward(self, x):  
    h1 = self.layer1(x)  
    h2 = self.layer2(h1)  
    out = self.flatten(h2)  
    return out
```



Lab Objective

Lab Objective

- In this lab, you will need to understand and implement a simple neural network with forward and backward pass using two hidden layers




Lab Description

Lab Description


- Implement a simple neural network with two hidden layers
- You can only use **Numpy** and other **python standard libraries**.
 - **Pytorch, TensorFlow,..... are not allowed**
- Plot your comparison figure showing the predictions and ground truth.
- Plot your learning curve (loss, epoch).
- Print the accuracy of your prediction .
- Print the training Loss in the end of the few last epochs.
- **List above results in your report**

Lab Description

- Each Layer should contain at least **one transformation** (e.g. Linear, CNN,...) and **one activation function** (e.g. sigmoid, tanh....)



Lab Description



$$\theta = \{w_1, w_2, w_3, w_4, \dots\}$$

$$\nabla L(\theta) = \begin{bmatrix} \partial L(\theta) / \partial w_1 \\ \partial L(\theta) / \partial w_2 \\ \partial L(\theta) / \partial w_3 \\ \vdots \end{bmatrix}$$

Compute $\nabla L(\theta^0)$

Compute $\nabla L(\theta^1)$

Compute $\nabla L(\theta^2)$


$$\theta^1 = \theta^0 - \rho \nabla L(\theta^0)$$

$$\theta^2 = \theta^1 - \rho \nabla L(\theta^1)$$


$$\theta^3 = \theta^2 - \rho \nabla L(\theta^2)$$

ρ : Learning rate


Lab Description – Flowchart



Lab Description - Data




generate_linear()



generate_XOR_easy()


Lab Description – Architecture



$X : [x_1, x_2]$ $y : \text{outputs}$ $\hat{y} : \text{ground truth}$

$W_1, W_2, W_3 : \text{weight matrix of network layers}$

Lab Description – Forward




$$Z_1 = \sigma(XW_1)$$


$$Z_2 = \sigma(Z_1W_2)$$

$$y = \sigma(Z_2W_3)$$

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$



Lab Description – Backward



Chain rule

$$y = g(x) \quad z = h(y)$$


$$\mathbf{x} \xrightarrow{g()} \mathbf{y} \xrightarrow{h()} \mathbf{z}$$

$$\frac{dz}{dx} = \frac{dz}{dy} \frac{dy}{dx}$$

$$\begin{aligned} \frac{\partial L(\theta)}{\partial w_1} &= \frac{\partial y}{\partial w_1} \frac{\partial L(\theta)}{\partial y} \\ &= \frac{\partial y}{\partial x''} \frac{\partial L(\theta)}{\partial y} \frac{\partial x''}{\partial w_1} \\ &= \frac{\partial y}{\partial x''} \frac{\partial L(\theta)}{\partial y} \frac{\partial x''}{\partial z} \frac{\partial z}{\partial w_1} \\ &= \frac{\partial y}{\partial x''} \frac{\partial L(\theta)}{\partial y} \frac{\partial x''}{\partial z} \frac{\partial z}{\partial x'} \frac{\partial x'}{\partial w_1} \end{aligned}$$

Lab Description – Gradient descent

Network Parameters $\theta = \{w_1, w_2, w_3, w_4, \dots\}$




$$\theta^1 = \theta^0 - \rho \nabla L(\theta^0)$$

$$\theta^2 = \theta^1 - \rho \nabla L(\theta^1)$$

$$\theta^3 = \theta^2 - \rho \nabla L(\theta^2)$$

ρ : Learning rate



Lab Description - Prediction

- In the training, you need to print loss
- In the testing, you need to show your predictions, also the accuracy

```
epoch 10000 loss : 0.16234523253277644
epoch 15000 loss : 0.2524336634177614
epoch 20000 loss : 0.1590783047540092
epoch 25000 loss : 0.22099447030234853
epoch 30000 loss : 0.3292173477217561
epoch 35000 loss : 0.40406233282426085
epoch 40000 loss : 0.43052897480298924
epoch 45000 loss : 0.4207525735586605
epoch 50000 loss : 0.3934759509342479
epoch 55000 loss : 0.3615008372106921
epoch 60000 loss : 0.33077879872648525
epoch 65000 loss : 0.30333537090819584
epoch 70000 loss : 0.2794858089741792
epoch 75000 loss : 0.25892812312991587
epoch 80000 loss : 0.24119780823897027
epoch 85000 loss : 0.22583656353511342
epoch 90000 loss : 0.21244497028971704
epoch 95000 loss : 0.2006912468389013
```

```
[[0.01025062]
 [0.99730607]
 [0.02141321]
 [0.99722154]
 [0.03578171]
 [0.99701922]
 [0.04397049]
 [0.99574117]
 [0.04162245]
 [0.92902792]
 [0.03348791]
 [0.02511045]
 [0.94093942]
 [0.01870069]
 [0.99622948]
 [0.01431959]
 [0.99434455]
 [0.01143039]
 [0.98992477]
 [0.00952752]
 [0.98385905]]
```


Input data generate

```
def generate_linear(n=100):  
    import numpy as np  
    pts = np.random.uniform(0, 1, (n, 2))  
    inputs = []  
    labels = []  
    for pt in pts:  
        inputs.append([pt[0], pt[1]])  
        distance = (pt[0]-pt[1])/1.414  
        if pt[0] > pt[1]:  
            labels.append(0)  
        else:  
            labels.append(1)  
    return np.array(inputs), np.array(labels).reshape(n, 1)
```

```
def generate_XOR_easy():  
    import numpy as np  
    inputs = []  
    labels = []  
  
    for i in range(11):  
        inputs.append([0.1*i, 0.1*i])  
        labels.append(0)  
  
        if 0.1*i == 0.5:  
            continue  
  
        inputs.append([0.1*i, 1-0.1*i])  
        labels.append(1)  
  
    return np.array(inputs), np.array(labels).reshape(21, 1)
```


Don't overwrite these functions!!!

Function usage

```
[x, y = generate_linear(n=100)]  
[x, y = generate_XOR_easy()]
```

Lab Description - Prediction

- Visualize the predictions and ground truth at the end of the training process



Scoring Criteria

- Report (40%)
- Demo(60%)
 - Experimental results (40%)
 - Questions (20%)
- Extra (10%)
 - Implement different optimizers. (2%)
 - Implement different activation functions. (3%)
 - Implement convolutional layers. (5%)

Scoring Criteria

- For experimental results, you have to achieve **at least 90% of accuracy to get the demo score.**
- If the zip file name or the report spec have format error, you will be **punished (-5)**

Report format

1. Introduction (20%)
2. Experiment setups (30%):
 - A. Sigmoid functions
 - B. Neural network
 - C. Backpropagation
3. Results of your testing (20%)
 - A. Screenshot and comparison figure
 - B. Show the accuracy of your prediction
 - C. Learning curve (loss, epoch curve)
 - D. anything you want to present
4. Discussion (30%)
 - A. Try different learning rates
 - B. Try different numbers of hidden units
 - C. Try without activation functions
 - D. Anything you want to share
5. Extra (10%)
 - A. Implement different optimizers. (2%)
 - B. Implement different activation functions. (3%)
 - C. Implement convolutional layers. (5%)

Important Date

- Assignment Deadline: 3/21 (Thu) 11:59 p.m.
- Demo date: 3/21 (Thu)
- Zip all files in one file
 - Report (.pdf)
 - Source code
- name it like「DL_LAB1_yourstudentID_name.zip」
 - ex: 「DL_LAB1_311554005_高宗霖.zip」

Reference

1. [http://www.denizyuret.com/2015/03/alec-radfords-animations-for-ht
ml](http://www.denizyuret.com/2015/03/alec-radfords-animations-for-html)
2. http://speech.ee.ntu.edu.tw/~tlkagk/courses_ML17_2.html

demo 時間

3/21 晚上實驗課 吳教授要上課

Lab 1 demo 時間預定排在 3/21 下午（每人約 5 分鐘）

若時間上有困難，請跟對應的助教另約 demo 時間

表單連結

U	V	W	X
	Google meet link		
	TA	高宗霖	OK/Please come in
15:50	高宗霖（我是學生		
15:55			
16:00			
16:05			
16:10			
16:15			
16:20			
16:25			

	LAB1 Back-Propaga tion	LAB2 2048 TD	LAB3 CNN	LAB4 CNN	LAB5 RNN+VAE	LAB6 Deep RL	LAB7 GAN
Announce	3/14	3/21 (上課前30分鐘)	3/28 (上課前30分鐘)	4/11	4/25	5/2 (上課前30分鐘)	5/9
DEMO	*3/21	4/11	4/11	4/25	5/16		