

# Package ‘SIPI’

July 15, 2021

**Type** Package

**Title** SIPI

**Version** 1.11

**Date** 2021-07-15

**Depends** SNPassoc, car, lmttest, parallel, pscl, ggplot2, MASS, ggpubr

**Author** Hui-Yi Lin and Po-Yu Huang

**Maintainer** Po-Yu Huang <jettly32@gmail.com>

**Description** Testing single nucleotide polymorphism (SNP) interactions is considered as a key for overcoming bottlenecks of genetic association studies. SNP Interaction Pattern Identifier (SIPI) evaluates SNP-SNP interactions associated with a binary or continuous outcome. The primary strengths of SIPI are (1) taking non-hierarchical models, reverse coding and inheritance modes (dominant, recessive and additive mode) into consideration and (2) using the Bayesian information criterion (BIC) to search for a best interaction pattern. For each SNP pair, the SIPI evaluates 45 interaction models. The best interaction pattern is the one with the lowest BIC value.

## Reference

(1) Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167. (2) Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

**LazyData** true

**License** GPL-2

## R topics documented:

AA9int . . . . . 2

CorSI . . . . .	5
Grid3by3 . . . . .	6
GridSNPxE . . . . .	8
MAFinfo . . . . .	9
parAA9int . . . . .	9
parSIPI . . . . .	11
plot3by3 . . . . .	13
plotSNPxE . . . . .	15
simData . . . . .	16
simData2 . . . . .	17
SIPI . . . . .	18
SNPmain . . . . .	20
SNPxE . . . . .	22

<b>Index</b>	<b>25</b>
--------------	-----------

---

AA9int	<i>AA9int (Additive-Additive 9 interaction models): Detect SNP-SNP interactions through testing the 9 models</i>
--------	--

---

## Description

AA9int (Additive-Additive 9 interaction models), a mini version of SIPI, evaluates SNP-SNP interactions associated with a binary or continuous outcome through testing nine interaction models. AA9int treats both SNPs as an additive mode and takes reverse coding and non-hierarchical models into consideration. The best interaction pattern is the one with the lowest value of the Bayesian information criterion (BIC). The details of the nine models/patterns are listed in the reference.

## Usage

```
AA9int(Outcome, SNPdata, PairInfo, X = NULL, categXNames = NULL,
       TestType = "WaldTest", ModelType = "binomial", OR = FALSE)
```

## Arguments

Outcome	Binary (1: event of interest; 0: reference) or continuous variable.
SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as <code>snpdata[snpdata=="-"] = NA</code> , where "-" is originally defined symbol of missing value.
PairInfo	3 types of PairInfo: (1) 2d-vector: names of the given SNP pair for one-pair analyses. ex: <code>c("SNP1", "SNP2")</code> (2) 2d-matrix or 2d-dataframe: names for candidate SNP pair. (3) "all": for pairwise analyses. (4) a list containing two 1d-vectors: for pairwise between these two vectors.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.

TestType	Specify the statistical test type: "WaldTest" = the Wald test; "LRT" = the likelihood ratio test. Default is "WaldTest".
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".
OR	If TRUE print the odds ratios, 95% confidence intervals and corresponding p-values.

**Value**

Returns a list with the following attributes:

selectedModel	The results of the best model with the lowest BIC value among the 9 models.
res9Models	For one-pair analyses only: Detailed results with all 9 models sorted by BIC (lowest first). Output variables: Var1: SNP 1; Var2: SNP 2 (the pattern/model labels are based on this order); Model: interaction model/pattern; Wald_Chisq: the Wald chi-square value of the interaction term; Wald_p: the Wald p-value of the interaction term; LRT_Chisq: the chi-square value of likelihood ratio test (LRT) for the interaction term; LRT_p: the LRT p-value of the interaction term; BIC: the Bayesian information criterion. The model with the lowest BIC value is preferred.
OR	For the "all" pairs analyses, only results of the best model will show. The group coding, please see suppl. Figures 1-3 in the end of this manual.

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

**References**

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

**See Also**

[parAA9int](#), [SIPI](#), [parSIPI](#)

**Examples**

```
##load data
data(simData)
```

```

#### define SNP data
SNPdata = simData[,3:12]

#####
### run AA9int one-pair analyses <Wald test>
#####

## For a SNP pair of SNP2 and SNP8
res_snp_2v8 = AA9int(simData$D,SNPdata,c("SNP2","SNP8"))

## print out the best model
res_snp_2v8$selectedModel

## list of 9 models for one SNP pair
res_snp_2v8$res9Models

#####
### run AA9int for a list of multiple SNP pairs <Wald test>
#####

## For 5 SNP pairs(1 vs. 6, 2 vs. 7, 3 vs. 8, 4 vs. 9, and 5 vs. 10)
pairMatrix = c("SNP1","SNP2","SNP3","SNP4","SNP5","SNP6","SNP7","SNP8","SNP9","SNP10")

pairMatrix = matrix(pairMatrix,5)

pairMatrix = as.data.frame(pairMatrix)

res_snp = AA9int(simData$D,SNPdata,pairMatrix)

#####
### run SIPI for all possible combinations of SNP pairs between two vectors <Wald test>
#####
## For 9 SNP pairs(1 vs. 6, 2 vs. 6, 3 vs. 6, 1 vs. 7, and 2 vs. 7, ..., 3 vs. 8)
vetor_1 = c("SNP1","SNP2","SNP3")
vetor_2 = c("SNP6","SNP7","SNP8")

res_snp = AA9int(simData$D,SNPdata,list(vetor_1,vetor_2))

#####
### run AA9int pairwise analyses <Wald test>
#####

res_all = AA9int(simData$D,SNPdata,"all")

#####
### run AA9int pairwise analyses <Wald test> adjusted for covariates
### [age(numeric), gender(binary), and group(categorical)]
#####

X1 = simData[,c("age","gender","group")]

res_all_cov = AA9int(simData$D,SNPdata,"all",X1,c("gender","group"))

```

```
#####
## export ORs and p-values
#####

try = AA9int(simData$D, SNPdata, "all", OR=TRUE)
write_OR_csv(try$OR, 'D:/OR.csv')
write_OR_csv(try$selectedModel, 'D:/p.csv')
```

CorSI

*Quantify similarity of SNP-SNP interaction patterns***Description**

CorSI quantifies similarity between two SNP interaction patterns based on correlation metrics.

**Usage**

```
corSI(p1_Outcome, p1_SNPdata, p2_Outcome, p2_SNPdata, method="CorSIw", plot=TRUE)
```

**Arguments**

p1_Outcome	Binary (1: event of interest; 0: reference) of first SNP-SNP interaction pattern
p1_SNPdata	SNP data of first SNP-SNP interaction pattern: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as snpdata[snpdata=="-"] = NA, where "-" is originally defined symbol of missing value.
p2_Outcome	Binary (1: event of interest; 0: reference) of second SNP-SNP interaction pattern
p2_SNPdata	SNP data of second SNP-SNP interaction pattern: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as snpdata[snpdata=="-"] = NA, where "-" is originally defined symbol of missing value.
Method	The method of similarity metric. Cor=correlation, CorSIw=weighted correlation, CorSIz= correlation with z-score normalization
plot	If TRUE print two 3-by-3 plots.

**Value**

Returns the results of the similarity metric and its p-value.

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

## References

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

## See Also

[SIPI](#), [Grid3by3](#), [plot3by3](#)

## Examples

```
##load data
data(simData2)

#### define SNP data
SNPdata = simData2[,c('snp1','snp2')]

#### define Outcome
Outcome = simData2$D

#### split data
sample_size = 1000
picked = sample(seq_len(nrow(SNPdata)),size = sample_size)
p1_Outcome = simData2$D[picked]
p1_SNPdata = SNPdata[picked,]
p2_Outcome = simData2$D[-picked]
p2_SNPdata = SNPdata[-picked,]

#####
### run CorSI analyses <CorSIw metric>
#####

## Using weighted correlation
corSI(p1_Outcome,p1_SNPdata,p2_Outcome,p2_SNPdata,method='CorSIw',plot=TRUE)
```

**Description**

Outcome proportions by the 3-by-3 genotype combinations of a give SNP pair.

**Usage**

```
Grid3by3(Outcome, SNPdata, PairInfo)
```

**Arguments**

Outcome	Binary outcome variable name: a binary variable with "1" as the event of interest and "0" as the reference.
SNPdata	SNP data. All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. An invalid character or blank field are considered to be missing values.
PairInfo	c("SNP1", "SNP2"): names of the given SNP pairs for one-pair analyses

**Value**

maj_min	Major and minor allele
table3by3	Present outcome proportions by genotype combinations
table3by3Freq	Sample size by genotype combinations

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

**See Also**

[plot3by3](#)

**Examples**

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]

#####
### run Grid3by3
#####
Grid3by3(simData$D, SNPdata, c("SNP1", "SNP2"))
```

---

GridSNPxE	<i>Outcome proportions by the combinations of SNP and environmental factor</i>
-----------	--

---

## Description

Outcome proportions by the combinations of a give SNP and environmental factor.

## Usage

```
GridSNPxE(Outcome, SNPdata, Env)
```

## Arguments

Outcome	Binary outcome variable name: a binary variable with "1" as the event of interest and "0" as the reference.
SNPdata	SNP data. SNP variable should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. An invalid character or blank field are considered to be missing values.
Env	Environment variable

## Value

maj_min	Major and minor allele
table3by3	Present outcome proportions by genotype combinations
table3by3Freq	Sample size by genotype combinations

## Author(s)

Hui-Yi Lin and Po-Yu Huang

## See Also

[plotSNPxE](#)

## Examples

```
##load data
data(simData2)

#### define SNP data
SNPdata = simData2[,9]

#### define Env data
Env = simData2$env_g2

#####
### run GridSNPxE
#####
GridSNPxE(simData2$D,SNPdata,Env)
```



---

MAFinfo	<i>SNP minor allele frequency (MAF)</i>
---------	---

---

**Description**

Obtain minor allele frequency (MAF) and major and minor allele.

**Usage**

```
MAFinfo(SNPdata)
```

**Arguments**

SNPdata	SNP data
---------	----------

**Value**

maj/min	major and minor allele
MAF	minor allele frequency
Missing (%)	missing vales
No_genotype	number of genotypes

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

**References**

Gonzalez JR, Armengol L, Sole X, Guino E, Mercader JM, Estivill X, Moreno V. SNPAssoc: an R package to perform whole genome association studies. *Bioinformatics*, 2007;23(5):654-5.

**Examples**

```
data(simData)
SNPdata = simData[,3:12]
MAFinfo(SNPdata)
```

---

parAA9int	<i>Parallel computing for AA9int</i>
-----------	--------------------------------------

---

**Description**

parAA9int is a parallel computing version of AA9int. This function can decrease computing time, which is useful for large-scale data.

**Usage**

```
parAA9int(Outcome, SNPdata, PairInfo, X = NULL, categXNames = NULL,
          TestType = "WaldTest", ModelType = "binomial",
          core_ratio = 0.9, OR = FALSE)
```

**Arguments**

Outcome	Binary (1: event of interest; 0: reference) or continuous variable.
SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as <code>snpdata[snpdata=="-"] = NA</code> , where "-" is originally defined symbol of missing value.
PairInfo	3 types of PairInfo: (1) 2d-vector: names of the given SNP pair for one-pair analyses. ex: <code>c("SNP1", "SNP2")</code> (2) 2d-matrix or 2d-dataframe: names for candidate SNP pair. (3) "all": for pairwise analyses. (4) a list containing two 1d-vectors: for pairwise between these two vectors.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.
TestType	Specify the statistical test type: "WaldTest" = the Wald test; "LRT" = the likelihood ratio test. Default is "WaldTest".
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".
core_ratio	The ratio of total cores for parallel computing. Default is 0.9.
OR	If TRUE print the odds ratios, 95% confidence intervals and corresponding p-values.

**Value**

Returns a data frame of the results of the best model with the lowest BIC value among the 9 models. For the "all" pairs analyses, only OR results of the best model will show. The group coding, please see suppl. Figures 1-3 in the end of this manual.)

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

**References**

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

**See Also**

[AA9int](#), [SIPI](#), and [parSIPI](#)

**Examples**

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]

#####
### run parAA9int pairwise analyses <Wald test>
#####

res_all = parAA9int(simData$D,SNPdata,"all")

#####
###run parAA9int pairwise analyses <Wald test> adjusted for covariates using SIPI with parallel computing
###[age(numeric), gender(binary), and group(categorical)]
#####

X1 = simData[,c("age","gender","group")]
res_all_X = parAA9int(simData$D,SNPdata,"all",X1,c("gender","group"))

#####
## export ORs and p-values
#####

try = parAA9int(simData$D,SNPdata,"all",OR=TRUE)
write_OR_csv(try$OR,'D:/OR.csv')
write_OR_csv(try$selectedModel,'D:/p.csv')
```

---

parSIPI

---

*Parallel computing for SIPI*


---

**Description**

parSIPI is a parallel computing version of SIPI. This function can decrease computing time, which is useful for large-scale data.

**Usage**

```
parSIPI(Outcome, SNPdata, PairInfo, X = NULL, categXNames = NULL,
        TestType = "WaldTest", ModelType = "binomial",
        core_ratio = 0.9, OR = FALSE)
```

**Arguments**

Outcome                      Binary (1: event of interest; 0: reference) or continuous variable.

SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as <code>snpdata[snpdata=="-"] = NA</code> , where "-" is originally defined symbol of missing value.
PairInfo	3 types of PairInfo: (1) 2d-vector: names of the given SNP pair for one-pair analyses. ex: <code>c("SNP1", "SNP2")</code> (2) 2d-matrix or 2d-dataframe: names for candidate SNP pair. (3) "all": for pairwise analyses. (4) a list containing two 1d-vectors: for pairwise between these two vectors.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.
TestType	Specify the statistical test type: "WaldTest" = the Wald test; "LRT" = the likelihood ratio test. Default is "WaldTest".
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".
core_ratio	The ratio of total cores for parallel computing. Default is 0.9.
OR	If TRUE print the odds ratios, 95% confidence intervals and corresponding p-values.

### Value

Returns a data frame of the results of the best model with the lowest BIC value among the 45 models for each SNP pair. For the "all" pairs analyses, only OR results of the best model will show. The group coding, please see suppl. Figures 1-3 in the end of this manual.)

### Author(s)

Hui-Yi Lin and Po-Yu Huang

### References

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

### See Also

[SIPI](#)

## Examples

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]

#####
### run parSIPI pairwise analyses <Wald test>
#####

res_all = parSIPI(simData$D,SNPdata,"all")

#####
###run parSIPI pairwise analyses <Wald test> adjusted for covariates using SIPI with parallel computing
###[age(numeric),gender (binary), and group(categorical)]
#####

X1 = simData[,c("age","gender","group")]
res_all_X = parSIPI(simData$D,SNPdata,"all",X1,c("gender","group"))

#####
## export ORs and p-values
#####

try = parSIPI(simData$D,SNPdata,"all",OR=TRUE)
write_OR_csv(try$OR,'D:/OR.csv')
write_OR_csv(try$selectedModel,'D:/p.csv')
```

---

plot3by3

*Heat table of outcome proportions by genotype combinations*

---

## Description

Create a heat table of sample sizes and outcome proportions by the 3-by-3 genotype combinations for a given SNP pair.

## Usage

```
plot3by3(x, SNP_info = T, outcome = T, freq = T, legend = T, monochrome = F,
         scale = "fixed", axis_fs = 1, outcome_fs = 1, freq_fs = 1, lgd_fs = 1,
         marginal = F)
```

## Arguments

x	List object output from function Grid3by3.
SNP_info	Put SNP information(SNP name and major/minor allele) on plot. Default is TRUE.
outcome	Include outcome proportions in each cell of plot. Default is TRUE. When no observations is in the given cell, 'NaN' will be shown. If there is no observation and outcome=FALSE, a warning will be shown.

freq	Include frequency in each cell. Default is TRUE.
legend	Include legend. Default is TRUE.
monochrome	Output monochrome plot. Default is FALSE
scale	A character string specifying the colour gradient scale type. "fixed" will lend color to heatmap with fixed color gradient scale from 0 to 1, "sliding" will lend color to heatmap with sliding gradient scale between minimum and maximum outcome proportion. Default is "fixed".
axis_fs	Axis font size. Adjusted both axis title font size and axis label font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
outcome_fs	Outcome font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
freq_fs	Frequency font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
lgd_fs	Legend font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
marginal	Show details for the genotypes of a individual SNP.

### Details

This function creates a heat table based on the output of Grid3by3, which generates outcome proportions by genotype combinations of a given SNP pair.

### Value

A heat table of outcome proportions.

### Author(s)

Hui-Yi Lin and Heng-Yuan Tung

### References

H. Wickham. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York, 2009.

### See Also

[Grid3by3](#)

### Examples

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]

#####
### run plot3by3
#####
x = Grid3by3(simData$D, SNPdata, c('SNP1', 'SNP2'))
plot3by3(x, SNP_info = F, outcome = F, legend = T, scale = "fixed", monochrome = T, lgd_fs = 1.2, marginal=T)
```

```
x = Grid3by3(simData$D, SNPdata, c('SNP4', 'SNP6'))
plot3by3(x, scale = "sliding", axis_fs = 1.2, outcome_fs = 0.9, freq_fs = 0.8, marginal = T)
plot3by3(x, scale = "sliding", freq = F, axis_fs = 1.2, outcome_fs = 0.9, marginal = T)
```

plotSNPxE

*Heat table of outcome proportions by combinations of SNP and environmental factor*

## Description

Create a heat table of sample sizes and outcome proportions by the combinations of a give SNP and environmental factor.

## Usage

```
plotSNPxE(x, SNP_info = T, outcome = T, freq = T, legend = T, monochrome = F,
          scale = "fixed", axis_fs = 1, outcome_fs = 1, freq_fs = 1, lgd_fs = 1,
          marginal = F)
```

## Arguments

x	List object output from function GridSNPxE.
SNP_info	Put SNP information(SNP name and major/minor allele) on plot. Default is TRUE.
outcome	Include outcome proportions in each cell of plot. Default is TRUE. When no observations is in the given cell, 'NaN' will be shown. If there is no observation and outcome=FALSE, a warning will be shown.
freq	Include frequency in each cell. Default is TRUE.
legend	Include legend. Default is TRUE.
monochrome	Output monochrome plot. Default is FALSE
scale	A character string specifying the colour gradient scale type. "fixed" will lend color to heatmap with fixed color gradient scale from 0 to 1, "sliding" will lend color to heatmap with sliding gradient scale between minimum and maximum outcome proportion. Default is "fixed".
axis_fs	Axis font size. Adjusted both axis title font size and axis label font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
outcome_fs	Outcome font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
freq_fs	Frequency font sizr. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
lgd_fs	Legend font size. Number greater than 1 will enlarge the font size, less than 1 will reduce the font size. Default is 1.
marginal	Show details for the genotypes of a individual SNP.

## Details

This function creates a heat table based on the output of GridSNPxE, which generates outcome proportions by the combinations of a give SNP and environmental factor.

**Value**

A heat table of outcome proportions.

**Author(s)**

Hui-Yi Lin and Heng-Yuan Tung

**References**

H. Wickham. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York, 2009.

**See Also**

[Grid3by3](#)

**Examples**

```
##load data
data(simData2)

#### define SNP data
SNPdata = simData2[,9]

#### define Env data
Env = simData2$env_g2

#####
### run plotSNPx
#####
Outcome = simData2$D
x = GridSNPx(Outcome,SNPdata,Env)
plotSNPx(x, SNP_info = T, outcome = T, freq = T, legend = T,
         monochrome = F, scale = "fixed", marginal = T,
         axis_fs = 1, outcome_fs = 1, freq_fs = 1, lgd_fs = 1)
```

---

simData

*An example data set for testing SNP-SNP interactions*

---

**Description**

simData is an example dataset with one binary outcome variable (D), the 10 SNPs, and three co-variates [age (numeric), gender (binary), and group (categorical)].

**Usage**

```
data(simData)
```



**Format**

A data frame with 1000 observations on the following 15 variables.

id A numeric vector for identification.

D A numeric vector for a binary outcome with "1" as the event of interest and "0" as the reference.

SNP1 to SNP10 A factor has three genotypes, which are composed of two of the four letters (C, T, A, and G), such as CC, TC and TT.

age numeric age.

gender 0: female, 1: male.

group 1: Group 1; 2: Group 2; and 3: Group 3.

**Examples**

```
data(simData)
```

---

simData2

*An example data set for testing SNP-environment interactions*

---

**Description**

simData2 is an example dataset with one binary outcome variable (D), the 5 SNPs, three covariates [cov1 (numeric), cov2 (numeric), and group (categorical)], and three environment factors [env\_g2 (binary), env\_g3 (categorical), and env\_level (numeric)].

**Usage**

```
data(simData2)
```

**Format**

A data frame with 2000 observations on the following 13 variables.

id A numeric vector for identification.

D A numeric vector for a binary outcome with "1" as the event of interest and "0" as the reference.

cov1 control numeric covariate 1

cov2 control numeric covariate 2

env\_g2 levels of environment factor, 0: low, 1: high.

group 1: Group 1, 2: Group 2, and 3: Group 3.

env\_level levels of environment factor (continuous)

env\_g3 levels of environment factor, 1: low, 2: medium, 3: high.

snp1 to snp5 SNP data with 3 genotypes, such as AA, AG and GG.

**Examples**

```
data(simData2)
```

SIPI

*SNP Interaction Pattern Identifier (SIPI): Detect SNP-SNP interactions through testing the 45 models*

## Description

SNP Interaction Pattern Identifier (SIPI) evaluates SNP-SNP interactions associated with a binary or continuous outcome. The primary strengths of SIPI are (1) taking non-hierarchical models, reverse coding and inheritance modes (dominant, recessive and additive mode) into consideration and (2) using BIC to search for a best interaction pattern. For each SNP pair, the SIPI evaluates 45 interaction models. The best interaction pattern is the one with the lowest value of the Bayesian information criterion (BIC). The details of the 45 models/patterns are listed in the SIPI published paper.

## Usage

```
SIPI(Outcome, SNPdata, PairInfo, X = NULL, categXNames = NULL,
     TestType = "WaldTest", ModelType = "binomial", OR = FALSE)
```

## Arguments

Outcome	Binary (1: event of interest; 0: reference) or continuous variable.
SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as <code>snpdata[snpdata=="-"] = NA</code> , where "-" is originally defined symbol of missing value.
PairInfo	3 types of PairInfo: (1) 2d-vector: names of the given SNP pair for one-pair analyses. ex: <code>c("SNP1", "SNP2")</code> (2) 2d-matrix or 2d-dataframe: names for candidate SNP pair. (3) "all": for pairwise analyses. (4) a list containing two 1d-vectors: for pairwise between these two vectors.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.
TestType	Specify the statistical test type: "WaldTest" = the Wald test; "LRT" = the likelihood ratio test. Default is "WaldTest".
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".
OR	If TRUE print the odds ratios, 95% confidence intervals and corresponding p-values.

**Value**

Returns a list with the following attributes:

<code>selectedModel</code>	The results of the best model with the lowest BIC value among the 45 models.
<code>res45Models</code>	For one-pair analyses only: Detailed results with all 45 models sorted by BIC (lowest first). Output variables: Var1: SNP 1; Var2: SNP 2 (the pattern/model labels are based on this order); Model: interaction model/pattern; Wald_Chisq: the Wald chi-square value of the interaction term; Wald_p: the Wald p-value of the interaction term; LRT_Chisq: the chi-square value of likelihood ratio test (LRT) for the interaction term; LRT_p: the LRT p-value of the interaction term; BIC: the Bayesian information criterion. The model with the lowest BIC value is preferred.
<code>OR</code>	For the "all" pairs analyses, only results of the best model will show. The group coding, please see suppl. Figures 1-3 in the end of this manual.

**Author(s)**

Hui-Yi Lin and Po-Yu Huang

**References**

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

**See Also**

[parSIPI](#), [AA9int](#), and [parAAint](#)

**Examples**

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]

#####
### run SIPI one-pair analyses <Wald test>
#####

## For a SNP pair of SNP2 and SNP8
res_snp_2v8 = SIPI(simData$D,SNPdata,c("SNP2","SNP8"))

## print out the best model
res_snp_2v8$selectedModel

## list of 45 models for one SNP pair
res_snp_2v8$res45Models
```

```
#####
### run SIPI for a list of multiple SNP pairs <Wald test>
#####

## For 5 SNP pairs(1 v.s. 6, 2 v.s. 7, 3 v.s. 8, 4 v.s. 9, and 5 v.s. 10)
pairMatrix = c("SNP1","SNP2","SNP3","SNP4","SNP5","SNP6","SNP7","SNP8","SNP9","SNP10")

pairMatrix = matrix(pairMatrix,5)

pairMatrix = as.data.frame(pairMatrix)

res_snp = SIPI(simData$D,SNPdata,pairMatrix)

#####
### run SIPI for all possible combinations of SNP pairs between two vectors <Wald test>
#####
## For 9 SNP pairs(1 vs. 6, 2 vs. 6, 3 vs. 6, 1 vs. 7, and 2 vs. 7, ..., 3 vs. 8)
vetor_1 = c("SNP1","SNP2","SNP3")
vetor_2 = c("SNP6","SNP7","SNP8")

res_snp = SIPI(simData$D,SNPdata,list(vetor_1,vetor_2))

#####
### run SIPI pairwise analyses <Wald test>
#####

res_all = SIPI(simData$D,SNPdata,"all")

#####
### run SIPI pairwise analyses <Wald test> adjusted for covariates
### [age(numeric), gender(binary), and group(categorical)]
#####

X1 = simData[,c("age","gender","group")]

res_all_cov = SIPI(simData$D,SNPdata,"all",X1,c("gender","group"))

#####
## export ORs and p-values
#####

try = SIPI(simData$D,SNPdata,"all",OR=TRUE)
write_OR_csv(try$OR,'D:/OR.csv')
write_OR_csv(try$selectedModel,'D:/p.csv')
```

## Description

SNPmain evaluates SNP main effect associated with a binary or continuous outcome through testing

three models. The best main effect pattern is the one with the lowest value of the p-value. The details of the three models/patterns are listed in the reference.

### Usage

```
SNPmain(Outcome, SNPdata, pairInfo, X = NULL, categXNames = NULL,
        ModelType = "binomial")
```

### Arguments

Outcome	Binary (1: event of interest; 0: reference) or continuous variable.
SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. An invalid character or blank field are considered to be missing values.
PairInfo	3 types of PairInfo: (1) 1d-vector: names of the given SNP. ex: c("SNP1", "SNP2", "SNP3") (2) "all": for all SNPs.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".

### Value

Returns the results of the best model with the lowest p-value among the 3 models. Output variables includes SNP (SNP name), Model (main effect model/pattern0), main.effect (coefficient), p-value, OR (odds ratio), CI\_2.5% and CI\_97.5% (95 % confidence interval).

### Author(s)

Hui-Yi Lin and Po-Yu Huang

### References

Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.

Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

**See Also**[SIPI](#)**Examples**

```
##load data
data(simData)

#### define SNP data
SNPdata = simData[,3:12]
Outcome = simData$D

#####
### run SNPmain analyses <Wald test>
#####

## For a list of SNPs (SNP1, SNP2, and SNP3)
res_snp_123 = SNPmain(Outcome,SNPdata,c("SNP1","SNP2","SNP3"))

## For all SNPs
res_snp_all = SNPmain(Outcome,SNPdata,"all")

#####
### run SNPmain analyses adjusted for covariates
### [age(numeric), gender (binary), and group (categorical)]
#####

X1 = simData[,c("age","gender","group")]
res_all_cov = SNPmain(Outcome,SNPdata,"all",X1,c("gender","group"))
```

SNPxE

*Detect SNP-Env interactions through testing the 27 models***Description**

SNPxE evaluates SNP-environment interactions associated with a binary or continuous outcome through testing 27 interaction models. The details of the nine models/patterns are listed in the reference.

**Usage**

```
SNPxE(Outcome, SNPdata, Env = NULL, Envtype='ord',Envreference=NULL,
      X = NULL, categXNames = NULL,
      ModelType = "binomial", SelectCriteria = "pvalue", OR = FALSE)
```

**Arguments**

Outcome                      Binary (1: event of interest; 0: reference) or continuous variable.

SNPdata	SNP data: All SNP variables should have a character variable attribute and contain two of four letters (C, T, A, and G). No other letters or numbers should be used. The missing values of SNPs need to be defined as "NA", such as <code>snpdata[snpdata=="-"] = NA</code> , where "-" is originally defined symbol of missing value.
Env	A environment variable with an ordinal or categorical feature (such as negative/positive, low/medium/high or levels).
EnvType	ord: ordinal Env feature; categ: categorical Env feature.
Envreference	The reference level of categorical feature.
X	Covariate(s) to be adjusted in the model (for missing values, keep the field blank), NULL=without covariate. Default is NULL.
categXNames	The variable names of categorical variables, NULL=without categorical covariates. Default is NULL.
ModelType	Model type: "binomial"=logistic regression; "gaussian"=linear regression. Default is "binomial".
SelectCriteria	The Criteria of model selection. SelectCriteria: "pvalue"=p-value, "bic"=Bayesian information criterion.
OR	If TRUE print the odds ratios, 95% confidence intervals and corresponding p-values.

### Value

Returns the results of the best model with the lowest value of SelectCriteria among the 27 models. Output variables includes SNP (SNP name), Model (interaction model/pattern), Coef (coefficient), p-value, OR (odds ratio), CI\_2.5% and CI\_97.5% (95 % confidence interval).

### Author(s)

Hui-Yi Lin and Po-Yu Huang

### References

- Lin HY, Chen DT, Huang PY, Liu YH, Ochoa A, Zabaleta J, Mercante DE, Fang Z, Sellers TA, Pow-Sang JM, Cheng CH, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, Consortium P, Park JY. SNP interaction pattern identifier (SIPI): an intensive search for SNP-SNP interaction patterns. *Bioinformatics*. 2017;33(6):822-33. PubMed PMID: 28039167.
- Lin HY, Huang PY, Chen DT, Tung HY, Sellers TA, Pow-Sang J, Eeles R, Easton D, Kote-Jarai Z, Amin Al Olama A, Benlloch S, Muir K, Giles GG, Wiklund F, Gronberg H, Haiman CA, Schleutker J, Nordestgaard BG, Travis RC, Hamdy F, Neal DE, Pashayan N, Khaw KT, Stanford JL, Blot WJ, Thibodeau SN, Maier C, Kibel AS, Cybulski C, Cannon-Albright L, Brenner H, Kaneva R, Batra J, Teixeira MR, Pandha H, Lu YJ, consortium P, Park JY. AA9int: SNP Interaction Pattern Search Using Non-Hierarchical Additive Model Set. *Bioinformatics*. 2018. doi: 10.1093/bioinformatics/bty461. PubMed PMID: 29878078.

### See Also

[SIPI](#)

**Examples**

```

##load data
data(simData2)

#### define SNP data
SNPdata = simData2[,9:13]

#### define Outcome
Outcome = simData2$D

#### define Env data
Env = simData2$env_g2

#####
### run SNPxE analyses <Wald test>
#####

## Using pvalue Criteria
res_snp_env_pvalue = SNPxE(Outcome,SNPdata,Env=Env,
                           ModelType="binomial",SelectCriteria="pvalue")

## Using bic Criteria
res_snp_env_bic = SNPxE(Outcome,SNPdata,Env=Env,
                        ModelType="binomial",SelectCriteria="bic")

#####
### run SNPxE analyses with categorical feature <Wald test>
#####
Env = simData2$env_g3
res_snp_env_pvalue = SNPxE(Outcome,SNPdata,
                           Env=Env,Envtype='categ',Envreference="2",
                           ModelType="binomial",SelectCriteria="pvalue")

#####
### run SNPxE analyses adjusted for covariates
### [cov1(numeric), cov2(numeric), and group(categorical)]
#####

X1 = simData2[,c("group","cov1","cov2")]
res_snp_env_pvalue_cov = SNPxE(Outcome,SNPdata,Env=Env,
                              X=X1,categXNames=c("group"),
                              ModelType="binomial",SelectCriteria="pvalue")

#####
## export ORs and p-values
#####
write.csv(res_snp_env_pvalue$Res_df,'D:/P.csv',row.names=FALSE)
write.csv(res_snp_env_pvalue$Coef_df1,'D:/OR.csv',row.names=FALSE)

```



# Index

## \*Topic **datasets**

simData, [16](#)

simData2, [17](#)

AA9int, [2](#), [11](#), [19](#)

CorSI, [5](#)

Grid3by3, [6](#), [6](#), [14](#), [16](#)

GridSNPxE, [8](#)

MAFinfo, [9](#)

parAA9int, [3](#), [9](#)

parAAint, [19](#)

parSIPI, [3](#), [11](#), [11](#), [19](#)

plot3by3, [6](#), [7](#), [13](#)

plotSNPxE, [8](#), [15](#)

simData, [16](#)

simData2, [17](#)

SIPI, [3](#), [6](#), [11](#), [12](#), [18](#), [22](#), [23](#)

SNPmain, [20](#)

SNPxE, [22](#)