

## Homework #4

---

Course: *Machine Learning (CS405)* – Professor: *Qi Hao*  
Due date: *23:59pm, November 22st, 2022*

### Question 1

Show that maximization of the class separation criterion given by  $m_2 - m_1 = \mathbf{w}^T(\mathbf{m}_2 - \mathbf{m}_1)$  with respect to  $\mathbf{w}$ , using a Lagrange multiplier to enforce the constraint  $\mathbf{w}^T\mathbf{w} = 1$ , leads to the result that  $\mathbf{w} \propto (\mathbf{m}_2 - \mathbf{m}_1)$ .

### Question 2

Show that the Fisher criterion

$$J(\mathbf{w}) = \frac{(m_2 - m_1)^2}{s_1^2 + s_2^2}$$

can be written in the form

$$J(\mathbf{w}) = \frac{\mathbf{w}^T \mathbf{S}_B \mathbf{w}}{\mathbf{w}^T \mathbf{S}_W \mathbf{w}}.$$

**Hint.**

$$y = \mathbf{w}^T \mathbf{x}, \quad m_k = \mathbf{w}^T \mathbf{m}_k, \quad s_k^2 = \sum_{n \in \mathcal{C}_k} (y_n - m_k)^2$$

### Question 3

Consider a generative classification model for  $K$  classes defined by prior class probabilities  $p(\mathcal{C}_k) = \pi_k$  and general class-conditional densities  $p(\phi|\mathcal{C}_k)$  where  $\phi$  is the input feature vector. Suppose we are given a training data set  $\{\phi_n, \mathbf{t}_n\}$  where  $n = 1, \dots, N$ , and  $\mathbf{t}_n$  is a binary target vector of length  $K$  that uses the 1-of- $K$  coding scheme, so that it has components  $t_{nj} = I_{jk}$  if pattern  $n$  is from class  $\mathcal{C}_k$ . Assuming that the data points are drawn independently from this model, show that the maximum-likelihood solution for the prior probabilities is given by

$$\pi_k = \frac{N_k}{N},$$

where  $N_k$  is the number of data points assigned to class  $\mathcal{C}_k$ .

**Question 4**

Verify the relation

$$\frac{d\sigma}{da} = \sigma(1 - \sigma)$$

for the derivative of the logistic sigmoid function defined by

$$\sigma(a) = \frac{1}{1 + \exp(-a)}$$

**Question 5**

By making use of the result

$$\frac{d\sigma}{da} = \sigma(1 - \sigma)$$

for the derivative of the logistic sigmoid, show that the derivative of the error function for the logistic regression model is given by

$$\nabla \mathbb{E}(\mathbf{w}) = \sum_{n=1}^N (y_n - t_n) \phi_n.$$

**Hint.** The error function for the logistic regression model is given by

$$\mathbb{E}(\mathbf{w}) = -\ln p(\mathbf{t}|\mathbf{w}) = -\sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}.$$

**Question 6 (Optional)**

There are several possible ways in which to generalize the concept of linear discriminant functions from two classes to  $c$  classes. One possibility would be to use  $(c - 1)$  linear discriminant functions, such that  $y_k(\mathbf{x}) > 0$  for inputs  $\mathbf{x}$  in class  $C_k$  and  $y_k(\mathbf{x}) < 0$  for inputs not in class  $C_k$ . By drawing a simple example in two dimensions for  $c = 3$ , show that this approach can lead to regions of  $\mathbf{x}$ -space for which the classification is ambiguous. Another approach would be to use one discriminant function  $y_{jk}(\mathbf{x})$  for each possible pair of classes  $C_j$  and  $C_k$ , such that  $y_{jk}(\mathbf{x}) > 0$  for patterns in class  $C_j$  and  $y_{jk}(\mathbf{x}) < 0$  for patterns in class  $C_k$ . For  $c$  classes, we would need  $c(c - 1)/2$  discriminant functions. Again, by drawing a specific example in two dimensions for  $c = 3$ , show that this approach can also lead to ambiguous regions.

**Question 7 (Optional)**

Given a set of data points  $\{\mathbf{x}^n\}$  we can define the convex hull to be the set of points  $\mathbf{x}$  given by

$$\mathbf{x} = \sum_n \alpha_n \mathbf{x}^n$$

where  $\alpha_n \geq 0$  and  $\sum_n \alpha_n = 1$ . Consider a second set of points  $\{\mathbf{z}^m\}$  and its corresponding convex hull. The two sets of points will be linearly separable if there exists a vector  $\hat{\mathbf{w}}$  and a scalar  $w_0$  such that  $\hat{\mathbf{w}}^T \mathbf{x}^n + w_0 > 0$  for all  $\mathbf{x}^n$ , and  $\hat{\mathbf{w}}^T \mathbf{z}^m + w_0 < 0$  for all  $\mathbf{z}^m$ . Show that, if their convex hulls intersect, the two sets of points cannot be linearly separable, and conversely that, if they are linearly separable, their convex hulls do not intersect.

### Program Question

Please download `hw4_ref.py` and `hw4_programQuestion.ipynb` files, complete the code and show the results as below. You need to complete `LinearRegression`, `LogisticRegression`, `SoftmaxRegression`, `FishersLinearDiscriminant`, `BayesianLogisticRegression` classes. Please check the details in lecture notes and textbook @Chapter 4.

The results should be like these figures.




Figure 1. Least Square for Classification




Figure 2. Softmax Regression and Fisher's linear discriminant




Figure 3. Probabilistic Discriminative Models