Excellent Vulkan Examples

From Sascha Willems

Vulkan C++ Examples and Demos

Vulkan- The new generation graphics and compute API from Khronos

- 1. Contents
 - 1. Shaders
 - 2. Examples
 - 1. Basics
 - 2. gITF
 - 3. Advanced
 - 4. Performance
 - 5. Physically Based Rendering
 - 6. Deferred
 - 7. Compute Shader
 - 8. Geometry Shader
 - 9. Tessellation Shader
 - 10. Hardware accelerated ray tracing
 - 11.Headless
 - 12.User Interface
 - 13.Effects
 - 14.Extensions
 - 15.Misc

Vulkan C++ Examples and Demos

Shaders

- 1. How Vulkan use Shaders?
 - Vulkan comsumes shaders in an intermediate representation called SPIR-V
 - 1. What is intermediate representation?
 - 1. Is a bytecode format as opposed to human-readable syntax like GLSL and HLSL.
 - 2. The bytecode format is called SPIR-V
 - 3. The bytecode format is a format that can used to write graphics and compute shaders
 - 2. Why use the bytecode format called SPIR-V?
 - 1. The compilers written by GPU vendors to turn shader code into native code are significantly less complex.
 - 2. If you use human-readable syntax like GLSL, some GPU vendors may rejecting your code due to syntax errors, even may compiler bugs, use SPIR-V can avoided such errors.

Vulkan C++ Examples and Demos

Shaders

- 1. How Vulkan use Shaders?
 - 3. How we write bytecode format shader?
 - We don't need to write the bytecode format by hand, Khronos released a compiler can compiles GLSL to SPIR-V.
 - 2. You can include this compiler as a library to produce SPIR-V at runtime.
 - 3. We can use compiler like glslangValidator.exe
 - 4. We can use compiler like glslc.exe
 - 1. What is good for using glslc?
 - 1. Glslc uses the same parameter format as well-known compilers like GCC and Clang and includes some extra functionality like includes.
 - 5. glslangValidator.exe and glslc.exe are included in Vulkan SDK.