

HTML 部分:

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8" />
  <title>美香稻爱心助农</title>
  <link rel="stylesheet" href="../css/index.css" />
</head>

<body>
  <!--公共头部区域-->
  <div class="head">
    <div class="container one">
      <div class="d1">
        <a href="javascript:void(0);">亲, 请登录</a>
        <a href="javascript:void(0);">免费注册</a>
      </div>
      <div class="d1-1">
        <a href="javascript:void(0);"><i class="fa fa-github-
alt"> </i></a>
        <a href="javascript:void(0);"><i class="fa fa-shopping-
cart"></i></a>
        <a href="javascript:void(0);">个人中心 </a>
        <a href="javascript:void(0);">切换账号</a>
        <a href="javascript:void(0);">退出账号</a>
      </div>
    </div>
  </div>
  <!--中间的搜索部分-->
  <header class="container two">
    <div class="logo">
      
    </div>
    <div class="form">
      <!--required 属性是一个布尔属性。required 属性规定必需在提交表单
之前填写输入字段。-->
      <input type="text" required>
      <div class="suosou">
        <i class="fa fa-search"></i>
        <span>安岳黄柠檬</span>
      </div>
    </div>
  </header>
</body>
</html>
```

```

        </div>
        <a href="javascript:void(0);" class="a1">搜索</a>
        <div class="form-1">
            <a href="">正宗土鸡蛋</a>
            <a href="javascript:void(0);">山东大白菜</a>
            <a href="javascript:void(0);">福建红心蜜柚</a>
            <a href="javascript:void(0);">四川猕猴桃</a>
            <a href="javascript:void(0);">新疆哈密瓜</a>
            <a href="javascript:void(0);">云南金凤梨</a>
        </div>
    </div>
    <!--二维码区域-->
    <div class="scan">
        <i class="fa fa-qrcode"></i>
        <a href="javascript:void(0);">扫一扫</a>
        <div class="img"></div>
    </div>
</header>
</body>

</html>

```

CSS 部分:

```

/*
公共头部部分
*/

body {
    width: 100%;
    background-color: #f5f4f4;
}

.container {
    width: 1200px;
    margin: 0 auto;
}

.head {
    height: 41px;
    background-color: #eeeeee;
}

```

```
}
```

```
/*flex 布局:
```

```
    设为 Flex 布局以后,
```

```
    子元素的 float、clear 和 vertical-align 属性将失效。
```

```
    flex 容器的属性
```

```
    1.flex-direction
```

```
    决定主轴的方向（即项目的排列方向），相对的另外一条轴就是交叉轴
```

```
    取值: row（默认）主轴为水平方向，起点在左端，row-reverse, column,
```

```
column-reverse
```

```
    2.flex-wrap
```

```
    默认情况下，项目都排在一条线（又称“轴线”）上。flex-wrap 属性定义，如果一  
    条轴线排不下，如何换行。
```

```
    取值: nowrap（影响到项目的宽度），wrap, wrap-reverse（超出的换到上面）
```

```
    3.flex-flow
```

```
    flex-flow 属性是 flex-direction 属性和 flex-wrap 属性的简写形式，默认值  
    为 row nowrap。
```

```
    flex-flow: row nowrap
```

```
    4.justify-content
```

```
    定义了项目在主轴上的对齐方式
```

```
    取值: flex-start, flex-end, center, space-between, space-around
```

```
    align-items
```

```
    定义项目在交叉轴上如何对齐
```

```
    取值: flex-start, flex-end, center, baseline, stretch(子容器沿交叉轴方  
    向的尺寸拉伸至与父容器一致)
```

```
*/
```

```
.one {
```

```
    display: flex;
```

```
    justify-content: space-between;
```

```
}
```

```
.d1 {
```

```
    height: 41px;
```

```
    line-height: 41px;
```

```
    font-size: 14px;
```

```
}
```

```
.d1 a {
```

```
    padding-right: 30px;
```

```
    color: #959595;
```

```
}

.d1-1 {
  display: flex;
  width: 350px;
  height: 15px;
  font-size: 14px;
  color: #959595;
  line-height: 41px;
  justify-content: space-between;
}

.d1-1 a {
  color: #959595;
}

.d1-1 a:not(:last-child) {
  margin-right: 30px;
}

/*中间搜索部分-CSS*/

.two {
  display: flex;
  justify-content: space-between;
  align-items: center;
}

.form {
  display: flex;
  position: relative;
}

.form input {
  width: 545px;
  height: 41px;
  border: 1px solid #009900;
  border-radius: 41px 0 0 41px;
  line-height: 41px;
  padding-left: 10px;
  position: relative;
}
```

```
/* “+” 是 兄弟选择器*/

.form input+.suosou {
    position: absolute;
    top: 10px;
    left: 10px;
    color: #cacaca;
}

/* “~” 是通用选择器*/

.form input:focus~.suosou,
.form input:valid~.suosou {
    display: none;
}

.form .a1 {
    width: 90px;
    height: 41px;
    background-color: #3a880e;
    border-radius: 0 41px 41px 0;
    text-align: center;
    line-height: 41px;
    font-size: 18px;
    color: white;
}

.form-1 {
    position: absolute;
    top: 41px;
    left: 20px;
}

.scan {
    width: 283px;
    height: 41px;
    background-color: #3a880e;
    border-radius: 41px;
    text-align: center;
    line-height: 41px;
    color: white;
}

.scan a {
```

```
    font: 22px;  
    color: white;  
}  
  
.logo img {  
    width: 80px;  
}
```