


EXP 4: Create UDF in PIG

Step-by-step installation of Apache Pig on Hadoop cluster on Ubuntu Prerequisite:

- Ubuntu 16.04 or higher version running (I have installed Ubuntu on Oracle VM (Virtual Machine) VirtualBox),
- Run Hadoop on ubuntu (I have installed Hadoop 3.2.1 on Ubuntu 16.04). You may refer to my blog “How to install Hadoop installation” click [here](#) for Hadoop installation).

Pig installation steps

Step 1: Login into Ubuntu




```
hadoop [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
Terminal
hadoop@hadoop-VirtualBox: ~
hadoop@hadoop-VirtualBox:~$ $ wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz
$: command not found
hadoop@hadoop-VirtualBox:~$ wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz
--2022-06-21 11:57:52-- https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz
Resolving dlcdn.apache.org (dlcdn.apache.org)... 151.101.2.132, 2a04:4e42::644
Connecting to dlcdn.apache.org (dlcdn.apache.org)|151.101.2.132|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 177279333 (169M) [application/x-gzip]
Saving to: 'pig-0.16.0.tar.gz.1'

pig-0.16.0.tar.gz.1 94%[=====] 158.94M 5.19MB/s eta 2s
```

Step 2: Go to <https://pig.apache.org/releases.html> and copy the path of the latest version of pig that you want to install. Run the following command to download Apache Pig in Ubuntu:

\$ wget <https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz>



```
hadoop [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
Terminal
hadoop@hadoop-VirtualBox: ~
hadoop@hadoop-VirtualBox:~$
```

Step 3: To untar pig-0.16.0.tar.gz file run the following command:

```
$ tar xvzf pig-0.16.0.tar.gz
```

Step 4: To create a pig folder and move pig-0.16.0 to the pig folder, execute the following command:


```
$ sudo mv /home/hadoop/pig-0.16.0 /home/hadoop/pig
```

Step 5: Now open the .bashrc file to edit the path and variables/settings for pig. Run the following command:

```
$ sudo nano .bashrc
```

Add the below given to .bashrc file at the end and save the file.

```
#PIG settings
export PIG_HOME=/home/hadoop/pig
export PATH=$PATH:$PIG_HOME/bin
export PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/
export PIG_CONF_DIR=$PIG_HOME/conf
export JAVA_HOME=/usr/lib/jvm/java-8-openjdk-amd64
export PIG_CLASSPATH=$PIG_CONF_DIR:$PATH
#PIG setting ends
```



Step 6: Run the following command to make the changes effective in the .bashrc file:


```
$ source .bashrc
```

Step 7: To start all Hadoop daemons, navigate to the `hadoop-3.2.1/sbin` folder and run the following commands:

```
$ ./start-dfs.sh $ ./start-yarn.sh jps
```

```
hadoop@hadoop-VirtualBox:~$ cd hadoop-3.2.1/sbin
hadoop@hadoop-VirtualBox:~/hadoop-3.2.1/sbin$ ./start-dfs.sh
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [hadoop-VirtualBox]
hadoop@hadoop-VirtualBox:~/hadoop-3.2.1/sbin$ ./start-yarn.sh
Starting resourcemanager
Starting nodemanagers
hadoop@hadoop-VirtualBox:~/hadoop-3.2.1/sbin$ jps
4817 DataNode
5298 ResourceManager
5000 SecondaryNameNode
5450 NodeManager
4683 NameNode
5982 Jps
hadoop@hadoop-VirtualBox:~/hadoop-3.2.1/sbin$
```

Step 8: Now you can launch pig by executing the following command: `$ pig`



```
hadoop [Running] - Oracle VM VirtualBox
File Machine View Input Devices Help
Terminal
hadoop@hadoop-VirtualBox: ~
hadoop@hadoop-VirtualBox:~$ pig
2022-06-21 12:29:24,863 INFO pig.ExecTypeProvider: Trying ExecType : LOCAL
2022-06-21 12:29:24,864 INFO pig.ExecTypeProvider: Trying ExecType : MAPREDUCE
2022-06-21 12:29:24,864 INFO pig.ExecTypeProvider: Picked MAPREDUCE as the ExecType
2022-06-21 12:29:24,934 [main] INFO org.apache.pig.Main - Apache Pig version 0.16.0 (r1746530) compiled Jun 01 2016, 23:10:49
2022-06-21 12:29:24,934 [main] INFO org.apache.pig.Main - Logging error message
s to: /home/hadoop/pig_1655794764927.log
2022-06-21 12:29:24,957 [main] INFO org.apache.pig.impl.util.Utils - Default bootup file /home/hadoop/.pigbootup not found
2022-06-21 12:29:25,273 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2022-06-21 12:29:25,273 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - fs.default.name is deprecated. Instead, use fs.defaultFS
2022-06-21 12:29:25,273 [main] INFO org.apache.pig.backend.hadoop.executionengine.HExecutionEngine - Connecting to hadoop file system at: hdfs://localhost:9000
2022-06-21 12:29:25,842 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - fs.default.name is deprecated. Instead, use fs.defaultFS
2022-06-21 12:29:25,862 [main] INFO org.apache.pig.PigServer - Pig Script ID for the session: PIG-default-c4e709d8-f6a3-4749-851f-c150e4603854
2022-06-21 12:29:25,862 [main] WARN org.apache.pig.PigServer - ATS is disabled since yarn.timeline-service.enabled set to false
grunt>
```

Step 9: Now you are in pig and can perform your desired tasks on pig. You can come out of the pig by the quit command:

```
> quit;
```

Procedure:

Create a sample text file

```
hadoop@Ubuntu:~/Documents$ nano sample.txt
```

Paste the below content to sample.txt

```
1,John
2,Jane
3,Joe
4,Emma
```

```
hadoop@Ubuntu:~/Documents$ hadoop fs -put sample.txt /home/hadoop/piginput/
```

Create PIG File

```
hadoop@Ubuntu:~/Documents$ nano demo_pig.pig
```

paste the below the content to demo_pig.pig

```
-- Load the data from HDFS data = LOAD '/home/hadoop/piginput/sample.txt'
USING PigStorage(',') AS (id:int>
```

```
-- Dump the data to check if it was loaded correctly
DUMP data;
```

Run the above file

```
hadoop@Ubuntu:~/Documents$ pig demo_pig.pig
```

```
2024-08-07 12:13:08,791 [main] INFO
org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil
- Total input paths to process : 1
(1,John)
(2,Jane)
```

(3,Joe)

(4,Emma)

Create udf file an save as uppercase_udf.py

uppercase_udf.py

```
- ----- def uppercase(text): return text.upper()
```

```
if __name__ == "__main__":
```

```
import sys for
```

```
line          in
```

```
sys.stdin:
```

```
    line = line.strip()
```

```
    result =
```

```
    uppercase(line)
```

```
    print(result)
```

Create the udfs folder on hadoop

```
hadoop@Ubuntu:~/Documents$ hadoop fs -mkdir /home/hadoop/udfs
```

put the upppercase_udf.py in to the abv folder

```
hadoop@Ubuntu:~/Documents$ hdfs dfs -put uppercase_udf.py /home/hadoop/udfs/
```

```
hadoop@Ubuntu:~/Documents$ nano udf_example.pig
```

copy and paste the below content on udf_example.pig

```
-- Register the Python UDF script
```

```
REGISTER 'hdfs:///home/hadoop/udfs/uppercase_udf.py' USING jython AS udf;
```

```
-- Load some data data = LOAD 'hdfs:///home/hadoop/sample.txt'
```

```
AS (text:chararray);
```

```
-- Use the Python UDF uppercased_data = FOREACH data GENERATE
```

```
udf.uppercase(text) AS uppercase_text;
```

```
-- Store the result
```

```
STORE uppercased_data INTO 'hdfs:///home/hadoop/pig_output_data';
```

```
-----  
---
```

place sample.txt file on hadoop hadoop@Ubuntu:~/Documents\$ hadoop

fs -put sample.txt /home/hadoop/ **To Run the pig file**

hadoop@Ubuntu:~/Documents\$ pig -f udf_example.pig

finally u get

Success!

Job Stats (time in seconds):

JobId Maps Reduces MaxMapTimeMinMapTime AvgMapTime MedianMapTime

MaxReduceTime MinReduceTime AvgReduceTime MedianReducetime

Alias Feature Outputs

job_local1786848041_0001 1 0 n/a n/a n/a n/a 00 0 0

data,uppercased_data MAP_ONLY hdfs:///home/hadoop/pig_output_data,

Input(s):

Successfully read 4 records (42778068 bytes) from: "hdfs:///home/hadoop/sample.txt"

Output(s):

Successfully stored 4 records (42777870 bytes) in:

"hdfs:///home/hadoop/pig_output_data"

Counters:

Total records written : 4

Total bytes written : 42777870

Spillable Memory Manager spill count : 0

Total bags proactively spilled: 0

Total records proactively spilled: 0

Job DAG:

job_local1786848041_0001

2024-08-07 13:33:04,631 [main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl JobTracker

metrics system already initialized! 2024-08-07 13:33:04,639

[main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl JobTracker

metrics system already initialized!

2024-08-07 13:33:04,644 [main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl - JobTracker metrics system

already initialized! 2024-08-07 13:33:04,667 [main] INFO

org.apache.pig.backend.hadoop.executionengine.mapReduceLayer.MapReduceLauncher

- Success!

Note :

If any error check jython package is installed and check the path specified on the above steps are give correctly

-- To check the output file is created hadoop@Ubuntu:~/Documents\$ hdfs

dfs -ls /home/hadoop/pig_output_data

Found 2 items

If you need to examine the files in the output folder,

use: **To view the output**

hadoop@Ubuntu:~/Documents\$ hdfs dfs -cat

/home/hadoop/pig_output_data/partm00000

1,JOHN

2,JANE

3,JOE

4,EMMA

Output:

File information - part-m-00000 ✕

[Download](#) [Head the file \(first 32K\)](#) [Tail the file \(last 32K\)](#)

Block Information -- Block 0 ▾

Block ID: 1073741869

Block Pool ID: BP-656159918-127.0.1.1-1725282353178

Generation Stamp: 1045

Size: 27

Availability:

- ubuntu.myguest.virtualbox.org

File contents

```
1,JOHN
2,JANE
3,JOE
4,EMMA
```

[Close](#)

```
hadoop@ubuntu:~/Documents$ hdfs dfs -cat /home/hadoop/pig_output_data/part-m-00000
1, JOHN
2, JANE
3, JOE
4, EMMA
hadoop@ubuntu:~/Documents$
```


Result:

Thus the UDF in Apache PIG has been created and executed in Mapreduce/HDFS mode Successfully.