

[Dashboard](#) / [My courses](#) / [CS23333-OOPUI-2023](#) / [Lab-09-Exception Handling](#) / [Lab-09-Logic Building](#)

Status	Finished
Started	Tuesday, 29 October 2024, 8:36 AM
Completed	Tuesday, 29 October 2024, 8:56 AM
Duration	19 mins 46 secs

Question 1

Correct

Marked out of 5.00

Write a Java program to create a method that takes an integer as a parameter and throws an exception if the number is odd.

Sample input and Output:

82 is even.

Error: 37 is odd.

Fill the preloaded answer to get the expected output.

For example:**Result**

82 is even.

Error: 37 is odd.

Answer: (penalty regime: 0 %)

Reset answer

```
1 class prog {
2     public static void main(String[] args) {
3         int n = 82;
4         trynumber(n);
5         n = 37;
6         trynumber(n) ; // call the trynumber(n);
7
8
9     }
10
11     public static void trynumber(int n) {
12         try {
13             checkEvenNumber(n); // call the checkEvenNumber()
14             System.out.println(n + " is even.");
15         } catch (ArithmeticException e) {
16             System.out.println("Error: " + e.getMessage());
17         }
18     }
19
20     public static void checkEvenNumber(int number) {
21         if (number % 2 != 0) {
22             throw new ArithmeticException(number + " is odd.");
23         }
24     }
25 }
26
```

	Expected	Got	
✓	82 is even. Error: 37 is odd.	82 is even. Error: 37 is odd.	✓

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

In the following program, an array of integer data is to be initialized.

During the initialization, if a user enters a value other than an integer, it will throw an InputMismatchException exception.

On the occurrence of such an exception, your program should print "You entered bad data."

If there is no such exception it will print the total sum of the array.

```
/* Define try-catch block to save user input in the array "name"
```

```
If there is an exception then catch the exception otherwise print the total sum of the array. */
```

Sample Input:

```
3
5 2 1
```

Sample Output:

```
8
```

Sample Input:

```
2
1 g
```

Sample Output:

```
You entered bad data.
```

For example:

Input	Result
3 5 2 1	8
2 1 g	You entered bad data.

Answer: (penalty regime: 0 %)

Reset answer

```

1 import java.util.Scanner;
2 import java.util.InputMismatchException;
3 class prog {
4     public static void main(String[] args) {
5         Scanner sc = new Scanner(System.in);
6         int length = sc.nextInt();
7         // create an array to save user input
8         int[] name = new int[length];
9         int sum=0;//save the total sum of the array.
10
11         /* Define try-catch block to save user input in the array "name"
12         If there is an exception then catch the exception otherwise print
13         the total sum of the array. */
14         try
15         {
16             for (int i=0;i<length;i++){
17                 name[i]=sc.nextInt();
18                 sum+=name[i];
19             }
20             System.out.println(sum);
21         }
22         catch(InputMismatchException e )
23         {
24             System.out.println("You entered bad data.");
25         }
26     }
27
28
29
30
31
32
33 }
```

```
34 | }
```

	Input	Expected	Got	
✓	3 5 2 1	8	8	✓
✓	2 1 g	You entered bad data.	You entered bad data.	✓

Passed all tests! ✓



Question 3

Correct

Marked out of 5.00

Write a Java program to handle `ArithmeticException` and `ArrayIndexOutOfBoundsException`.

Create an array, read the input from the user, and store it in the array.

Divide the 0th index element by the 1st index element and store it.

if the 1st element is zero, it will throw an exception.

if you try to access an element beyond the array limit throws an exception.

Input:

5

10 0 20 30 40

Output:

`java.lang.ArithmeticException: / by zero`

I am always executed

Input:

3

10 20 30

Output

`java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3`

I am always executed

For example:

Test	Input	Result
1	6 1 0 4 1 2 8	<code>java.lang.ArithmeticException: / by zero</code> I am always executed

Answer: (penalty regime: 0 %)

```

1 import java.util.*;
2 import java.lang.*;
3 class prog{
4     public static void main(String args[]){
5         Scanner s = new Scanner(System.in);
6         int n= s. nextInt();
7         int a[] = new int[n];
8         try{
9             for (int i=0;i<n;i++){
10                 a[i]= s.nextInt();
11             }
12             for (int i=0;i<n;i++){
13                 int result=a[i]/a[i+1];
14             }
15         }
16         catch(Exception e){
17             System.out.println(e);
18         }
19         finally{
20             System.out.println("I am always executed");
21         }
22     }
23 }
24 }
```

	Test	Input	Expected	Got	
✓	1	6 1 0 4 1 2 8	<code>java.lang.ArithmeticException: / by zero</code> I am always executed	<code>java.lang.ArithmeticException: / by zero</code> I am always executed	✓

	Test	Input	Expected	Got	
✓	2	3 10 20 30	java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3 I am always executed	java.lang.ArrayIndexOutOfBoundsException: Index 3 out of bounds for length 3 I am always executed	✓

Passed all tests! ✓

◀ Lab-09-MCQ

Jump to...



[The "Nambiar Number" Generator ▶](#)