


CS5010 Milestone3 Preliminary Design

By Linhao Qian (NUID: 002325915)

UML Diagram



Testing Plan

Testing design for TargetCharacter

Testing construction	Input	Expected Value
Constructor disallows null name	TargetCharacter(null, 50)	IllegalArgumentException
Constructor disallows empty name	TargetCharacter("", 50)	IllegalArgumentException
Constructor disallows non-positive health	TargetCharacter("doctor", 0)	IllegalArgumentException

Testing getName()	Input	Expected Value
TargetCharacter with normal name	TargetCharacter("Leo", 50)	"Leo"

Testing getHealth()	Input	Expected Value
TargetCharacter with positive health	TargetCharacter("Leo", 50)	50

Testing reduceHealth(int damage)	Input	Parameter	Actual Testing
Reduce positive health value	TargetCharacter("Leo", 50)	3	assertEquals(getHealth(), 47)
Test invalid damage	TargetCharacter("Leo", 50)	-3	IllegalArgumentException

Testing design for Pet

Testing construction	Input	Expected Value
Constructor disallows null name	Pet(null)	IllegalArgumentException
Constructor disallows empty name	Pet("")	IllegalArgumentException

Testing getName()	Input	Expected Value
Pet with normal name	Pet("cat")	"cat"

Testing <code>setSpace(Space space)</code> and <code>getSpace()</code>	Input	Expected Value
Set a normal space and get it	<code>setSpace(new MySpace(0, 0, 3, 3, "Kitchen"));</code> <code>getSpace();</code>	<code>new MySpace(0, 0, 3, 3, "Kitchen")</code>
Disallow set a null space	<code>setSpace(null);</code>	<code>IllegalArgumentException</code>

Testing design for Player

Testing construction	Input	Expected Value
Test Computer Constructor With Null Name	<code>ComputerControlledPlayer (null, new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>IllegalArgumentException</code>
Test Human Constructor With Null Name	<code>HumanControlledPlayer (null, new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>IllegalArgumentException</code>
Test Computer Constructor With Empty Name	<code>ComputerControlledPlayer ("", new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>IllegalArgumentException</code>
Test Human Constructor With Empty Name	<code>HumanControlledPlayer ("", new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>IllegalArgumentException</code>
Test Computer Constructor With Null Space	<code>ComputerControlledPlayer ("Leo", null)</code>	<code>IllegalArgumentException</code>
Test Human Constructor With Null Space	<code>HumanControlledPlayer ("Leo", null)</code>	<code>IllegalArgumentException</code>

Testing <code>getName()</code>	Input	Expected Value
HumanControlledPlayer with normal name	<code>HumanControlledPlayer ("Leo", new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>"Leo"</code>
ComputerControlledPlayer with normal name	<code>ComputerControlledPlayer ("Leo", new MySpace(0, 0, 3, 3, "Kitchen"))</code>	<code>"Leo"</code>

Testing <code>addItem(Item item)</code> , <code>getItem(String itemName)</code> , and <code>getItems()</code>	Input	Expected Value
Add and get an item	<code>addItem(new MyItem("Revolver", 3));</code>	<code>new MyItem("Revolver", 3)</code>

	getItems().get(0); getItem("Revolver")	
--	---	--

Testing removeItem(Item item)	Input	Expected Value
Remove an item	Item = new MyItem("Revolver", 3) addItem(item); getItems().size(); removeItem(item); getItems().size();	1; 0;

Testing setSpace(Space space) and getSpace()	Operation	Expected Value
Set and get a space	setSpace(new MySpace(0, 0, 3, 3, "Kitchen")); getSpace()	MySpace(0, 0, 3, 3, "Kitchen")

Testing isNeighbor ()	Testing ideas
Determine whether a player is the neighbor of current player	Add a player to the neighbor space of current player, then test if the new added player is current player's neighbor.

Testing isSameSpace ()	Testing ideas
Determine whether a player is in the same space of current player	Add a player to the current space of current player, then test if the new added player is in the same space of current player.

Testing getMostPowerful ItemName ()	Input	Expected Value
Get the most powerful item name	addItem(new MyItem("Revolver", 3)) addItem(new MyItem("Knife", 2))	"Revolver"

Testing design for MyItem

Testing construction	Input	Expected Value
Constructor disallows	MyItem("", 3)	IllegalArgumentException

empty name		
Constructor disallows null name	MyItem(null, 3)	IllegalArgumentException
Constructor disallows non-positive damage	MyItem("Revolver", 0)	IllegalArgumentException

Testing getName()	Input	Expected Value
Item with normal name	MyItem("Revolver", 0, 3)	"Revolver"

Testing getDamage()	Input	Expected Value
Item with positive damage	MyItem("Revolver", 0, 3)	3

Testing design for MySpace

Testing construction	Input	Expected Value
Constructor disallows negative row1	MySpace(-1, 0, 3, 3, "Kitchen")	IllegalArgumentException
Constructor disallows negative col1	MySpace(0, -1, 3, 3, "Kitchen")	IllegalArgumentException
Constructor disallows the value of row2 to be less than the value of row1	MySpace(0, 0, -3, 3, "Kitchen")	IllegalArgumentException
Constructor disallows the value of col2 to be less than the value of col1	MySpace(0, 0, 3, -3, "Kitchen")	IllegalArgumentException
Constructor disallows empty name	MySpace(0, 0, 3, 3, "")	IllegalArgumentException
Constructor disallows null name	MySpace(0, 0, 3, 3, null)	IllegalArgumentException

Testing getPosition()	Input	Expected Value
Space with correct position	MySpace(0, 0, 3, 3, "Kitchen")	new int[]{0, 0, 3, 3}

Testing getName()	Input	Expected Value
Space with normal name	MySpace(0, 0, 3, 3, "Kitchen")	"Kitchen"

Testing addItem(Item item), removeItem(Item item)	Operation	Actual Testing

item), getItem(String itemName), and getItem()		
Test multiple methods	Item item = new Item("Revolver", 0, 3);	addItem(item); assertTrue(getItems().get(0).equals(item)); assertEquals(getItem("Revolver", item) removeItem(item); assertEquals(getItems().size, 0);

Testing addNeighbor(Space space) and getNeighbors()	Operation	Actual Testing
Add a neighbor and get the neighbors list	Space space = new MySpace(0, 0, 3, 3, "Kitchen");	Space newSpace = new MySpace(0, 4, 3, 6, "Parlor"); space.addNeighbor(newSpace); assertEquals(getNeighbors().get(0), newSpace)

Testing design for MyWorld (i.e., the model testing design)

Testing reading world.txt file	Testing ideas
Read the txt file and generate the world	The MyWorld toString() method can print the world's information, so we can compare the printed information with the expected information after generating the MyWorld object.

Testing invalid world description	Testing ideas
The txt file has an invalid world size	Set the world size in the txt file to 36×0 , then read the file. It should throw an IllegalArgumentException

Testing invalid space	Testing ideas
The txt file has overlapping spaces	Set two overlapping spaces in the txt file, then read the file. It should throw an IllegalArgumentException

Testing invalid item	Testing ideas
The txt file has an item with an	Set an item's space index to a non-existent index

space index out of bounds	in the txt file, then read the file. It should throw an <code>IllegalArgumentException</code>
---------------------------	---

Testing <code>getNeighbors()</code> and <code>displaySpaceInformation()</code> under different neighboring conditions	Testing ideas
Test a space with no neighbors	Make one space non adjacent to other spaces in the txt file, then read the file and get that space. Use <code>assertEquals()</code> to check if its <code>getNeighbors()</code> method returns a 0-length list, and check if its <code>displaySpaceInformation()</code> method returns the correct string.
Test a space with one neighbor	Find one space with only one neighbor. Use <code>assertEquals()</code> to check if its <code>getNeighbors()</code> method returns a 1-length list, and check if its <code>displaySpaceInformation()</code> method returns the correct string.
Test a space with multiple neighbors	Find one space with multiple neighbors. Use <code>assertEquals()</code> to check if its <code>getNeighbors()</code> method returns correct space list, and check if its <code>displaySpaceInformation()</code> method returns the correct string.

Testing <code>displaySpaceInformation()</code> under other conditions	Testing ideas
Test a space with no Items	Find one space with no items. Use <code>assertEquals()</code> to check if its <code>displaySpaceInformation()</code> method returns the correct string.
Test a space with one item	Find one space with one item. Use <code>assertEquals()</code> to check if its <code>displaySpaceInformation()</code> method returns the correct string.
Test a space with players	Add a player to a specified space. Use <code>assertEquals()</code> to check if its <code>displaySpaceInformation()</code> method returns the correct string.

Testing the start space of the target character	Testing ideas
The target character should start from space 0.	The target character should start from space 0, so we can just call <code>getTargetCharacterPosition()</code>

	method at the beginning to check if it returns 0.
--	---

Testing moving target character	Testing ideas
The target character can move from space 0 to space 1.	Call moveTargetCharacter() method once. Check if getTargetCharacterPosition() returns 1.
The target character can move multiple times.	Call moveTargetCharacter() method 10 times. Check if getTargetCharacterPosition() returns 11.
The target character can move from the last room in the index list to room 0.	Set x equals to the length of the space list. Call moveTargetCharacter() method x times. Check if getTargetCharacterPosition() returns 0.

Testing getting players	Testing ideas
Get the world's player list	The world should have an empty player list at the beginning, so getPlayers() returns an empty list.

Testing adding players	Testing ideas
Add human players	Add 2 human players, then use assertEquals() and assertEquals() to test if they are the correct players.
Add computer players	Add 2 computer players, then use assertEquals() and assertEquals() to test if they are the correct players.

Testing displayPlayerInformation()	Testing ideas
Display human player information	Add 1 human player carrying 1 item and another human player carrying 0 item, then use assertEquals() to check if the displayPlayerInformation() method returns the correct strings for both of them.
Display computer player information	Add 1 computer player carrying 1 item and another computer player carrying 0 item, then use assertEquals() to check if the displayPlayerInformation() method returns the correct strings for both of them.

Testing taking turns	Testing ideas
The players in the player list should take turns to play the game	Add 2 players, and reset the turn. Use assertEquals() to check if the getTurn() method returns the first player. Then call nextTurn(), check if getTurn()

	method returns the second player.
--	-----------------------------------

Testing player moving around	Testing ideas
The players can move to neighboring spaces	Add 1 human player and 1 computer player, then move them to one of their neighboring space, respectively. Use <code>assertSame()</code> to check if they are in the expected spaces.
The players cannot move to non-neighboring spaces	Move a player to a non-neighboring space. It should throw an <code>IllegalArgumentException</code> .

Testing player picking up item	Testing ideas
The players can pick up item in current space when their item number doesn't reach the limit.	Add a player to a space with 2 items, then make the player pick up the 2 items. Use <code>assertSame()</code> to check if the player carry the expected items.
The players cannot pick up items that doesn't exist in current space	Make a player pick up a non-exist item. It should throw an <code>IllegalArgumentException</code> .
The players cannot pick up items when they have already carried enough items	Make a player pick up an item after their item number reached the limit. It should throw an <code>UnsupportedOperationException</code> .

Testing player looking around	Testing ideas
The player is in the initial space with the target character and the pet.	Add a player to the initial space. Use <code>assertEquals()</code> to check if the <code>lookAround</code> method returns the expected information (including target character and pet information).
The player is in a space which has a neighbor where the pet stays.	Add a player to a space which has a neighbor where the pet stays. Use <code>assertEquals()</code> to check if the <code>lookAround</code> method returns the expected information (the pet-occupied space should not reveal its information).
The player is in a space which doesn't have any items.	Add a player to a space which doesn't have any items. Use <code>assertEquals()</code> to check if the <code>lookAround</code> method returns the expected information (the item information should be correct).

Testing the start space of the pet	Testing ideas
The pet should start from space 0.	The pet should start from space 0, so we can just call <code>assertSame()</code> method to test if it stays in the

	correct space.
--	----------------

Testing moving pet	Testing ideas
The pet can be moved to a specified space	Move the pet to a specified space. Use <code>assertSame()</code> to check if it is in the expected space.

Testing pet wandering	Testing ideas
The pet should move with every turn following a depth-first traversal of the spaces in the world.	Let the game go through 4-5 turns. After each turn, check the position of the pet to confirm if it has entered each space according to the depth first rule.

Testing if the current player can be seen by others	Testing ideas
A player cannot be seen by its neighbor if the pet is in the same space.	Add a player A to the space where the pet stays, then add another player B to its neighbor. Player B shouldn't be able to see player A.
A player can be seen by other players in the same space, even if the pet is in the same space.	Add two players to the space where the pet stays. The two players should be able to see each other.
A player cannot be seen by others if there is no other player staying in the same space or neighbor spaces.	Add a player to a space which doesn't have any other player as well as neighbor players. The player shouldn't be seen by any others.

Testing computer player automatic make an attempt	Testing ideas
When a computer player stays with the target character in the same space, the player should automatically make an attempt with the most powerful item if no one can see he/she.	Add a computer player to the space where the target character stays. Make sure the player has some items and cannot be seen by others. The player should then automatically make an attempt with the most powerful item.

Testing making an attempt	Testing ideas
A computer player makes an attempt with an item successfully.	Add a computer player to the space where the target character stays. Make sure the player has some items and cannot be seen by others. The player should then make an attempt successfully.
A human player makes an	Add a human player to the space where the target

attempt with an item successfully.	character stays. Make sure the player has some items and cannot be seen by others. Make the player attack the target character. The player should then make an attempt successfully.
A computer player fails to make an attempt because there are other players in the same space.	Add a computer player to the space where the target character stays. Then add another player to the same space. Make the player attack the target character. The player should then fail to make an attempt.
A human player fails to make an attempt because there are other players in the same space.	Add a human player to the space where the target character stays. Then add another player to the same space. Make the player attack the target character. The player should then fail to make an attempt.
A computer player makes an attempt successfully with pet's help.	Add a computer player to the space where the target character stays. Make sure the player has a neighbor player and the pet is in that neighbor space. Make the player attack the target character. The player should then make an attempt successfully.
A human player makes an attempt successfully with pet's help.	Add a human player to the space where the target character stays. Make sure the player has a neighbor player and the pet is in that neighbor space. Make the player attack the target character. The player should then make an attempt successfully.
A computer player fails to make an attempt because there are other players in the neighbor space without pet.	Add a computer player to the space where the target character stays. Then add another player to a neighbor space without pet. Make the player attack the target character. The player should then fail to make an attempt.
A human player fails to make an attempt because there are other players in the neighbor space without pet.	Add a human player to the space where the target character stays. Then add another player to a neighbor space without pet. Make the player attack the target character. The player should then fail to make an attempt.
A computer player makes an attempt without any item successfully.	Add a computer player to the space where the target character stays. Make sure the player has no item and cannot be seen by others. The player should then make an attempt successfully.
A human player makes an attempt without any item successfully.	Add a human player to the space where the target character stays. Make sure the player has no item and cannot be seen by others. Make the player attack the target character. The player should then

	make an attempt successfully.
A player cannot use pokeEyes if the player has at least 1 item.	Add a player to the space where the target character stays. Make sure the player has at least 1 item and cannot be seen by others. Make the player attack the target character by poking him in the eye. This should throw an IllegalArgumentException.

Testing design for GameController

Testing start()	Testing ideas
Start the game	Use a mock model to test whether the game can successfully complete a run

Testing AddComputerPlayer	Testing ideas
Add a computer-controlled player	Use a mock model to test whether a computer controlled player is successfully added to the game after execute()

Testing AddHumanPlayer	Testing ideas
Add a humancontrolled player	Use a mock model to test whether a human controlled player is successfully added to the game after execute()

Testing DisplayPlayerInformation	Testing ideas
Display a player's information	Use a mock model to test whether a player's information is correctly displayed after execute()

Testing DisplaySpaceInformation	Testing ideas
Display a space's information	Use a mock model to test whether a space's information is correctly displayed after execute()

Testing GenerateMap	Testing ideas
Generate the world map	Use a mock model to test whether the map is successfully generated after execute()

Testing LookAround	Testing ideas
Display the neighboring information of the space a computer player is currently occupying	Use a mock model to test whether the current computer player's neighboring information is correctly displayed after execute()
Display the neighboring information of the space a human player is currently occupying	Use a mock model to test whether the current human player's neighboring information is correctly displayed after execute()

Testing MovePlayer	Testing ideas
Move a computer player from current space to a neighbor space	Use a mock model to test whether the computer player moves to expected space after execute()
Move a human player from current space to a neighbor space	Use a mock model to test whether the human player moves to expected space after execute()

Testing PickupItem	Testing ideas
A computer player pick up an item from current space	Use a mock model to test whether the chosen item is successfully picked up by the computer player after execute()
A human player pick up an item from current space	Use a mock model to test whether the chosen item is successfully picked up by the human player after execute()

Testing movePet	Testing ideas
A computer player move the pet to a specified space	Use a mock model to test if the pet is in the specified space after execute()
A human player move the pet to a specified space	Use a mock model to test if the pet is in the specified space after execute()

Testing makeAnAttempt	Testing ideas
Make an attempt on the target character's life successfully	Use a mock model to test if the target character's life is reduced after execute()
Fail to make an attempt on the target character's life	Use a mock model to test if the attack fails after execute()
A computer player automatically makes an attempt with the most powerful item	Use a mock model to test if the computer player automatically makes an attempt with the most powerful item after execute()

Testing Human player win	Testing ideas
A human player kills the target character and win the game	Use a mock model to let a human player kills the target character, and test whether the printed information shows that the human player win

Testing Computer player win	Testing ideas
A computer player kills the target character and win the game	Use a mock model to let a computer player kills the target character, and test whether the printed information shows that the computer player win

Testing target character escapes	Testing ideas
The maximum number of turns is reached in which case the target character escapes and runs away to live another day and nobody wins	Use a mock model to play the game, and make sure the target character is not killed until the game ends. Test whether the printed information shows that it's a tie game