

King Saud University College of Computer and Information Sciences Computer Science Department	
CSC 111 Introduction to Programming with Java	First Semester 1440-1441

Tutorial # 10

Q1: What is the output of the following java programs:

A.

```
public class A{
public static void main(String[] args){
char ch='A';
System.out.println("ch before calling chMethod1: "+ ch);
chMethod1(ch);
System.out.println("ch after calling chMethod1: "+ ch);
ch= chMethod2 (ch);
System.out.println("ch after calling chMethod2: "+ ch);}
public static void chMethod1(char ch){
ch=(char) (ch+1);}
public static char chMethod2(char ch{
ch=(char) (ch+1);
return ch;
}}
```

Output:

ch before calling chMethod1: A
ch after calling chMethod1: A
ch after calling chMethod2: B

B.

```
public class B{
public static void main (String[] args){
System.out.println(calc(10));
System.out.println(calc(10,4,5));
System.out.println(calc(4,6));
}
public static int calc (int x){
System.out.println("received one parameter");
return x+x;
}
public static int calc (int x, int y){
System.out.println("received two parameters");
return x+y;
}
public static double calc (int x, int y, int z){
System.out.println("received three parameters");
return x+y+z;
}}
```

Output:

received one parameter
20
received three parameters
19.0
received two parameters
10

King Saud University College of Computer and Information Sciences Computer Science Department	
CSC 111 Introduction to Programming with Java	First Semester 1440-1441

Q2. Match each method head with a method call , use line number to specify.

Methods heads:

Line 1 public static int count (int x, int y)

Line 2 public static int count (int x, int y, int z)

Line 3 public static void count (int x)

Line 4 public static double count (double x, double y)

int num1=1, answer1;

double num2=1.0, answer2;

a- answer1=count (4,5,num1);

b- answer1=count (num1,10);

c- answer2=count (num2,11.9);

d- count (num1);

e- count (num1, num2);

Method head	Method call
Line 1	b
Line 2	a
Line 3	d
Line 4	c,e

Q3: Find the error in the following code:

```
import java.util.*;
public class q3{
static Scanner console = new Scanner(System.in);
    static int k = 0;
    public static void main (String[] args){
        int x=console.nextInt();
        if (x%2==0){
            boolean x=true; //cannot redeclare an identifier
        }
        for (int i=0;i<x;i++){
            if (i==5)
                break;
            System.out.print (i);} // i exists in the loop only
    } //end of main
    public static void m1 (int[] x){
        int i;
        for (i=0; i<x.length; i++)
            x[i] = console.nextInt(); //console not read
    } //end of m1
    public static void m2 (int[] y, int index){
        System.out.printf ("%d", y[index]);
    } // m2 is nested within m1
    public static int m3 (int[] y){ //cannot have two methods with the same signature
        int sum=0; int
        for (int i=0; i<y.length; i++) //i was not declared
            sum+=y[i]++;
        if (sum >100)
            return sum-100; //didn't cover all the cases to return a value
    } //end of m3
} //end of class
```