



HEAPS

CSC212: Data Structures


Sequential Representation of binary trees

- There are three methods of representing a binary tree using array representation.

1. Using index values to represent edges:

```
class Node<T> {  
    T          data;  
    int        left;  
    int        right;  
}  
Node<T>[] BinaryTree=new Node[TreeSize];
```

Method 1: Example



Index	Element	Left	Right
1	A	2	3
2	B	4	6
3	C	0	0
4	D	0	0
5	I	0	0
6	E	7	0
7	G	5	0

Node

Method 2

2. Store the nodes in one of the natural traversals:


```
class Node<T> {  
    T                data;  
    boolean          left;  
    boolean          right;  
};
```

Pre order root left right
inorder left root right
post order left right root

```
Node<T>[] BinaryTree=new Node<T>[TreeSize];
```

Method 2: Example

root - Left - right




Index	Element	Left	Right
1	A	T	T
2	B	T	T
3	D	F	F
4	E	T	F
5	G	T	F
6	I	F	F
7	C	F	F

Elements stored in Pre-Order traversal


Method 3

3. Store the nodes in fixed positions: (i) root goes into first index, (ii) in general left child of $\text{tree}[i]$ is stored in $\text{tree}[2i]$ and right child in $\text{tree}[2i+1]$.

$A \rightarrow 1$
 $B \rightarrow 2$
 $C \rightarrow 3$
 $D \rightarrow 4$
 $E \rightarrow 5$
 $F \rightarrow 6$
 $G \rightarrow 7$



Method 3: Example




A	B	C	D	E	-	-	-	-	G	-	
1	2	3	4	5	6	7	8	9	10	11	12

Heaps

- A heap is a complete binary tree.
- A heap is best implemented in sequential representation (using an array).
- Two important uses of heaps are:
 - (i) efficient implementation of priority queues
 - (ii) sorting -- Heapsort.

A Heap




Any node's key value is less than its children's.

Heaps


- Heaps are represented sequentially using the third method. 2^i & 2^{i+1}
- Heap is a complete binary tree: shortest-path length tree with nodes on the lowest level in their leftmost positions.
- Complete Binary Tree: let h be the height of the heap
 - for $i = 0, \dots, h - 1$, there are 2^i nodes of depth i
 - at depth $h - 1$, all nodes in the last level are as far left as possible

Heaps (Cont.)

- Max-Heap has max element as root. Min-Heap has min element as root.
- The elements in a heap satisfy heap conditions: for Min-Heap: $\text{key}[\text{parent}] \leq \text{key}[\text{left-child}]$ and $\text{key}[\text{right-child}]$.
- The **last node** of a heap is the rightmost node of maximum depth



Heap: An example




**All the three arrangements
satisfy min heap conditions**

[1]	10	10	10
[2]	20	30	40
[3]	25	20	20
[4]	30	40	50
[5]	40	50	42
[6]	42	25	30
[7]	50	55	25
[8]	52	52	52
[9]	55	42	55



Heap: An example




**All the three arrangements
satisfy min heap conditions**

[1]	10	10	10
[2]	20	30	40
[3]	25	20	20
[4]	30	40	50
[5]	40	50	42
[6]	42	25	30
[7]	50	55	25
[8]	52	52	52
[9]	55	42	55



Heap: An example



**All the three arrangements
satisfy min heap conditions**

[1]	10	10	10
[2]	20	30	40
[3]	25	20	20
[4]	30	40	50
[5]	40	50	42
[6]	42	25	30
[7]	50	55	25
[8]	52	52	52
[9]	55	42	55



ADT Heap



Elements: The elements are called HeapElements.

Structure: The elements of the heap satisfy the heap conditions.

Domain: Bounded. Type name: Heap.

ADT Heap

Operations:

- **Method** SiftUp ()
Input: none. **requires:** Elements $H[1], H[2], \dots, H[n-1]$ satisfy heap conditions.
results: Elements $H[1], H[2], \dots, H[n]$ satisfy heap conditions. **Output:** none.
- **Method** SiftDown (int i)
Input: i. **requires:** Elements $H[i+1], H[i+2], \dots, H[n]$ satisfy the heap conditions.
results: Elements $H[i], H[i+1], \dots, H[n]$ satisfy the heap conditions.
Output: none.
- **Method** Insert(int key, T data)
input: key, data. **requires:** Elements $H[1], H[2], \dots, H[n]$ satisfy heap conditions.
results: The key and data are inserted in $H[n+1]$. Elements $H[1], H[2], \dots, H[n+1]$ must satisfy the heap conditions. **Output:** none

ADT Heap



Operations:

- **Method** RemoveRoot(HeapElement<T> result)
input: none. **requires:** Elements $H[1], H[2], \dots, H[n]$ satisfy heap condition.
results: The HeapElement in $H[1]$ is removed, and its value is assigned to result. Elements $H[1], H[2], \dots, H[n-1]$ must satisfy the heap conditions. **output:** none.
- **Method** Full(boolean result)
- **Method** Size(int result)

Insertion into a Heap



- The insertion algorithm consists of three steps
 - Find the insertion node z (the new last node)
 - Store k at z
 - Restore the heap-order property (discussed next)

Upheap




- After the insertion of a new key k , the heap-order property may be violated
- Algorithm upheap (siftUp) restores the heap-order property by swapping k along an upward path from the insertion node
- Upheap terminates when the key k reaches the root or a node whose parent has a key smaller than or equal to k
- Since a heap has height $O(\log n)$, upheap runs in $O(\log n)$ time


Example 1



Example 2





Example 3




Removal from a Heap

- The removal algorithm consists of three steps
 - Replace the root key with the key of the last node w
 - Remove w
 - Restore the heap-order property (discussed next)




Downheap


- After replacing the root key with the key k of the last node, the heap-order property may be violated
- Algorithm downheap (siftDown) restores the heap-order property by swapping key k along a downward path from the root
- Downheap terminates when key k reaches a leaf or a node whose children have keys greater than or equal to k
- Since a heap has height $O(\log n)$, downheap runs in $O(\log n)$ time




Downheap



Downheap




Downheap




DownHeap/SiftDown


Downheap




Downheap




Downheap



Downheap




Downheap




DownHeap/SiftDown


Downheap




Downheap




Downheap



Downheap




Downheap




DownHeap/SiftDown

Downheap



Heap applications



Priority queue

- Consider a priority queue with n items implemented by means of a heap
 - the space used is $O(n)$
 - methods **enqueue** and **serve** take $O(\log n)$ time
 - methods **length**, **full** take time $O(1)$ time

Heap sort


- Using a heap-based priority queue, we can sort a sequence of n elements in $O(n \log n)$ time
- The resulting algorithm is called heap-sort
- Heap-sort is much faster than quadratic sorting algorithms, such as bubble sort and selection-sort



Priority Queue

Heaps and Priority Queues

- We can use a heap to implement a priority queue
- We store a (key, element) item at each internal node
- We keep track of the position of the last node



ADT Heap: Element



```
public class HeapElem <T>{  
    public int key;  
    public T data;  
  
    public HeapElem(int _key, T _data){  
        key= _key;  
        data= _data;  
    }  
}
```

Priority Queue as Heap



Representation as a Heap

```
public class HeapPQ<T> {  
  
    private Heap<T> heap;  
  
    public HeapPQ(int _maxSize){  
        heap= new Heap<T>(_maxSize);  
    }  
}
```

Priority Queue as Heap



```
public int length(){
    return heap.size();
}

public boolean full(){
    return heap.full();
}

public void enqueue(int pr, T val){
    heap.insert(pr, val);
}



public HeapElem<T> serve(){
    return heap.removeRoot();
}
```



Heap sort

Vector-based Heap Implementation

- We can represent a heap with n keys by means of a vector of length $n + 1$
- For the node at rank i
 - the left child is at rank $2i$
 - the right child is at rank $2i + 1$
- Links between nodes are not explicitly stored
- The cell at rank 0 is not used
- Operation insert corresponds to inserting at position $n + 1$
- Operation serve corresponds to removing at position n
- Yields in-place heap-sort




Merging Two Heaps

- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property




Merging Two Heaps

- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property



Merging Two Heaps


- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property



Merge

Merging Two Heaps


- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property



Downheap/SiftDown

Merging Two Heaps


- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property



Downheap/SiftDown

Merging Two Heaps


- We are given two two heaps and a key k
- We create a new heap with the root node storing k and with the two heaps as subtrees
- We perform downheap to restore the heap-order property




Downheap/SiftDown

Bottom-up Heap Construction



- We can construct a heap storing n given keys in using a bottom-up construction with $\log n$ phases
- In phase i , pairs of heaps with $2^i - 1$ keys are merged into heaps with $2^{i+1} - 1$ keys





Example





Example (contd.)



Example (contd.)



Example (end)



HeapSort

- Heap can be used for sorting. Two step process:
 - Step 1: the data is put in a heap.
 - Step 2: the data are extracted from the heap in sorted order.
- HeapSort based on the idea that heap always has the smallest or largest element at the root.

ADT Heap: Implementation

size = 5 4

```
public void sort(){
```

```
    int n= size;
```

```
    for(int i= 1; i<=n; i++){
```

```
        int tmpKey= keys[1];
```

```
        T tmpData= data[1];
```

```
        keys[1]= keys[size];
```

```
        data[1]= data[size];
```

```
        size--;
```

```
        siftDown(1);
```


```
        keys[size+1]= tmpKey;
```

```
        data[size+1]= tmpData;
```


```
    }
```

```
}
```

```
}
```



tmp = A




the array after one iteration

Example of Heap-sorting

Keys →

idx →

X	600 25	50	250	10	33	130	200	5	2	25 600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = ~~10~~ 9
tmp = 600

X	600	50	250	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 10
tempKey = 600

X	25	50	250	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 10
tempKey = 600

X	25	50	250	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	25	50	250	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	250	50	25	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	250	50	25	10	33	130	200	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	250	50	200	10	33	130	25	5	2	25		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	250	50	200	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 600

X	250	50	200	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 250

X	2	50	200	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 9
tempKey = 250

X	2	50	200	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	2	50	200	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	200	50	2	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	200	50	2	10	33	130	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	200	50	130	10	33	2	25	5	2	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	200	50	130	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 250

X	200	50	130	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 200

X	5	50	130	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 8
tempKey = 200

X	5	50	130	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	5	50	130	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	130	50	5	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	130	50	5	10	33	2	25	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	130	50	25	10	33	2	5	5	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	130	50	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 200

X	130	50	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 130

X	5	50	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 7
tempKey = 130

X	5	50	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	5	50	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	50	5	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	50	5	25	10	33	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	50	33	25	10	5	2	5	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	50	33	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 130

X	50	33	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12



```


public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6

tmpKey = 50

X	2	33	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 6
tempKey = 50

X	2	33	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	2	33	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	33	2	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	33	2	25	10	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	33	10	25	2	5	2	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	33	10	25	2	5	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 50

X	33	10	25	2	5	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 5
tempKey = 33

X	5	10	25	2	5	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4
tempKey = 33

X	5	10	25	2	5	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4
tempKey = 33

X	25	10	5	2	5	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4
tempKey = 33

X	25	10	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4
tempKey = 33

X	25	10	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12



```


public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4

tempKey = 25

X	2	10	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 4
tempKey = 25

X	2	10	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 25

X	2	10	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 25

X	10	2	5	2	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 25

X	10	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 25

X	10	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 10

X	5	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 3
tempKey = 10

X	5	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = 2
tempKey = 10

X	5	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = 2
tempKey = 10

X	5	2	5	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = 2
tempKey = 10

X	5	2	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = 2
tempKey = 10

X	5	2	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12




```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
  
```

Size = 2
 tmpKey = 5

X	2	2	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12



```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 2
tempKey = 5

X	2	2	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12

2

```
public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
```

Size = 1
tempKey = 5

X	2	2	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12

2

```

public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}

```

Size = 1
tempKey = 5

X	2	5	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12

2

```
public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
```

Size = 1
tempKey = 5

X	2	5	10	25	33	50	130	200	250	600		
0	1	2	3	4	5	6	7	8	9	10	11	12

2

```
public void sort(){
    int n= size;
    for(int i= 1; i < n; i++){
        int tmpKey= keys[1];
        T tmpData= data[1];
        keys[1]= keys[size];
        data[1]= data[size];
        size--;
        siftDown(1);
        keys[size+1]= tmpKey;
        data[size+1]= tmpData;
    }
}
```

Size = 1
tempKey = 5