



King Saud University

College of Computer and Information Sciences

Department of Computer Science

Data Structures CSC 212**Final Exam Solution - Spring 2018**

Date: 05/05/2018

Duration: 3 hours

Guidelines

- No calculators or any other electronic devices are allowed in this exam.
- Use a pencil in choice questions.

Student ID:

Name:

Section:

Instructor:

1	2.1	2.2	3.1	3.2	4	5	6	7	8	Total

Question 1 16 points

Grading scheme: Part a and b: 1pt fo each question. Part c: 2 pts for 1, 2, 3 and 1 pt for 4.(a) Choose the correct frequency for every line as well as the total O of the following code:

```

1  i = 1;
2  while(i < n)
3      i = i * 2;
```

- Line 1: (A) 0 (B) 1 (C) 2 (D) n (E) n^2
- Line 2: (A) n (B) $n + 1$ (C) $\log(n)$ (D) $\log(n) + 1$ (E) 2^n
- Line 3: (A) n (B) $n + 1$ (C) $\log(n)$ (D) $\log(n) + 1$ (E) 2^n
- Total O : (A) 1 (B) n (C) n^2 (D) $\log(n)$ (E) 2^n

(b) Choose the correct frequency for every line as well as the total O of the following code:

```

1  c = 10;
2  for (i = 1; i <= c; i++)
3      for (j = 0; j < n; j++)
4          count++;
```

- Line 1: (A) 0 (B) 1 (C) 2 (D) n (E) n^2
- Line 2: (A) n (B) c (C) 11 (D) 10 (E) 9
- Line 3: (A) n (B) $10n$ (C) $10(n + 1)$ (D) c (E) n^2
- Line 4: (A) $count + 2$ (B) $10n$ (C) $11n$ (D) n^2 (E) $n(n + 1)/2$
- Total O : (A) 1 (B) n (C) n^2 (D) $n \log(n)$ (E) n^3

(c) Choose the correct answer:

- $n^3 + n^2 \log n$ is : (A) $O(n^3)$ (B) $O(n^2)$ (C) $O(n^2 \log(n))$ (D) $O(n^5)$ (E) None
- $2^n + n^n$ is : (A) $O(n)$ (B) $O(n^2)$ (C) $O(2^n)$ (D) $O(n^n)$ (E) None
- $n^4 \log n + 2^n$ is : (A) $O(n)$ (B) $O(n^4)$ (C) $O(n^5)$ (D) $O(\log(n))$ (E) None

4. When traversing all nodes in a binary tree of depth d . The complexity would be:

- (A) $O(d)$ (B) $O(d^2)$ (C) $O(2^d)$ (D) $O(\log(d))$ (E) None

Question 2 10 points

Grading scheme: 1pt for every question.

(a) Complete the code below by choosing the correct answer:

• Line 2:

- (A) `!m.find(nb2)`
 (B) `m.find(nb1)`
 (C) `!m.find(nb1)`
 (D) `m.find(nb2)`
 (E) None

• Line 3:

- (A) `return true`
 (B) `return m.find(nb1)`
 (C) `return false`
 (D) `return !m.find(nb1)`
 (E) None

• Line 4:

- (A) `m.enqueue(nb2)`
 (B) `m.retrieve()`
 (C) `m.retrieve(nb1)`
 (D) `m.find(nb2)`
 (E) None

• Line 5:

- (A) `false`
 (B) `m.retrieve().serve()`
 (C) `true`
 (D) `m.find(nb1)`
 (E) None

• Line 6:

- (A) `for (int i = q.length(); i >= 0 ; i--)`
 (B) `for (int i = 1; i <= q.length(); i++)`
 (C) `while (q.length() > 0)`
 (D) `for (int i = 0; i <= q.length(); i++)`
 (E) None

• Line 7:

- (A) `q.serve()`
 (B) `q.serve(nb2)`
 (C) `m.retrieve()`
 (D) `q.head.data`
 (E) None

• Line 8:

- (A) `q.enqueue(r)`
 (B) `m.enqueue(r)`
 (C) `q.enqueue()`
 (D) `q.serve(r)`
 (E) None

• Line 9:

- (A) `nb2 == r.to`
 (B) `nb1.equals(r.to)`
 (C) `nb1 == r.from`
 (D) `nb2.equals(r.from)`
 (E) None

• Line 10:

- (A) `found = (nb2 == r.to)`
 (B) `found = false`
 (C) `found = true`
 (D) `found = !found`
 (E) None

• Line 12:

- (A) `return found`
 (B) `return found || (q.length() == 0)`
 (C) `return false`
 (D) `return true`
 (E) None

(b) Complete the code below by choosing the correct answer:

- | | |
|---|---|
| <ul style="list-style-type: none"> • Line 3: <ul style="list-style-type: none"> <input type="radio"/> (A) while (i < q.length()) <input type="radio"/> (B) while (q.length() > 0) <input type="radio"/> (C) for (int i = 1; i <= q.length(); i--) <input checked="" type="radio"/> (D) for (int i = 0; i < q.length(); i++) <input type="radio"/> (E) None • Line 5: <ul style="list-style-type: none"> <input type="radio"/> (A) q.serve() <input type="radio"/> (B) st.push(q) <input type="radio"/> (C) q.enqueue() <input type="radio"/> (D) st.pop() <input checked="" type="radio"/> (E) None • Line 6: <ul style="list-style-type: none"> <input type="radio"/> (A) found && st.empty() <input type="radio"/> (B) found <input checked="" type="radio"/> (C) !found <input type="radio"/> (D) found && !st.empty() <input type="radio"/> (E) None • Line 8: <ul style="list-style-type: none"> <input checked="" type="radio"/> (A) !st.empty() && !found <input type="radio"/> (B) !found <input type="radio"/> (C) st.empty() found <input type="radio"/> (D) st.empty() && !found <input type="radio"/> (E) None • Line 9: <ul style="list-style-type: none"> <input type="radio"/> (A) st.push() <input checked="" type="radio"/> (B) st.pop() <input type="radio"/> (C) q.serve() <input type="radio"/> (D) st.serve() <input type="radio"/> (E) None | <ul style="list-style-type: none"> • Line 10: <ul style="list-style-type: none"> <input checked="" type="radio"/> (A) ts.push(r) <input type="radio"/> (B) ts.push(st.pop()) <input type="radio"/> (C) st.push(r) <input type="radio"/> (D) ts.pop() <input type="radio"/> (E) None • Line 11: <ul style="list-style-type: none"> <input type="radio"/> (A) nb.equals(r.from) <input type="radio"/> (B) nb == r.from <input type="radio"/> (C) nb == r.to <input checked="" type="radio"/> (D) nb.equals(r.to) <input type="radio"/> (E) None • Line 12: <ul style="list-style-type: none"> <input type="radio"/> (A) found = (nb == r.to) <input type="radio"/> (B) return true <input checked="" type="radio"/> (C) found = true <input type="radio"/> (D) found = false <input type="radio"/> (E) None • Line 14: <ul style="list-style-type: none"> <input type="radio"/> (A) ts.empty() <input type="radio"/> (B) !st.empty() <input checked="" type="radio"/> (C) !ts.empty() <input type="radio"/> (D) st.empty() <input type="radio"/> (E) None • Line 15: <ul style="list-style-type: none"> <input type="radio"/> (A) st.push(q.serve().pop()) <input type="radio"/> (B) st.push(st.pop()) <input type="radio"/> (C) ts.push(st.pop()) <input checked="" type="radio"/> (D) st.push(ts.pop()) <input type="radio"/> (E) None |
|---|---|

Question 3 10 points

Grading scheme: All questions 1 pt except part (a) Line 7: 2 pts.

- (a) Write the method `public boolean isPathTree()`, member of the `BT` class, which returns true if the `BT` is a path tree, and false otherwise. A `BT` is a path tree if it does not have any node that has two children.

The method `public boolean isPathTree()` calls a **recursive** method `private boolean isPTRec(BTNode p)`.

Choose the correct option to complete the code of these methods:

```

1 public boolean isPathTree() {
2     ...
3 }
4 private boolean isPTRec(BTNode<T> p) {
5     ...
6     ...
7     ...
8 }

```

1. Line 2:

- ☐ (A) `return ((isPTRec(root.left))&&(isPTRec(root.right)))`;
☐ (B) `return ((isPathTree(root.left))&&(isPathTree(root.right)))`;
☐ (C) `return ((isPTRec(current.left))&&(isPTRec(current.right)))`;
☒ (D) `return isPTRec(root)`;
☐ (E) None

2. Line 5:

- ☐ (A) `if (p != null) return true`;
☒ (B) `if (p == null) return true`;
☐ (C) `if (root == null) return true`;
☐ (D) `if (p != null) return false`;
☐ (E) None

3. Line 6:

- ☐ (A) `if ((p.left==null)|| (p.right==null)) return`

`false`;

- ☐ (B) `if ((p.left!=null)|| (p.right!=null)) return false`;
☐ (C) `if ((p.left==null)&&(p.right==null)) return true`;
☒ (D) `if ((p.left!=null)&&(p.right!=null)) return false`;
☐ (E) None

4. Line 7:

- ☐ (A) `return true`;
☒ (B) `return isPTRec(p.left)&& isPTRec(p.right)`;
☐ (C) `return isPTRec(p.left)|| !isPTRec(p.right)`;
☐ (D) `return !isPTRec(p.left)|| !isPTRec(p.right)`;
☐ (E) None

(b) Choose the correct result in each of the following cases:

1. The list 1: *A, B, C, D, E*, after calling `1.f(1)`, 1 becomes:

- ☐ (A) *B, C, D, E* ☐ (B) *A, B, E, C, D* ☒ (C) *E, B, C, D* ☐ (D) *A, D, E, B, C* ☐ (E) None

2. The list 1: *A, B, C, D, E*, after calling `1.f(0)`, 1 becomes:

- ☐ (A) *empty* ☒ (B) *E, A, B, C, D* ☐ (C) *B, C, D, E, A* ☐ (D) *A, B, C, D, E* ☐ (E) None

3. The list 1: *A, B, C, D, E*, after calling `1.f(2)`, 1 becomes:

- ☐ (A) *empty* ☐ (B) *E, D, C, B, A* ☐ (C) *A, D, E, B, C* ☒ (D) *E, C, D* ☐ (E) None

4. The list 1: *A, B, C, D, E*, after calling `1.f(5)`, 1 becomes:

- ☐ (A) *A* ☐ (B) *E, A, B, C, D* ☐ (C) *C, D, E, A, B* ☒ (D) *A, B, C, D, E* ☐ (E) None

Question 4..... 14 points

Grading scheme: Part (a) and (c) 1.5pts each question. Part (b) 2 pts.

(a) Consider the following heap represented as an array: 4, 16, 14, 22, 20, 18. Choose the correct answer for every operation (all operations are done on the above heap).

- Heap after inserting 6: (A) 4,16,14,22,20,18,6 (B) 4,6,16,22,20,18,14 (C) 4,16,14,22,20,6,18
(D) 6,16,4,22,20,18,14 (E) **None**
- Heap after inserting 16: (A) **4,16,14,22,20,18,16** (B) 4,16,16,22,20,18,14 (C) 4,16,14,22,20,16,18
(D) 4,16,14,16,20,18,22 (E) None
- Heap after inserting 0: (A) 4,16,14,22,20,18,0 (B) **0,16,4,22,20,18,14** (C) 4,16,0,22,20,18,14
(D) 0,16,4,22,20,14,18 (E) None
- Heap after deleting one key: (A) 16,22,14,18,20 (B) **14,16,18,22,20** (C) 16,14,20,18,22
(D) 16,20,14,22,18 (E) None
- Heap after deleting two keys: (A) 16,22,14,18 (B) 20,18,14,22 (C) 16,20,14,22 (D) 22,14,20,18
(E) **None**






(b) What is the result of a bottom-up min-heap construction of the array: 1,5,11,4,6,0? (A) 0,1,4,6,5,11
(B) 1,0,4,5,6,11 (C) **0,4,1,5,6,11** (D) 0,4,1,6,11,5 (E) None.


(c) Choose the correct answer:


- Bottom-up heap construction is: (A) **$O(n)$** (B) $O(\log n)$ (C) $O(n^2 \log n)$ (D) $O(n^2)$
(E) None.
- The serve operation in a heap priority queue is: (A) $O(1)$ (B) **$O(\log n)$** (C) $O(n)$
(D) $O(n \log n)$ (E) None.
- What is the minimum number of nodes in a heap of height k ? (A) $2^k - 1$ (B) $\log k$ (C) **2^k**
(D) 2^{k-1} (E) None.

Question 5 14 points


Grading scheme: 2pt for every question.

- After inserting the key 46 in the AVL , the tree becomes: (A)  (B)  (C)  (D) 
(E) None


- After inserting the key 2 in the AVL , the tree becomes:




3. After deleting the key 9 from the AVL , the tree becomes:




4. After deleting the key 4 from the AVL , the tree becomes:




5. After deleting the key 10 from the AVL , the tree becomes:



6. After deleting the key 1 from the AVL , the tree becomes:



7. Consider the following tree . If the balance of A is -2 and that of B is -1, then after performing a single right rotation at A, then:

- (a) The balance of A becomes: 0
- (b) The balance of B becomes: 0

Grading scheme: (Total number of mistakes / 50 * 14) rounded up to the nearest 0.5.

1. Linear rehashing ($c=2$). Fill in the following table:

Key	14	15	4	16	27	20	35	47	10	7
Position	4	5	6	8	7	0	9	1	2	3
Number of probes	1	1	2	2	1	1	3	3	2	4

2. External chaining. Fill in the following table:

Key	14	15	4	16	27	20	35	47	10	7
Index of the list	4	5	4	6	7	0	5	7	0	7

3. Coalesced chaining with cell size 3 and address region size 7 (you must change the hash function to $H(key) = key \% 7$.) Fill in the following table (put -1 if there is no next element):

Key	14	15	4	16	27	20	35	47	10	7
Position	0	1	4	2	6	9	8	5	3	7
Index of next element	8	-1	-1	-1	9	-1	7	-1	-1	-1

Question 7 14 points

Grading scheme: 2pt for every question.

1	3	6
---	---	---

1. After inserting the key 7 in the B+ tree, the **root** of tree becomes:

- (A)

5	
---	--

 (B)

5	6
---	---


 (C)

6	
---	--

 (D)

7	
---	--

 (E) None



2. After inserting the key 14 in the B+ tree, the **root** of the tree becomes:

- (A)

7	11
---	----

 (B)

7	10
---	----


 (C)

6	
---	--

 (D)

8	
---	--


 (E) None



3. After inserting the key 10 in the B+ tree, the **root** of the tree

becomes:

- (A) [5 | 10] (B) [7 | 11] (C) [7 | 10] (D) [7 | 9] (E) None




4. After deleting the key 9 from the B+ tree

, the **root** of the tree

becomes:

- (A) [8 |] (B) [7 | 11] (C) [7 | 10] (D) [7 | 9] (E) None




5. After deleting the key 12 from the B+ tree

, the **root** of the tree

becomes:

- (A) [8 |] (B) [7 | 11] (C) [7 | 10] (D) [7 | 9] (E) None



6. After deleting the key 11 from the B+ tree

, the **root** of the tree

becomes:

- (A) [7 |] (B) [7 | 12] (C) [7 | 8] (D) [12 |] (E) None


7. A B+ tree of order 4 leaves can contain the following number of data elements:

- (A) 3 to 4 elements (B) 2 to 4 elements (C) 1 to 4 elements (D) 4 to 4 elements (E) None

Question 8 8 points

Grading scheme: (1) 3pts: -0.5pts for every incorrect edge (missing or extra); (2) 3pts: -0.25pts for every incorrect edge (missing or extra) and round up to the nearest 0.5; (3) 2pts (1 + 1).

1. Given the following adjacency matrix, draw the weighted graph it represents.



2. Give the adjacency list representation of the graph.

0	$\rightarrow (1, 1) \rightarrow (2, 2)$
1	$\rightarrow (0, 1) \rightarrow (2, 1) \rightarrow (3, 3)$
2	$\rightarrow (0, 2) \rightarrow (1, 1) \rightarrow (3, 4)$
3	$\rightarrow (1, 3) \rightarrow (2, 4)$
4	$\rightarrow (5, 3)$
5	$\rightarrow (4, 3)$

3. What is the cycle with the largest number nodes in the graph? What is its total weight?

Cycle: $(0, 1, 3, 2, 0)$ or any other equivalent cycle.

Total weight: 10.