Lecture 7 z-Transform

Digital Signal Processing by Yu Yajun @ SUSTech

353

Motivation

- Fourier Transform provides a frequency domain representation of discrete-time signal, but it may not exist for some sequences. (Reason?)
- Not easy for algebraic manipulations.
- z-transform used for:
 - Analysis of LTI systems
 - Solving difference equations
 - Determining system stability
 - Finding frequency response of stable systems

Eigen Functions of LTI Systems

• Consider an LTI system with impulse response h[n]:

$$x[n] \qquad y[n] \qquad$$

- We already showed that $x[n] = e^{j\omega n}$ are eigenfunctions
- What if $x[n] = z^n$, where z is a continuous complex variable z = Re(z) + jIm(z)?

Digital Signal Processing by Yu Yajun @ SUSTech

355

Eigen Functions of LTI Systems

$$z^n \longrightarrow h[n] \qquad y[n]$$

$$y[n] = \sum_{k=-\infty}^{\infty} h[k]z^{n-k} = \left(\sum_{k=-\infty}^{\infty} h[k]z^{-k}\right)z^n = H(z)z^n$$

- $x[n] = z^n$ are also eigen-functions of LTI Systems
- H(z) is called a z-transform transfer function
- H(z) exists for larger class of h[n] than $H(e^{j\omega})$

Definition

• *z*-Transform:

$$\angle X(z) = Z\{x[n]\} = \sum_{n=-\infty}^{\infty} x[n]z^{-n} \lor$$

where, z is a complex variable.

Example

\overline{n}	$n \le -1$	0	1	2	3	4	5	n > 5
x[n]	0	2	4	6	4	2	1	0

$$X(z) = 2 + 4z^{-1} + 6z^{-2} + 4z^{-3} + 2z^{-4} + z^{-5}$$

Digital Signal Processing by Yu Yajun @ SUSTech

357


z-Transform vs. DTFT

• Let $z = re^{j\omega}$, then the expression reduces to

$$X(re^{j\omega}) = \sum_{n=-\infty}^{\infty} x[n]r^{-n}e^{-j\omega n},$$

This can be interpreted as the Fourier Transform of the modified sequence $x[n]r^{-n}$.

- ্রান্ত্র If r = 1 (i. e. , |z| = 1), the z-transform reduces to DTFT.
- The contour |z| = 1 is a circle in the z plan of unity radius, called **unit circle**.



z-Transform and LTI system

Consider a system of an unit delay system

$$y[n] = x[n-1]$$

The impulse response of the unit delay is

$$h[n] = \delta[n-1]$$

• Its z-transform is

$$H(z) = z^{-1}$$

$$Z^{-1}$$

• Similarly, delay of k samples: $h[n] = \delta[n - k]$



Digital Signal Processing by Yu Yajun @ SUSTech

359

z-Transform of FIR System


Consider a causal FIR LTI system

ider a causal FIR LIT system
$$y[n] = \sum_{m=0}^{M} b_m x[n-m]$$
apulse response is

• Its impulse response is

$$h[n] = \sum_{m=0}^{M} b_m \delta[n-m]$$
 $x[n-2]$

n	n<0	0	1	2	•••	M	<i>n</i> > <i>M</i>
h[n]	0	b_0	\boldsymbol{b}_1	b_2	•••	b_M	0



System Diagram of an FIR system

z-Transform of FIR System

Take z-transform on both side of the input-output relation

$$Y(z) = Z\{y[n]\} = Z\left\{\sum_{m=0}^{M} b_m x[n-m]\right\} = \sum_{n=-\infty}^{\infty} \sum_{m=0}^{M} b_m x[n-m] z^{-n}$$

$$= \sum_{m=0}^{M} b_m \sum_{n=-\infty}^{\infty} x[n-m] z^{-n} = \sum_{m=0}^{M} b_m z^{-m} \sum_{n=-\infty}^{\infty} x[n-m] z^{-(n-m)}$$


$$= \sum_{m=0}^{M} b_m z^{-m} Z\{x[n]\} = Z\{h[n]\} X(z) = H(z) X(z)$$

The z-transform of the output of a FIR system is the product of the z-transform of the input signal and the z-transform of the impulse response.

Digital Signal Processing by Yu Yajun @ SUSTech

361

Transfer Function



is called the **z-transform transfer function** (or system function) of a LTI FIR system

Transfer Function and Impulse Response

• When the input $x[n] = \delta[n]$, the *z*-transform of the impulse response satisfies :

$$Z\{h[n]\} = H(z)Z\{\delta[n]\}.$$

• Since the *z*-transform of the unit impulse $\delta[n]$ is equal to one, we have

$$Z\{h[n]\} = H(z)$$


That is, the *z*-transform transfer function H(z) is the *z*-transform of the impulse response h[n].

Digital Signal Processing by Yu Yajun @ SUSTech

363

364

Cascade & Parallel Connection



Example

Consider an FIR system

$$y[n] = 6x[n] - 5x[n-1] + x[n-2]$$

- So, the impulse response is $h[n] = \{6, -5, 1\}, 0 \le n \le 2$
- The z-transform transfer function is:

$$H(z) = 6 - 5z^{-1} + z^{-2}$$

$$= (3 - z^{-1})(2 - z^{-1}) = 6\frac{\left(z - \frac{1}{3}\right)\left(z - \frac{1}{2}\right)}{z^2}$$


Digital Signal Processing by Yu Yajun @ SUSTech

365

z-transform of Difference Equation

$$\sum_{m=0}^{N} b_m y[n-m] = \sum_{m=0}^{M} a_m x[n-m]$$

• Revisit system diagram for normalized $b_0 = 1$



 Take z-transform on both sides of the input-output relation

$$\sum_{m=0}^{N} b_m Y(z) z^{-m} = \sum_{m=0}^{M} a_m X(z) z^{-m}$$

• We have:

$$\frac{Y(z)}{X(z)} = \frac{\sum_{m=0}^{M} a_m z^{-m}}{\sum_{m=0}^{N} b_m z^{-m}} \triangleq H(z)$$

- *H*(*z*) is the *z*-transform transfer function of the LTI system defined by the linear constant-coefficient difference equation.
- The multiplication rule still holds: Y(z) = H(z)X(z), i.e.,

$$Z\{y[n]\} = H(z)Z\{x[n]\}$$

Digital Signal Processing by Yu Yajun @ SUSTech

367

Rational z-transform

- The transfer function of a difference equation (or a generally infinite impulse response (IIR) system) is a rational form H(z) = P(z)/D(z).
- Since LTI systems are often realized by difference equations, the rational form is the most common and useful form of *z*-transforms.
- LTI system with z-transforms represented as a rational function of z^{-1}

$$H(z) = \frac{P(z)}{D(z)} = \frac{p_0 + p_1 z^{-1} + \dots + p_{M-1} z^{-(M-1)} + p_M z^{-M}}{d_0 + d_1 z^{-1} + \dots + d_{N-1} z^{-(N-1)} + d_N z^{-N}}$$


where the degree of P(z) is M, and that of D(z) is N. The degree of the system is the larger one of M and N.

Alternate representations:

• A ratio of two polynomials in *z*,

$$H(z) = z^{(N-M)} \frac{p_0 z^M + p_1 z^{M-1} + \dots + p_{M-1} z + p_M}{d_0 z^N + d_1 z^{N-1} + \dots + d_{N-1} z + d_N}$$

• A product of second order rational z-transforms,



Digital Signal Processing by Yu Yajun @ SUSTech

369

• For the **z**-transform of General Difference Equation

$$\sum_{m=0}^{N} b_m Y(z) z^{-m} = \sum_{m=0}^{M} a_m X(z) z^{-m}$$

• When b_0 is normalized to 1, and $b_m = 0$ for $m = 1 \dots N$, the difference equation degenerates to an FIR system we have investigated before.

$$H(z) = \frac{Y(z)}{X(z)} = \sum_{m=0}^{M} a_m z^{-m}$$

 It can still be represented by a rational form of the variable z as

$$H(z) = \frac{\sum_{m=0}^{M} a_m z^{(M-m)}}{z^M}$$


Poles and Zeros

- **才&**% 小
- The **pole** of a *z*-transform X(z) are the values of *z* for which $X(z) = \infty$.
- The **zero** of a *z*-transform X(z) are the values of *z* for which X(z) = 0.
- When X(z) = P(z)/D(z) is a rational form, and both P(z) and D(z) are polynomials of z, the poles of X(z) are the roots of D(z), and the zeros are the roots of P(z), respectively.

Digital Signal Processing by Yu Yajun @ SUSTech

371

Examples



- Zeros of a system function
 - The system function of the FIR system y[n] = 6x[n] 5x[n-1] + x[n-2] has been shown as

$$H(z) = 6 \frac{\left(z - \frac{1}{3}\right)\left(z - \frac{1}{2}\right)}{z^2}$$

- The zeros of this system are 1/3 and 1/2, and the pole is 0.
- Since 0 and 0 are double roots of D(z), the pole is a second-order pole.

- In most practical cases, the complex poles and zeros of z-transforms occur as complex conjugate pairs, and simple poles and zeros (i.e., poles or zeros of order 1) are real.
- In such cases, rational *z*-transform are ratios of polynomials with real coefficients.
- For example, let $z = a_i \pm jb_i$ be a pair of complex conjugate poles of the rational z-transform H(z), where a_i and b_i are real, i.e.,

$$H(z) = \frac{Y(z)}{(z - a_i - jb_i)(z - a_i + jb_i)}$$

$$= \frac{Y(z)}{(z - a_i)^2 + b_i^2} = \frac{Y(z)}{z^2 - 2a_i z + (a_i^2 + b_i^2)}$$

Digital Signal Processing by Yu Yajun @ SUSTech

373

Region of Convergence (ROC)

- **ROC:** the set \mathcal{R} of values of z for which a sequence's ztransform converges, i.e., $\sum_{n=-\infty}^{\infty} x[n]z^{-n}$ converges.
- Since z-transform of x[n] is equivalent to DTFT of $x[n]r^{-n}$, if $x[n]r^{-n}$ is absolutely summable, i.e., $\sum_{n=-\infty}^{\infty}|x[n]r^{-n}|<\infty$,

$$\sum_{n=-\infty}^{\infty} |x[n]r^{-n}| < \infty,$$

the z-transform of x[n] uniformly converges.


ROC examples

• Example 1: Right-sided sequence $x[n] = a^n \mu[n]$

$$X(z) = \sum_{n=0}^{\infty} a^n z^{-n} = \sum_{n=0}^{\infty} (az^{-1})^n$$

recall:
$$1 + x + x^2 + \dots = \frac{1}{1-x}$$
, if $|x| < 1$

- So, $X(z) = \frac{1}{1 az^{-1}}$, for $|az^{-1}| < 1$
- ROC = $\{z: |z| > |a|\}$



Digital Signal Processing by Yu Yajun @ SUSTech

375


ROC examples

• Example 2:
$$x[n] = \left(\frac{1}{2}\right)^n \mu[n] + \left(-\frac{1}{3}\right)^n \mu[n]$$

$$X(z) = \frac{1}{1 - \frac{1}{2}z^{-1}} + \frac{1}{1 + \frac{1}{3}z^{-1}},$$

• ROC =
$$\left\{z: |z| > \frac{1}{2}\right\} \cap \left\{z: |z| > \frac{1}{3}\right\}$$

= $\left\{z: |z| > \frac{1}{2}\right\}$



ROC examples

• Example 3: Left sided sequence $x[n] = -a^n \mu[-n-1]$

$$X(z) = \sum_{n=-\infty}^{-1} -a^n z^{-n}$$

$$= \sum_{m=1}^{\infty} -a^{-m} z^m = 1 - \sum_{m=0}^{\infty} (a^{-1} z)^m$$

• If $|a^{-1}z| < 1$, i.e., |z| < |a|, $X(z) = 1 - \frac{1}{1 - a^{-1}z} = \frac{-a^{-1}z}{1 - a^{-1}z} = \frac{1}{1 - az^{-1}}$

Digital Signal Processing by Yu Yajun @ SUSTech


377

ROC examples

- Example 3 continued.
- Expression is the same as that of Example 1!
- ROC = $\{z: |z| < |a|\}$ is different




- Different sequences may have the same *z*-transform expression.
- The *z*-transform without ROC does not uniquely define a sequence!




ROC examples

• Example 4:
$$x[n] = -\left(\frac{1}{2}\right)^n \mu[-n-1] + \left(-\frac{1}{3}\right)^n \mu[n]$$

$$X(z) = \frac{1}{1 - \frac{1}{2}z^{-1}} + \frac{1}{1 + \frac{1}{3}z^{-1}}, \quad \text{Expression Same as that of Example 2}$$





Digital Signal Processing by Yu Yajun @ SUSTech

379

380

ROC examples

• Example 5:
$$x[n] = \left(\frac{1}{2}\right)^n \mu[n] - \left(-\frac{1}{3}\right)^n \mu[-n-1]$$

ROC = $\left\{z: |z| > \frac{1}{2}\right\} \cap \left\{z: |z| < \frac{1}{3}\right\} = \emptyset$

• Example 6:
$$x[n] = a^n$$
, two sided $a \neq 0$

$$ROC = \{z: |z| > a\} \cap \{z: |z| < a\} = \emptyset$$

ROC Examples

Example 7: Finite sequence $x[n] = a^n \mu[n] \mu[-n + M - 1]$

Example 7: Finite sequence
$$x[n] = a^n \mu[n] \mu[-n + M - 1]$$

$$X(z) = \sum_{n=0}^{M-1} a^n z^{-n}$$
Finite, always converges
$$= \frac{1 - a^M z^{-M}}{1 - a z^{-1}} = \frac{1}{z^{M-1}} \cdot \frac{z^M - a^M}{z - a}$$
Zero cancels pole

There are M roots of $z^M = a^M$, $z_k = ae^{j\frac{2\pi k}{M}}$. The root of k = 0 cancels the pole at z = a. Thus there are M-1 zeros, $z_k = ae^{j\frac{2\pi k}{M}}$. $ae^{j\frac{2\pi k}{M}}$, k = 1, ..., M, and a (M-1)th order pole at zero.

$$X(z) = \prod_{k=1}^{M-1} \left(1 - ae^{j\frac{2\pi k}{M}} z^{-1}\right) \rightarrow (1-ae^{j\frac{2\pi k}{M}} z^{-1})$$

• ROC = $\{z: |z| > 0\}$


Digital Signal Processing by Yu Yajun @ SUSTech

381


ROC examples

• Example 7 continued:

Infinite Sequence



Finite Sequence



Digital Signal Processing by Yu Yajun @ SUSTech

Properties of ROC



For right-sided sequences: ROC extends outward from the outermost pole to infinityExamples 1, 2


- For left-sided: ROC inwards from the inner most pole to the original point.
 - Example 3
- For two-sided: ROC either is a ring or do not exist
 - Examples 4, 5, 6

Digital Signal Processing by Yu Yajun @ SUSTech

383


Properties of ROC

• For finite duration sequences, ROC is the entire *z*plane, except possibly z=0, $z=\infty$



$$X(z) = 1 + z^{-1} + z^{-2} + z^{-3}$$

ROC excludes z = 0



$$X(z) = 1 + z^1 + z^2$$

ROC excludes $z = \infty$

Properties of ROC


• In general, ROC of a z-transform is in a form: $R_{\chi^-} < |z| < R_{\chi^+}$, an annular region

- The DTFT $X(e^{j\omega})$ of x[n] absolutely convergent iff the ROC of the z-transform X(z) of x[n] includes the unit circle.
 - ROC can't contain poles

Digital Signal Processing by Yu Yajun @ SUSTech


385

Example



(a) A system with three poles.

Digital Signal Processing by Yu Yajun @ SUSTech




Different possibilities of the ROC. (b) ROC to a right-sided sequence. (c) ROC to a left-sided sequence.

Digital Signal Processing by Yu Yajun @ SUSTech

387

收敛区域不包含任何不疑。



Different possibilities of the ROC. (d) ROC to a two-sided sequence. (e) ROC to another two-sided sequence.

ROC for LTI System

- Consider the transfer function H(z) of a linear system:
- If the system is stable, the impulse response h(n) is absolutely summable and therefore has a Fourier transform, then the ROC must include the unit circle.
 - If the system is causal, then the impulse response h(n) is right-sided, and thus the ROC extends outward from the outermost (i.e., largest magnitude) finite pole in H(z) to (and possibly include) $z = \infty$.
 - Therefore, a stable causal LTI system has all poles inside unit circle.

Digital Signal Processing by Yu Yajun @ SUSTech

389

Properties of the z-transform

Property	Sequence		z-Transform	ROC	
	x[n]	\leftrightarrow	X(z)	\mathcal{R}_{κ}	
Conjugate	$x^*[n]$	\leftrightarrow	$X^*(z^*)$	当城城路路支充。当人的城市	
Time shifting	$x[n-n_d]$	\leftrightarrow	$z^{-n_d}X(z)$	R_{x} 中 $R_$	
Multiplication by an exponential sequence	$r^n x[n]$	\leftrightarrow	$X\left(\frac{Z}{r}\right)$	$ r \mathcal{R}_{arkappa}$	
Differentiation of $X(z)$	nx[n]	\leftrightarrow	$-z\frac{dX(z)}{dz}$	\mathcal{R}_{κ} except possibly the point $z = 0$ or ∞	
Time-reversal	x[-n]	\leftrightarrow	$X(z^{-1})$	$1/\mathcal{R}_{\kappa}$	
Convolution	$x[n] \circledast y[n]$	\leftrightarrow	X(z)Y(z)	Includes $\mathcal{R}_{x} \cap \mathcal{R}_{y}$	

Digital Signal Processing by Yu Yajun @ SUSTech


Commonly Used z-transform Pairs

Sequence		z-Transform	ROC			
$\delta[n]$	\leftrightarrow	1	All values of z			
		$\frac{1}{1-z^{-1}} \leftarrow$	z > 1			
$\rightarrow -\mu[-n-1]$	\leftrightarrow	$\frac{1}{1-z^{-1}}$	z < 1			
$-\mu[-n-1]$ $\delta[n-m]$	\leftrightarrow	z^{-m}	All z, except 0 (if $m>0$) or ∞ (if $m<0$)			
$\alpha^n\mu[n]$	\leftrightarrow	$\frac{1}{1-\alpha z^{-1}} <$	$ z > \alpha $			
$\rightarrow \alpha^n \mu[-n-1]$	\leftrightarrow	$\frac{1}{1-\alpha z^{-1}}$	$ z < \alpha $			
$n\alpha^n\mu[n]$	\leftrightarrow	$\frac{\alpha z^{-1}}{(1-\alpha z^{-1})^2}$	$ z > \alpha $			
用性质						
Digital Signal Processing by Yu Yajun @ SUSTech						

391

392

Commonly Used *z***-transform Pairs**



Example

 Determine the z-transform and its ROC of the causal sequence

$$x[n] = (r^n \cos \omega_0 n) \mu[n]$$

• We can express $x[n] = v[n] + v^*[n]$, where

$$v[n] = \frac{1}{2}r^n e^{j\omega_0 n} \mu[n] = \frac{1}{2}\alpha^n \mu[n]$$

• The z-transform of v[n] is given by

$$V(z) = \frac{1}{2} \cdot \frac{1}{1 - \alpha z^{-1}} = \frac{1}{2} \cdot \frac{1}{1 - r e^{j\omega_0} z^{-1}}, |z| > |\alpha| = |r|$$

Digital Signal Processing by Yu Yajun @ SUSTech

393

 Using the conjugate property, we obtain the ztransform of $v^*[n]$ as

$$V^*(z^*) = \frac{1}{2} \cdot \frac{1}{1 - \alpha^* z^{-1}} = \frac{1}{2} \cdot \frac{1}{1 - re^{-j\omega_0} z^{-1}}, |z| > |r|$$

• Finally, using the linear property, we get
$$X(z) = \frac{1}{2} \cdot \frac{1}{1 - re^{j\omega_0}z^{-1}} + \frac{1}{2} \cdot \frac{1}{1 - re^{-j\omega_0}z^{-1}} = \frac{1 - (r\cos\omega_0)z^{-1}}{1 - (2r\cos\omega_0)z^{-1} + r^2z^{-2}}, |z| > |r|$$

Inversion of the z-Transform

In general, by contour integral

$$\chi x[n] = \frac{1}{2\pi j} \oint_C X(z) z^{n-1} dz$$

where *C* is any counterclockwise contour encircling the point z = 0 in the ROC.

- Ways to avoid it:
 - Inspection (known transforms)
 - Properties of the *z*-transform
 - Partial fraction expansion
 - Power series expansionResidue theorem

Digital Signal Processing by Yu Yajun @ SUSTech

395

By Inspection

• Eg. If we need to find the inverse *z*-transform of

$$X(z) = \frac{1}{1 - 0.5z^{-1}}, \qquad |z| < 0.5$$

From the transform pair we see that

$$x[n] = 0.5^n \mu[n]$$
 or $x[n] = -0.5^n \mu[-n-1]$

• Since ROC is |z| < 0.5, the sequence is left-sided. Therefore,

$$x[n] = -0.5^n \mu[-n-1]$$

Digital Signal Processing by Yu Yajun @ SUSTech

By Partial Fraction Expansion

• If X(z) is the rational form with

$$X(z) = \frac{P(z)}{D(z)} = \frac{\sum_{i=0}^{M} p_i z^{-i}}{\sum_{i=0}^{N} d_i z^{-i}} \xrightarrow{\mathbb{Z}^{-N}} Z^{-N}$$

• If $M \ge N$, then X(z) can be expressed as

$$X(z) = \sum_{l=0}^{M-N} \eta_l z^{-l} + \frac{P_1(z)}{D(z)}$$

where the degree of $P_1(z)$ is less than N.

• The rational function $\frac{P_1(z)}{D(z)}$ is called a called a <u>proper</u> fraction. 有分数

Digital Signal Processing by Yu Yajun @ SUSTech

397

- To develop the proper fraction of $\frac{P_1(z)}{D(z)}$ from X(z), a long division of P(z) by D(z) should be carried out in a reversed order until the remainder polynomial $P_1(z)$ is of lower degree than that of the denominator D(z).
- Example: consider

$$X(z) = \frac{2 + 0.8z^{-1} + 0.5z^{-2} + 0.3z^{-3}}{1 + 0.8z^{-1} + 0.2z^{-2}}$$

By long division in a revered order, we arrive at

$$X(z) = -3.5 + 1.5z^{-1} + \frac{5.5 + 2.1z^{-1}}{1 + 0.8z^{-1} + 0.2z^{-2}}$$

Proper fraction

- Simple pole: in most practical cases, the rational z-transform of interest X(z) is a proper fraction with simple poles.
- Let the poles of X(z) be at $z = \lambda_k$, $1 \le k \le N$

• A partial-fraction expansion of X(z) is of the form



$$X(z) = \sum_{l=1}^{N} \left(\frac{\rho_l}{1 - \lambda_l z^{-1}} \right) \rightarrow \text{真分数可以含成这样}.$$

The constants ρ_l in the partial-fraction expansion are called the **residue**, and are given by

$$\rho_l = (1 - \lambda_l z^{-1}) X(z) \Big|_{z = \lambda_l}$$

Digital Signal Processing by Yu Yajun @ SUSTech

- Assume that each term of the sum in partial-fraction expansion has an ROC given by $|z| > |\lambda_l|$, and thus has an inverse transform of the form $\rho_l(\lambda_l)^n \mu[n]$.
- Therefore, the inverse transform x[n] of X(z) is given by

$$x[n] = \sum_{l=1}^{N} \rho_l(\lambda_l)^n \mu[n]$$

Example

• Let the z-transform H(z) of a causal system h[n] is given by

$$H(z) = 1 + \frac{z(z+2)}{(z-0.2)(z+0.6)} = 1 + \frac{1+2z^{-1}}{(1-0.2z^{-1})(1+0.6z^{-1})}$$

• The second term is a proper fraction. A partial-fraction expansion of H(z) is then of form

$$H(z) = 1 + \frac{\rho_1}{1 - 0.2z^{-1}} + \frac{\rho_2}{1 + 0.6z^{-1}}$$

And

$$\rho_{1} = (1 - 0.2z^{-1}) \underbrace{\frac{1 + 2z^{-1}}{(1 - 0.2z^{-1})(1 + 0.6z^{-1})}}_{z=0.2} = 2.75$$

$$\rho_{2} = (1 + 0.6z^{-1}) \underbrace{\frac{1 + 2z^{-1}}{(1 - 0.2z^{-1})(1 + 0.6z^{-1})}}_{z=-0.6} = -1.75$$

Digital Signal Processing by Yu Yajun @ SUSTech

401

• Thus, we have

$$H(z) = 1 + \frac{2.75}{1 - 0.2z^{-1}} + \frac{-1.75}{1 + 0.6z^{-1}}$$

• Since it is given that h[n] is causal, the inverse transform of the above is given by

$$h[n] = \delta[n] + 2.75(0.2)^n \mu[n] - 1.75(-0.6)^n \mu[n]$$

Another example

• Find the inverse *z*-transform of

$$X(z) = \frac{(1+z^{-1})^2}{\left(1 - \frac{1}{2}z^{-1}\right)(1-z^{-1})}, |z| > 1$$

• Since both the numerator and denominator are of degree 2, a constant term exists.

$$X(z) = B_0 + \frac{A_1}{\left(1 - \frac{1}{2}z^{-1}\right)} + \frac{A_2}{(1 - z^{-1})}$$

• B_0 can be determined by the fraction of the coefficients of z^{-2} . $B_0 = \frac{1}{\frac{1}{2}} = 2$.

Digital Signal Processing by Yu Yajun @ SUSTech

403

• Therefore,
$$X(z) = 2 + \frac{-1+5z^{-1}}{\left(1-\frac{1}{2}z^{-1}\right)(1-z^{-1})} = 2 + \frac{A_1}{\left(1-\frac{1}{2}z^{-1}\right)} + \frac{A_2}{(1-z^{-1})}$$

$$A_1 = \frac{-1+5z^{-1}}{\left(1-\frac{1}{2}z^{-1}\right)(1-z^{-1})} \cdot \left(1-\frac{1}{2}z^{-1}\right) \Big|_{z=\frac{1}{2}} = -9$$

$$A_2 = \frac{-1+5z^{-1}}{\left(1-\frac{1}{2}z^{-1}\right)(1-z^{-1})} \cdot (1-z^{-1}) \Big|_{z=1} = 8$$

$$X(z) = 2 - \frac{9}{\left(1-\frac{1}{2}z^{-1}\right)} + \frac{8}{(1-z^{-1})}$$

From the ROC, the solution is right-handed. So

$$x[n] = 2\delta[n] - 9\left(\frac{1}{2}\right)^n \mu[n] + 8\mu[n]$$

By Power Series Expansion

$$X(z) = \sum_{n = -\infty}^{\infty} x[n]z^{-n}$$

$$= \dots + x[-2]z^{2} + x[-1]z + x[0] + x[1]z^{-1} + x[2]z^{-2}$$

$$+ \dots$$

• We can determine any particular value of the sequence by finding the coefficient of the appropriate power of z^{-1} .

Digital Signal Processing by Yu Yajun @ SUSTech

405

Example: Finite-length Sequence

- Find the inverse z-transform of $X(z) = z^2(1 0.5z^{-1})(1 + z^{-1})(1 z^{-1})$
- By directly expand X(z), we have $X(z) = z^2 0.5z 1 + 0.5z^{-1}$
- Thus, $x[n] = \delta[n+2] 0.5\delta[n+1] \delta[n] + 0.5\delta[n-1]$

Example: Rational z-Transform

- If a rational z-transform is expressed as a ratio of polynomials in z^{-1} , the power series expansion can be obtained by long division.
- Consider

$$H(z) = \frac{1 + 2z^{-1}}{1 + 0.4z^{-1} - 0.12z^{-2}}$$

The long division of the numerator by the denominator yields

$$H(z) = 1 + 1.6z^{-1} - 0.52z^{-2} + 0.4z^{-3} - 0.2224z^{-4} + \cdots$$

• Thus, $h[n] = \delta[n] + 1.6\delta[n-1] - 0.52\delta[n-2] + 0.4\delta[n-3] - 0.2224\delta[n-4] + \cdots$

Digital Signal Processing by Yu Yajun @ SUSTech

407

Frequency Response from Transfer Function

• z-transform transfer function

$$H(z) = H_{re}(z) + jH_{im}(z) = |H(z)|e^{jargH(z)}$$

where
$$\arg H(z) = \tan^{-1} \frac{H_{\text{im}}(z)}{H_{\text{re}}(z)}$$

If the ROC of H(z) includes the unit circle, the frequency response $H(e^{j\omega})$ of the LTI digital system can be obtained by evaluating H(z) on the unit circle:

$$H(e^{j\omega}) = H(z)\Big|_{z=e^{j\omega}}$$

• For a real coefficient transfer function

$$\left|H(e^{j\omega})\right|^{2} = H(e^{j\omega})H^{*}(e^{j\omega}) = H(e^{j\omega})H(e^{-j\omega})$$

$$= H(z)H(z^{-1})\Big|_{z=e^{j\omega}}$$

Digital Signal Processing by Yu Yajun @ SUSTech

Stability Condition in Terms of Pole Locations

- A stable causal LTI system has all poles inside unit circle.
 - A causal LTI FIR digital filter with bounded impulse response coefficients is always stable, as all its poles are at the origin in the *z*-plane.
 - A causal LTI IIR digital filter may or may not be stable.
 - An originally stable IIR filter characterized by infinite precision coefficients and with all poles inside the unit circle may become unstable after implementation due to the unavoidable quantization of all coefficients.

Digital Signal Processing by Yu Yajun @ SUSTech

409

Example

Analyze the stability of the causal system

$$H(z) = \frac{1}{1 - 1.845z^{-1} + 0.850586z^{-2}}$$

and the system implemented by keeping 2 digits after the decimal points of the coefficients.

A: the poles of the systems are the roots of

$$1 - 1.845z^{-1} + 0.850586z^{-2}$$

= $z^{-2}(z^2 - 1.845z^1 + 0.850586)$

We have,
$$z_p = \frac{1.845 \pm \sqrt{1.845^2 - 4 \times 0.850586}}{2} = 0.943$$
, or 0.902

Both poles are in the unit circle, and the system is stable.

• If the system is implemented by keeping 2 digits after the decimal points of the coefficients, the transfer function becomes

$$H(z) = \frac{1}{1 - 1.85z^{-1} + 0.85z^{-2}}$$

The root of the denominator is

$$z_p = \frac{1.85 \pm \sqrt{1.85^2 - 4 \times 0.85}}{2} = 1, \text{ or } 0.85$$

i.e., one pole is on the unit circle. So the system becomes unstable.

Digital Signal Processing by Yu Yajun @ SUSTech