

Policy Gradient Methods Summary



go right



Wait, I am still calculating Q-values.....

Reinforcement Learning

December 22, 2022

Policy Gradient Methods

Learn the policy function directly

$$\pi(a|s, \boldsymbol{\theta}) = \Pr\{A_t = a|S_t = s, \boldsymbol{\theta}_t = \boldsymbol{\theta}\}\$$

Constraints:

$$\pi(a|s, \boldsymbol{\theta}) > 0$$
, for all $a \in \mathcal{A}, s \in \mathcal{S}$


$$\sum_{a} \pi(a|s, \boldsymbol{\theta}) = 1, \quad \text{for all } s \in \mathcal{S}$$

which can be enforced by using the softmax function

Advantages of Policy Parametrization

A parametrized policy

- can approach a deterministic policy over time (in comparison to epsilongreedy, which will always explore)
- can model stochastic policies



HSLU December 22, 2022 Page 3

Policy Gradient Theorem

Goal: optimize the total return from a (particular) state

$$J(\boldsymbol{\theta}) \doteq v_{\pi_{\boldsymbol{\theta}}}(s_0)$$

The gradient of the Loss function is proportional to the gradient of the policy

$$\nabla J(\boldsymbol{\theta}) \propto \sum_{s} \mu(s) \sum_{a} q_{\pi}(s, a) \nabla \pi(a|s, \boldsymbol{\theta})$$

HSLU December 22, 2022

REINFORCE: Monte Carlo Policy Gradient

Update the weights according to:

$$\boldsymbol{\theta}_{t+1} \doteq \boldsymbol{\theta}_t + \alpha G_t \frac{\nabla \pi(A_t | S_t, \boldsymbol{\theta})}{\pi(A_t | s, \boldsymbol{\theta})}$$
$$= \boldsymbol{\theta}_t + \alpha G_t \nabla \ln \pi(A_t | S_t, \boldsymbol{\theta})$$


The second line can be derived from

$$\nabla \ln(f(x)) = \frac{\nabla f(x)}{f(x)}$$

This is gradient ascent, as we want to maximize the return

How does Policy Gradient work?

- The gradient will push the selected action to have a higher probability (at the expense of the others)
- The amount that it will be pushed depends on the return G



HSLU December 22, 2022 Page 6

Actor Critic: Policy Gradient Method with Critic

For the 1-step return target function, we need a value function

$$\boldsymbol{\theta}_{t+1} \doteq \boldsymbol{\theta}_t + \alpha \left(R_{t+1} + \gamma \hat{v}(S_{t+1}, \mathbf{w}) - \hat{v}(S_t, \mathbf{w}) \right) \nabla \ln \pi (A_t | S_t, \boldsymbol{\theta}_t)$$
$$= \boldsymbol{\theta}_t + \alpha \delta_t \nabla \ln \pi (A_t | S_t, \boldsymbol{\theta}_t)$$

The value function is approximated too

One step Actor-Critic (episodic) for estimating $\pi_{\theta} \approx \pi_*$

```
Input:
```

a differentiable policy parameterization $\pi(a|s,\theta)$

a differentiable state-value function parametrization $\hat{v}(s, \mathbf{w})$

step sizes $\alpha^{\theta} > 0, \alpha^{\mathbf{w}} > 0$

Initialize:

policy parameters $\boldsymbol{\theta}$ and state-value weights \mathbf{w}

Loop for each episode:

Initialize S, first state of episode

$$I \leftarrow 1$$

For each time step of the episode:

Choose
$$A \sim \pi(\cdot|S, \boldsymbol{\theta})$$

Take action A, observe S', R

$$\delta \leftarrow R + \gamma \hat{v}(S', \mathbf{w}) - \hat{v}(S, \mathbf{w})$$

$$\mathbf{w} \leftarrow \mathbf{w} + \alpha^{\mathbf{w}} \delta \nabla \hat{v}(S, \mathbf{w})$$

$$\boldsymbol{\theta} \leftarrow \boldsymbol{\theta} + \alpha^{\boldsymbol{\theta}} I \delta \nabla \ln \pi(A|S, \boldsymbol{\theta})$$

$$I \leftarrow \gamma I$$

$$S \leftarrow S'$$

HSLU December 22, 2022

TRPO and PPO Methods

In policy gradient methods, the update is calculated as

$$\boldsymbol{\theta}_{t+1} = \boldsymbol{\theta}_t + \alpha \nabla J(\boldsymbol{\theta})|_{\boldsymbol{\theta} = \boldsymbol{\theta}_t}$$

The new values for θ should be near to the old values, as we use a small step size, however, the **policy** could still change significantly with a change of θ

TRPO and PPO Methods ensure that the policy does not change too much

PPO

$$p_t(\boldsymbol{\theta}) = \frac{\pi_{\boldsymbol{\theta}}(a_t|s_t)}{\pi_{\boldsymbol{\theta}_{\text{old}}}(a_t|s_t)}$$

$$L^{CLIP}(\boldsymbol{\theta}) = \mathbb{E}_t[\min(r_t(\boldsymbol{\theta})A_t, \operatorname{clip}(r_t(\boldsymbol{\theta}), 1 - \epsilon, 1 + \epsilon)A_t]$$

- \blacksquare Clip the advantage function when it is outside of the comfort interval bounded by $1\pm\epsilon$
- Due to the minimum operation, the probability ratio is ignored outside the zone only if it would improve the objective, it is included if it makes the objective worse

HSLU December 22, 2022 Page 10