```
=== 测试1: Synchronized方式 ===
Thread-0 生产: 产品{id=1, name='生产者A-1'}, 库存:1
Thread-3 消费: 产品{id=1, name='生产者A-1'}, 库存:0
Thread-1 生产: 产品{id=2, name='生产者B-1'}, 库存:1
Thread-4 消费: 产品{id=2, name='生产者B-1'}, 库存:0
Thread-0 生产: 产品{id=3, name='生产者A-2'}, 库存:1
Thread-2 消费: 产品{id=3, name='生产者A-2'}, 库存:0
Thread-1 生产: 产品{id=4, name='生产者B-2'}, 库存:1
Thread-4 消费: 产品{id=4, name='生产者B-2'}, 库存:0
Thread-0 生产: 产品{id=5, name='生产者A-3'}, 库存:1
Thread-3 消费: 产品{id=5, name='生产者A-3'}, 库存:0
Thread-1 生产: 产品{id=6, name='生产者B-3'}, 库存:1
Thread-2 消费: 产品{id=6, name='生产者B-3'}, 库存:0
Thread-0 生产: 产品{id=7, name='生产者A-4'}, 库存:1
Thread-4 消费: 产品{id=7, name='生产者A-4'}, 库存:0
Thread-0 生产: 产品{id=8, name='生产者A-5'}, 库存:1
Thread-2 消费: 产品{id=8, name='生产者A-5'}, 库存:0
Thread-1 生产: 产品{id=9, name='生产者B-4'}, 库存:1
Thread-4 消费: 产品{id=9, name='生产者B-4'}, 库存:0
```

Question 0011 q01

```
=== 同步方法版本 ===
Creep-A attack...
Creep-B attack...
Creep-A: 当前player的hp值= 80
Creep-B: 当前player的hp值= 60
Creep-A attack...
Creep-A: 当前player的hp值= 40
Creep-B attack...
Creep-B: 当前player的hp值= 20
Creep-B attack...
Creep-A attack...
Creep-B: 当前player的hp值= 0
Creep-B: player is dead.
Creep-A: player is already dead.
Creep-A end.
Creep-B end.

=== 同步块版本 ===
Creep-A attack...
Creep-B attack...
Creep-A: 当前player的hp值= 80
Creep-B: 当前player的hp值= 60
Creep-A attack...
Creep-B attack...
Creep-A: 当前player的hp值= 40
Creep-B: 当前player的hp值= 20
Creep-A attack...
Creep-B attack...
Creep-A: 当前player的hp值= 0
Creep-A: player is dead.
Creep-B: player is already dead.
Creep-B end.
Creep-A end.
```

Question 0010 q02

```
=== 测试整数链表 ===
添加节点: 10, 20, 30, 40
链表内容: 10 -> 20 -> 30 -> 40 -> null
链表大小: 4

--- 测试查找功能 ---
查找值20的下标: 1
查找值50的下标: -1

--- 测试删除尾节点 ---
删除尾节点后: 链表内容: 10 -> 20 -> 30 -> null
当前链表大小: 3

--- 测试删除指定值节点 ---
删除值20后: 链表内容: 10 -> 30 -> null
当前链表大小: 2

--- 测试删除不存在的值 ---
尝试删除值100后: 链表内容: 10 -> 30 -> null

=== 测试字符串链表 ===
添加节点: Java, Python, C++, JavaScript
链表内容: Java -> Python -> C++ -> JavaScript -> null
链表大小: 4

--- 测试查找功能 ---
查找'Python'的下标: 1
查找'C++'的下标: 2
查找'Go'的下标: -1

--- 测试删除指定值节点 ---
删除'Python'后: 链表内容: Java -> C++ -> JavaScript -> null

--- 测试删除尾节点 ---
删除尾节点后: 链表内容: Java -> C++ -> null
```

```
=== 测试边界情况 ===
空链表大小: 0
空链表是否为空: true
在空链表中查找值10: -1
删除空链表尾节点后大小: 0

--- 测试单个节点链表 ---
链表内容: 100 -> null
查找值100的下标: 0
删除尾节点后: 链表内容: null
链表大小: 0

=== 所有测试完成 ===
```

Question 0010 q03