



Time Series Models & Databases


Applied Machine & Deep Learning (190.015)

Univ.-Prof. Dr. Elmar Rueckert

Telefon: +43 3842 402 - 1901
Email: teaching@ai-lab.science

WO AUS FORSCHUNG ZUKUNFT WIRD

Chair of Cyber-Physical-Systems



1st Week:

	MON 02.10.2023	TUE 03.10.2023	WED 04.10.2023	THUR 05.10.2023	FRI 06.10.2023
Topic	Intro to ML Organisation	Neural Networks	Representation Learning	Robot Learning	AML Projects
9 am :15 :30 :45					
10 am :15 :30 :45	Quizz on ML Introduction to ML	Quizz on Neural Nets Introduction to Multi-Layer-Perceptrons	Introduction to Deep Representation Learning		Quizz on AML Project Topic Presentations
11 am :15 :30 :45	15 min Break Statistics, Model Validation, Figures & Evaluations	15 min Break Handout on Neural Networks using playground.tensorflow	JupyterHub NB on Rep. Learning 30 min Break		Team Ass., Git Repos & Wiki Instructions AML Summary
12 pm :15 :30 :45	30 min Lunch Break Course Organisation & Grading	30 min Lunch Break Introduction to CNNs	Curiosity (MLPs), Imagination (Dreamer) and Information (Empowerment)	Quizz on Robotics Introduction to Robot Learning	
1 pm :15 :30 :45	15 min Break Python Programming with our JupyterHub Quizz Summary	15 min Break JupyterHub NB on MLPs CNNs Quizz Summary	Quizz Summary	15 min Break Handout on Robot Learning (Model Learning & RL)	
2 pm :15 :30 :45				15 min Break Introduction to Mobile Robotics & SLAM	
3 pm :15 :30 :45				JupyterHub NB on Path Planning Quizz Summary	

Legend

Quizz on ML	Online Quizz using https://tweedback.de
Course Content Presentation	Using google slides, etc.
15 min Break	Breaks to recover or to continue programming
Organisation & Instructions	Using google slides, etc.
Practical Exercise	Using online tools, our JupyterHub, etc.
Latest Research	State-of-the-art research

Outlook of this lecture

- An introduction to Probabilistic Time Series Models
 - Single Time Step Model
 - Multi Time step Model
- Some Applications in Research
- Let's implement Databases in Jupyter Hub

Probabilistic Time-Series Models (L8) Machine Learning (190.012)

Univ.-Prof. Dr. Elmar Rueckert¹

¹*teaching@ai-lab.science*, Montanuniversität Leoben, Austria


June 3, 2022

Chair of Cyber-Physical-Systems

For more details, please have a look at these slides:
<https://cloud.cps.unileoben.ac.at/index.php/s/YTNmPbgsSbTFdsZ>.


Definition of Time Series

Time series are defined as a **series of data points** indexed or listed **in time order**.



[Slides on Time Series by Prof. Rueckert.](#)


Time Series Data



Definition: A **trajectory** is a vector of time series data of **any type** (e.g., joint angles, forces, Cartesian coordinates, or inhomogeneous mixtures)!

Consider D as vector with $D = \{y_1, y_2, \dots, y_T\}$
representing **1-dimensional** time series data with the
time indices $t=1 \dots T$!

Time Series Data




Attention: Individual dimensions (e.g. the x and y Cartesian coord.) are organized in a sequential order where first the **complete dimension one** is stored!

For **multiple trajectories** (e.g., recordings), we define D as vector with $D = \{y_{1,1}, y_{2,1}, \dots, y_{T,1}, y_{2,1}, \dots, y_{T,n}\}$, where n denotes the number of trajectories!

Single-time step Model

Well that are our simple probabilistic regression models, summarized [here](#)!



2 Steps:

1. Learning $p(w) = N(w | \mu_{w|y}, \Sigma_{w|y})$

Ridge Regression

$$w = (A^T A + \lambda I)^{-1} A^T y$$

Maximum A-Posteriori

$$w = (A^T A + \sigma^2 \lambda I)^{-1} A^T y$$

$$\mu_{w|y} = \sum_{j=1}^n w_j \quad \Sigma_{w|y} = \text{cov}([w_1, \dots, w_n])$$

2 Steps:

1. Learning $p(w) = N(w | \mu_{w|y}, \Sigma_{w|y})$
2. Prediction $y^* = ?$

The Marginal distribution is defined as:

$$p(A) = \sum_b p(A|B) p(B=b) \dots \text{for discrete distributions}$$

$$p(a) = \int_b p(a|b) p(b) db \dots \text{for continuous distributions}$$

$$p(y^*) = \int_w p(y^*|w) p(w) dw = \int_w N(y^* | \phi(x^*)^T w, \sigma_y^2) N(w | \mu_{w|y}, \Sigma_{w|y}) dw$$


$$p(y^* | x^*, X, w) = \int \mathcal{N}(y^* | \phi(x^*)^T w, \sigma_y^2) \mathcal{N}(w | \mu_{w|y}, \Sigma_{w|y}) dw$$

Marginal or predictive
distribution

Likelihood

prior

Multi-time step Model



For simplicity, we consider
only 1-dimensional time
series data!

$$D = \{y_{1,1}, y_{2,1}, \dots, y_{T,1}, y_{2,1}, \dots, y_{T,n}\},$$

where n denotes the number of
trajectories!

The Model (the likelihood):

$$p(y_t | \mathbf{w}) = \mathcal{N}(y_t | \boldsymbol{\phi}_t^T \mathbf{w}, \sigma_y^2)$$

The Model (the likelihood):

$$p(y_t | \mathbf{w}) = \mathcal{N}(y_t | \boldsymbol{\phi}_t^T \mathbf{w}, \sigma_y^2)$$

The Basis Functions
(our model assumption):

$$\boldsymbol{\phi}_t : \mathbb{R}^1 \rightarrow \mathbb{R}^M$$

per time-step & per feature i:

$$\phi_t^i = \exp\left\{-\frac{1}{2h}(z_t - c_i)^2\right\}$$

per time-step over M features:

$$\boldsymbol{\phi}_t = \frac{1}{\sum_{i=1}^M \phi_t^i} [\phi_t^1, \phi_t^2, \dots, \phi_t^M]$$






Figure 4.5: Shown are five *normalized* basis functions arranged in the movement phase interval $[0, 1]$.

The model can be used to represent any non-linear function, see the next slide!


A basis functions




A basis functions




features




B




mean of features




covariance



correlation ($p < 0.05$)



learned model



The Multi-time Step Model

$$\begin{aligned} p(\boldsymbol{\tau}_j | \mathbf{w}) &= \prod_{t=1}^T p(y_{t,j} | \mathbf{w}) , \\ &= \prod_{t=1}^T \mathcal{N}(y_{t,j} | \boldsymbol{\phi}_t^T \mathbf{w}, \sigma_y^2) , \\ &= \mathcal{N}(\boldsymbol{\tau}_j | \mathbf{A} \mathbf{w}, \sigma_y^2 \mathbf{I}) . \end{aligned}$$

$$\mathbf{A} = [\boldsymbol{\phi}_1, \boldsymbol{\phi}_2, \dots, \boldsymbol{\phi}_T]^T \in \mathbb{R}^{T \times M}$$

$$\mathbf{w}_{LS}^j = (\mathbf{A}^T \mathbf{A})^{-1} \mathbf{A}^T \boldsymbol{\tau}_j$$

Assumption: i.i.d. time series data samples!

$$\mathcal{N}(a | \mu_1, \sigma_1) \mathcal{N}(b | \mu_2, \sigma_2) = \mathcal{N} \left(\begin{bmatrix} a \\ b \end{bmatrix} \middle| \begin{bmatrix} \mu_1 \\ \mu_2 \end{bmatrix}, \begin{bmatrix} \sigma_1 & 0 \\ 0 & \sigma_2 \end{bmatrix} \right)$$

Attention: Individual dimensions (e.g. the x and y Cartesian coord.) are organized in a sequential order where first the **complete dimension one** is stored, see [Slide 5](#)!

Multi-time Step Model

$$\begin{aligned} p(\boldsymbol{\tau}_j | \boldsymbol{w}) &= \prod_{t=1}^T p(y_{t,j} | \boldsymbol{w}) , \\ &= \prod_{t=1}^T \mathcal{N}(y_{t,j} | \boldsymbol{\phi}_t^T \boldsymbol{w}, \sigma_y^2) , \\ &= \mathcal{N}(\boldsymbol{\tau}_j | \boldsymbol{A} \boldsymbol{w}, \sigma_y^2 \boldsymbol{I}) . \end{aligned}$$

$$\boldsymbol{A} = [\boldsymbol{\phi}_1, \boldsymbol{\phi}_2, \dots, \boldsymbol{\phi}_T]^T \in \mathbb{R}^{T \times M}$$

$$\boldsymbol{w}_{LS}^j = (\boldsymbol{A}^T \boldsymbol{A})^{-1} \boldsymbol{A}^T \boldsymbol{\tau}_j$$

Predictions with the multi-time step model


$$\begin{aligned} p(\boldsymbol{\tau}) &= \int \mathcal{N}(\boldsymbol{\tau} | \mathbf{A}\mathbf{w}, \sigma_y^2 \mathbf{I}) \mathcal{N}(\mathbf{w} | \boldsymbol{\mu}_{\mathbf{w}|y}, \boldsymbol{\Sigma}_{\mathbf{w}|y}) d\mathbf{w}, \\ &= \mathcal{N}(\boldsymbol{\tau} | \mathbf{A}\boldsymbol{\mu}_{\mathbf{w}|y}, \sigma_y^2 \mathbf{I} + \mathbf{A}\boldsymbol{\Sigma}_{\mathbf{w}|y}\mathbf{A}^T). \end{aligned}$$

$$\boldsymbol{\mu}_{\mathbf{w}|y} = \frac{1}{n} \sum_{j=1}^n \mathbf{w}^j \text{ and ,}$$

$$\boldsymbol{\Sigma}_{\mathbf{w}|y} = \frac{1}{n-1} \sum_{j=1}^n (\mathbf{w}^j - \boldsymbol{\mu}_{\mathbf{w}|y})(\mathbf{w}^j - \boldsymbol{\mu}_{\mathbf{w}|y})^T$$

Conditional Rule to predict future time series data points, see [page 31 in the script](#):

$$p(\mathbf{a}|\mathbf{b}) = \mathcal{N}(\mathbf{x}_a | \mathbf{u}_a + \boldsymbol{\Sigma}_{ab} \boldsymbol{\Sigma}_{bb}^{-1} (\mathbf{b} - \mathbf{u}_b), \boldsymbol{\Sigma}_{aa} - \boldsymbol{\Sigma}_{ab} \boldsymbol{\Sigma}_{bb}^{-1} \boldsymbol{\Sigma}_{ba}^T)$$



Conditional Rule to predict future time series data points, see [page 31 in the script](#):

$$p(a|b) = N(x_a | u_a + \Sigma_{ab} \Sigma_{bb}^{-1} (b - u_b), \Sigma_{aa} - \Sigma_{ab} \Sigma_{bb}^{-1} \Sigma_{ba}^T)$$

$$p(\tau^o) = N(\tau^o \mid A^o \mu_{w|o}, \sigma_y^2 I + A^o \Sigma_{w|o} A^{oT})$$

$$\mu_{w|o} = \mu_{w|y} + L(o - A^o \mu_{w|y}) \text{ and ,}$$

$$\Sigma_{w|o} = \Sigma_{w|y} - L A^o \Sigma_{w|y} \text{ and ,}$$

$$L = \Sigma_{w|y} A^{oT} (\sigma_o I + A^o \Sigma_{w|y} A^{oT})^{-1}$$

A reformulated version using definitions of [the matrix cookbook](#).

Multi-dimensional **multi-time step models**

$$A = [\phi_1, \phi_2, \dots, \phi_T]^T \in \mathbb{R}^{T \times M}$$



$A \in \mathbb{R}^{TD \times MD}$ for D -dimensional data

$$w_{LS}^j = (A^T A)^{-1} A^T \tau_j$$






$w \in \mathbb{R}^{MD}$

Attention: Individual dimensions (e.g. the x and y Cartesian coord.) are organized in a sequential order where first the **complete dimension one** is stored!

Assumption: The model captures the correlation between the multiple dimensions through the covariance matrix $\Sigma_{w|y}$. This implies a local linear relationship between the individual dimensions.

Enough Theory - Some Applications

When a single primitive is not sufficient




Rueckert, Elmar; Mundo, Jan; Paraschos, Alexandros; Peters, Jan; Neumann, Gerhard. [Extracting Low-Dimensional Control Variables for Movement Primitives](#). Proceedings of the International Conference on Robotics and Automation (ICRA), 2015.

Gaussian Mixture Model as Prior

$$p(\mathbf{w}^{[i]}) = \sum_{k=1}^K \pi_k \mathcal{N} \left(\mathbf{w}^{[i]} | \mathbf{b}_k + \mathbf{M}_k \mathbf{h}_k^{[i]}, \alpha^{-1} \mathbf{I} \right)$$

K mixture components weights as before projection matrix \mathbf{M} and low-dim. latent variables \mathbf{h}

$$\begin{aligned} \boldsymbol{\mu}_{\mathbf{w}^{[i]}} &= \boldsymbol{\Sigma}_{\mathbf{w}^{[i]}} \left(\beta \boldsymbol{\Psi}_{1:T}^{[i]T} \mathbf{y}_{1:T}^{[i]} + \sum_{k=1}^K \bar{\alpha}_k \mu_{z_k^{[i]}} \left(\boldsymbol{\mu}_{\mathbf{b}_k} + \bar{\mathbf{M}}_k \boldsymbol{\mu}_{\mathbf{h}_k^{[i]}} \right) \right), \\ \boldsymbol{\Sigma}_{\mathbf{w}^{[i]}} &= \left(\beta \boldsymbol{\Psi}_{1:T}^{[i]T} \boldsymbol{\Psi}_{1:T}^{[i]} + \sum_{k=1}^K \bar{\alpha}_k \mu_{z_k^{[i]}} \mathbf{I} \right)^{-1} \end{aligned}$$




Rueckert, Elmar; Mundo, Jan; Paraschos, Alexandros; Peters, Jan; Neumann, Gerhard. [Extracting Low-Dimensional Control Variables for Movement Primitives](#). Proceedings of the International Conference on Robotics and Automation (ICRA), 2015.


A




B




C



D




E




K=1 example: projection matrix M and low-dim. latent variables h

$$p(\mathbf{w}^{[i]}) = \sum_{k=1}^K \pi_k \mathcal{N}(\mathbf{w}^{[i]} | \mathbf{b}_k + \mathbf{M}_k \mathbf{h}_k^{[i]}, \alpha^{-1} \mathbf{I})$$


C





D




A




B



C




D




K=2 example: projection matrix M and low-dim. latent variables h


A




B



C




D



Conditioning


$$p(\mathbf{w}_o|\mathbf{o}) \propto \mathcal{N}(\mathbf{o}|\Phi_o\mathbf{w}_o, \Sigma_o)p(\mathbf{w})$$




(a) Conditioning

Combination and Blending

$$p_{new}(\tau) \propto \prod_i p_i(\tau) \alpha^{[i]}$$



(b) Combination




(c) Blending

Paraschos, Alexandros; Daniel, Christian; Peters, Jan; Neumann, Gerhard. [Probabilistic Movement Primitives](#). *Advances in Neural Information Processing Systems (NIPS)*, MIT Press, 2013.

Multiplication

$$p(w_o^{\text{angle}} | o) p(w_o^{\text{distance}} | o)$$



Paraschos, A.; Daniel, C.; Peters, J.; Neumann, G. (2018). [Using Probabilistic Movement Primitives in Robotics](#), *Autonomous Robots (AURO)*, **42**, **3**, pp.529-551.

Generalizing to box 4 while avoiding the obstacle



(1x)
Interaction pattern: hold screw driver



Everton, M., Neumann, G., Llorente, R., Ben Amor, H., Peters, J., & Menda, G.
Intelligent Autonomous Systems, TU-Darmstadt, 2014


**3rd requested
demonstration: screw driver**



Summary of Time Series & Databases

- An introduction to Probabilistic Time Series Models
 - Single Time Step Model
 - Multi Time step Model
- Some Applications in Research
- Let's implement Databases in Jupyter Hub

$$\begin{aligned} p(\tau_j | \mathbf{w}) &= \prod_{t=1}^T p(y_{t,j} | \mathbf{w}) , \\ &= \prod_{t=1}^T \mathcal{N}(y_{t,j} | \phi_t^T \mathbf{w}, \sigma_y^2) , \\ &= \mathcal{N}(\tau_j | \mathbf{A} \mathbf{w}, \sigma_y^2 \mathbf{I}) . \end{aligned}$$



Thank you for your attention!

Visit our Youtube Channel:


<https://youtube.com/@CPSAustria>



Phone: +43 3842 402 – **1901** (Sekretariat CPS)

Email: cps@unileoben.ac.at

Web: <https://cps.unileoben.ac.at>



Disclaimer: The lecture notes posted on this website are for personal use only. The material is intended for educational purposes only. Reproduction of the material for any purposes other than what is intended is prohibited. The content is to be used for educational and non-commercial purposes only and is not to be changed, altered, or used for any commercial endeavor without the express written permission of Professor Rueckert.