



Statistics & Validation


Applied Machine & Deep Learning (190.015)

Univ.-Prof. Dr. Elmar Rueckert

Telefon: +43 3842 402 - 1901
Email: teaching@ai-lab.science

WO AUS FORSCHUNG ZUKUNFT WIRD

Chair of Cyber-Physical-Systems



Topics of this lecture

Legend


Quizz on ML	Online Quizz using https://tweedback.de
Course Content Presentation	Using google slides, etc.
15 min Break	Breaks to recover or to continue programming
Organisation & Instructions	Using google slides, etc.
Practical Exercise	Using online tools, our JupyterHub, etc.
Latest Research	State-of-the-art research

	MON 02.10.2023	TUE 03.10.2023	WED 04.10.2023	THUR 05.10.2023	FRI 06.10.2023
Topic	Intro to ML Organisation	Neural Networks	Representation Learning	Robot Learning	AML Projects
9 am :15 :30 :45					
10 am :15 :30 :45	Quizz on ML Introduction to ML	Quizz on Neural Nets Introduction to Multi-Layer-Perceptrons	Introduction to Deep Representation Learning		Quizz on AML Project Topic Presentations
11 am :15 :30 :45	15 min Break Statistics, Model Validation, Figures & Evaluations	15 min Break Handout on Neural Networks using playground.tensorflow	JupyterHub NB on Rep. Learning 30 min Break		Team Ass., Git Repos & Wiki Instructions AML Summary
12 pm :15 :30 :45	30 min Lunch Break Course Organisation & Grading	30 min Lunch Break Introduction to CNNs	Curiosity (MLPs), Imagination (Dreamer) and Information (Empowerment)	Quizz on Robotics Introduction to Robot Learning	
1 pm :15 :30 :45	15 min Break Python Programming with our JupyterHub Quizz Summary	15 min Break JupyterHub NB on MLPs CNNs Quizz Summary	Quizz Summary	15 min Break Handout on Robot Learning (Model Learning & RL)	
2 pm :15 :30 :45				15 min Break Introduction to Mobile Robotics & SLAM	
3 pm :15 :30 :45				JupyterHub NB on Path Planning Quizz Summary	

Outlook of this lecture


- Model Verification and Evaluation
- Overfitting & No free Lunch Theorem
- K-fold cross validation
- Figures - Best Practices & Examples

Three principled ways to verify a model



Formal Verification: Vapnik–Chervonenkis (VC) Dimension for sigmoid activation functions: at least $\Omega(|E|^2)$, at most $O(|E|^2 |V|^2)$, with the sets E of edges and V of Nodes in a directed acyclic graph.


Model Verification Example - Learning to Balance



Rottmann, N.; Kunavar, T.; Babič, J.; Peters, J.; Rueckert, E. [Learning Hierarchical Acquisition Functions for Bayesian Optimization](#) International Conference on Intelligent Robots and Systems (IROS' 2020), 2020.

The learning algorithm is based on Bayesian Optimization (BO).

Or is a recurrent network beneficial to model the data?




BO is a global optimizer that learns a distribution over policies and rewards.

Goal: Find the best policy

The learning algorithm is based on **Bayesian Optimization (BO)**.

Or is a recurrent network beneficial to model the data?



BO is a global optimizer that learns a distribution over policies and rewards.

Goal: Find the best policy


BO uses an *acquisition function* to select the next best policy candidate.

e.g., the expected improvement:

$$\alpha(x; D) = (\mu(x) - \tau) \Phi \left(\frac{\mu(x) - \tau + \xi}{\sigma(x)} \right) + \sigma(x) \phi \left(\frac{\mu(x) - \tau + \xi}{\sigma(x)} \right),$$

The learning algorithm is based on **Bayesian Optimization (BO)**.

Or is a recurrent network beneficial to model the data?



Our approach: Using a hierarchical acquisition function.

- Hierarchical BO: features \rightarrow policies


$$c^{[k+1]} = \max_c \alpha(c; D^{[1:k]})$$

$$\theta^{[k+1]} = \max_{\theta} \alpha(\theta; c^{[k+1]}, D^{[1:k]})$$

Learning Performance using features 4 & 5 only


TABLE III: Feature description

Feature 1	success
Feature 2	maximum deviation of the CoM in x direction
Feature 3	maximum deviation of the CoM in y direction
Feature 4	velocity of the CoM in x direction at 200 ms
Feature 5	velocity of the CoM in y direction at 200 ms
Feature 6	velocity of the CoM in x direction at 400 ms
Feature 7	velocity of the CoM in y direction at 400 ms



Model Verification Example - Learning to Balance



Learning Performance using different selections of features – the model verification!



Note: Mean and standard deviations are illustrated **and** the **performance scores of the individual experiments** as dots. The scattering of the dots indicates how often the RL approach gets stuck in a **sub-optimal local minima**.

Rottmann, N.; Kunavar, T.; Babič, J.; Peters, J.; Rueckert, E. [Learning Hierarchical Acquisition Functions for Bayesian Optimization](#) International Conference on Intelligent Robots and Systems (IROS' 2020), 2020.

Data Verification Example - Learning the Dynamics Model of a Robot arm



Rueckert, Elmar; Nakatenus, Moritz; Tosatto, Samuele; Peters, Jan [Learning Inverse Dynamics Models in \$O\(n\)\$ time with LSTM networks](#)
Proceedings of the International Conference on Humanoid Robots (HUMANOIDS), 2017.

Data Verification Example - Learning the Dynamics Model of a Robot arm

The **goal** is to predict the optimal motor torques given the joint angles, velocities and accelerations.

This function is called **Inverse Dynamics Model**:

$$\tau = M(q)\ddot{q} + h(q, \dot{q}) + \epsilon(q, \dot{q}, \ddot{q})$$

A supervised learning problem:

$$\mathbf{y} = f(\mathbf{x}) + \zeta : \mathbb{R}^{3d \times 1} \mapsto \mathbb{R}^{d \times 1}$$

$$\mathbf{y} = \tau$$

$$\mathbf{x} = [\mathbf{q}^T, \dot{\mathbf{q}}^T, \ddot{\mathbf{q}}^T]^T$$

Given a **dataset**, the goal is to minimize the **mean-squared error (MSE)** of the predicted and the true motor torques:


$$\text{dataset } \mathcal{D} = \langle \mathbf{x}_t, \mathbf{y}_t \rangle_{t=1, \dots, n}$$

$$MSE = \frac{1}{dn} \sum_{j=1}^d \sum_{t=1}^n \left(\hat{y}_t^{[j]} - \tilde{y}_t^{[j]} \right)^2$$

Data Verification Example - Learning the Dynamics Model of a Robot arm


Verification of the Learning Algorithm - Baseline Comparisons

- The naive approach is to simply compute the output based on the sum of the current state and the current velocity.
- Gaussian Processes are state-of-the-art model learning approaches.
- Our approach is a recurrent neural network called long-short-term-memory (LSTM) network.




Data Verification Example - Learning the Dynamics Model of a Robot arm

Verification of the Importance of Capturing Temporal Dependencies in the Data.
Or is a recurrent network beneficial to model the data?




Data Verification Example - Learning the Dynamics Model of a Robot arm

Verification of the Number of Data Samples needed for training the model.



Data Verification Example - Learning the Dynamics Model of a Robot arm




Evaluation of the Computational & Memory Costs of the model.



Rueckert, Elmar; Nakatenus, Moritz; Tosatto, Samuele; Peters, Jan [Learning Inverse Dynamics Models in O\(n\) time with LSTM networks](#)
Proceedings of the International Conference on Humanoid Robots (HUMANOIDS), 2017.

Overfitting & No Free Lunch Theorem

By that we can detect Overfitting or Underfitting!




Avoid underfitting: As long as you do not observe an increase in the test error, you should increase the model complexity! For example, increase the number of layers or neurons in a neural network.


No free Lunch Theorem

“All models are wrong, but some models are useful”, by George Box (Box and Draper 1987, p424).

There is not a single best model or learning algorithm that works optimally for all kinds of problems. This is called the [no free lunch theorem](#) (Daniel Wolpert 1996).




19



Example of a Cross-domain research study: Tanneberg, Daniel; Rueckert, Elmar; Peters, Jan. [Evolutionary training and abstraction yields algorithmic generalization of neural computers](#), Nature Machine Intelligence, pp. 1–11, 2020.

No free Lunch Theorem

“As a consequence of the no free lunch theorem, we need to develop many different types of models, to cover a wide variety of data that occurs in the real world”, by Kevin P. Murphy ([p24 in his machine learning book](#))





From <https://medium.com/@LeonFedden/the-no-free-lunch-theorem-62ae2c3ed10c>

K-fold cross validation

- To verify the correctness of the model on new but related data.
- To test the generalization ability.
- To identify Overfitting or Underfitting.


- **Ideal case: Large Dataset**



22

- **Typical case: Small Datasets (or long tails)**



K-Fold Cross Validation



Each dot corresponds to one test result. Compute the mean and the standard deviation to identify when Overfitting kicks in.

K-fold Cross Validation

- **Data Verification:** To test if your dataset is large enough.
- **Model Verification:** To test if your model has enough free parameters.




Examples:



- **Data Verification:** 23
 - M ... samples: Test for the minimum number of training samples,
 - M ... samples: Are the data sets balanced?
- **Model Verification:**
 - M ... network or model type.
 - Number of Hidden Layer, neurons etc.



Figures

- Make sure that all axis have labels.
- Always add a legend (images or tables may be exceptions).
- Use different line colors, e.g., via `matplotlib.colors` import `LinearSegmentedColormap`, `ListedColormap`.
- Use a minimum line width of 2 and different line styles.
- The font size of text in figures should be equal to the figure caption font size.
- The caption of a figure needs to be self-explaining. All major elements in a figure need to be defined.
- Remove bounding boxes of legends and of the graph if not needed.
- Remove all redundant or unnecessary elements.





Bar Plot Examples

With an inline detail plot.





Learning Curve Examples

With a statistics as a table on top.



Typical evaluation of multiple learning methods on multiple 'runs', from [Sheller et al. 2020](#).


Neural Network Model Figures



Xue, Honghu; Hein, Benedikt; Bakr, Mohamed; Schildbach, Georg; Abel, Bengt; Rueckert, Elmar. [Using Deep Reinforcement Learning with Automatic Curriculum Learning for Mapless Navigation in Intralogistics](#). Applied Sciences (MDPI), Special Issue on Intelligent Robotics, 2022.


Tanneberg, Daniel; Rueckert, Elmar; Peters, Jan. [Evolutionary training and abstraction yields algorithmic generalization of neural computers](#). Nature Machine Intelligence, pp. 1–11, 2020.

Algorithm & Task Figures



Tanneberg, Daniel; Rueckert, Elmar; Peters, Jan. [Evolutionary training and abstraction yields algorithmic generalization of neural computers](#). Nature Machine Intelligence, pp. 1–11, 2020.

Task Performance Statistics




Tanneberg,
Daniel;
Rueckert,
Elmar; Peters,
Jan.

**Evolutionary
training and
abstraction
yields
algorithmic
generalization
of neural
computers.**

Nature Machine
Intelligence, pp.
1–11, 2020.

More on Figures will follow in the Jupyter Python Tutorial

`%%html ...`



Chair of Cyber-Physical-Systems, Austria

Credentials	
Host	Montanuniversitaet Leoben
Web	https://cps.unileoben.ac.at
Mail	cps@unileoben.ac.at
Authors	Vedant Dave, Fotis Lygerakis, Linus Nwankwo, Melanie Neubauer, Nikolaus Feith and Elmar Rueckert
Corresponding Authors	melanie.neubauer@unileoben.ac.at , rueckert@unileoben.ac.at
Last edited	02.10.2023

Database Basics





This is a tutorial on the basics of interfacing databases for beginners.

Content

1. Motivation for learning Python?
2. How to run Python on your computer?

Summary of Statistics & Validation

- Model Verification and Evaluation
- Overfitting & No free Lunch Theorem
- K-fold cross validation
- Figures - Best Practices & Examples



Thank you for your attention!

Visit our Youtube Channel:


<https://youtube.com/@CPSAustria>



Phone: +43 3842 402 – **1901** (Sekretariat CPS)

Email: cps@unileoben.ac.at

Web: <https://cps.unileoben.ac.at>



Disclaimer: The lecture notes posted on this website are for personal use only. The material is intended for educational purposes only. Reproduction of the material for any purposes other than what is intended is prohibited. The content is to be used for educational and non-commercial purposes only and is not to be changed, altered, or used for any commercial endeavor without the express written permission of Professor Rueckert.