

Step in compilation Identification and classification

Problem:

Now, to produce software we use a lot of tools in the compile chain. Not only one compiler.

A software is a result of many translations at different times.

Goal:

Identify and classify this different times.

Example: FFTW

DSL for FFT function generation

Library generation :

Decomposition & description allow to generate variant FFTW.

During installation:

Performance evaluation of each variant

At runtime:

Function selection by planer

Example: HPBCG

DSL for including compilette in your code

```
#cpu cell
typedef int (*pifi)(int);
pifi multiplyFunc;

pifi multiplyCompile(int multiplyValue)
{
    insn *code;

    posix_memalign(&code, 1024, 16);
    printf("Code generation for multiply value %d\n", multiplyValue);
    #[
        .org    code
        mpyi    $3, $3, (multiplyValue)
        bi $lr
    ]#;
    printf("Code generated\n");
    return (pifi)code;
}
```

Example: HPBCG

External processing:

- Parse assembler chunk in the code and assemble it in binary chunk.

Compilation:

- create code generator

Runtime :

- instantiate chunk of binary by putting correct constant value in the compilette.
- Call it

Analysis of some different tool:

FFTW : Fast Fourier Transform generator

SPIRAL: Code generation for DSP

Rathaxes : Code generation for driver

Mesa : 3d library

Gcc : C/C++ (and more) compiler

Llvm : a modular backend for create compiler

Nanojit : a C++ library that allow to emits machine code

HPBCG : High Performance Binary code generator

VPU : Fast, architecture neutral dynamic code generator

Java : Compiler and Virtual machine.

.NET : Compiler and Virtual machine.

Cuda : language extension for GPU programming

OpenCL : language extension for GPU programming

Result : Different technics are used

ECG: External code generation

High level algorithm representation and decomposition allow to generate specialized part of program

ICG: Internal code generation

Use program information to generate specialized part of program

IT: Install Time

Copy program and dependencies into a specific machine

LT:Loading Time

Collect usable part of code and load program

SC: Static compilation

translate program into optimized machine code

IC: Iterative Compilation

Use previous running information to optimize code

JIT: Just-in-time compilation

runtime code translation of already compiled IR in machine code

DDS: Data driven specialization

Runtime selection of the fastest algorithm

Result analysis:

Heterogenous **tools** → different **goals**

Give more or less **abstraction**

Give more or less **optimization**

Done **early** or **late** in compilation chain


Not the same concern: **model** or **data**

Different point of view:

Program

Architecture

So we need to take account of these parameter.



Emergence of an organisation:

2 MAJOR OPOSITION :

MODEL ↔ DATA

ABSTRACT ARCHITECTURE ↔ REAL ARCHITECTURE

More generic with abstraction in our program we are,
Less known values we use.

More Specialized with known values in our program we are,
Less abstraction we use.

Algorithm



Model

Real
Architecture



Abstract Architecture

Data

Instructions
Executions

Algorithm

Model

DSL

Statically compiled
Language

Stack
Based
Vm

Registers
Based
Vm

Real
Architecture

la32

Abstract Architecture

Data

Instructions
Executions

Emergence of an organisation:

Code generation centric: Mainly works on source code (or AST) guided by the model.

- * External code generation: generation via external tool after processing a DSL.
- * Internal code generation: features of language (preproc, metaprogramming) for a generation, use the semantics of the host language.

Package centric: Mainly on architecture concrete, works on the the system (type of OS and library), guided by the machine.


- * Install time: action taken when copying the software in the system
- * Loading time: action taken when loading the software into memory


Compiler centric: Cold optimization of the program guided by the source code.

- * Static compilation: Classical compilation
- * Iterative compilation: compilation with consideration of the preceding run.

Runtime centric: Live optimization algorithm guided by the data and the concrete machine.


- * JIT: Compilation and dynamic specialization based on the data to be processed (hotspot compiles). Huge runtime overhead.
- * Data-driven Specialization: selecting among a set of functions the most appropriate in relation to input data. Little or no runtime overhead.






Model

**Real
Architecture**



Abstract Architecture

Data



Algorithm

Model


Real
Architecture

Abstract Architecture

Compiler centric

Data

Instructions
Executions



Algorithm

Model


Real
Architecture


Abstract Architecture


Runtime centric

Data

Instructions
Executions







Times:

T0-T1:

ECG: External code generation

T1-T2:

ICG: Internal code generation

SC: Static compilation

T2-T3:

: IT: Install Time

LT: Loading Time

T3-T4:

JIT: Just-in Time

DDS: Data-driven Specialisation

T0-T4:

IC : Iterative compilation

Some program life cycle thread

FFTW vs SPIRAL:

Both present a DSL

Both allow to describe mathematical abstraction

HPBCG vs VPU

VPU allow to emit via library virtual machine instruction

HPBCG allow to emit REAL instruction

Both generate some code before compilation

Both generate code in runtime

Algorithm


Model

FFTW

SPIRAL

Real
Architecture

Abstract Architecture



Data

Instructions
Executions

Algorithm

Model

VPU


HPBCG


Real
Architecture

Abstract Architecture

Data

Instructions
Executions





The Perfect Curve

Allow to crawl the different abstraction level throw algorithm to real instruction in all different time of execution.

What's about :

Optimisation?

multi-paradigm?

The Perfect Curve constraints:

Frontend agnostic

Modularity and flexibility

Mutli-architecture

Compilation and optimisation

Code emition handling (JIT and more)

The Perfect Curve constraints:


Frontend agnostic

Modularity and flexibility

Mutli-architecture

Compilation and optimisation

Code emition handling (JIT and more)



Questions?