

NoWalletConnect

Product documentation

USDT checkout without a wallet-connect popup.

For merchants, integrators, and operators.

Updated September 2026

1. What NoWalletConnect is

NoWalletConnect is a crypto checkout for USDT. The customer does not connect MetaMask, Phantom, or any other wallet to the site. They send USDT themselves to a receive address.

The product:

- Shows the correct network and token.
- Locks amount and/or network when those values are in the payment URL.
- Lets the customer fill any value the merchant did not lock.
- Shows a QR code and copyable receive address.
- Waits for a matching incoming payment, then confirms it with an explorer link.
- Returns the buyer to the merchant site with success parameters.

Money goes to the **merchant wallet**, not to a NoWalletConnect custody account.

2. Who uses it

Merchant — Has a merchant ID, email, Polygon wallet, Solana wallet, and a return URL. Shares a payment link or embeds a Pay button.

Customer — Opens that link, fills unlocked fields, and sends USDT from their own wallet.

NoWalletConnect — Looks up the merchant, shows the right receive address, verifies the transfer, records the payment, and redirects back.

3. The idea in one sentence

Pay by sending USDT to an address, not by connecting a wallet to a website.

4. Networks and tokens

Customer chooses	They must send	Token standard
Polygon	USDT only	ERC-20
Solana	USDT only	SPL

Wrong network or wrong token can be unrecoverable. Checkout warns before they send.

5. Objects in the system

Merchant ID — Short public handle, for example NWC. It appears in every payment link. It is not a secret and is not enough, by itself, to open the dashboard.

Email — Paired with the ID for dashboard sign-in. Both must belong to the same database row.

Wallets — Polygon (0x...) receives Polygon USDT. Solana address receives Solana USDT. The customer never types these. The payment page loads them from the merchant record.

Return URL / webhook — HTTPS page on the merchant site. After a confirmed payment, checkout redirects here with status, amount, tx hash, merchant, and network.

Payment record — After a confirmed transfer, a row stores date, merchant ID, amount, transaction hash, and network. The dashboard uses that for analytics.

6. Pages

guide.html — Integration guide. Merchants copy a button snippet, replace MERCHANT_ID, and optionally lock amount and network.

pay.html — First customer screen. Requires `?merchant=ID`. If amount is in the URL, that field is locked. If network is in the URL, that choice is locked. Missing values stay editable. Proceed sends the customer to the payment page with merchant, amount, and network.

checkout / payment page — Shows exact amount, network and token, a network warning, QR, copyable address, a 15-minute window, waiting / expired / received status, and a success view with explorer link. Must read merchant, amount, and network from the URL.

merchant.html — Dashboard. Sign-in is merchant ID + email. Shows wallets, checkout link, volume, counts, network split, last 7 days, history, and CSV export.

7. Payment URL rules

Base link:

```
https://solacediamond.github.io/nowalletconnect/pay.html?merchant=MERCHANT_ID
```

Param	Required	If present	If missing
merchant	Yes	Shown on the page	Link is invalid
amount	No	Locked. Customer cannot change it	Customer types the amount
network	No	Locked to polygon or solana	Customer picks the network

Examples

```
pay.html?merchant=NWC
pay.html?merchant=NWC&amount=49.99
pay.html?merchant=NWC&network=solana
pay.html?merchant=NWC&amount=49.99&network=polygon
```

A fully locked package is the right pattern for a fixed-price product. An open amount link is the right pattern for donations or custom invoices.

8. Full payment path

```
Merchant website
  Pay button → pay.html?merchant=ID[&amount=X][&network=Y]
               locked fields stay fixed; missing fields are filled by the customer
               ↓
Payment page?merchant=ID&amount=X&network=Y
```

QR + address from the merchant record
↓
Customer wallet sends exact USDT
↓
Verifier watches the receive address
↓
Success → payment row → redirect to merchant return URL

9. Success return

After USDT is confirmed, checkout should send the buyer to the webhook URL saved on the merchant row, with these query parameters:

Param	Meaning
status	success
amount	USDT amount paid
tx_hash	On-chain transaction hash
merchant	Merchant ID
network	polygon or solana
payment_id	Local payment reference

Example return:

```
https://yoursite.com/order-complete?status=success&amount=49.99  
&tx_hash=0x...&merchant=NWC&network=polygon&payment_id=pay_123
```

Read it on the merchant page:

```
const q = new URLSearchParams(location.search);  
if (q.get("status") === "success" && q.get("merchant") === "MERCHANT_ID") {  
  const paid = parseFloat(q.get("amount"));  
  const tx = q.get("tx_hash");  
  const network = q.get("network");  
}
```

The return URL comes from the merchant webhook field, not from the payment link. Use a real HTTPS page on your site.

10. Payment window

- Watching starts when a valid amount and wallet exist.
- Poll every few seconds.
- Treat a matching amount to the receive address as paid.
- Expire after 15 minutes. The last 5 minutes can show an urgent timer.
- Check again restarts a lookup.
- Exact-amount matching matters. Underpay or overpay may not confirm automatically.

11. What merchants should tell customers

- Send USDT only.
- Use the same network shown on screen.
- Send the exact amount.
- Do not close the page until it says received, or save the address and amount.
- If the timer expires, start a new checkout.

12. Embed rules

Allowed to change — Button label, colors, padding, font size, radius.

Do not change — Host path unless you were given a new URL; the query names merchant, amount, and network; dropping the Powered by NoWalletConnect credit.

Sample button (price locked, network open):

```
<a href="https://solacediamond.github.io/nowalletconnect/pay.html?merchant=MERCHANT_ID&amount=49.99">Pay 49.99 U
```

13. Dashboard analytics

Figures come from payment rows for that merchant ID only.

Metric	Meaning
Volume	Sum of USDT amounts
Payments	Number of rows
Average	Volume ÷ payments
Largest	Max single amount
Polygon / Solana	Count and volume per network
Last 7 days	Sum per day if the date field parses
Table	Date, amount, network, explorer link

Filters: All / Polygon / Solana. Search matches amount or transaction hash. Export downloads the visible rows as CSV. An empty table means that merchant has no matching rows, or the ID on the payment does not match the signed-in merchant.

14. Pricing

- \$0.25 setup (one time).
- No monthly fee.
- No NoWalletConnect cut per payment.
- Sender pays network fees.

- Merchant receives the USDT at their wallet.

15. Limits and safety

- Merchant ID in a URL is public. Do not treat it as a password.
- Dashboard access is ID + email. Anyone who knows both can open the dashboard in this model.
- Apps that expose the full database make emails and wallets visible. Production should look up one row on a server.
- Never tell customers they can send ETH, SOL, BTC, or USDT on another chain.
- Webhook / return URL is required on the registration form even if labeled optional.
- A payment only appears in the dashboard when the PAYMENTS row uses the same merchant ID as sign-in.

16. Quick test

- Confirm a test merchant exists (ID, email, both wallets, return URL).
- Open merchant.html and sign in with that ID and email.
- Open pay.html?merchant=ID&amount;=1 in a private window.
- Confirm amount is locked and network can still be chosen (unless network was also in the URL).
- Continue and confirm the QR address equals the wallet on file for that network.
- Send a test amount only if you intend to. Otherwise stop at the QR.
- After a real test payment, confirm the dashboard row and the return URL query params.

17. Glossary

Term	Meaning
pay.html	Amount + network screen. Locks URL params.
Payment page	Address, QR, waiting, success
Merchant ID	Public store handle
Return URL	Merchant page that receives success params
Database	Source of merchants and payment history
Verifier	Service that checks the chain for incoming USDT
Receive address	Merchant wallet for the chosen network

18. Support

Telegram: <https://t.me/noWalletConnect>

Integration guide: guide.html in the product site.

Product overview: README.md in the repository.