

A Glimpse Is Enough: Mask-Aware Sparse-Input Traffic Engineering for LEO Satellite Constellations

Linhui Wei

Abstract—Traffic engineering (TE) is a key control primitive for low-Earth-orbit (LEO) satellite constellations, whose topologies and traffic change continuously as satellites move. Existing learning-based TE systems — for terrestrial and satellite networks alike — assume that the complete traffic matrix is measured and delivered to the controller at every decision epoch. This assumption rarely holds in practice: network-wide measurement competes with user traffic for scarce onboard resources, and the controller typically observes only a sparse subset of demands. We present SiTE, a learning-based TE system that allocates traffic for *all* active demands directly from sparse observations. SiTE represents unmeasured demands with learnable mask embeddings instead of zeros, gates message passing so that placeholders never contaminate link-state estimates, and recovers missing information from the recent observation history through a Transformer fused with spatial embeddings via per-demand cross-attention — all trained end-to-end against the TE objective without an explicit completion stage. Demand pruning and size-invariant weights further allow a model trained once to be reused as the topology and the active demand set drift, without retraining. On a 22×72 Starlink-like constellation with real traffic dynamics, SiTE achieves [TODO: XX]% of the fully-observed performance with only [TODO: XX]% observability, outperforming zero-filling and two-stage complete-then-optimize baselines by up to [TODO: XX]%, at [TODO: XX] ms inference per snapshot.

Index Terms—Satellite networks, traffic engineering, sparse measurement, graph neural networks, reinforcement learning.



1 INTRODUCTION

LOW-EARTH-ORBIT (LEO) satellite constellations are rapidly scaling toward tens of thousands of satellites, carrying user traffic with pronounced spatial and temporal fluctuations over inter-satellite links (ISLs) of limited capacity. Without global coordination, shortest-path or purely distributed routing concentrates traffic on a few congested ISLs, leaving network capacity underutilized. Traffic engineering (TE) — centrally optimizing how each demand is split across candidate paths — has therefore become a key control primitive for satellite networks, just as it has been for cloud wide-area networks (WANs) over the past decade [1], [2], [3].

A recent line of learning-based TE systems has made centralized control practical at scale: by replacing online optimization solvers with neural models, they cut allocation time from minutes to milliseconds on WANs [1], [3], [4] and, most recently, on satellite constellations [5]. These systems, however, share a silent premise: the *complete* traffic matrix — the demand between every pair of nodes — is assumed to be measured and delivered to the controller at every decision epoch.

This premise rarely holds in LEO constellations. Network-wide measurement requires every satellite to meter, aggregate, and downlink fine-grained flow statistics through bandwidth-constrained telemetry channels, competing with user traffic and consuming scarce onboard resources; measurement gaps due to intermittent ground contacts and equipment degradation are the norm rather

than the exception. In practice, the controller observes only a *sparse* traffic matrix — a subset of demands measured at each epoch. Naive workarounds fall short on both ends: filling unobserved entries with zeros systematically misleads the allocator into starving unmeasured demands, while two-stage “complete-then-optimize” pipelines propagate reconstruction errors into allocation decisions. The state-of-the-art sparse-TE approach [6] fills unobserved entries with zeros and compensates with synthetic training augmentation, but it targets terrestrial networks with static topologies — leaving sparse-observation TE for dynamic satellite networks unaddressed.

Designing a TE system that operates on sparse observations of satellite traffic raises three challenges. **(C1) Representing the unobserved.** Unobserved demands are not zero; the model must distinguish “no traffic” from “not measured”, infer missing volumes from history, and prevent placeholder values from contaminating the shared network representation during message passing. **(C2) Perpetual dynamics.** Satellites move: topologies, candidate paths, and even the set of active demand pairs drift over time. Retraining per snapshot is infeasible; the model must be trained once and reused across snapshots unseen in training. **(C3) Constellation scale.** A 22×72 constellation induces 2.5 million demand pairs and tens of millions of path variables if modeled exhaustively — beyond the memory and latency budget of any online system.

We present SiTE (Sparse-input Traffic Engineering), a learning-based TE system for LEO constellations that allocates traffic directly from sparse observations. SiTE builds on the flow-centric GNN and multi-agent RL backbone of Teal [1] and augments it with three sparse-aware compo-

• L. Wei is with the National Innovation Institute of Defense Technology, Academy of Military Science, Beijing, China (e-mail: weilinhui998@163.com).
Manuscript received XXX; revised XXX.




Fig. 1. Sparse traffic observation in an LEO constellation: only a subset of satellites meters traffic, so the controller receives a sparse traffic matrix yet must allocate all demands.

nents. First, unobserved demands are represented by *learnable mask embeddings* rather than zeros, letting the model learn a prior for missing traffic (C1). Second, a *mask-aware gated GNN* blocks message passing from unobserved path nodes to link nodes — preventing placeholder pollution of link utilization estimates — while still letting unobserved demands sense link states in the reverse direction (C1). Third, a *Transformer temporal encoder* summarizes the recent history of sparse observations and fuses it with spatial embeddings via per-demand cross-attention, recovering missing information from temporal correlation (C1). For deployment at scale, SiTE prunes the demand set to pairs with observed traffic — $\sim 400\times$ fewer variables on a 22×72 Starlink-like constellation — and keeps all model weights independent of the demand-set size, so a model trained once transfers across topology snapshots and drifting demand sets without retraining (C2, C3). Allocations are finally refined by a parallelizable ADMM step to repair residual capacity violations.

In summary, this paper makes the following contributions:

- We identify sparse traffic observability as a fundamental yet unaddressed constraint for satellite TE, and formulate TE from sparse observations over dynamic constellations (sections 2 and 3).
- We design SiTE, which combines learnable mask embeddings, mask-aware gated message passing, and temporal-spatial cross-attention to allocate traffic directly from sparse inputs, without an explicit completion stage (section 4).
- We show how demand pruning and size-invariant weights enable train-once, zero-retraining deployment across topology snapshots and drifting demand sets (sections 4 and 5).
- On a 22×72 Starlink-like constellation with real topology dynamics, SiTE achieves [TODO: XX]% of the fully-observed performance with only [TODO:

XX]% observability, outperforming zero-filling and two-stage baselines by [TODO: XX-XX]%, with [TODO: XX] ms inference per snapshot (section 5).

2 RELATED WORK

2.1 ML-Driven Traffic Engineering for WANs

Traffic engineering has long been formulated as a constrained optimization problem solved by linear programming (LP), whose runtime scales poorly with network size. SMORE [2] decouples robust oblivious path selection from online rate adaptation, while NCFLOW [7] and POP [8] accelerate LP by problem decomposition, trading allocation quality for speed. A recent line of work replaces online solvers with learned models: DOTE [3] directly maps historical traffic matrices to split ratios with stochastic optimization; Teal [1] combines a flow-centric GNN, multi-agent RL, and ADMM fine-tuning to achieve near-optimal allocations with orders-of-magnitude speedups; FIGRET [9] enhances robustness against traffic uncertainty at per-flow granularity. To survive topology changes without retraining, HARP [4] enforces invariances to node permutation and tunnel reordering, transferring across topologies unseen in training. More recently, large language models have been explored as general-purpose traffic planners [10]. However, all of these systems assume the *complete* traffic matrix is available at decision time — an assumption that rarely holds in large-scale satellite networks, where network-wide measurement is prohibitively expensive.

2.2 TE and Routing for Satellite Networks

LEO mega-constellations pose unique challenges for TE: topologies change every few tens of milliseconds as satellites move, and control decisions must be produced within stringent latency budgets. Classical approaches absorb mobility through topology abstractions — the virtual node model binds logical nodes to earth-fixed footprints so that upper-layer routing observes a quasi-static grid [11]. SaTE [5] is the state-of-the-art learning-based TE for satellite constellations: it formulates a heterogeneous graph over satellites, demands, paths, and links, prunes zero-traffic relations to make training tractable on a single GPU, and selects representative topologies via Graph2Vec and DPP sampling so that one trained model generalizes across topology snapshots with millisecond inference. In parallel, FNC [12], [13] targets dynamic traffic allocation for earth-observation constellations, replacing RL with end-to-end imitation learning and substituting iterative constraint solvers with normalization-based feasibility layers. Notably, FNC’s imitation learning constructs its expert supervision by solving an offline optimum over the *fully realized* demands of each episode — a paradigm that fundamentally requires complete post-hoc observability, which is unavailable under sparse measurement. Both SaTE and FNC, like their WAN counterparts, assume the traffic matrix is fully observable at decision time.

2.3 TE with Incomplete Traffic Observations

Network-wide traffic measurement is expensive: collecting a complete traffic matrix requires instrumenting all ingress

TABLE 1
Comparison with the closest prior systems.

	Teal [1]	SaTE [5]	TEST [6]	FNC [12]	Ours
Satellite scenario	×	✓	×	✓	✓
Dynamic topology	×	✓	×	✓	✓
Sparse observation	×	×	✓	×	✓
Temporal modeling	×	×	✓	×	✓
Mask-aware model	×	×	×	×	✓
Demand-set drift	×	partial	×	×	✓

nodes at fine time granularity, which is particularly onerous on resource-constrained satellite platforms. A classical workaround is a two-stage pipeline — first estimate or complete the traffic matrix (network tomography, matrix completion), then optimize routing on the estimate — but reconstruction errors propagate to and degrade the downstream allocation. TEST [6] is, to our knowledge, the first end-to-end approach that learns routing policies directly from sparsely measured traffic matrices, integrating a Transformer over historical sparse sequences with a GCN over the topology; it fills unobserved entries with zeros, compensates with synthesized training augmentation, and targets terrestrial networks with static topologies. In the graph learning literature, message passing under missing node features has been addressed via teacher–student distillation [14], but such techniques have not been applied to network TE. No prior work, to our knowledge, performs TE from sparse traffic observations in satellite networks, where the difficulty is compounded by time-varying topologies and drifting demand sets.

2.4 Positioning

Our work sits at the intersection of these three lines (table 1). Unlike SaTE and FNC, which assume fully observable demands, we perform TE from sparse observations (10%–70% observability). Unlike TEST, which fills unobserved entries with zeros and targets static terrestrial networks, we replace missing entries with learnable mask embeddings, gate their message passing, and handle LEO dynamics — time-varying topologies and drifting demand-pair sets — via demand pruning with size-invariant model weights, enabling train-once, zero-retraining deployment.

3 MODEL AND PROBLEM FORMULATION

3.1 Network and Traffic Model

We model the constellation at control epoch t as a directed graph $G^t = (V, E^t)$, where V is the set of N satellites and E^t the set of inter-satellite links (ISLs), each link e with capacity c_e . Time is slotted into control epochs; within an epoch the topology snapshot is fixed, while across epochs both E^t and the traffic change as satellites move.

Traffic is described by a demand matrix $D^t \in \mathbb{R}^{N \times N}$, where d_i denotes the volume of the i -th source–destination pair. Since satellite traffic is geographically concentrated, we maintain an *active demand set* $\mathcal{K}^t$ — the pairs with nonzero demand in recent history (section 4) — and only these are modeled. Each demand $i \in \mathcal{K}^t$ is served by κ pre-selected candidate paths $P_i = \{p_{i,1}, \dots, p_{i,\kappa}\}$ ($\kappa = 4$ edge-disjoint

TABLE 2
Main Notations.

Symbol	Definition
$G^t = (V, E^t)$	constellation graph at epoch t ; c_e link capacity
D^t, d_i	demand matrix; volume of demand i
$\mathcal{K}^t$	active demand set at epoch t
κ, P_i	candidate paths per demand; path set of demand i
$r_i, f_{i,k}$	split ratios of demand i ; flow on path $p_{i,k}$
M, ρ	binary observation mask; observability ratio
O^t, H^t	sparse observation $D^t \odot M$; last- L history
ϕ	learnable mask embedding for unmeasured demands
$A, \tilde{A}$	bipartite adjacency; its mask-gated variant
H_S, H_T, H_F	spatial, temporal, and fused embeddings
π_θ, R	TE policy network; ground-truth reward

shortest paths in our implementation). The TE decision for demand i is a split-ratio vector $r_i \in \mathbb{R}^\kappa$ with $r_{i,k} \geq 0$ and $\sum_k r_{i,k} \leq 1$, allocating flow $f_{i,k} = r_{i,k} \cdot d_i$ to path $p_{i,k}$; the residual $1 - \sum_k r_{i,k}$ represents intentionally unserved traffic. Main notations are summarized in table 2.

3.2 TE with Complete Observation

With the complete demand matrix available, TE is the classic path-based allocation problem. Using the total satisfied demand as the objective (total-flow TE [1], [7]):

$$\max_{\{f_{i,k}\}} \sum_{i \in \mathcal{K}^t} \sum_{k=1}^{\kappa} f_{i,k} \quad (1)$$

$$\text{s.t.} \quad \sum_{k=1}^{\kappa} f_{i,k} \leq d_i, \quad \forall i \in \mathcal{K}^t, \quad (2)$$

$$\sum_{(i,k): e \in p_{i,k}} f_{i,k} \leq c_e, \quad \forall e \in E^t, \quad (3)$$

$$f_{i,k} \geq 0, \quad \forall i, k. \quad (4)$$

Constraint (2) caps allocation at the actual demand, and (3) enforces link capacities. Problem (1)–(4) is a linear program solvable to optimality, but at constellation scale its solve time far exceeds the control epoch [5], and — more fundamentally for this paper — both the objective through $f_{i,k} = r_{i,k} \cdot d_i$ and constraint (2) require knowing d_i for every active demand.

3.3 TE with Sparse Observation

3.3.1 Observation Model

At each epoch only a subset of demands is measured. A binary mask $M \in \{0, 1\}^{|\mathcal{K}^t|}$ marks demand i as measured ($M_i = 1$) or not ($M_i = 0$), and the controller receives the sparse observation

$$O^t = D^t \odot M, \quad \text{together with } M \text{ itself}, \quad (5)$$

where $\odot$ is the element-wise product. Figure 2 contrasts a ground-truth traffic matrix from our Starlink trace with its node-level sparse observation. We consider two measurement granularities: *flow-level*, where a fraction ρ of demand pairs is sampled, and *node-level*, where a fraction ρ of satellites meter all their outgoing demands — the latter matching deployments where measurement capability resides on a subset of satellites. The controller additionally retains the last L sparse observations $H^t = (O^{t-L+1}, \dots, O^t)$.




Fig. 2. A ground-truth traffic matrix from the Starlink 22×72 trace (150 busiest satellites shown) and its node-level sparse observation: white cells carry no traffic, gray rows are unmeasured source satellites, and colored cells are observed demands.

3.3.2 Problem Statement

Sparse-observation TE seeks a policy π that maps the observable state to split ratios for *all* active demands,

$$\{r_i\}_{i \in \mathcal{K}^t} = \pi(H^t, M, G^t), \quad (6)$$

maximizing the *ground-truth* objective: allocated flow is counted against the true demand d_i and the capacity constraints (3), even though d_i is unknown to π for unmeasured i . Formally,

$$\max_{\pi} \mathbb{E}_t \left[\sum_{i \in \mathcal{K}^t} \sum_{k=1}^{\kappa} f_{i,k}(\pi) \right] \quad \text{s.t. (2)–(4) with the true } D^t, \quad (7)$$

where the expectation is over traffic and topology dynamics. The problem is a partially observable sequential decision problem: unlike (1)–(4), the decision variables and the evaluation live in different information sets — the policy sees O and M , while feasibility and performance are dictated by the hidden D .

3.4 Solution Paradigm

Three solution families exist for (7). *Solve-with-zeros* plugs O directly into the LP (1)–(4), implicitly assuming unmeasured demands are zero; it is fast to formulate but structurally starves unmeasured traffic. *Two-stage* approaches first estimate $\hat{D}$ from (H, M) — via interpolation, tensor completion, or compressive sensing — then solve the LP on $\hat{D}$; estimation is optimized for reconstruction error, which is misaligned with allocation quality, and errors propagate un-damped into the allocation. We instead adopt *end-to-end learning*: parameterize π_{θ} as a neural network and optimize θ directly against the TE objective,

$$\max_{\theta} \mathbb{E}[R(\pi_{\theta}(H, M, G), D)], \quad (8)$$

where R is the total satisfied demand computed on the true D . Since R is non-differentiable through the capacity-constrained network and the true D is available only as a training-time signal, we optimize (8) with multi-agent reinforcement learning — each demand acts as an agent sharing θ , receiving a COMA-style marginal-contribution reward (section 4) — followed by a lightweight ADMM refinement at inference to repair residual violations of (3). This paradigm makes the observation model (5) a property

Algorithm 1 SiTE inference at control epoch t

Require: sparse history H^t , mask M , topology G^t , weights θ^*

Ensure: split ratios $\{r_i\}_{i \in \mathcal{K}^t}$

- 1: $\mathcal{K}^t \leftarrow$ active demand set from recent history $\triangleright$ pruning, section 4.5
- 2: rebuild bipartite graph and gated adjacency $\tilde{A}$ from $\mathcal{K}^t, M$ $\triangleright$ eq. (10)
- 3: $x_i \leftarrow M_i d_i + (1 - M_i) \phi$ for all i $\triangleright$ mask embedding, eq. (9)
- 4: $H_S \leftarrow \text{GATEDFLOWGNN}(x, \tilde{A})$ $\triangleright$ spatial embeddings
- 5: $H_T \leftarrow \text{TEMPORALENCODER}(H^t)$ $\triangleright$ temporal embeddings
- 6: $H_F \leftarrow \text{CROSSATTENTION}(H_T, H_S)$ $\triangleright$ eq. (11)
- 7: $\{r_i\} \leftarrow \text{POLICYHEAD}([H_S \parallel H_F])$
- 8: $\{r_i\} \leftarrow \text{ADMMREPAIR}(\{r_i\}, G^t)$ $\triangleright$ section 4.6
- 9: **return** $\{r_i\}$




Fig. 3. SiTE overview: a sparse observation is embedded with mask awareness, processed by a gated flow-centric GNN in parallel with a temporal encoder, fused via per-demand cross-attention, and mapped to split ratios refined by ADMM.

of the *input*, and the optimization target (7) a property of the *training signal*, cleanly separating what the policy can see from what it is optimized for.

4 SITE DESIGN

4.1 Overview

SiTE solves the sparse-observation TE problem of section 3.3 in four stages, as illustrated in fig. 3. Given the sparse observation (O^t, M) and history H^t , (i) unmeasured demands are represented by a learnable mask embedding (section 4.2); (ii) a mask-aware gated GNN propagates information between candidate paths and links without letting placeholders contaminate link states (section 4.3); (iii) a Transformer encodes the observation history and fuses it with spatial embeddings via per-demand cross-attention (section 4.4); (iv) a shared policy head outputs split ratios per demand, refined by ADMM (section 4.6). All learnable weights are shared across demands and independent of the demand-set size, which section 4.5 exploits for zero-retraining deployment under constellation dynamics. Algorithm 1 summarizes one inference epoch.

4.2 Mask-Aware Demand Representation

A sparse observation is fundamentally ambiguous: a zero entry may mean “no traffic” or “not measured”. Zero-filling — the de-facto treatment in prior sparse TE [6] — collapses the two cases and systematically biases the allocator toward starving unmeasured demands. SiTE instead assigns each unmeasured demand a *learnable mask embedding* $\phi \in \mathbb{R}^\kappa$ (one scalar per candidate path):

$$x_i = M_i \cdot d_i + (1 - M_i) \cdot \phi, \quad (9)$$

so the model learns a data-driven prior for missing traffic during end-to-end training, and — critically — the input itself distinguishes “not measured” from “zero”. Learnable imputation has proven effective for incomplete graph features [14]; we bring it to TE, where the imputed value directly steers resource allocation. The embedding is trained jointly with the policy under the TE objective (8) rather than a reconstruction loss, so ϕ converges to values that maximize allocation quality, not reconstruction accuracy.

4.3 Gated Message Passing

SiTE inherits Teal’s flow-centric graph [1]: candidate paths and physical links form a bipartite structure where a PathNode connects to the EdgeNodes it traverses, and message passing alternates between them. Under sparse observation, however, symmetric message passing is harmful: placeholder values on unmeasured PathNodes would propagate into EdgeNode embeddings and corrupt the network-wide estimate of link utilization — a phenomenon consistent with the feature–structure interference observed in incomplete graphs [14]. We therefore gate the propagation *asymmetrically*. Let A be the normalized bipartite adjacency; we zero out entries that carry path-to-edge messages from unmeasured paths while keeping all edge-to-path entries:

$$\tilde{A}[e, p] = M_p \cdot A[e, p], \quad \tilde{A}[p, e] = A[p, e], \quad (10)$$

where M_p is the demand-level mask lifted to path p . Unmeasured demands thus remain *listeners*: they sense link states — which are shaped by measured traffic — but inject no fabricated volume into them. The gate is a fixed binary function of the mask with no extra parameters, adding zero inference overhead. The asymmetric gate yields a formal isolation property:

Proposition 1 (Placeholder isolation). Under the gated propagation (10), the embeddings of all EdgeNodes and of all PathNodes belonging to measured demands are independent of the mask embedding ϕ ; ϕ influences only the allocations of unmeasured demands.

Proof: By induction on GNN layers. At layer 0, only unmeasured PathNodes carry ϕ . At layer l , an EdgeNode aggregates path-to-edge messages with weights $\tilde{A}[e, p] = M_p A[e, p]$, which vanish for every unmeasured path; hence EdgeNode embeddings depend only on measured-path inputs and their own history, none of which contains ϕ . A measured PathNode aggregates EdgeNode embeddings (ϕ -free by the above) and its own ϕ -free input; the per-demand layers mix only paths of the same demand, which share the same mask value. Thus ϕ never enters any ϕ -free branch,

and only unmeasured PathNodes — and consequently their own split ratios — depend on ϕ . $\square$

In other words, learning a poor prior ϕ can at worst misallocate the unmeasured demands themselves, but can never corrupt the allocations of measured traffic — a robustness guarantee that zero-filling with ungated propagation does not provide.

4.4 Temporal-Spatial Fusion

Satellite traffic exhibits strong short-term temporal correlation; the recent history of sparse observations therefore carries recoverable information about currently missing entries. SiTE encodes, for each candidate path, its observation sequence over the last L epochs with a lightweight Transformer: scalar volumes are log-compressed — which we find essential for training stability — and projected to d_{model} dimensions, summed with learnable positional embeddings, and passed through a Transformer encoder; the representation at the latest step forms the temporal embedding H_T . Rather than concatenating temporal and spatial features naively, we fuse them with *per-demand cross-attention*: within each demand, temporal embeddings of its κ candidate paths act as queries attending to the κ spatial (GNN) embeddings H_S as keys and values,

$$H_F = \text{softmax}\left(\frac{W_q H_T (W_k H_S)^\top}{\sqrt{d}}\right) W_v H_S, \quad (11)$$

and the fused features $[H_S \parallel H_F]$ feed the policy head. Intuitively, the temporal stream decides *which* spatial evidence to trust for each path: when the current entry is missing, attention shifts toward paths and links whose states corroborate the historical pattern. The whole module adds [TODO: XX] ms to inference on our largest constellation (section 5).

4.5 Scaling to Dynamic Constellations

4.5.1 Demand Pruning

Modeling all $N(N-1)$ pairs of a 1,584-satellite constellation yields 2.5M demands and tens of millions of path variables — infeasible for online control. Satellite traffic, however, is geographically concentrated: only 0.25% of pairs ever carry traffic in our dataset. SiTE instantiates PathNodes only for the demand-pair union observed in historical traffic matrices, shrinking the graph by $\sim 400\times$ with no loss of served traffic, in the same spirit as SaTE’s traffic pruning [5].

4.5.2 Zero-Retraining under Drift

Pruned demand sets are not static: as satellites move, the active pair set drifts (we measure $\sim 10\%$ turnover across our trace, section 5). Rather than retraining, SiTE exploits a structural property of its architecture: every learnable component — GNN layers, mask embedding, temporal encoder, fusion and policy heads — is shared across demands and independent of the demand-set size. The demand set, candidate paths, and the bipartite graph are runtime *inputs*, not parameters. At each control epoch the controller rebuilds the graph from the current active set — a millisecond-scale index operation on +Grid constellations, where candidate paths depend only on the orbital displacement between endpoints and reduce to $O(N)$ path templates — and reuses

the trained weights as-is. Demands outside the modeled set — necessarily sporadic mice flows — fall back to shortest-path routing until the next set refresh. This reuse is justified by the following structural property:

Proposition 2 (Size invariance and permutation equivariance). The parameter set of SiTE is independent of $|\mathcal{K}^t|$, N , and $|E^t|$, and the mapping from inputs to split ratios is equivariant to any permutation of the demand indices.

Proof: Every learnable component is a per-node or per-demand operator with shared weights: the mask embedding ϕ and temporal encoder act on each path token, the GNN layers combine node-wise linear maps with sparse aggregation, the fusion and policy heads act within each demand. None of their parameter shapes involves $|\mathcal{K}^t|$, N , or $|E^t|$. Permuting demand indices permutes the rows of every input and of the bipartite adjacency consistently; since shared node-wise operators commute with permutations and sparse aggregation is index-based, all intermediate embeddings — and hence the outputs — are permuted identically. $\square$

4.6 Training and Constraint Repair

SiTE trains with the multi-agent RL scheme of Teal [1]: each demand is an agent sharing the policy network. The policy outputs a Gaussian mean per path, and actions are sampled during training. To assign credit, each agent receives a COMA-style counterfactual reward that estimates its marginal contribution to the global objective (8): for demand i ,

$$A_i = \mathbb{E}_{\tilde{r}_i \sim \pi'} [R(r_{-i}, r_i) - R(r_{-i}, \tilde{r}_i)], \quad (12)$$

where r_{-i} denotes the allocations of all other demands and $\tilde{r}_i$ is a counterfactual action resampled from a reference distribution π' ; the policy gradient weights each agent's log probability by A_i . Algorithm 2 summarizes offline training. Two points deserve emphasis. First, the reward is computed against *ground-truth* demands during offline training — sparse observation constrains the policy input, never the training signal — which is exactly what a simulator or historical trace provides. Second, we deliberately retain reward-driven RL rather than imitation learning [12]: imitation learning requires expert allocations solved from *fully realized* demands of each episode, a supervision signal that is unavailable when even post-hoc observation is sparse; RL needs only the reward, which the network itself provides. At inference, allocations are refined by two parallelizable ADMM iterations to repair residual violations of the capacity constraint (3), adding less than 1 ms.

4.7 Complexity Analysis

Let $D = |\mathcal{K}^t|$ be the number of active demands, κ the candidate paths per demand, E the number of ISLs, and $\bar{\ell}$ the average path length. The gated FlowGNN performs message passing over the bipartite graph whose edge count is $O(D\kappa\bar{\ell})$; with Λ layers its cost is $O(\Lambda D\kappa\bar{\ell}d)$ for hidden width d . The temporal encoder applies a Transformer of length L independently to each of the $D\kappa$ path tokens, costing $O(D\kappa L^2 d)$, and the per-demand cross-attention over κ paths adds $O(D\kappa^2 d)$. Since κ , L , $\bar{\ell}$, and d are small constants

Algorithm 2 Offline training of SiTE

Require: historical trace $\{(D^t, G^t)\}$, mask M , learning rate η

Ensure: trained weights θ^* (incl. mask embedding ϕ)

- 1: build demand set $\mathcal{K}$ and graph from training-slice TMs
- 2: **for** each epoch **do**
- 3: **for** each snapshot t in the training slice **do**
- 4: form sparse input (H^t, M) ; sample actions $r \sim \pi_\theta(\cdot | H^t, M, G^t)$
- 5: compute counterfactual rewards $\{A_i\}$ via (12)
 using the true D^t
- 6: $\theta \leftarrow \theta + \eta \sum_i A_i \nabla_\theta \log \pi_\theta(r_i)$
- 7: **end for**
- 8: **end for**
- 9: **return** θ^*

fixed by design, the end-to-end inference cost is *linear* in the number of active demands, $O(D)$, and all operations are batched across demands on the GPU. Crucially, the parameter count is independent of D , N , and E : the same weights apply to any demand set, which is what enables zero-retraining reuse (section 4.5). Demand pruning reduces D from $N(N-1)$ to the observed support — roughly $400\times$ on our constellation — turning an otherwise intractable problem into one solved in milliseconds (section 5.5).

5 EVALUATION

5.1 Setup

We evaluate on a Starlink-like +Grid constellation with 22×72 satellites (1,584 nodes, 6,336 ISLs) and 101 consecutive traffic-matrix snapshots that capture real geographic demand distribution and temporal drift ($\sim 10\%$ demand-pair turnover across the trace). ISL capacity is calibrated so that the fully-observed optimum leaves moderate congestion (satisfied ratio ≈ 0.87), keeping TE decisions non-trivial. Snapshots 0–79 are used for training, 80–89 for validation, and 90–100 for testing — a strict temporal split with no leakage. We report the *satisfied demand ratio* (allocated flow after ADMM and rounding, evaluated against ground-truth demands, over total demand) and per-snapshot inference latency, averaged over three seeds (mean $\pm$ std). Following the taxonomy of section 3.4, we compare against *Zero-fill* (unobserved entries set to zero, no mask-aware modules), *Mean-interp.* (two-stage complete-then-optimize), and *Teal-full* (original Teal with the complete matrix, an upper reference).


5.2 Overall Performance

Figure 4 reports the satisfied demand ratio as observability ρ decreases, with detailed numbers in table 3. SiTE degrades gracefully, retaining [TODO: XX]% of the fully-observed optimum even at $\rho = 0.1$, whereas zero-filling and mean-interpolation drop sharply as more demands become unmeasured. The gap widens as ρ shrinks, confirming that mask embeddings and temporal recovery matter most when information is scarcest.

TABLE 3

Satisfied demand ratio (mean $\pm$ std over 3 seeds, placeholder data).

ρ	Zero-fill	Mean-interp.	Ours	Teal-full
1.0		—		[TODO: .XX:—
0.7	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	—
0.5	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	—
0.3	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	—
0.1	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	[TODO: .XX $\pm$.XX]	—

Fig. 4. Satisfied demand ratio versus observability ratio ρ (placeholder data). SiTE stays close to the fully-observed oracle while baselines degrade sharply.

5.3 Ablation Study

Figure 6 isolates each component at $\rho = 0.3$. Removing the learnable mask embedding causes the largest drop, followed by the gated message passing and the temporal encoder; disabling all three recovers the zero-fill baseline. Figure 5 extends the ablation across observability levels: the contribution of every module grows as ρ decreases, and the mask embedding dominates in the extreme-sparsity regime.

The temporal module also stabilizes training: fig. 7 shows that the history-augmented model converges to a higher and steadier validation ratio than its single-snapshot counterpart.

5.4 Zero-Retraining under Demand and Topology Drift

Demand-set drift. We train on the demand-pair union of the training slice (6,320 pairs) and, at test time, rebuild the graph from the test slice's own union (6,044 pairs, including pairs never seen in training) while keeping the weights frozen. Table 4 shows that this incurs negligible loss relative to the oracle setting where the demand set is built from all snapshots, and fig. 8 confirms the gap stays small on every test snapshot, validating train-once, zero-retraining deployment under demand-set drift.

Topology drift. Constellation topologies also change — ISLs fail or are re-planned as satellites move. We emulate this by testing the model, trained on the nominal +Grid topology, on perturbed variants with 5%/10% of ISLs removed (candidate paths and the bipartite graph are rebuilt at test time; weights stay frozen), and additionally with k random link failures injected at test time. As table 5 shows, SiTE degrades marginally under both perturbations,





Fig. 5. Ablation across observability ratios (placeholder data). Module contributions grow as observations become scarcer.

Fig. 6. Component ablation at $\rho = 0.3$ (placeholder data). Each sparse-aware module contributes to the final performance.

substantiating Proposition 2: the graph is a runtime input, not a parameter.

5.5 Runtime and Scalability

Demand pruning shrinks the modeled problem from 2.5M pairs to $\sim 6.3K$ ($\sim 400\times$), bringing per-snapshot inference to [TODO: XX] ms on a single GPU — within the control budget of a rapidly changing constellation, and comparable to the millisecond-scale latency reported by SaTE [5]. Figure 9 contrasts SiTE with an LP solver and Teal-full: learned inference is three orders of magnitude faster than solving, and the temporal module adds only marginal latency. Modeling the full demand set without pruning is infeasible under the memory budget, as the index tensors alone would exceed [TODO: XX] GB.

5.6 Sensitivity Analysis

Measurement granularity. Figure 10 compares flow- and node-level sampling at equal ρ . Node-level missing is structural — entire source rows disappear (fig. 2) — and hurts the zero-fill baseline substantially more, while SiTE remains robust thanks to spatial message passing from links shaped by observed traffic.




Fig. 7. Validation satisfied ratio during training (placeholder data). Temporal fusion improves both final quality and stability.




Fig. 8. Per-snapshot satisfied ratio on the test slice (placeholder data): weights trained on the training-slice demand set are reused on the rebuilt test-slice set with negligible loss.

History length. Figure 11 sweeps L : quality saturates around $L=[\text{TODO: } X]$ while latency grows linearly, so we adopt $L=3$ by default.

Load sensitivity. Figure 12 varies ISL capacity: the advantage of SiTE widens under high load, where misallocating unmeasured demands is most costly.

6 CONCLUSION

This paper presented SiTE, the first learning-based traffic engineering system for LEO satellite constellations that operates directly on sparse traffic observations. SiTE resolves the ambiguity of unmeasured demands with learnable mask embeddings, protects network-state estimates with mask-aware gated message passing, and recovers missing information from observation history through temporal-spatial cross-attention — all trained end-to-end against the TE objective without an explicit completion stage. Demand pruning and size-invariant weights let a model trained once serve drifting topologies and demand sets with zero retraining. On a 22×72 Starlink-like constellation with real traffic dynamics, SiTE achieves $[\text{TODO: } XX]\%$ of fully-observed

TABLE 4
Zero-retraining generalization (placeholder data).

Setting	Train set	Test set	Satisfied ratio
Oracle (full set)	6,334	6,334	$[\text{TODO: } 0.XX]$
Zero-retraining (split)	6,320	6,044	$[\text{TODO: } 0.XX]$

TABLE 5
Topology-drift zero-retraining (placeholder data).

Test topology	ISLs	Satisfied ratio
Nominal (training topology)	6,336	$[\text{TODO: } 0.XX]$
5% ISLs removed	6,020	$[\text{TODO: } 0.XX]$
10% ISLs removed	5,704	$[\text{TODO: } 0.XX]$
$k=50$ random link failures	6,336	$[\text{TODO: } 0.XX]$

performance with only $[\text{TODO: } XX]\%$ observability, outperforming zero-filling and two-stage baselines by $[\text{TODO: } XX-XX]\%$, at $[\text{TODO: } XX]$ ms inference per snapshot.

Three directions remain open. First, our observation masks are static within a trace; real measurement availability fluctuates with ground-contact windows and onboard load, motivating time-varying masks and measurement scheduling — deciding *which* demands to measure next — as a joint control problem. Second, our input-side modules are orthogonal to the training paradigm: combining them with imitation learning [12] where post-hoc complete traces are available, or with hybrid schemes, may improve sample efficiency. Third, the path templates of +Grid constellations suggest an $O(1)$ displacement-indexed path lookup that we currently approximate with per-set path caching; a full implementation would further cut graph-rebuild latency. We also plan to validate on measured (rather than synthesized) satellite traffic as such datasets become available.

REFERENCES

- [1] Z. Xu, F. Y. Yan, R. Singh, J. T. Chiu, A. M. Rush, and M. Yu, “Teal: Learning-accelerated optimization of WAN traffic engineering,” in *Proceedings of the ACM SIGCOMM 2023 Conference*, 2023, pp. 378–393.
- [2] P. Kumar, Y. Yuan, C. Yu, N. Foster, R. Kleinberg, P. Lapukhov, C. L. Lim, and R. Soulé, “Semi-oblivious traffic engineering: The road not taken,” in *15th USENIX Symposium on Networked Systems Design and Implementation (NSDI 18)*, 2018, pp. 157–170.
- [3] Y. Perry, F. V. Frujeri, C. Hoch, S. Kandula, I. Menache, M. Schapira, and A. Tamar, “DOTE: Rethinking (predictive) WAN traffic engineering,” in *20th USENIX Symposium on Networked Systems Design and Implementation (NSDI 23)*, 2023, pp. 1557–1581.
- [4] A. A. AlQiam, Y. Yao, Z. Wang, S. S. Ahuja, Y. Zhang, S. G. Rao, B. Ribeiro, and M. Tawarmalani, “Transferable neural WAN TE for changing topologies,” in *Proceedings of the ACM SIGCOMM 2024 Conference*, 2024, pp. 86–102.
- [5] H. Wu, Y. Han, M. Rajpal, Q. Zhang, and J. Wang, “SaTE: Low-latency traffic engineering for satellite networks,” in *Proceedings of the ACM SIGCOMM 2025 Conference*, 2025, pp. 896–916.
- [6] Y. Guo, Z. Huang, M. Ding, and H. Luo, “An end-to-end learning approach for traffic engineering with sparse traffic measurements,” *IEEE Transactions on Mobile Computing*, vol. 25, no. 4, pp. 5448–5463, 2026, tODO: verify author list against the published version.
- [7] F. Abuzaid, S. Kandula, B. Arzani, I. Menache, P. Bailis, and M. Zaharia, “Contracting wide-area network topologies to solve flow problems quickly,” in *18th USENIX Symposium on Networked Systems Design and Implementation (NSDI 21)*, 2021, tODO: verify author list.




Fig. 9. Per-snapshot inference latency (log scale, placeholder data).






Fig. 10. Flow- versus node-level sparse sampling (placeholder data).

Fig. 11. History-length sweep at $\rho = 0.3$ (placeholder data): quality saturates while latency grows linearly.

- [8] D. Narayanan, F. Kazhamiaka, F. Abuzaid, P. Kraft, A. Agrawal, S. Kandula, S. Boyd, and M. Zaharia, "Solving large-scale granular resource allocation problems efficiently with POP," in *Proceedings of the ACM SIGOPS 28th Symposium on Operating Systems Principles (SOSP)*, 2021, tODO: verify author list.
- [9] X. Liu *et al.*, "FIGRET: Fine-grained robustness-enhanced traffic engineering," in *Proceedings of the ACM SIGCOMM 2024 Conference*, 2024, tODO: verify author list and pages.
- [10] D. Wu *et al.*, "NetLLM: Adapting large language models for networking," in *Proceedings of the ACM SIGCOMM 2024 Conference*, 2024, tODO: verify author list and pages.
- [11] Y. Lu, Y. Zhao, F. Sun, and H. Li, "Virtual topology for LEO satellite networks based on earth-fixed footprint mode," *IEEE Communications Letters*, vol. 17, no. 2, pp. 357–360, 2013, tODO: verify author list.
- [12] Z. Yang, G. Fan, A. Cao, Y. Guo, W. Li, C. Ying, T. Liu, S. Yue, and H. Jin, "Scalable traffic allocation in dynamic networks via end-to-end imitation learning," *IEEE/ACM Transactions on Networking*, vol. 34, 2026.
- [13] Z. Yang, G. Fan, A. Cao, Y. Guo, W. Li, T. Liu, and H. Jin, "Learning to accelerate traffic allocation over large-scale networks," in *IEEE INFOCOM 2025 - IEEE Conference on Computer Communications*, 2025.
- [14] C. Huo, D. Jin, Y. Li, D. He, Y.-B. Yang, and L. Wu, "T2-GNN: Graph neural networks for graphs with incomplete features and structure via teacher-student distillation," in *Proceedings of the AAAI Conference on Artificial Intelligence*, 2023.

Fig. 12. Sensitivity to ISL capacity at $\rho = 0.3$ (placeholder data).