

Angular component



By CODEMIND Technology

Contact us +91 96650 44698

1

Components in Angular

Components are building block of Angular application. The main job of Angular Component is to generate a section of web page called view. Every component will have an associated template and it will be used to generate views.

Each component has its own template, its own HTML code, maybe its own styling, and more importantly also its own business logic. And this is the great benefit. It allows you to split up your complex application, your complex webpage into reusable parts.

Let us create a new component in our angularapp application :

Create a new component using cli command :

`> ng generate component expense-entry or ng g c expense-entry`

Output :

CREATE src/app/expense-entry/expense-entry.component.html (28 bytes)

CREATE src/app/expense-entry/expense-entry.component.spec.ts (671 bytes)

CREATE src/app/expense-entry/expense-entry.component.ts (296 bytes)

CREATE src/app/expense-entry/expense-entry.component.css (0 bytes)

UPDATE src/app/app.module.ts

Here

- ExpenseEntryComponent is created under src/app/expense-entry folder.
- Component class, Template and stylesheet are created.
- AppModule is updated with new component.

Open src/app/app.component.html and include newly created component.

```
<app-expense-entry></app-expense-entry>
```

Here,

app-expense-entry is the selector value and it can be used as regular HTML Tag.

Templates

The integral part of Angular component is Template. It is used to generate the HTML content. Templates are plain HTML with additional functionality.

templateUrl

We already know how to use templateUrl. It expects the relative path of the template file. For example, AppComponent set its template as app.component.html.

```
templateUrl: './app.component.html',
```

Attach Stylesheet

Angular Templates can use CSS styles similar to HTML. Template gets its style information from two sources, a) from its component b) from application configuration.

Component configuration

Component decorator provides two option, **styles** and **styleUrls** to provide CSS style information to its template.

- **Styles** – styles option is used to place the CSS inside the component itself.

```
styles: ['h1 { color: 'ff0000'; }']
```

- **styleUrls** – styleUrls is used to refer external CSS stylesheet. We can use multiple stylesheet as well.

```
styleUrls: ['./app.component.css', './custom_style.css']
```

Note : For practice create multiple component using angular cli .