

Digit Recognition

with Support Vector Machines

Lisa GAEDKE-MERZHÄUSER
Paul KORSMEIER
Lisa MATTRISCH
Vanessa SCHRECK

Freie Universität Berlin, Mathematical Aspects of Machine Learning


July 18, 2017

Outline

1. Introduction to Our Data Set
2. Our Approach
3. Sequential Minimal Optimization (SMO)
4. Multi-Class Classification
5. Results & Conclusions

Introduction to Our Data Set

Main Goal: train algorithm to recognize handwritten digits




Data:

- ▶ 42,000 greyscale images
- ▶ 28 by 28 pixels each
- ▶ partitioned into ten classes

Our Approach

We want to use the concept of SVMs.



- ▶ **Problem I:** SVMs are binary classifiers
- ▶ **Problem II:** Need to solve optimization problem


Our Approach

1. Implement solver for our QP
 - ▶ 3 versions
2. Implement basic SVM algorithm
 - ▶ linear kernel / Gaussian kernel
 - ▶ Parameter optimization
3. Combine individual SVMs in different ways
 - ▶ 3 versions
4. Validate and compare results

Sequential Minimal Optimization (SMO)

Multi-Class Classification

- ▶ Choose k groups of the classes
- ▶ Train k SVMs that separate each group from the rest
- ▶ Compare outcome to what would arise for each digit.
- ▶ **Problem:** Points may not be classified uniquely.
- ▶ Handle overlappings by minimizing distance to barycenters



Multi-Class Classification

1. One-vs-All

Idea: For each $i \in \{0, 1, \dots, 9\}$, train an SVM that separates class i from the rest

Class	f_0	f_1	f_2	f_3	f_4	f_5	f_6	f_7	f_8	f_9
0	-1	1	1	1	1	1	1	1	1	1
1	1	-1	1	1	1	1	1	1	1	1
2	1	1	-1	1	1	1	1	1	1	1
3	1	1	1	-1	1	1	1	1	1	1
4	1	1	1	1	-1	1	1	1	1	1
5	1	1	1	1	1	-1	1	1	1	1
6	1	1	1	1	1	1	-1	1	1	1
7	1	1	1	1	1	1	1	-1	1	1
8	1	1	1	1	1	1	1	1	-1	1
9	1	1	1	1	1	1	1	1	1	-1

Multi-Class Classification

2. Error Correcting Output Codes

Idea: Relabeling with large Hamming distance according to:

Class	f_0	f_1	f_2	f_3	f_4	f_5	f_6	f_7	f_8	f_9	f_{10}	f_{11}	f_{12}	f_{13}	f_{14}
0	1	1	-1	-1	-1	-1	1	-1	1	-1	-1	1	1	-1	1
1	-1	-1	1	1	1	1	-1	1	-1	1	1	-1	-1	1	-1
2	1	-1	-1	1	-1	-1	-1	1	1	1	1	-1	1	-1	1
3	-1	-1	1	1	-1	1	1	1	-1	-1	-1	-1	1	-1	1
4	1	1	1	-1	1	-1	1	1	-1	-1	1	1	-1	-1	1
5	-1	1	-1	-1	1	1	-1	-1	1	1	-1	-1	-1	-1	1
6	1	-1	1	1	1	-1	-1	-1	-1	1	-1	1	-1	-1	1
7	-1	-1	-1	1	1	1	1	-1	1	-1	1	1	-1	-1	1
8	1	1	-1	1	-1	1	1	-1	-1	1	-1	-1	-1	1	1
9	-1	1	1	1	-1	-1	-1	-1	1	-1	1	-1	-1	1	1

Results & Conclusions

# training points	One-vs-All uniquely classified, linear	One-vs-All with bary-centers, linear	One-vs-All uniquely classified, Gaussian	One-vs-All with bary-centers, Gaussian	ECOC, linear	ECOC, Gaussian
500						
1000						
2000						
5000						
10000						

Table: Correctly Classified Digits

Results & Conclusions

# training points	One-vs-All uniquely classified, linear	One-vs-All with bary-centers, linear	One-vs-All uniquely classified, Gaussian	One-vs-All with bary-centers, Gaussian	ECOC, linear	ECOC, Gaussian
500	65.9%	74.1%	75.4%	83.3%	74.2%	87.4%
1000	68.2%	75.0%	84.3%	89.0%	78.0%	92.7%
2000	70.2%	76.4%	89.8%	91.9%	77.8%	94.3%
5000	70.0%	73.8%	88.9%	91.6%	82.0%	95.2%
10000	64.6%	67.5%	88.0%	90.6%	82.5%	95.4%

Table: Correctly Classified Digits

Results & Conclusions




Figure: Visualizing very illegible digits