

Nonlinear Regression

Table of contents

Preparation	1
Loading Required Packages and Data	1
Create Nonlinear Function	2
Analysis	3
Identify Starting Values	3
Fitting the Model	4
Visualisation	6
Bootstrapping Confidence Intervals	6
Predicting Average and Individual Trajectories	7
Selecting a Random Sample for Plotting	7
Creating the Plot	8
Model Performance	9
Evaluating the Model	9
Cross-Validation	10

To illustrate nonlinear regression we use a model that combines a Gaussian and a logistic function.

To reproduce the results, it is necessary to prepare the data set, plot base, and training and test data sets, as outlined in the “Data Preparation” section.

Preparation

Loading Required Packages and Data

Load the necessary packages, data sets, and other supporting files. Each element serves a specific purpose:

- **tidyverse**: For data manipulation and visualisation.

- **nls.mltstart**: To identify reasonable starting values for the nonlinear regression.
- **nlme**: To fit the nonlinear regression model.
- **boot**: To calculate the bootstrapped 95% CI.
- **caret**: To compute model performance indices.
- **plot_base**: A pre-configured ggplot object for visualisation.
- **Training and Test Data sets**: Required for cross-validation.

```
# Load necessary packages
library(tidyverse)
library(nls.mltstart)
library(nlme)
library(boot)
library(caret)

# Load the data set
load("data/wido.rdata")

# Load the pre-configured plot base
plot_base <- readRDS("objects/plot_base.rds")

# Load training and test datasets for cross-validation
training_datasets <- readRDS("objects/training_datasets.rds")
test_datasets <- readRDS("objects/test_datasets.rds")
```

Create Nonlinear Function

Create a custom nonlinear function by combining the formula for a Gaussian function and the formula for a logistic function using a plus sign.

```
# Define the nonlinear function
nonlinfunc <- function(mnths, bas, amp, wid, cen, newequi) {
  return ((bas + amp * exp(-(mnths - cen)^2 / (2 * wid^2))) + (newequi*(1 /
    ↪ (1 + exp(-(mnths - cen) / wid)))
  ))
}
```

Analysis

Identify Starting Values

We fit the nonlinear regression model including random effects in `nlme`. Because this requires starting values for the parameters, we estimate the model without random effects, using `nls_multstart`. This function repeatedly fits the model, each time using different starting values. The results of the model without random effects will inform the specification of starting values for the model with random effects.

```
# Fit the model without random effects, specify reasonable limits for the
  ↪ starting values of the parameters
nonlin_norandomeffects <- nls_multstart(lifesatisfaction ~ nonlinfunc(mnths,
  ↪ bas, amp, wid, cen, newequi),
  data = wido,
  lower=c(bas=-7, amp=-7, wid=-200, cen=-200,
  ↪ newequi=-7),
  upper=c(bas=7, amp=7, wid=200, cen=200, newequi=7),
  start_lower = c(bas=-7, amp=-7, wid=-200, cen=-200,
  ↪ newequi=-7),
  start_upper = c(bas=7, amp=7, wid=200, cen=200,
  ↪ newequi=7),
  iter = 500,
  supp_errors = "Y")

summary(nonlin_norandomeffects)
```

Formula: `lifesatisfaction ~ nonlinfunc(mnths, bas, amp, wid, cen, newequi)`

Parameters:

	Estimate	Std. Error	t value	Pr(> t)	
bas	4.91869	0.04360	112.815	< 2e-16	***
amp	-0.67021	0.08010	-8.367	< 2e-16	***
wid	-10.85987	1.62611	-6.678	3.01e-11	***
cen	5.01145	1.61313	3.107	0.00192	**
newequi	0.28449	0.05627	5.056	4.62e-07	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 1.081 on 2317 degrees of freedom

Number of iterations to convergence: 44
Achieved convergence tolerance: 1.49e-08

Fitting the Model

We use these results to specify starting values for the model with random effects. We add random effects for the “baseline”- and “new equilibrium”-parameters.

```
# Fit the model with the identified starting values and random effects for
  ↪ baseline and new equilibrium
nonlin_randomeffects_bas_newequi <- nlme(lifesatisfaction ~ nonlinfunc(mnths,
  ↪ bas, amp, wid, cen, newequi),

                                data = wido,
                                fixed= bas + amp + wid + cen + newequi
                                  ↪ ~ 1,
                                random = bas + newequi ~ 1,
                                groups = ~ id,
                                start = c(bas=5.2, amp=-0.7, wid=10.9,
                                  ↪ cen=5.0, newequi=-0.3))

summary(nonlin_randomeffects_bas_newequi)
```

Nonlinear mixed-effects model fit by maximum likelihood

Model: lifesatisfaction ~ nonlinfunc(mnths, bas, amp, wid, cen, newequi)

Data: wido

	AIC	BIC	logLik
	5307.388	5359.14	-2644.694

Random effects:

Formula: list(bas ~ 1, newequi ~ 1)

Level: id

Structure: General positive-definite, Log-Cholesky parametrization

	StdDev	Corr
bas	0.8598767	bas
newequi	0.9276880	-0.384
Residual	0.6248258	

Fixed effects: bas + amp + wid + cen + newequi ~ 1

	Value	Std.Error	DF	t-value	p-value
bas	5.167437	0.0657563	2110	78.58468	0e+00
amp	-0.716649	0.0591928	2110	-12.10703	0e+00

```

wid      6.539394 0.5826737 2110  11.22308    0e+00
cen      2.513732 0.6178153 2110   4.06874    0e+00
newequi -0.315205 0.0777650 2110  -4.05330    1e-04

```

Correlation:

```

      bas      amp      wid      cen
amp    -0.078
wid     0.103   0.336
cen    -0.068  -0.048   0.241
newequi -0.437 -0.082 -0.011   0.157

```

Standardized Within-Group Residuals:

```

      Min      Q1      Med      Q3      Max
-4.89041434 -0.48124295  0.06419164  0.54053713  3.50118182

```

Number of Observations: 2322

Number of Groups: 208

```
intervals(nonlin_randomeffects_bas_newequi)
```

Approximate 95% confidence intervals

Fixed effects:

```

      lower      est.      upper
bas     5.0386217  5.1674368  5.2962518
amp    -0.8326063 -0.7166491 -0.6006918
wid     5.3979505  6.5393944  7.6808384
cen     1.3034460  2.5137316  3.7240172
newequi -0.4675448 -0.3152051 -0.1628653

```

Random Effects:

Level: id

```

      lower      est.      upper
sd(bas)     0.7682378  0.8598767  0.9624467
sd(newequi)  0.8057144  0.9276880  1.0681267
cor(bas,newequi) -0.5197132 -0.3835289 -0.2283371

```

Within-group standard error:

```

      lower      est.      upper
0.6052182  0.6248258  0.6450687

```

Visualisation

Bootstrapping Confidence Intervals

Use bootstrapping to estimate the confidence intervals for the predicted values of the model. This provides a robust measure of uncertainty.

```
# For reproducibility
set.seed(123)

# To avoid convergence issues, we adapt the control values for the nlme fit
↪ (increase iterations, etc.)
control_options <- nlmeControl(
  maxIter = 2000,    # Increase max number of iterations
  pnlsMaxIter = 500, # Increase the max number of iterations for the PNLs
  ↪ step
  msMaxIter = 2000, # Increase the maximum iterations for the optimization
  ↪ step
  pnlsTol = 0.1,    # Relax tolerance for PNLs step
)

# Define a function to refit the nonlinear mixed-effects model and generate
↪ predictions
predict_fun <- function(data, indices) {
  # Resample the data using the bootstrap indices
  boot_data <- data[indices, ]

  # Refit the nonlinear mixed-effects model on the resampled data
  boot_model <- nlme(
    lifesatisfaction ~ nonlinfunc(mnths, bas, amp, wid, cen, newequi),
    data = boot_data,
    fixed = bas + amp + wid + cen + newequi ~ 1,
    random = bas + newequi ~ 1,
    groups = ~ id,
    start = c(bas=5.2, amp=-0.7, wid=10.9, cen=5.0, newequi=-0.3),
    control = control_options
  )

  # Predict on the original dataset
  # Predict using only fixed effects (set level = 0)
  return(predict(boot_model, newdata = data, level = 0))
}
```

```

# Perform the bootstrap
boot_results <- boot(data = wido, statistic = predict_fun, R = 1000, sim =
  ↪ "ordinary")

# Calculate 95% confidence intervals from bootstrapped results
ci <- apply(boot_results$t, 2, quantile, probs = c(0.025, 0.975), na.rm = T)

# Assign the results to the original data frame
wido$lower_bound <- ci[1, ]
wido$upper_bound <- ci[2, ]

```

Predicting Average and Individual Trajectories

Predict both the population-level (fixed effects) and individual-level (random effects) trajectories of life satisfaction.

```

# Predict population-level trajectories based on fixed effects
wido$lifesatisfaction_nl_fix <- predict(nonlin_randomeffects_bas_newequi,
  ↪ wido, level = 0)

# Predict individual-level trajectories based on random effects
wido$lifesatisfaction_nl_rand <- predict(nonlin_randomeffects_bas_newequi,
  ↪ newdata = wido)

```

Selecting a Random Sample for Plotting

For better visualisation, select a random sample of individuals to display their individual trajectories.

```

# For reproducibility
set.seed(123)

# Randomly sample 50 participants
rsample_ids <- sample(unique(wido$id), 50)


# Filter the data to include only the randomly selected participants
wido_rsample <- wido %>%
  filter(id %in% rsample_ids)

```

Creating the Plot

Combine all elements to create the plot, which includes individual trajectories, the population trajectory, and the confidence interval of the population trajectory.

```
# Create the plot using the pre-configured plot base
plot_base +
  geom_line(
    data = wido_rsample,
    aes(x = mnths, y = lifesatisfaction_nl_rand, group = id),
    color = "grey70", linewidth = 0.4
  ) +
  geom_ribbon(
    data = wido,
    aes(x = mnths, ymin = lower_bound, ymax = upper_bound),
    fill = "firebrick4", alpha = 0.2
  ) +
  geom_line(
    data = wido,
    aes(x = mnths, y = lifesatisfaction_nl_fix),
    color = "firebrick4", linewidth = 1
  ) +
  ggtitle("Nonlinear Regression: Gaussian + \nLogistic Function") +
  theme(plot.title = element_text(size = 13, face = "bold"))
```



Model Performance

Evaluating the Model

Assess the model's performance using the Bayesian Information Criterion (BIC), R-squared (R^2), Mean Absolute Error (MAE), and Root Mean Squared Error (RMSE).

```
# Compute BIC for the fitted model
round(BIC(nonlin_randomeffects_bas_newequi), 2)
```

```
[1] 5359.14
```

```
# Calculate  $R^2$ , MAE, and RMSE for the fixed effects predictions
data.frame(
  R2_FE = round(R2(wido$lifesatisfaction_nl_fix, wido$m_lifesat_per_mnth),
    ↪ 2),
  R2_FE = round(MAE(wido$lifesatisfaction_nl_fix, wido$m_lifesat_per_mnth),
    ↪ 2),
  R2_FE = round(RMSE(wido$lifesatisfaction_nl_fix, wido$m_lifesat_per_mnth),
    ↪ 2)
)
```

```
      R2_FE R2_FE.1 R2_FE.2
1  0.28    0.29    0.39
```

```
# Calculate  $R^2$ , MAE, and RMSE for the random effects predictions
data.frame(
  R2_RE = round(R2(wido$lifesatisfaction_nl_rand, wido$lifesatisfaction), 2),
  R2_RE = round(MAE(wido$lifesatisfaction_nl_rand, wido$lifesatisfaction),
    ↪ 2),
  R2_RE = round(RMSE(wido$lifesatisfaction_nl_rand, wido$lifesatisfaction),
    ↪ 2)
)
```

```
      R2_RE R2_RE.1 R2_RE.2
1  0.73    0.43    0.58
```

Cross-Validation

To assess the replicability of the model, perform cross-validation using the training and test data sets. For each training data set, fit the model and compute performance metrics for the associated test data set R^2 , MAE, and RMSE.

```
# Initialize vectors to store the performance metrics
R2_values <- c()
RMSE_values <- c()
MAE_values <- c()

# Perform the cross-validation
for (i in 1:length(training_datasets)) {
  # Get the current training and test data set
  training_data <- training_datasets[[i]]
  test_data <- test_datasets[[i]]

  # Fit the nonlinear model using nlme
  nlme_model <- nlme(
    lifesatisfaction ~ nonlinfunc(mnth, bas, amp, wid, cen, newequi),
    data = training_data,
    fixed = bas + amp + wid + cen + newequi ~ 1,
    random = bas + newequi ~ 1 | id,
    start = c(bas=5.2, amp=-0.7, wid=10.9, cen=5.0, newequi=-0.3),
  )

  # Predict fixed effects
  predictions <- predict(nlme_model, newdata = test_data, level = 0)

  # Compute average test trajectory
  test_data <- test_data %>%
    group_by(mnth) %>%
    mutate(mean_ls = mean(lifesatisfaction, na.rm = TRUE))

  # Compute performance metrics
  R2_value <- R2(predictions, test_data$mean_ls)
  RMSE_value <- RMSE(predictions, test_data$mean_ls)
  MAE_value <- MAE(predictions, test_data$mean_ls)

  # Store the metrics
  R2_values <- c(R2_values, R2_value)
  RMSE_values <- c(RMSE_value, RMSE_value)
}
```

```

MAE_values <- c(MAE_values, MAE_value)
}

# Compute average performance metrics (mean)
average_R2 <- mean(R2_values)
average_MAE <- mean(MAE_values)
average_RMSE <- mean(RMSE_values)

# Compute average performance metrics (SD)
sd_R2 <- sd(R2_values)
sd_MAE <- sd(MAE_values)
sd_RMSE <- sd(RMSE_values)

# Combine the mean and standard deviation into one data.frame
combined_metrics <- data.frame(
  Metric = c("R2", "MAE", "RMSE"),
  Mean = round(c(average_R2, average_MAE, average_RMSE), 2),
  SD = round(c(sd_R2, sd_MAE, sd_RMSE), 2)
)

# Print the combined metrics
print(combined_metrics)

```

	Metric	Mean	SD
1	R ²	0.10	0.02
2	MAE	0.59	0.07
3	RMSE	0.74	0.00