



School: Campus:
Academic Year: Subject Name: Subject Code:
Semester: Program: Branch: Specialization:
Date:

Applied and Action Learning

(Learning by Doing and Discovery)

Name of the Experiment : Build the Network – Peer-to-Peer Simulation

* Coding Phase: Pseudo Code / Flow Chart / Algorithm

☐ **Initialize Network**

Define the number of nodes (peers) participating in the network.
Assign each node a unique ID and empty ledger/memory.

☐ **Create Connections**

Each node connects to a few other nodes randomly (simulating a mesh network).
Maintain a list of peers each node can send/receive messages from.

☐ **Message Broadcast**

One node (the initiator) sends a transaction or message to its peers.
Each peer forwards the message to its connected nodes (except the sender).

☐ **Verification Process**

Each node validates the message (e.g., checks if it's new and not already received).
Invalid or duplicate messages are ignored.

☐ **Ledger Update**

If the message (transaction/block) is valid, it's added to the node's ledger.

☐ **Consensus (Optional)**

If simulating blockchain consensus, include a simple rule like:
The first valid message received by all nodes is accepted.
Nodes reject conflicting data.

☐ **End Simulation**

Display how many nodes successfully received and accepted the message.
Show that the network achieved synchronization without a central server.

Software used

1. MetaMask Wallet
2. VS Code.
3. MS Word.
4. Brave for researching.

* Implementation Phase: Final Output (no error)

- ☐ Input: Number of peers (e.g., 6)
- ☐ Establish peer connections.
- ☐ Node 1 broadcasts a message.
- ☐ Nodes 2–6 receive and validate the message.
- ☐ Ledger updated in each node.
- ☐ Output:

Message broadcast from Node 1
 Node 2 received message from Node 1
 Node 3 received message from Node 2
 Node 4 received message from Node 3
 All nodes synchronized ☐

* Observations:

- The message reaches all nodes without any central server.
- Duplicate messages are automatically avoided using validation.
- The network demonstrates **decentralization**, **fault tolerance**, and **equal node importance**.
- Communication delay or missing peers can affect synchronization — similar to real blockchain networks.
- When consensus rules are added, the simulation behaves like a mini blockchain environment.

ASSESSMENT

Rubrics	Full Mark	Marks Obtained	Remarks
Concept	10		
Planning and Execution/ Practical Simulation/ Programming	10		
Result and Interpretation	10		
Record of Applied and Action Learning	10		
Viva	10		
Total	50		

Signature of the Student:

Name :

Regn. No. :

Signature of the Faculty: